DATABASE CODING TABLE

TAIYUAN/Wusu

A I ADAJL	CODINO	IADEL						AIV WUS
Path	Waypoint	Fly	Magnetic	Turn	Altitude	IAS	VPA/TCH	Navigation
Terminator	ID	over	Course(°)	Direction	(m)	(kt)	VI A/ 1011	Specification
			RWY31	STAR ANPIG	-9ZA			_
IF	ANPIG				<u>3600</u>			RNAV1
TF	YN711				2700			RNAV1
TF	YN704				2100	MAX205		RNAV1
			RWY31	STAR BISAL-	9YA			
IF	BISAL							RNAV1
TF	YN710				<u>3600</u>			RNAV1
TF	YN708				2700			RNAV1
TF	YN707							RNAV1
TF	YN706							RNAV1
TF	YN704				2100	MAX205		RNAV1
			RWY31	STAR BISAL-	-9ZA			
IF	BISAL							RNAV1
TF	YN710				<u>3600</u>			RNAV1
TF	YN708				2700			RNAV1
TF	YN704				2100	MAX205		RNAV1
			RWY31	STAR TUTNA	-9YA		I	
IF	TUTNA							RNAV1
TF	NITID							RNAV1
TF	YN712				<u>3600</u>			RNAV1
TF	YN710							RNAV1
TF	YN708				2700			RNAV1
TF	YN707							RNAV1
TF	YN706							RNAV1
TF	YN704				2100	MAX205		RNAV1
	1		RWY31	STAR TUTNA	-9ZA	1	ı	1
IF	TUTNA							RNAV1
TF	NITID							RNAV1
TF	YN712				<u>3600</u>			RNAV1
TF	YN710							RNAV1
TF	YN708				2700			RNAV1
TF	YN704				2100	MAX205		RNAV1
			RWY31	STAR OMKAK	-9YA	1	ı	1
IF	OMKAK							RNAV1
TF	YN712				3600			RNAV1
TF	YN710							RNAV1
TF	YN708				2700			RNAV1
TF	YN707							RNAV1
TF	YN706							RNAV1
 Changes: New cho						l	I	