

AERODROME GROUND
MOVEMENT CHART - ICAO

APRON ELEV 170 ft

TWR 118.7 126.2
GND 121.875

CHEONGJU / Cheongju Intl

ELEVATIONS IN FEET
DIMENSION IN METER
BEARINGS ARE MAGNETIC

VAR 8° W 2020
ANNUAL RATE OF CHANGE
5' W

HS 1	Aircraft shall pay extra caution to Critical area and do not cross the hold line for RWY 24R without authorization from ATC.
HS 2	Aircraft shall pay extra caution to other aircrafts (departing or landing helicopters) while taxiing around hot spot areas.

	SURFACE	WIDTH	BEARING STRENGTH
APRON	Concrete	NIL	SPOT 1~13, 71~78 PCR 1 006 R/B/W/T
TWY B3	Asphalt	33 m	PCR 577 F/A/X/T
TWY B4	Asphalt	33 m	PCR 577 F/A/X/T
TWY E1	Asphalt, Concrete	36 m	PCR 1 006 R/B/W/T, PCR 577 F/A/X/T
TWY E2	Asphalt	30 m	PCR 577 F/A/X/T
TWY A3	Asphalt	25 m	PCR 629 F/B/X/T
TWY C3	Concrete	33 m	PCR 1 006 R/B/W/T
TWY D3	Concrete	28 m	PCR 1 006 R/B/W/T
TWY E	Asphalt, Concrete	23 m	PCR 629 F/B/X/T, PCR 1 006 R/B/W/T (TWY C3, D3 Intersection)

TAXIWAY EDGE LIGHTS ON ALL TAXIWAYS.
Frequent vehicles and maintenance equipment on parallel TWY.

AIRCRAFT STANDS	
1, 2, 3, 4, 5 6L, 6R, 8, 9, 10, 12L, 12R, 13L, 13R	B737
11	A300
6, 7, 12	B747
71 ~ 78	DA40
13	A380-800, B747-8

LEGEND	
A1, A2	Taxiway
≡≡≡	RWY Holding Position
3	Aircraft Stand
---	Intermediate Holding Position
○ HS 1	Hot Spot with Ident
⊠	HELIPAD

STAND NR	INS COORDINATES FOR AIRCRAFT STANDS(WGS-84)	
1	36°43'14.23"N	127°29'42.64"E
2	36°43'15.12"N	127°29'44.08"E
3	36°43'15.95"N	127°29'45.59"E
4	36°43'16.93"N	127°29'47.18"E
5	36°43'17.82"N	127°29'48.61"E
6	36°43'19.32"N	127°29'50.21"E
6L	36°43'18.32"N	127°29'50.26"E
6R	36°43'19.15"N	127°29'51.61"E
7	36°43'20.55"N	127°29'52.68"E
8	36°43'21.35"N	127°29'55.09"E
9	36°43'22.36"N	127°29'56.74"E
10	36°43'23.26"N	127°29'58.18"E
11	36°43'24.88"N	127°29'59.43"E
12	36°43'26.50"N	127°30'02.03"E
12L	36°43'25.50"N	127°30'01.86"E
12R	36°43'26.31"N	127°30'03.19"E
13	36°43'28.04"N	127°30'04.48"E
13L	36°43'27.12"N	127°30'04.50"E
13R	36°43'27.94"N	127°30'05.81"E
71	36°43'09.79"N	127°29'48.30"E
72	36°43'10.25"N	127°29'47.86"E
73	36°43'10.71"N	127°29'47.42"E
74	36°43'11.18"N	127°29'46.98"E
75	36°43'09.08"N	127°29'47.15"E
76	36°43'09.54"N	127°29'46.71"E
77	36°43'10.00"N	127°29'46.27"E
78	36°43'10.46"N	127°29'45.83"E

Change : Information of marking aids for RWY 06L/24R and 06R/24L.