

# STANDARD ARRIVAL CHART-INSTRUMENT


VAR 6° W

APP01 125.45 (119.55)  
APP02 119.825 (119.55)

ATIS 126.45  
TWR 118.35 (118.7)

ZSNB NINGBO/Lishe  
RNAV RWY 31

BEARINGS ARE MAGNETIC.  
ALTITUDES, ELEVATIONS,  
AND HEIGHTS IN METERS.  
DME DISTANCES IN KILOMETERS.  
NAUTICAL MILES.



NOT TO SCALE


RNAV1  
GNSS, RADAR REQUIRED

or  
RNP1  
GNSS

A NH2 holding procedure need radar guidance.

TL 3600  
TA 3000  
3300 (QNH ≥ 1031hPa)  
2700 (QNH ≤ 979hPa)

ANDONG  
114.8 AND  
CH 95X  
N30 15.4E121 13.3



Changes: APP frequency.

ZHOUSHAN  
112.3 HSN  
CH 70X  
N29 55.9E122 21.8

LISHE  
227 BK  
N29 53.7E121 20.0

SHENGZHOU  
113.4 SHZ  
CH 81X  
N29 36.0E120 49.0

STAR	ROUTING
ISP-91A (by ATC)	ISPUR-OVNEV-NB211
HSN-91A	HSN-OVNEV-NB111-NB208-NB302-NB204
HSN-92A (by ATC)	HSN-OVNEV-NB211
SHZ-91A	SHZ-NB206-NB303-NB205-NB204
AND-91A	AND-NB107-NB210-NB208-NB302-NB204
AND-92A (by ATC)	AND-OVNEV-NB211

