
N30°17.4'E104°26.6' ELEV 442.5m


D-ATIS(English) 127.075 D-ATIS(Chinese) 126.8 Delivery01 121.825(121.55) Delivery02 122.2(121.55)


ZUTF/TFU

TWR01 118.8(118.15) TWR02 130.5(118.15) TWR03 124.375(118.15)

GND01 121.925(121.55) GND02 122.6(121.55) GND03 121.775(121.55) APN01 122.7(122.15) APN02 122.825(122.15) APN03 122.15(122.7) APN04 122.675(122.15)







Note: RWY02/20, 11 marking is similar to RWY01/19.



TAKE-OFF MINIMA(WITH RELIABLE ALTN)(m)						LIGHTS		
ACFT Type		RWY01/19,02/20,11		LVP in force REDL RCLL		RWY01/02	RWY19/20	RWY11
		REDL	NIL(Day only)	RWY01/19/02/20/11	RWY01/02/11			
2 TURB ENG or 3&4 ENG	A B C D	RVR400	RVR500	RVR200 RVR250	een RVR150	PALS CAT III SFL PAPI RTZL REDL	PALS CAT I SFL PAPI REDL RCLL	REDL RCLL RENL
Other 1&2 ENG		RVR1600/VIS1600					RENL	
Note: Nil. RVR16007V151600 RCLL RENL RENL RENL								
Changes: New	ch	art.						