DATABASE CODING TABLE SHANGHAI/Hongqiao Waypoint Fly Magnetic Turn Altitude Navigation VPA/TCH Terminator ID over Course(°) Direction (m) (kt) Specification RWY18L/18R STAR SAS-61A ΙF SASAN 5000 RNAV1 2400 ΤF SS420 RNAV1 or by ATC TF SS204 MAX210 RNAV1 <u>600</u> RWY18L/18R STAR SAS-62A(by ATC) ΙF SASAN 5000 RNAV1 2400 ΤF SS420 RNAV1 or by ATC TF POMOK RNAV1 TF SS201 MAX210 RNAV1 600 RWY18L Approach Transition SS201 ΙF SS201 RNAV1 <u>600</u> MAX210 TF SF1 RNAV1 TF SS013 550 AT180 RNAV1 RWY18L Approach Transition SS204 ΙF SS204 MAX210 RNAV1 600 TF SS013 AT180 RNAV1 550 RWY18L Missed Approach CA183 300 RNP1 DF SS205 R 900 MAX210 RNP1 RWY18R Approach Transition SS201 IF SS201 MAX210 RNAV1 <u>600</u> TF SF1 RNAV1 RNAV1 ΤF SS033 <u>550</u> AT180 RWY18R Approach Transition SS204 SS204 MAX210 RNAV1 IF 600 TF SS033 <u>550</u> AT180 RNAV1 RWY18R Missed Approach 183 СА 300 RNP1 DF SS205 R 900 MAX210 RNP1 RWY18L/18R Missed Approach Holding(Outbound Time:1min) НМ SS205 003 ALT by ATC MAX230 RNAV1 RWY36L/36R STAR PUD-71A ΙF PUD RNAV1 ΤF SS205 <u>1800</u> RNAV1

SS405

PUD

TF

IF

Changes: Nil.

RWY36L/36R STAR PUD-72A

RNAV1

RNAV1

MAX210

600