DATABASE CODING TABLE SHANGHAI/Pudong Path Waypoint Fly Magnetic Turn Altitude IAS VPA/TCH Terminator ID over Course(°) Direction (m) (kt) Specification RWY16L/16R/17L/17R STAR AND-83A ΙF AND RNAV1 3000 TF PD208 RNAV1 or by ATC TF XSY RNAV1 2100 TF PD231 AT230 RNAV1 <u>1800</u> ΤF MP1 <u>600</u> or <u>900</u> MAX210 RNAV1 RWY16L Approach Transition PD201 ΙF PD201 MAX210 RNAV1 <u>600</u> TF PF7 RNAV1 TF PD073 600 RNAV1 RWY16L Approach Transition MP1 ΙF MP1 <u>600</u> MAX210 RNAV1 PF7 TF RNAV1 TF PD073 600 RNAV1 RWY16R Approach Transition PD201 PD201 MAX210 RNAV1 ΙF 600 ΤF PF3 RNAV1 TF 600 PD033 RNAV1 RWY16R Approach Transition MP1 IF MP1 600 MAX210 RNAV1 PF3 RNAV1 TF ΤF PD033 <u>600</u> RNAV1 RWY17L Approach Transition PD201 PD201 900 MAX210 RNAV1 PF1 RNAV1 TF TF PD013 900 RNAV1 RWY17L Approach Transition MP1 ΙF MP1 RNAV1 <u>900</u> MAX210 TF PF1 RNAV1 TF PD013 900 RNAV1 RWY17R Approach Transition PD201 RNAV1 IF PD201 900 MAX210 TF PF5 RNAV1 PD053 900 RNAV1 ΤF RWY17R Approach Transition MP1 MP1 MAX210 RNAV1 ΙF 900

Changes: Format adjustment.

PF5

TF

RNAV1