## NANNING/Wuxu

MINDAGE	CODINO	IADLL						NG/ WUX
Path	Waypoint	Fly	Magnetic	Turn	Altitude	IAS	VPA/TCH	Navigation
Terminator	ID	over	Course(°)	Direction	(m)	(km/h)	VPA/ICH	Specificatio
TF	P1							RNAV1
TF	NN412							RNAV1
TF	NN463					MAX460		RNAV1
TF	NN464							RNAV1
TF	NN466							RNAV1
TF	NN467							RNAV1
TF	NN473				<u>1628</u>			RNAV1
TF	NN457				1028	MAX380		RNAV1
			RWY05	STAR LON-	08A			
IF	LON							RNAV1
TF	XEREN							RNAV1
TF	WUY				<u>6900</u>			RNAV1
TF	NN459					MAX460		RNAV1
TF	NN461							RNAV1
TF	NN462							RNAV1
TF	NN463							RNAV1
TF	NN464							RNAV1
TF	NN466							RNAV1
TF	NN467							RNAV1
TF	NN473				<u>1628</u>			RNAV1
TF	NN457				1028	MAX380		RNAV1
			RWY05	STAR UVU-	08A			
IF	UVUNO							RNAV1
TF	WUY				<u>6900</u>			RNAV1
TF	NN459					MAX460		RNAV1
TF	NN461							RNAV1
TF	NN462							RNAV1
TF	NN463							RNAV1
TF	NN464							RNAV1
TF	NN466							RNAV1
TF	NN467							RNAV1
TF	NN473				<u>1628</u>			RNAV1
TF	NN457				1028	MAX380		RNAV1
	1	F	RWY05 Holdi	ng(Outbound	Time:1min)			
НМ	NN452	Y	138	R	2228	MAX460		RNAV1
НМ	NN456	Y	296	L	2228	MAX460		RNAV1
НМ	NN463	Y	280	R	2828	MAX460		RNAV1
НМ	NN469	Y	080	L	1928	MAX460		RNAV1
НМ	NN 4 7 1	Y	227	R	2828	MAX460		RNAV1