SHANGHAI/Pudong

Path	Waypoint	Fly	Magnetic	Turn	Altitude	IAS		Navigation
Terminator	ID	over	Course(°)	Direction	(m)	(kt)	VPA/TCH	Specificati
TF	PD231				2100			RNAV1
					<u>1800</u>	AT230		
TF	PD232				2100			RNAV1
TF	PD233							RNAV1
TF	PD234							RNAV1
TF	PD235				2100			RNAV1
TF	MP1				600 or 900	MAX210		RNAV1
			 RWY16L/16R/	171 / 17R STA				1
IF	ВК							RNAV1
TF	SAMKI				5700			RNAV1
TF	BAVIK				3700			RNAV1
	BAVII				3000			INVAVI
TF	PD208				or by ATC		RNA	RNAV1
TF	XSY				OI DY AIC			RNAV1
IF	731				2100			KNAVI
TF	PD231					AT230	RNAV1	
TF	MD1				1800	MAY 210		DNA)/1
I F	MP1		DWV161 /16D/	171 /17D CTA	600 or 900	MAX210		RNAV1
ır	AND		RWY16L/16R/	 	R AND-STA			DNIA)/1
IF	AND				7000			RNAV1
TF	PD208				3000			RNAV1
TC	VCV				or by ATC			DNAV4
TF	XSY				0100			RNAV1
TF	PD207				2100			RNAV1
TF	PDL				45.00			RNAV1
TF	PD202				<u>1500</u>			RNAV1
TF	PD201				600 or 900	MAX210		RNAV1
			RWY16L/16R/	1/L/1/R STAI	R AND-82A			
IF	AND							RNAV1
TF	PD208				3000			RNAV1
					or by ATC			
TF	XSY							RNAV1
TF	PD231				2100	AT230	RNAV1	
					<u>1800</u>			
TF	PD232				2100			RNAV1
TF	PD233							RNAV1
TF	PD234							RNAV1
TF	PD235				2100			RNAV1
TF	MP1				<u>600</u> or <u>900</u>	MAX210		RNAV1