

# INSTRUMENT APPROACH CHART-ICAO ZWTN/HTN

**5V-1**

AD ELEV 1447.0  
THR ELEV 1405.9

HETIAN/Kungang  
VOR/DME RWY11L

VAR2.5°E

Hotan Tower <b>TWR</b> <b>118.65</b> (130.0)		<b>VOR HTN</b> <b>113.1</b>	<b>Final Apch Crs</b> <b>112°</b>	<b>FAF D5.2 HTN</b> <b>1806</b> <b>(400)</b>	<b>MISSED APPROACH</b> Climb straight ahead to D4.0HTN, turn LEFT to HTN at 2400(900) or above, contact ATC.				
TL 4800 TA 4200 4500(QNH≥1031hPa) 3900(QNH≤979hPa) TH (2700) or by ATC		Note: 1. Missed approach turn MAX IAS205kt. 2. Circling N of RWY only.						BEARINGS ARE MAGNETIC. ALTITUDES, ELEVATIONS AND HEIGHTS IN METERS. ALL DISTANCES IN NAUTICAL MILES.	

DME (HTN)	8	7	6	5	4	3	2	1		
ALT				1788 (382)	1691 (285)	1594 (188)				

FAF-MAPt 3.0NM						
GS kt	80	100	120	140	160	180
min:sec	2:15	1:48	1:30	1:17	1:08	1:00
5.2m/s	2.1	2.7	3.3	3.8	4.3	4.9

VOR/DME			CIRCLING		
MDA(H)	OCA(H)	VIS	MDA(H)	OCA(H)	VIS
A			1687(240)	1593(146)	3500
B	1541(135)	1538(132)			
C			1717(270)	1657(210)	4000
D					

Changes: New chart.