SHANGHAI/Pudong

ATABASE				-	A11.2		TANGHA	
Path	Waypoint	Fly	Magnetic	Turn	Altitude	IAS	VPA/TCH	Navigation
Terminator	ID	over	Course(°)	Direction	(m)	(kt)		Specificati
TF	PD053				900			RNAV1
					g(Outbound Ti		1	1
НМ	PD220	Y	348	R	ALT by ATC	MAX230		RNP1
			· · ·	roach Holdin	g(Outbound T		T	1
НМ	PDL	Y	348	L	ALT by ATC	MAX230		RNP1
		RWY16L		R Holding(Ou	tbound Time:1		1	
НМ	PD208	Y	062	L	ALT by ATC	MAX230		RNAV1
НМ	PH1	Y	246	L	2400	MAX230		RNAV1
НМ	PH2	Υ	275	L	ALT by ATC	MAX230		RNAV1
НМ	PINOT	Υ	276	L	2400	MAX230		RNAV1
		RWY16L/	16R/17L/17R	Holding(Outl	oound Time:1.	5min)	_	
НМ	SH1	Υ	115	L	ALT by ATC	MAX250		RNAV1
НМ	SH2	Υ	115	R	ALT by ATC	MAX250		RNAV1
НМ	РН3	Υ	164	L	ALT by ATC	MAX250		RNAV1
НМ	PH4	Y	164	R	ALT by ATC	MAX250		RNAV1
		RI	WY34L/34R/	35L/35R ST	AR SAS-91A			
IF	SASAN				6000			RNAV1
TF	SS202							RNAV1
TF	SS420				4800			RNAV1
TF	JTN				<u>3900</u>			RNAV1
TF	PD408				3000			RNAV1
TF	PD404							RNAV1
TF	PD403							RNAV1
TF	PD402							RNAV1
TF	PD401				600 or 900	MAX220		RNAV1
		RV	VY34L/34R/.	35L/35R ST.	AR SAS-92A		1	
IF	SASAN				6000			RNAV1
TF	SS202							RNAV1
TF	SS420				4800			RNAV1
TF	JTN				3900			RNAV1
TF	PD408				3000			RNAV1
TF	PD431				1800	AT230		RNAV1
TF	MP2				600 or 900	MAX220		RNAV1
		RV	L VY34L/34R/.	1 35L/35R ST			<u> </u>	1
IF	SASAN				6000			RNAV1
TF	SS202							RNAV1
TF	SS420				4800			RNAV1
TF	JTN				3900			RNAV1
• •	J.11				3000		-	RNAV1