

## Lecture 3




Cheng-Ming Huang

EE, NTUT

# Mathematical Morphology

---

- ❑ Mathematical morphology works on shape
- ❑ Shape: prime carrier of information in machine vision
- ❑ Morphological operations:
  - simplify image data
  - preserve essential shape characteristics,
  - eliminate irrelevancies



# Binary Morphology

---

- ❑ Set theory: language of binary mathematical morphology
- ❑ Sets in mathematical morphology: represent shapes
- ❑ Category
  - Dilation, erosion: primary morphological operations
  - Opening, closing: composed from dilation, erosion
- ❑ Related to shape representation, decomposition, primitive extraction

# Binary Morphology

- 以二值化影像型態學為例，何時使用型態學處理？
  - 去除雜訊、簡化影像資料、保留重要區塊



灰階影像



二值化影像



型態學



連通元件

# Binary Morphology

---

- $A$  : 輸入影像
- $B$  : 結構元素(**structuring element**)
- 逐列逐行掃描輸入影像每一像素點，將其鄰近區域與結構元素，進行集合運算操作
- 結構元素又稱為核心(**kernel**)、遮罩(**mask**)、濾波器(**filter**)

0	1	0
1	1	1
0	1	0

 $B$ 


0	0	0	0	0
0	0	0	0	0
0	0	1	0	0
0	0	0	0	0
0	0	0	0	0

$A$

# Set Theory

---


- 定義集合  $A, B$  在歐式二維空間中  $\mathbb{Z}^2$  (**Euclidean 2-space**)
- 若  $a = (a_1, a_2)$  是  $A$  的元素，  
則  $a \in A$
- 若  $b$  不是  $A$  的元素，  
則  $b \notin A$




# Set Theory

## □ 聯集 $A \cup B$

- 包含  $A$  與  $B$  的所有元素



$$A \cup B$$




## □ 交集 $A \cap B$

- 同時屬於  $A$  與  $B$  的元素
- 若沒有交集，即  $A \cap B = \emptyset$  為空集合





$$A \cap B$$




$$A \cap B = \emptyset$$

## □ $A$ 為 $B$ 的子集合 $A \subseteq B$ ，則

- $A$  的所有元素完全包含於  $B$
- $A \cap B = A$
- $A \cup B = B$



$$A \cap B$$



$$A \cup B$$

# Set Theory

## □ 集合的數學描述式


## □ 例： $A = \{ a \mid a = b + c, \text{ for } b \in B \}$

此集合的元素

屬於此集合之元素  
須滿足的條件


大括號內為集合的描述

- $A$  集合的元素  $a$ ，為將  $B$  集合的所有元素  $b$  位移  $c = (c_1, c_2)$






# Set Theory



□  $A$  的補集  $A^c$

■ 不屬於  $A$  的元素


$$A^c = \{w \mid w \notin A\}$$



□  $A$  與  $B$  的差集  $A - B$

■ 屬於  $A$ ，但不屬於  $B$  的元素

$$A - B = \{w \mid w \in A, w \notin B\} = A \cap B^c$$



# Set Theory

## □ 集合的反射 $\hat{C}$




- 元素的座標乘上負號  $(x, y) \rightarrow (-x, -y)$

$$\hat{C} = \{w \mid w = -c, \text{ for } c \in C\}$$

## □ 集合的平移 $(C)_z$

- 將  $C$  集合的所有元素位移  $z = (z_1, z_2)$
- 元素的座標位移  $(x, y) \rightarrow (x + z_1, y + z_2)$

$$(C)_z = \{w \mid w = c + z, \text{ for } c \in C\}$$



# Binary Dilation

---

- Combine two sets by vector addition of set elements

- Dilation of A by B

Euclidean  $N$ -space:  $E^N$

$$A \oplus B$$

- Addition commutative  $\rightarrow$  dilation commutative

$$A \oplus B = B \oplus A$$




- A: referred as set (image)
- B: structuring element (kernel)

# Binary Dilation

## □ 膨脹的數學描述式

$$A \oplus B = \left\{ z \mid \underline{(\hat{B})_z} \cap A \neq \emptyset \right\}$$

- $B$  對於其原點反射得  $\hat{B}$ ，  
並平移此反射  $z$  單位 (逐列逐行掃描 平移  $z$ )
- 其位移與  $A$  重疊至少一個元素
- 滿足以上敘述之  $z$  點，即屬於  $A \oplus B$
- 又可描述為  $A \oplus B = \left\{ z \mid [(\hat{B})_z \cap A] \subseteq A \right\}$



$A \oplus B$




# Binary Dilation

## □ Example

$$A_t = \{c \in E^N \mid c = a + t \text{ for some } a \in A\}$$

$$A = \{(0, 1), (1, 1), (2, 1), (2, 2), (3, 0)\}$$



$$B = \{(0, 0), (0, 1)\}$$



$$A \oplus B = \{(0, 1), (1, 1), (2, 1), (3, 0) \\ (0, 2), (1, 2), (2, 2), (2, 3), (3, 1)\}$$

## □ Example

□ Dilation by kernel without origin:  
might not have  
common pixels with A



# Binary Dilation

---

□ Dilating  $A$  by kernel with origin guaranteed to contain  $A$

□ Addition associative  $\rightarrow$  dilation associative

$$(A \oplus B) \oplus C = A \oplus (B \oplus C)$$

□ Dilation distributes over union

$$(B \cup C) \oplus A = (B \oplus A) \cup (C \oplus A)$$


□ Dilating by union of two sets: the union of the dilation

$$A \oplus (B \cup C) = (A \oplus B) \cup (A \oplus C)$$


# Binary Dilation

- ❑ Decompose kernels to make dilations/erosions fast
- ❑ Example: dilate  $n \times n$  image by  $2^M$  kernel

computational complexity



# Binary Dilation



Historically, certain computer programs were written using only two digits rather than four to define the applicable year. Accordingly, the company's software may recognize a date using "00" as 1900 rather than the year 2000.



certain computer programs were written using only two digits rather than



four to define the applicable year. Accordingly, the company's software may recognize a date using "00" as 1900 rather than the year 2000.





# Binary Erosion



□ Erosion of A by B:  $A \ominus B$



□ 侵蝕的數學描述式


$$A \ominus B = \{ z \mid \underline{(B)_z} \subseteq A \}$$

- A 被 B 侵蝕，  
使得 B 位移  $z$  後 (逐列逐行掃描 平移  $z$ )，  
可被包含在 A 中
- 滿足以上敘述之  $z$  點，即屬於  $A \ominus B$



# Binary Erosion

- Eroding  $A$  by kernel without origin can have nothing in common with  $A$



**Figure 5.5** Erosion of a set  $A$  by a structuring element  $B$  that does not contain the origin. As a result, no point of the erosion is guaranteed to be in common with  $A$ . However, some translations of  $A \ominus B$  are contained in  $A$ .

# Binary Erosion

- Erosion of intersection of two sets: intersection of erosions  $(A \cap B) \ominus K = (A \ominus K) \cap (B \ominus K)$





Figure 5.7 An instance of the relationship  $(A \cap B) \ominus K = (A \ominus K) \cap (B \ominus K)$ .

# Binary Erosion

- Erosion of kernel of intersection of two sets:  
contains union of erosions


$$A \ominus (B \cap C) \supseteq (A \ominus B) \cup (A \ominus C)$$



**Figure 5.8** An instance in which  $A \ominus (B \cap C)$  is a proper superset of  $(A \ominus B) \cup (A \ominus C)$ , thereby showing that the general relation  $A \ominus (B \cap C) \supseteq (A \ominus B) \cup (A \ominus C)$  cannot be made any stronger.

# Binary Erosion

□ Erosion Dilation Duality  $(A \ominus B)^c = A^c \oplus \check{B}$



**Figure 5.6** Duality relation between erosion and dilation. The set  $A$  eroded by  $B$  is the complement of the set  $A^c$  dilated by  $\check{B}$ . By convention, we understand that for the complemented set  $A^c$  or  $A^c \oplus \check{B}$ , all pixels outside the area illustrated are binary-1 pixels.

# Binary Erosion

---



- Chain rule for erosion holds when kernel decomposable through dilation

$$A \ominus (B \oplus C) = (A \ominus B) \ominus C$$

- Duality does not imply cancellation on morphological equalities

$$(B \ominus C) \oplus C \neq B$$

# Binary Erosion



# Binary Morphology

---

- Opening of image B by kernel K

$$B \circ K = (B \ominus K) \oplus K$$

- Closing of image B by kernel K

$$B \bullet K = (B \oplus K) \ominus K$$

- Opening with disk kernel

- smooths contours, breaks narrow isthmuses
- eliminates small islands, sharp peaks, capes


- Closing by disk kernel

- smooths contours, fuses narrow breaks, long, thin gulfs
- closing with disk kernel: eliminates small holes, fill gaps on the contours




# Binary Morphology

- Opening  
erosion, then dilation








- Closing  
dilation, then erosion







# Binary Morphology

- Opening  
erosion, then dilation



$$A \circ B = (A \ominus B) \oplus B$$

- Closing  
dilation, then erosion




$$A \bullet B = (A \oplus B) \ominus B$$

# Binary Morphology

## □ Erosion


$$A \ominus B = \{z \in E \mid B_z \subseteq A\}$$



**Original: dark**  
**Result: light**


## □ Dilation

$$A \oplus B = \bigcup_{b \in B} A_b$$



## □ Opening


$$A \circ B = (A \ominus B) \oplus B$$



## □ Closing

$$A \bullet B = (A \oplus B) \ominus B$$

**Original: dark**  
**Result: light + dark**



# Binary Morphology

---



dilation



binary image



erosion




opening




closing

# Applications of Binary Morphology



**Figure 5.16** Extraction of the body and handle of a shape  $F$  by opening with  $L$  for the body and taking the residue of the opening for the handle; (a)  $F$ , (b)  $F \circ L$ , and (c)  $F - F \circ L$ .





**Figure 5.17** Extraction of the trunk and arms of a shape  $F$  by opening with vertically and horizontally oriented structuring elements.

# Applications of Binary Morphology

---


□ Boundary extraction

□ Region filling




# Applications of Binary Morphology

---




(a)




(b)

**Figure 5.19** (a) A binary image. (b) Opening of (a) with a disk structuring element.



(a)



(b)


**Figure 5.23** (a) A binary image with five clusters of points. Points within each cluster satisfy the partition property with distance  $\rho_0$ , and the clusters are farther from each other than  $2\rho_0$  pixels. (b) The image of (a) closed by a disk with a radius just greater than  $2\rho_0$ .

# Applications of Binary Morphology


---

☐ Extract connected component


☐ Convex Hull




☐ Thinning




☐ Thickening



☐ Skeleton




☐ Pruning





# Binary Morphology

## □ Noise removal







# Hit-and-Miss Transform

- ❑ Selects corners, isolated points, border points
- ❑ Intersection of erosions

$$A \otimes (J, K) = (A \ominus J) \cap (A^c \ominus K)$$

- ❑ Example: find upper right-hand corner



# Hit-and-Miss Transform




Figure 5.11 Location of upper right-hand corner points by the hit-and-miss transform.

# Binary Morphology


## □ Hit-and-miss (Hit-or-miss)

using kernel J 和原始影像做erosion；


using kernel K 和（255－原始影像）做erosion；

然後再將兩者的結果取交集


original image



J




K



J




K



# 車牌影像偵測

## □ 流程圖



- 去除二值化影像中車牌的雜訊，提升偵測率
- 斷開處理（侵蝕後 再膨脹）
- 原圖大小：**1280\*800**
- 車牌候選影像區域, 最小：**200\*100**、最大：**300\*200**
- 結構元素：正方形 **3\*3**