

# Group\_tssl\_lab4

October 28, 2022

## 1 TSSL Lab 4 - Recurrent Neural Networks

In this lab we will explore different RNN models and training procedures for a problem in time series prediction.

```
[28]: import numpy as np
import tensorflow as tf
from tensorflow import keras
from tensorflow.keras import layers
import pandas
import matplotlib.pyplot as plt

plt.rcParams["figure.figsize"] = (10,6) # Increase default size of plots
```

Set the random seed, for reproducibility

```
[29]: np.random.seed(42)
tf.random.set_seed(42)
```

### 1.1 1. Load and prepare the data

We will build a model for predicting the number of [sunspots](#). We work with a data set that has been published on [Kaggle](#), with the description:

*Sunspots are temporary phenomena on the Sun's photosphere that appear as spots darker than the surrounding areas. They are regions of reduced surface temperature caused by concentrations of magnetic field flux that inhibit convection. Sunspots usually appear in pairs of opposite magnetic polarity. Their number varies according to the approximately 11-year solar cycle.*

The data consists of the monthly mean total sunspot number, from 1749-01-01 to 2017-08-31.


```
[31]: # Read the data
data=pandas.read_csv('Sunspots.csv',header=0)
dates = data['Date'].values
y = data['Monthly Mean Total Sunspot Number'].values
ndata=len(y)
print(f'Total number of data points: {ndata}')

# We define a train/test split, here with 70 % training data
```

```
ntrain = int(ndata*0.7)
ntest = ndata-ntrain
print(f'Number of training data points: {ntrain}')
```

Total number of data points: 3252  
Number of training data points: 2276

```
[32]: plt.plot(dates[:ntrain], y[:ntrain])
plt.plot(dates[ntrain:], y[ntrain:])
plt.xticks(range(0, ndata, 300), dates[::300], rotation = 90); # Show only one
↪ tick every 25th year for clarity
```



There is a clear seasonality to the data, but the amplitude of the peaks very quite a lot. Also, we note that the data is nonnegative, which is natural since it consists of counts of sunspots. However, for simplicity we will not take this constraint into account in this lab assignment and allow ourselves to model the data using a Gaussian likelihood (i.e. using MSE as a loss function).

From the plot we see that the range of the data is roughly  $[0, 400]$  so as a simple normalization we divide by the constant `MAX_VAL=400`.

```
[33]: MAX_VAL = 400
y = y/MAX_VAL
```

## 1.2 2. Baseline methods

Before constructing any sophisticated models using RNNs, let's consider two baseline methods,

1. The first baseline is a “naive” method which simply predicts  $y_t = y_{t-1}$ .
2. The second baseline is an AR( $p$ ) model (based on the implementation used for lab 1).

We evaluate the performance of these method in terms of mean-squared-error and mean-absolute-error, to compare the more advanced models with later on.

```
[34]: def evaluate_performance(y_pred, y, split_time, name=None):
    """This function evaluates and prints the MSE and MAE of the prediction.

    Parameters
    -----
    y_pred : ndarray
        Array of size (n,) with predictions.
    y : ndarray
        Array of size (n,) with target values.
    split_time : int
        The leading number of elements in y_pred and y that belong to the
    ↪ training data set.
        The remaining elements, i.e. y_pred[split_time:] and y[split_time:] are
    ↪ treated as test data.
    """

    # Compute error in prediction
    resid = y - y_pred

    # We evaluate the MSE and MAE in the original scale of the data, i.e. we
    ↪ add back MAX_VAL
    train_mse = np.mean(resid[:split_time]**2)*MAX_VAL**2
    test_mse = np.mean(resid[split_time:]**2)*MAX_VAL**2
    train_mae = np.mean(np.abs(resid[:split_time]))*MAX_VAL
    test_mae = np.mean(np.abs(resid[split_time:]))*MAX_VAL

    # Print
    print(f'Model {name}\n Training MSE: {train_mse:.4f}, MAE: {train_mae:.
    ↪4f}\n Testing MSE: {test_mse:.4f}, MAE: {test_mae:.4f}')
```

**Q1:** Implement the naive baseline method which predicts according to  $\hat{y}_{t|t-1} = y_{t-1}$ . Since the previous value is needed for the prediction we do not get a prediction at  $t = 1$ . Hence, we evaluate the method by predicting values at  $t = 2, \dots, n$  (cf. an AR( $p$ ) model where we start predicting at  $t = p + 1$ ).

```
[35]: # Store the predictions in an array of length ndata-1. Note that there is a
    ↪ shift in the indices
    # between the prediction and the observation sequence, since there is no
    ↪ prediction available for the first observation.
```

```

# Specifically, y_pred_naive[t] is a prediction of y[t+1], so the first element
↳ of y_pred_naive is a prediction of the
# second element of y, and so on. We will use the same "bookkeeping convention"
↳ throughout the lab, so it is important that
# you understand it!
y_pred_naive = np.repeat(y[0], ndata-1)

evalutate_performance(y_pred_naive, # Predictions
                      y[1:],        # Correspondsing target values
                      ntrain-1,      # Number of leading elements in the input
↳ arrays corresponding to training data points
                      name='Naive')

```

Model Naive

```

Training MSE: 4453.5391,    MAE: 56.0993
Testing MSE:  5673.2161,    MAE: 63.8356

```

Next, we consider a slightly more advanced baseline method, namely an  $AR(p)$  model.

```

[36]: # We import two functions that were written as part of lab 1
from tssltools_lab4 import fit_ar, predict_ar_1step

p=30 # Order of the AR model (set by a few manual trials)
ar_coef = fit_ar(y[:ntrain], p) # Fit the model to the training data

# Predict. Note that y contains both training and validation data,
# and the prediction is for the values y_{p+1}, ..., y_{n}.
y_pred_ar = predict_ar_1step(ar_coef, y)

```

```

[37]: evalutate_performance(y_pred_ar, # The prediction array is of length n-p
                             y[p:],    # Corresponding target values
                             ntrain-p,  # Number of leading elements in the input
↳ arrays corresponding to training data points
                             name='AR')

```

Model AR

```

Training MSE: 603.8656,    MAE: 17.3420
Testing MSE:  590.3732,    MAE: 17.6221

```

### 1.3 3. Simple RNN

We will now construct a model based on a recurrent neural network. We will initially use the SimpleRNN class from *Keras*, which correspond to the basic Jordan-Elman network presented in the lectures.

**Q2:** Assume that we construct an “RNN cell” using the call `layers.SimpleRNN(units = d, return_sequences=True)`. Now, assume that an array  $X$  with the dimensions  $[Q, M, P]$  is fed as the input to the above object. We know that  $X$  contains a set of sequences (time series) with equal lengths. Specify which of the symbols  $Q, M, P$  that corresponds to each of the items below:

- The length of the sequences (number of time steps) - The number of features (at each time step), i.e. the dimension of each time series - The number of sequences

Furthermore, specify the values of  $Q, M, P$  for the data at hand (treated as a single time series).

*Hint:* Read the documentation for [SimpleRNN](#) to find the answer.

**A2:** For this data, the length of sequence is  $M(3252)$ , number of feature  $P(1)$  number of sequences  $Q(1)$ .

**Q3:** Continuing the question above, answer the following:

- What is the meaning of setting `units = d`?
- Assume that we pass a single time series of length  $n$  as input to the layer. Then what is the dimension of the *output*?
- If we would had set the parameter `return_sequences=False` when constructing the layer, then what would be the answer to the previous question?

**A3:**

1  $d$  is the output dimension

2 the dimension would be  $(1, n, d)$

3 if its false, then there the iterated sequences will be drop and only return the sequence from last iteration last run.

In *Keras*, each layer is created separately and are then joined by a `Sequential` object. It is very easy to construct stacked models in this way. The code below corresponds to a simple Jordan-Elman Network on the form,

$$\mathbf{h}_t = \sigma(W\mathbf{h}_{t-1} + Uy_{t-1} + b),$$

$$\hat{y}_{t|t-1} = C\mathbf{h}_t + c,$$

*Note:* It is not necessary to explicitly specify the input shape, since this can be inferred from the input on the first call. However, for the `summary` function to work we need to tell the model what the dimension of the input is so that it can infer the correct sizes of the involved matrices. Also note that in *Keras* you can sometimes use `None` when some dimensions are not known in advance.

```
[38]: d = 10 # hidden state dimension

model0=keras.Sequential([
    # Simple RNN layer
    layers.SimpleRNN(units = d, input_shape=(None,1), return_sequences=True,
    ↪activation='tanh'),
    # A linear output layer
    layers.Dense(units = 1, activation='linear')
])

# We store the initial weights in order to get an exact copy of the model when
↪trying different training procedures
model0.summary()
init_weights = model0.get_weights().copy()
```

Model: "sequential"

Layer (type)	Output Shape	Param #
simple_rnn (SimpleRNN)	(None, None, 10)	120
dense (Dense)	(None, None, 1)	11

=====  
Total params: 131  
Trainable params: 131  
Non-trainable params: 0  
=====

**Q4:** From the model summary we can see the number of parameters associated with each layer. Relate these numbers to the dimensions of the weight matrices and bias vectors  $\{W, U, b, C, c\}$  in the mathematical model definition above.

**A4:**

For hidden, we have hidden state with 10 dimension, so  $Wh_{t-1}$  this matrix product will have **1010 parameter**,  $Uy_{t-1}$  is **101** and also for b is  $**10*1**$  so in total is  $100+10+10=120$ .

For Dense, the input dimension is 10 output is 1 and also consider bias we have  $10*1+1 = 11$

## 1.4 4. Training the RNN model

In this section we will consider a few different ways of handling the data when training the simple RNN model constructed above. As a first step, however, we construct explicit input and target (output) arrays for the training and test data, which will simplify the calls to the training procedures below.

The task that we consider in this lab is one-step prediction, i.e. at each time step we compute a prediction  $\hat{y}_{t|t-1} \approx y_t$  which depend on the previous observations  $y_{1:t-1}$ . However, when working with RNNs, the information contained in previous observations is aggregated in the *state* of the RNN, and we will only use  $y_{t-1}$  as the *explicit input* at time step  $t$ .

Furthermore, when addressing a problem of time series prediction it is often a good idea to introduce an explicit skip connection from the input  $y_{t-1}$  to the prediction  $\hat{y}_{t|t-1}$ . Equivalently, we can *define the target value* at time step  $t$  to be the residual  $\tilde{y}_t := y_t - y_{t-1}$ . Indeed, if the model can predict the value of the residual, then we can simply add back  $y_{t-1}$  to get a prediction of  $y_t$ .

Taking this into consideration, we define explicit input and output arrays as shifted versions of the data series  $y_{1:n}$ .

```
[39]: # Training data
x_train = y[:ntrain-1] # Input is denoted by x, training inputs are x[0]=y[0], ...
      ↪ ..., x[ntrain-1]=y[ntrain-1]
yt_train = y[1:ntrain] - x_train # Output is denoted by yt, training outputs
      ↪ are yt[0]=y[1]-y[0], ..., yt[ntrain-1] = y[ntrain]-y[ntrain-1]

# Test data
```

```

x_test = y[ntrain-1:-1] # Test inputs are x_test[0] = y[ntrain-1], ...,
↳ x_test[n_test] = y[n-1]
yt_test = y[ntrain:] - x_test # Test outputs are yt_test[0] =
↳ y[ntrain]-y[ntrain-1], ..., yt_test[n_test] = y[n]-y[n-1]

# Reshape the data
x_train = x_train.reshape((1,ntrain-1,1))
yt_train = yt_train.reshape((1,ntrain-1,1))
x_test = x_test.reshape((1,n_test,1))
yt_test = yt_test.reshape((1,n_test,1))

```

#### 1.4.1 Option 1. Process all data in each gradient computation (“do nothing”)

The first option is to process all data at each iteration of the gradient descent method.

```

[40]: model1 = keras.models.clone_model(model0) # This creates a new instance of the
↳ same model
model1.set_weights(init_weights) # We set the initial weights to be the same
↳ for all models

```

**Q5:** What should we set the *batch size* to, in order to compute the gradient based on the complete training data sequence at each iteration? Complete the code below!

*Note:* You can set `verbose=1` if you want to monitor the training progress, but if you do, please **clear the output of the cell** before generating a pdf with your solutions, so that we don’t get multiple pages with training errors in the submitted reports.

```

[42]: model1.compile(loss='mse', optimizer='rmsprop', metrics=['mse'])
history = model1.fit(x_train, yt_train,
                    epochs = 200,
                    batch_size = 1,
                    verbose = 0,
                    validation_data = (x_test, yt_test))


```

We plot the training and test error vs the iteration (epoch) number, using a helper function from the `tssltools_lab4` module.

```

[43]: from tssltools_lab4 import plot_history
start_at = 10 # Skip the first few epochs for clarity
plot_history(history, start_at)

```



**Q6:** Finally we compute the predictions of  $\{y_t\}$  for both the training and test data using the model's `predict` function. Complete the code below to compute the predictions.

*Hint:* You need to reshape the data when passing it to the `predict` to comply with the input shape used in *Keras* (cf. above).

*Hint:* Since the model is trained on the residuals  $\tilde{y}_t$ , don't forget to add back  $y_{t-1}$  when predicting  $y_t$ . However, make sure that you don't “cheat” by using a non-causal predictor (i.e. using  $y_t$  when predicting  $y_t$ )!

```
[45]: # Predict on all data using the final model.
x_data1 = y[:ndata-1]
x_data1 = x_data1.reshape((1,ndata-1,1))
# We predict using y_1,...,y_{n-1} as inputs, resulting in predictions of the
# values y_2, ..., y_n.
# That is, y_pred1 should be an (n-1,) array where element y_pred[t] is based
# only on values y[:t]
y_pred1 = model1.predict( x_data1 ).flatten() + y[1:ndata]
```

1/1 [=====] - 1s 810ms/step

Using the prediction computed above we can plot them and evaluate the performance of the model in terms of MSE and MAE.

```
[46]: def plot_prediction(y_pred):
    # Plot prediction on test data
    plt.plot(dates[ntrain:], y[ntrain:])
```




```
plt.plot(dates[ntrain:], y_pred[ntrain-1:])
plt.xticks(range(0, ntest, 300), dates[ntrain::300], rotation = 90); #
↪ Show only one tick every 25th year for clarity
plt.legend(['Data', 'Prediction'])
plt.title('Predictions on test data')
```

```
[47]: # Plot prediction
plot_prediction(y_pred1)

# Evaluate MSE and MAE (both training and test data)
evalutate_performance(y_pred1, y[1:], ntrain-1, name='Simple RNN, "do nothing"')
```

Model Simple RNN, "do nothing"  
 Training MSE: 139.9240, MAE: 8.7518  
 Testing MSE: 138.9893, MAE: 8.9234



### 1.4.2 Option 2. Random windowing

Instead of using all the training data when computing the gradient for the numerical optimizer, we can speed it up by restricting the gradient computation to a smaller window of consecutive time steps. Here, we sample a random window within the training data and “pretend” that this window is independent from the observations outside the window. Specifically, when processing

the observations within each window the hidden state of the RNN is initialized to zero at the first time point in the window.

To implement this method in Python, we will make use of a *generator function*. A generator is a function that can be paused, return an intermediate value, and then resumed to continue its execution. An intermediate return value is produced using the `yield` keyword.

Generators are used in *Keras* to implement infinite loops that feed the training procedure with training data. Specifically, the `yield` statement of the generator should return a pair `x`, `y` with inputs and corresponding targets from the training data. Each epoch of the training procedure will then call the generator for a total of `steps_per_epoch` such `yield` statements.

```
[48]: def generator_train(window_size):
        while True:
            """The upper value is excluded in randint, so the maximum value that we
            ↪ can get is tt = ntrain-window_size-1.
            Hence, the maximum end point of a window is ntrain-1, in agreement with
            ↪ the fact that the size of input/output is ntrain-1
            when working with one-step-ahead prediction."""
            start_of_window = np.random.randint(0, ntrain - window_size) # First
            ↪ time index of window (inclusive)
            end_of_window = start_of_window + window_size # Last time index of
            ↪ window (exclusive, i.e. this is really the first index after the window)
            yield x_train[:,start_of_window:end_of_window,:], yt_train[
            ↪ ,start_of_window:end_of_window,:]
```

```
[49]: model2 = keras.models.clone_model(model0) # This creates a new instance of the
            ↪ same model
        model2.set_weights(init_weights) # We set the initial weights to be the same
            ↪ for all models
```


**Q7:** Assume that we process a window of observations of length `window_size` at each iteration. Then, how many gradient steps per epoch can we afford, for computational cost per epoch to be comparable to the method considered in Option 1? Set the `steps_per_epoch` parameter of the fitting function based on your answer.

```
[51]: window_size = 100
        model2.compile(loss='mse', optimizer='rmsprop', metrics=['mse'])
        history = model2.fit(generator_train(window_size),
                               epochs = 200,
                               verbose = 0,
                               steps_per_epoch = int(ntrain/window_size) ,
                               validation_data = (x_test, yt_test))
        print('finish')
```

finish

Similarly to above we plot the error curves vs the iteration (epoch) number.

```
[52]: plot_history(history, start_at)
```



**Q8:** Comparing this error plot to the one you got for training Option 1, can you see any *qualitative* differences? Explain the reason for the difference.

**A8:** The Option2 error curve converge faster, that's because in option2 we have many updates run in parallel, so we can witness lower error in the first 50 epoch in option2 than option1.

**Q9:** Compute a prediction for all values of  $\{y_2, \dots, y_n\}$  analogously to **Q6**.


```
[53]: # Predict on all data using the final model.
# We predict using y_1,...,y_{n-1} as inputs, resulting in predictions of the
# values y_2, ..., y_n
y_pred2 = model2.predict( x_data1 ).flatten() + y[1:ndata]
```

```
1/1 [=====] - 1s 747ms/step
```

```
[54]: # Plot prediction on test data
plot_prediction(y_pred2)

# Evaluate MSE and MAE (both training and test data)
evalutate_performance(y_pred2, y[1:], ntrain-1, name='Simple RNN, windowing')
```

```
Model Simple RNN, windowing
Training MSE: 155.0455, MAE: 8.9405
Testing MSE: 161.8407, MAE: 9.1183
```



### 1.4.3 Option 3. Sequential windowing with stateful training

As a final option we consider a model aimed at better respecting the temporal dependencies between consecutive windows. This is based on “statefulness” which simply means that the RNN remembers its hidden state between calls. That is, if model is in stateful mode and is used to process two sequences of inputs after each other, then the final state from the first sequence is used as the initial state for the second sequence.

```
[55]: # To enable stateful training, we need to create model where we set
      ↪ stateful=True in the RNN layer
model3=keras.Sequential([
    # Simple RNN layer with stateful=True
    layers.SimpleRNN(units = d, batch_input_shape=(1,None,1),
    ↪ return_sequences=True, stateful=True, activation='tanh'),
    # A linear output layer
    layers.Dense(1, activation='linear')
])
model3.set_weights(init_weights)
```

**Q10:** When working with stateful training we need to make some adjustments to the training data generator.

1. First, the RNN model doesn't keep track of the actual time indices of the different windows

that it is fed. Hence, if we feed the model randomly selected windows, it will still treat them as if they were consecutive, and retain the state from one window to the next. To avoid this, we therefore need to make sure that the generator outputs windows of training data that are indeed consecutive (and not randomly selected as above).

2. When training the model we will process the whole training data multiple times (i.e. we train for multiple epochs). However, if we have statefulness *between epochs* this would effectively result in a “circular dependence”, where the final state at time step  $t = n_{\text{train}}$  would be used as the initial state at time  $t = 1$ . To avoid this, we can manually reset the state of the model by calling `model.reset_states()`.

Taking these two points into consideration, complete the code for the stateful data generator below.

```
[56]: def generator_train_stateful(window_size, model):
    """In addition to the window_size, the generator also takes the model as
    ↪input so
    that we can reset the RNN states at appropriate intervals."""

    # Compute the total number of windows of length window_size that we need to
    ↪cover all the training data.
    # Note 1. The length of x_train (and yt_train) is ntrain-1 since we work
    ↪with 1-step prediction.
    # Note 2. The final window could be smaller than window_size, if
    ↪(ntrain-1) is not evenly divisible by the window_size.
    number_of_windows = int( ndata/window_size )

    while True:
        for i in range(number_of_windows):
            # First time index of window (inclusive)
            start_of_window = i*window_size

            # Last time index of window (exclusive, i.e. this is the index to
            ↪the first time step after the window)
            # Note 3. Python allows using end_of_window > ntrain-1, it will
            ↪simply truncate the indexing at the final element of the array!
            end_of_window = (i+1)*window_size

            yield x_train[:,start_of_window:end_of_window,:], yt_train[
            ↪,start_of_window:end_of_window,:]


            """NOTE! In addition to replacing the ????? with the correct code, you
            ↪need to move the line"""
            model.reset_states()
            """to the correct place in the function definition above!"""
```

With the generator defined we can train the model.

```
[57]: window_size = 100
model3.compile(loss='mse', optimizer='rmsprop', metrics=['mse'])
history = model3.fit(generator_train_stateful(window_size, model3),
                    epochs = 200,
                    verbose = 0,
                    steps_per_epoch = ntrain//window_size,
                    validation_data = (x_test, yt_test))
```

Similarly to above we plot the error curves vs the iteration (epoch) number.

```
[58]: plot_history(history, start_at)
```



**Q11:** Comparing this error plot to the one you got for training Options 1 and 2, can you see any *qualitative* differences?

*Optional:* If you have a theory regarding the reason for the observed differences, feel free to explain!

**A11:**

Observation:

The training error is similar to option2 and lower than option1 in the first 50 epoches because option2 and 3 update multiple times in one epoch. The training error in option3 seems to be the combination of a trend and a seasonality.

**Q12:** Compute a prediction for all values of  $\{y_2, \dots, y_n\}$  analogously to **Q6**.

```
[59]: # Predict on all data using the final model.
```


```
# We predict using y_1,...,y_{n-1} as inputs, resulting in predictions of the
↪ values y_2, ..., y_n
y_pred3 = model3.predict( x_data1 ).flatten() + y[1:ndata]
```

1/1 [=====] - 1s 713ms/step

```
[60]: # Plot prediction on test data
plot_prediction(y_pred3)

# Evaluate MSE and MAE (both training and test data)
evalutate_performance(y_pred3, y[1:], ntrain-1, name='Simple RNN, windowing/
↪stateful')
```

Model Simple RNN, windowing/stateful  
 Training MSE: 153.0344, MAE: 8.9033  
 Testing MSE: 152.5176, MAE: 8.9782



## 1.5 5. Reflection

**Q13:** Which model performed best? Did you manage to improve the prediction compared to the two baseline methods? Did the RNN models live up to your expectations? Why/why not? Please reflect on the lab using a few sentences.

**A13:** It's clear that statful training and random window are better than simply one sequence. Although they share the similar MAE and MSE, but last two methods converge faster. Since our data here is simple scalar numeric data, the correlation between each timestamp is easy to be encoded so RNN performance match our expectations. We could try some methods like cross-validation to fine-tuning the number of hidden states or testing more layers to reach even better performance.

## 1.6 6. A more complex network (OPTIONAL)

If you are interested, feel free to play around with more complex models and see if you can improve the predictive performance! It is very easy to build stacked models in *Keras*, see the example below.

```
[ ]: # A stacked model with 3 layers of LSTM cells, two Dense layers with Relu
      ↪ activation and a final linear output layer
model4 = tf.keras.models.Sequential([
    tf.keras.layers.LSTM(64, batch_input_shape=(1,None,1), return_sequences=True,
    ↪stateful=True),
    tf.keras.layers.LSTM(64, batch_input_shape=(1,None,1), return_sequences=True,
    ↪stateful=True),
    tf.keras.layers.LSTM(64, batch_input_shape=(1,None,1), return_sequences=True,
    ↪stateful=True),
    tf.keras.layers.Dense(32, activation="relu"),
    tf.keras.layers.Dense(16, activation="relu"),
    tf.keras.layers.Dense(1),
])

model4.summary()
```

We can store the best model in a file, so that we can load it after analysing the training procedure.

```
[ ]: checkpoint_filepath = './'
model_checkpoint_callback = tf.keras.callbacks.ModelCheckpoint(
    filepath=checkpoint_filepath,
    save_weights_only=True,
    monitor='val_loss',
    save_best_only=True) # Save only the best model, determined by the
    ↪validation loss
```

Train the model

```
[ ]: window_size = 100
model4.compile(loss='mse', optimizer='rmsprop', metrics=['mse'])
history = model4.fit(generator_train_stateful(window_size, model4),
    epochs = 200,
    verbose = 0,
    steps_per_epoch = ntrain//window_size,
    validation_data = (x_test, yt_test),
    callbacks=[model_checkpoint_callback])
```



```
[ ]: plot_history(history, start_at)
```

**Q14 (optional):** Based on the training and test error plots, are there signs of over- or underfitting?

**A14:**

We load the best model from checkpoint.

```
[ ]: model4.load_weights(checkpoint_filepath)
```

```
[ ]: # Predict on all data using the final model.
# We predict using y_1,...,y_{n-1} as inputs, resulting in predictions of the
# values y_2, ..., y_n
y_pred4 = model4.predict(????).flatten() + ????
```

```
[ ]: # Predict on all data using the final model.
# We predict using y_1,...,y_{n-1} as inputs, resulting in predictions of the
# values y_2, ..., y_n
y_pred4 = model4.predict(y[:-1].reshape(1, ndata-1, 1)).flatten() + y[:-1]
```

```
[ ]: # Plot prediction on test data
plot_prediction(y_pred4)

# Evaluate MSE and MAE (both training and test data)
evaluate_performance(y_pred4, y[1:], ntrain-1, name='Stacked RNN, windowing/
# stateful')
```