

# Arophix



## Android Apk reverse engineering using Apktool

# and Frida

---

ON [APRIL 22, 2019](#) / BY [RUSSELL](#) / IN [ANDROID](#), [HOOKING](#), [REVERSE ENGINEERING](#)

## Android Apk reverse engineering using Apktool and Frida

### Table of Content

1. Environment Setup (macOS mojave)
2. Tamper Smali Code
3. Hooking Android Java Methods
4. Hooking Android C Functions
5. References

### Environment Setup (macOS mojave)

All the steps mentioned below are on macOS Mojave

## Install Tools on PC

### 1. Install `frida-tools` with `pip3`

Run command `$ pip --version` and `$ pip3 --version` to check which *pip* is from at **Python 3x**. E.g. you should see version information like below:

```
$ pip 19.0.3 from /usr/local/lib/python3.7/site-packages/pip (python 3.7)
```

Then run the right **pip** command to install `frida-tools` , e.g. `pip3`

```
$ pip3 install frida-tools
```

Success outputs:

```
....  
Successfully built frida-tools frida  
  
Installing collected packages: colorama, frida, six, wcwidth, prompt-toolkit, pygments, frida-tools
```

```
Successfully installed colorama-0.4.1 frida-12.4.7 frida-tools-1.3.2 prompt-toolkit-2.0.9 pygments-2.3.1  
six-1.12.0 wcwidth-0.1.7
```

## 2. Testing your installation

Copy the `cat` binary to a temporary folder, e.g., `/tmp/cat` then run `cat` from that directory:

```
$ mkdir ~/frida  
$ cp /bin/cat /frida/cat  
$ /frida/cat
```

In another terminal, make a file `example.py` with the following contents:

```
import frida  
  
def on_message(message, data):  
    print("[on_message] message:", message, "data:", data)  
  
session = frida.attach("cat")  
  
script = session.create_script('""use strict';
```

```
rpc.exports.enumerateModules = function () {  
    return Process.enumerateModulesSync();  
};  
""")  
script.on("message", on_message)  
script.load()  
  
print([m["name"] for m in script.exports.enumerate_modules()])
```

Then run the `example.py` script with below command

```
$ python3 example.py
```

The output should be something similar to this (depending on your platform and library versions):

```
[u'cat', ..., u'ld-2.15.so']
```

### 3. Android `adb` command

Make sure `adb` can see your device:

```
$ adb devices -l
```

This will also ensure that the adb daemon is running on your desktop, which allows Frida to discover and communicate with your device regardless of whether you've got it hooked up through USB or WiFi.

## Install `frida-server` on Emulator (or Real Device)

Below steps are based on **Android Emulator Nexus 6P (x86)** api 23 on macOS Majave.

First off, download the latest `frida-server` for Android from [frida-server releases page](#), e.g. for Android `x86` emulator, you should download `frida-server-12.4.7-android-x86.xz`, and get it run on your emulator:

```
$ adb root # might be required
$ adb push frida-server /data/local/tmp/
$ adb shell "chmod 755 /data/local/tmp/frida-server"
$ adb shell "/data/local/tmp/frida-server &"
```

For the last step, if you see below error:

```
Unable to load SELinux policy from the kernel: Failed to open file "/sys/fs/selinux/policy": Permission denied
```

Then you need to run `frida-server` using the root shell, e.g.

```
$ adb shell
angler:/ $ su
angler:/ # /data/local/tmp/frida-server &
[1] 12089
angler:/ #
```

`[1] 12089` is the process id of `frida-server` .

## A quick smoke-test

Now, on your desktop it's time to make sure the basics are working. Run:

```
frida-ps -U
```

This should give you a process list along the lines of:

```
PID Name
-----
```

```
721 ATFWD-daemon
4450 adbd
730 android.hardware.biometrics.fingerprint@2.1-service
407 android.hardware.configstore@1.0-service
408 android.hardware.graphics.allocation@2.0-service
409 android.hardware.usb@1.0-service
410 android.hardware.wifi@1.0-service
406 android.hidl.allocation@1.0-service
```

## Tamper Smali Code

To tamper a `Boolean` value inside Java source code, i.e. the `Boolean bTamperingSuccess` = `false`; , or some other code you have interest in.

## Tools required

### apktool

`apktool` can be fetched from [Apktool website](#). Just follow the steps inside this page to install apktool.



## adb

adb is shipped with Android SDK, it can be found from directory `<your-some-path>/Android/sdk/platform-tools/adb`

## apksigner

apksigner is to sign your apk with a keystore file. This tool can be found at directory `<ANDROID_HOME>/Android/sdk/build-tools/28.0.3/apksigner` , and the usage is documented at [command-line apksigner](#).

## Steps

1. Clone the example project from [DecompileApk](#).
2. Find the already compiled apk file `DecompileApk/app/release/app-release.apk` .
3. Decompile it using **apktool**.

```
$ cd <your-path>/DecompileApk/app/release/  
$ apktool d --no-res -f app-release.apk
```

You will see below outputs

```
I: Using Apktool 2.4.0 on app-release.apk
I: Copying raw resources...
I: Baksmaling classes.dex...
I: Copying assets and libs...
I: Copying unknown files...
I: Copying original files...
```

4. Look for `DecompileApk/app/release/app-release/smali/com/arophix/decompileapk/MainActivity.smali` under the smali code directory and find below code

```
const/4 p1, 0x0
```

5. Just change `0x0` (meaning `false`) to `0x1` (meaning `true`) and save the file.
6. Using **apktool** to build the tampered apk.

```
apktool b app-release
```

You should see below outputs

```
I: Using Apktool 2.4.0
I: Checking whether sources has changed...
I: Smaling smali folder into classes.dex...
I: Checking whether resources has changed...
I: Copying raw resources...
```

```
I: Copying libs... (/lib)
I: Building apk file...
I: Copying unknown files/dir...
I: Built apk...
```

7. Find the newly built apk from `dist` directory `DecompileApk/app/release/app-release/dist/app-release.apk`
8. Sign the apk using **apksigner** and keystore located at `DecompileApk/app/decompileapk.jks` (please modify the paths for keystore and apk per your own case accordingly),

```
$ <ANDROID_HOME>/sdk/build-tools/28.0.3/apksigner sign --ks ../decompileapk.jks app-release.apk
```

You should see below outputs and enter the password `123456`

```
Keystore password for signer #1:
```

9. Install the signed apk using adb command.

```
$ adb install <path-to-the-tampered-apk>/app-release.apk
```

10. Instead of seeing `"Hello from C++"` from the screen, you should now see `"Hello, Android reverse engineer!"` .

## Hooking Android Java Methods

Hooking Android Java source code using Frida.

Find the script from `hook_java_methods.py` and run it using below command, and then click on the button of your started Android app.

```
$ python3 hook_java_methods.py
```

```
[*] Running CTF
```

```
[*] onClick
```

```
[*] Called - isPhoneRooted()
```

```
[*] onClick
```

```
[*] Called - isPhoneRooted()
```

If you see an error like below:

```
$ frida.ServerNotRunningError: unable to connect to remote frida-server: closed
```

Remember that you have started `frida-server` on your emulator.

Meanwhile, on your emulator screen, you should see the toast message changed to

`Device not rooted` if success.

# Hooking Android C Functions

Hooking Android C source code using Frida.

## 1. Decompile APK

Firstly, decompile the apk using apktool to extract the shared library, i.e.

```
libnative-lib.so .
```

```
$ cd DecompileApk/app/release  
$ apktool d --no-res app-release.apk
```

## 2. Find the target JNI method

Secondly, use below command to find the JNI function to hook.

```
$ nm --demangle --dynamic app-release/lib/x86/libnative-lib.so
```

You should see below outputs:

```
00004d80 T Java_com_arophix_decompileapk_MainActivity_stringFromJNI  
000090b0 T std::bad_typeid::what() const  
00005cf0 T std::bad_exception::what() const
```

```
00005e70 T std::bad_array_length::what() const
00005df0 T std::bad_array_new_length::what() const
00008ff0 T std::bad_cast::what() const
...
```

### 3. Hook C function by name

Find the script from [hooknative-by-function-name.py](#) and run it using below command, and then click on the button of your started Android app.

```
$ python3 hooknative-by-function-name.py

[*] Running Arophix Hook Test ...
Java_com_arophix_decompileapk_MainActivity_stringFromJNI called with:
ret: 0x200019
```

If you see an error like below:

```
$ frida.ServerNotRunningError: unable to connect to remote frida-server: closed
```

Remember that you have started `frida-server` on your emulator.

Meanwhile, on your emulator screen, you should see the text changed to `Frida is` hooking this displayed text from Native layer by function name. if success.

#### 4. Hook C function by address

Find the script from [hooknative-by-function-address.py](#) and run it using below command, and then click on the button of your started Android app.

```
$ python3 hooknative-by-function-address.py
```

```
[*] Running Arophix Hook Test ...
```

```
[+] membase: 0xb2acd000
```

```
[+] addressOfStringFromJni: 0xb2ad1d80
```

```
[++] addressOfStringFromJni: 0xb2ad1d80
```

```
ret: 0x19
```

If you see an error like below:

```
$ frida.ServerNotRunningError: unable to connect to remote frida-server: closed
```

Remember that you have started `frida-server` on your emulator.

Meanwhile, on your emulator screen, you should see the text changed to `Frida is` hooking this displayed text from Native layer by function address. if success.

# References

- <https://www.frida.re/docs/android/>
- <https://www.frida.re/docs/examples/android/>
- <https://11x256.github.io/Frida-hooking-android-part-1/>
- <https://github.com/antojoseph/frida-android-hooks/blob/master/hooks-native-code.py>
- <https://awakened1712.github.io/hacking/hacking-frida/>
- <https://awakened1712.github.io/hacking/hacking-frida/#c-hook-a-static-function-by-resolving-its-address>
- <https://stackoverflow.com/questions/51811348/find-manually-registered-obfuscated-native-function-address>



**AUTOMATTIC**

**We're hiring  
backend developers.  
Join us!**

[APPLY](#)

WordPress, Jetpack, Akismet, WooCommerce, LifterLMS, Sensei, P...

[REPORT THIS AD](#)

**Make money  
off your blog**

**WordAds**

[REPORT THIS AD](#)

---

**Share this:**



One blogger likes this.

---

**Related**

Tamper an Android native  
shared library (.so) using IDA  
Pro 7.0  
In "Android"

Android Substrate Hooking C  
Code  
In "Android"

A step by step tutorial to test  
Android backup and restore  
In "Android"

#### PREVIOUS

Tamper an Android native shared library (.so) using IDA Pro 7.0

#### NEXT

A step by step tutorial to test Android backup and restore

## Leave a Reply

Enter your comment here...

Advertisements



[REPORT THIS AD](#)

 Follow Arophix  2

## FOLLOW BLOG VIA EMAIL

Enter your email address to follow this blog and receive notifications of new posts by email.

Join 4 other followers

**FOLLOW**

---

## RECENT POSTS

---

### **A step by step tutorial to test Android backup and restore**

SEPTEMBER 12, 2019

---

### **Android Apk reverse engineering using Apktool and Frida**

APRIL 22, 2019

---

### **Tamper an Android native shared library (.so) using IDA Pro 7.0**

OCTOBER 31, 2018

---

### **Android Xposed Hook Example**

OCTOBER 16, 2018

---

### **sed command usage**

OCTOBER 5, 2018

## ANDROID JNI

- Android JNI – Overview
- Android JNI – Object Operations
- Android JNI – Class Operations, Exceptions and References
- Android JNI – String Operations
- Android JNI – Array Operations
- Android JNI – NIO and Reflection Support
- Android JNI – Summary

## HOOKING

- Android Substrate Hooking C Code
- Android Xposed Hook Example

→ Tamper an Android native shared library (.so) using IDA Pro 7.0

## ARCHIVES

📅 September 2019 (1)

📅 April 2019 (1)

📅 October 2018 (3)

📅 July 2018 (2)

📅 April 2018 (3)

📅 March 2018 (2)

📅 February 2018 (1)

📅 January 2018 (1)

📅 December 2017 (10)

📅 November 2017 (2)

## CATEGORIES

📁 Android (19)

📁 Hooking (4)

📁 Native (8)

📁 JNI (8)

📁 Git (2)

📁 Reverse Engineering (2)

📁 shell script (1)

📁 Software Engineering (2)

📁 Continuous Integration (2)

📁 Vim (4)

## BLOGS I FOLLOW

Applications – Android Police – Android news, reviews, apps, games, phones, tablets

---

Android « Gadget Hacks

---

Android Central - Android Forums, News, Reviews, Help and Android Wallpapers

---

Android

---

CSDN → 版主推荐-技术区 → RSS

---

CSDN博客推荐文章

---

Arophix

---

Discover

---

Longreads

---

The Daily Post

---

The WordPress.com Blog

---



## RECENT COMMENTS



e on Setup Jenkins with Docker on...



e on Setup Jenkins with Docker on...



Gradle sync issue on... on Android Gradle Plugin 3.0+ syn...



Android Gradle Plugi... on Gradle proxy configuration



Android Gradle Plugi... on Gradle sync issue on Debian OS...




Gradle proxy configur... on Android Gradle Plugin 3.0+ syn...



Gradle proxy configur... on Gradle sync issue on Debian OS...



Gradle sync issue on... on Gradle proxy configuration



Russell on Android Substrate Hooking C...



Russell on Android Substrate Hooking C...

April 2019

M	T	W	T	F	S	S
1	2	3	4	5	6	7
8	9	10	11	12	13	14
15	16	17	18	19	20	21
22	23	24	25	26	27	28

M

T

W

T

F

S

S

29

30

« OCT

SEP »

Advertisements



[REPORT THIS AD](#)

BLOG AT WORDPRESS.COM.