Document Title

WANG Xiyu

August 27, 2024

Contents

1 Introduction

2 ϵ-Closure

ϵ-Closure of a state refers to the set of states where through n ϵ transitions (consuming n ϵ starting from the state by the NFA), that could be reached.
Consider the below NFA, of which the transition function is listed as:



$$\delta(q_0, \epsilon) = \{q_0, q_2\}$$
$$\delta(q_1, \epsilon) = \{q_1\}$$
$$\delta(q_2, \epsilon) = \{q_2\}$$
$$\delta(q_0, a) = \{q_1\}$$
$$\delta(q_0, b) = \{q_0, q_2\}$$
$$\delta(q_1, a) = \{q_1\}$$

$$\delta(q_1, b) = \{q_2\}$$
$$\delta(q_2, a) = \{q_0, q_2\}$$
$$\delta(q_2, b) = \{q_1\}$$

Thus the ϵ-Closure of each state is:

$$EClose(q_0) = \{q_0, q_2\}$$

$$EClose(q_1) = \{q_1\}$$
$$EClose(q_2) = \{q_2\}$$

2.1 Subsection Title

2.1.1 Subsubsection Title

```
// Add your code example here
```

Column 1	Column 2	Column 3
Data 1	Data 2	Data 3

Table 1: Table caption



Figure 1: This is a sample caption.