

Introduction to Computational Physics – Exercise 9

Simon Groß-Bölting, Lorenz Vogel, Sebastian Willenberg

June 26, 2020

The Lorenz Attractor

The Lorenz attractor problem is given by the following coupled set of differential equations:

$$\dot{x} = -\sigma(x - y) \quad (1)$$

$$\dot{y} = rx - y - xz \quad (2)$$

$$\dot{z} = xy - bz \quad (3)$$

As discussed in the lecture, the fixed points are $(0, 0, 0)$ for all r , and (for $r > 1$) the points $C_{\pm} = (\pm a_0, \pm a_0, r - 1)$ with $a_0 = \sqrt{b(r - 1)}$. For the entire exercise, please use $\sigma = 10$ and $b = 8/3$. The value of r can be experimented with. When you create numerical solutions you can make plots in 2-D projection (e.g. in the (x, y) - or (x, z) -plane). You can also try a full 3-D plot.

Task: Solve numerically, using `rk4`, the above coupled set of equations for the values $r = 0.5, 1.17, 1.3456, 25.0$ and 29.0 . Choose the initial conditions near one of the fixed points: C_{\pm} for $r > 1$ and $(0, 0, 0)$ for $r < 1$. Explain the behavior, as much as possible, with the stability properties of the fixed points.

To solve the problem numerically we can use the Runge-Kutta Algorithm to approximate the functions x , y and z . It is important to note that $x(t)$, $y(t)$ and $z(t)$ are time-dependent. We will start by importing the packages that we will need for this exercise:

```
1 import numpy as np; import matplotlib.pyplot as plt
2 from mpl_toolkits.mplot3d import Axes3D
```

The `numpy` package allows us to work with arrays while the `matplotlib.pyplot` and `mplot3d` packages will allow us to plot our data in a three-dimensional graph. The next step is to define our parameters:

```
1 # set initial conditions
2 sigma = 10
3 b = 8/3
4 r = np.array([0.5, 1.17, 1.3456, 25.0, 29.0])
5 a0 = np.sqrt(b*(r[r>1.]-1))
```

The coupled set of differential equations are defined in the following manner:

```
1 # Lorenz system: coupled set of equations
2 def dx(x, y, z, sigma):
3     return -sigma*(x-y)
4 def dy(x, y, z, r):
5     return r*x-y-x*z
6 def dz(x, y, z, b):
7     return x*y-b*z
```

All the differential equations in our Lorenz system are dependent of the functions x , y and z and a variable σ , r or b . That means that we have to rewrite our `rk4` algorithm in such a way that we will iterate over x , y and z instead of iterating over y and t (or rather x). The `rk4_step` function looks as follows:

```
1 def rk4_step(x0, y0, z0, fx, fy, fz, h, fx_args={}, fy_args={}, fz_args={}):
2     ''' Simple python implementation for one RK4 step.
3     Inputs: (i=x,y,z)
4             i0 - M x 1 numpy arrays specifying all variables of the three
5                 ODE's at the current time step
6             f - function that calculates the derivates of all variables of the ODE
7             h - step size
```

```

8         fi_args - dictionary of additional arguments to be passed to the function fi
9         Output: (i=x,y,z)
10        ip1 - M x 1 numpy array of variables of the first ODE at time step i0+h '''
11        k1_x = h*fx(x0, y0, z0, **fx_args)
12        k1_y = h*fy(x0, y0, z0, **fy_args)
13        k1_z = h*fz(x0, y0, z0, **fz_args)
14
15        k2_x = h*fx(x0+k1_x/2., y0+k1_x/2., z0+k1_x/2., **fx_args)
16        k2_y = h*fy(x0+k1_y/2., y0+k1_y/2., z0+k1_y/2., **fy_args)
17        k2_z = h*fz(x0+k1_z/2., y0+k1_z/2., z0+k1_z/2., **fz_args)
18
19        k3_x = h*fx(x0+k2_x/2., y0+k2_x/2., z0+k2_x/2., **fx_args)
20        k3_y = h*fy(x0+k2_y/2., y0+k2_y/2., z0+k2_y/2., **fy_args)
21        k3_z = h*fz(x0+k2_z/2., y0+k2_z/2., z0+k2_z/2., **fz_args)
22
23        k4_x = h*fx(x0+k3_x/2., y0+k3_x/2., z0+k3_x/2., **fx_args)
24        k4_y = h*fy(x0+k3_y/2., y0+k3_y/2., z0+k3_y/2., **fy_args)
25        k4_z = h*fz(x0+k3_z/2., y0+k3_z/2., z0+k3_z/2., **fz_args)
26
27        xp1 = x0+1./6.*(k1_x+2.*k2_x+2.*k3_x+k4_x)
28        yp1 = y0+1./6.*(k1_y+2.*k2_y+2.*k3_y+k4_y)
29        zp1 = z0+1./6.*(k1_z+2.*k2_z+2.*k3_z+k4_z)
30        return (xp1,yp1,zp1)
31
32def rk4(x0, y0, z0, fx, fy, fz, h, n, fx_args={}, fy_args={}, fz_args={}):
33    ''' Simple implementation of RK4
34        Inputs: (i=x,y,z)
35                i0 - M x 1 numpy arrays specifying all variables of the three
36                    ODE's at the current time step
37                f - function that calculates the derivatives of all variables of the ODE
38                h - step size
39                fi_args - dictionary of additional arguments to be passed to the function fi
40        Output: (i=x,y,z)
41                in - N+1 x M numpy array with the results of the integration for
42                    every time step (includes i0) '''
43    xn = np.zeros(n+1); yn = np.zeros(n+1); zn = np.zeros(n+1)
44    xn[0] = x0; yn[0] = y0; zn[0] = z0
45
46    for n in np.arange(1,n+1,1):
47        xn[n], yn[n], zn[n] = rk4_step(x0=xn[n-1], y0=yn[n-1], z0=zn[n-1],
48                                       fx=fx, fy=fy, fz=fz, h=h, fx_args=fx_args,
49                                       fy_args=fy_args, fz_args=fz_args)
50    return (xn,yn,zn)

```

The only thing that is left to get the results is to plot our values:

```

1  N = 10000    # number of steps
2  h = 0.001    # step size
3
4  for i in range(0,len(r)):
5      # choose the initial conditions near one of the fixed points
6      if r[i] < 1: x0 = 1. ; y0 = 1. ; z0 = 1.
7      else: x0 = a0[i-1]+1.; y0 = a0[i-1]+1. ; z0 = (r[i]-1.)+1.
8
9      # solve numerically the above coupled set of equations (using Runge-Kutta-4)
10     xn, yn, zn = rk4(x0=x0, y0=y0, z0=z0, fx=dx, fy=dy, fz=dz, h=h, n=N,
11                      fx_args={'sigma':sigma}, fy_args={'r':r[i]}, fz_args={'b':b})
12
13     # plot the solution (3-D plot)
14     fig = plt.figure(); ax = fig.add_subplot(111, projection='3d')
15     ax.set_title(r'Lorenz Attractor for $r=${}'.format(r[i]))
16     ax.scatter(xn,yn,zn, marker='.', s=1, c='blue')
17     ax.scatter([x0],[y0],[z0], marker='x', s=25, c='green')
18     ax.scatter([x0-1.],[y0-1.],[z0-1.], marker='x', s=25, c='red')
19     ax.set_xlabel(r'$x$-axis'); ax.set_ylabel(r'$y$-axis'); ax.set_zlabel(r'$z$-axis')
20     fig.savefig('figures/3D-Plot-Lorenz-Attractor_r={}.pdf'.format(r[i]), format='pdf')
21
22 plt.show(); plt.clf(); plt.close()

```

It is important to note here that our initial conditions were set to $(x_0, y_0, z_0) = (1, 1, 1)$ in the case that $r < 1$. That means that our initial conditons are always real.

Task: Determine the sequence z_k for $r = 26.5$, where z_k is a local maximum in z on the solution curve after k periods. Plot z_{k+1} as a function of z_k . When sufficient points are there, connect the points.

The resulting function $z_{k+1} = f(z_k)$ has an intersection with the diagonal $z_{k+1} = z_k$. It is a fixed point of the function $f(z_k)$. Is the slope m of this function > 1 , < -1 or between -1 and $+1$? Notice: The theory of discrete maps says that there is no periodic solution if $|m| > 1$. So, in such a case we can deduce that this solution of the Lorenz system is not periodic.