From Scores to Supported Claims: Measurement Audits of Document and Retrieval Evaluation

***Abstract*—Evaluation scores are used to compare systems, but their interpretation depends on what an evaluator observes, how observations are scored and what comparison is supported. We examine these dependencies in three audits: a staged document evaluator, the released FinRank evidence-ranking benchmark and researcher-generated runs on two BEIR datasets. In the staged evaluator, 96 of 118 controlled header changes were visible; under a single-responsive-leaf restriction, flat and hierarchical scores had the same ordering up to an approximately 0.375 scale factor, despite different fixed-threshold detection rates. In FinRank, changing the tie policy shifted absolute pairwise accuracy while preserving the direction of the examined hard-versus-random comparison. For the BEIR runs, a paired sign-flip analysis with Holm correction supported two of ten lexical-system comparisons on SciFact and one on NFCorpus. An exact-tie-aware point-estimate baseline also passed our duplicate and degradation controls. These findings show how explicit measurement contracts qualify or preserve particular comparisons; they do not establish a universally validated audit method.**

***Index Terms*—measurement validity, document evaluation, information retrieval, reproducibility, benchmark auditing.**

I. Introduction

A lower detection rate can indicate a weaker evaluator, but it can also arise when the same numerical threshold is applied to scores on different scales. Likewise, a change in benchmark score need not change the comparison for which the score was reported; and the highest mean in a leaderboard does not by itself establish that every apparent ordering is supported by the data. Such distinctions matter when researchers use evaluation results to select systems or interpret a benchmark.

We ask: **which interpretations remain supported when the observation surface, scoring rule and comparison procedure are made explicit?** We investigate three evaluation constructions. First, controlled changes to public financial tables probe a staged document evaluator. Second, we inspect tie handling and source identity in FinRank [4]. Third, we assess researcher-generated lexical retrieval runs on SciFact and NFCorpus from BEIR [5], with a later dense-model exploration. The BEIR runs are our own constructions, not the published benchmark leaderboard.

Our contributions are empirical and bounded. We explain a detection-rate difference by a positive score rescaling under a single-responsive-leaf restriction; show that a particular FinRank comparison retains its direction despite changes in absolute scores; and distinguish point-estimate rankings from comparisons supported under a specified paired statistical procedure. Each finding is tied to an explicit measurement object and relevant limitations.

Prior work has examined metric and construct validity [1], [2], [3]. AgentSuite [9] audits interacting components in agent benchmarks at broader scale. Our study instead examines arithmetic, observation and comparison contracts in specific document and retrieval evaluations. It does not propose a new general theory of validity or claim an observed change in a user's decision.

II. Audit Design

We distinguish three questions: whether a change is **visible** at a selected evidence surface; whether a specified predicate **detects** it; and whether it changes an outcome under a stated equivalence contract. Visibility, detection and outcome change are separate observations. We then examine score sensitivity, the stability of a named comparison and numerical reproducibility.

The designs differ. Case 1 uses controlled perturbations. Case 2 inspects a released benchmark, including source-informed post-hoc identity analysis. Case 3 uses researcher-generated systems and test queries from a public benchmark; its original audit choices were not independently timestamped before the first run. We preserve fixed outputs and identify later explorations rather than treating them as prospective confirmation.

The cases target three interpretations. First, a detection-rate difference does not necessarily imply a ranking difference when the score scales differ. Second, a shift in absolute accuracy need not reverse a stated comparison. Third, a higher retrieval mean is a point estimate; it does not automatically establish every pairwise system ordering. Each case below specifies what is held fixed and what is varied.

For each construction we identify the input and outcome carrier, the evaluator or scoring implementation, the original reporting convention, the comparison of interest, and any alternative rule applied to fixed outputs. We use the term *decision* for a stated analytical interpretation such as the direction of a comparison; no intervention with a human decision-maker was conducted. The analysis can preserve an initial interpretation as well as qualify it. An audit of a score is useful even when the direction remains stable, because it identifies which aspects of the scoring contract matter to that conclusion.

The cases are complementary rather than replications of one universal intervention. The document case compares response visibility and threshold behavior in an instrumented construction. The FinRank case varies tie credit for a released financial retrieval benchmark. The BEIR case investigates

TABLE I
ORIGINAL SEED-42 OPERATING-POINT DETECTION; TABLE AND INJECTION COUNTS ARE DIFFERENT UNITS.

Unit	Flat	Hierarchical
Source tables	75/95	20/95
Header injections	85/118	13/118

metric definitions, query-level variation and uncertainty for newly constructed runs. Consequently, their sample counts, populations and effect sizes are not combined into one overall audit-success rate.

III. CONTROLLED DOCUMENT EVALUATION

The frozen staged evaluator has parsing and question-answering checkpoint trees with twelve scored leaves. Its seed-42 panel contains 95 TAT-QA-derived source tables [6] and 118 controlled header changes across six families. Mapping and regression artifacts form the observed surface. A change is visible if that surface records a difference; protocol detection and downstream harm are separate quantities. The audit holds the evaluated inputs and scores fixed while comparing declared aggregation and threshold conventions. It does not observe every internal state or possible downstream use.

Of 118 injections, 96 were visible. None of the 13 OCR-like changes was visible on this surface. This observation does not establish 13 harmful misses: one existing semantic judge classified the cases as referentially equivalent, without an independent human reference.

In this construction the QA tree was frozen and only the field-hit-rate leaf responded. The unrounded hierarchical contrastive score was a positive rescaling of the flat score, with fitted slope approximately 0.375 and identical observed rankings. The original flat field-hit-rate drop and hierarchical parsing-root drop each used a numerical operating threshold of **at least 2.0**, on their respective scales. At these original operating points the flat and hierarchical protocols detected 75/95 versus 20/95 tables, or 85/118 versus 13/118 injections. Tables and injections are distinct units. The difference in rates therefore does not by itself establish a difference in ranking ability.

The separate matched-threshold reanalysis used strict greater-than comparisons: a flat threshold of 1.0 corresponds to a hierarchical threshold of 0.375; the recorded fold detects 21 cases under either. It is not the original 2.0 operating-point analysis. This distinction also matters for boundary values: 12 of the 95 tables have a flat drop exactly equal to 2.0.

This comparison illustrates why a threshold needs both a numeric value and a scale. In the observed single-leaf setting, multiplying every flat contrast by a positive constant preserves order. A corresponding threshold must be multiplied by the same constant if the same decision rule is to be retained. The original protocols did not apply corresponding thresholds. The matched-grid example tests the relationship on saved outputs; it does not certify that a production threshold has been calibrated. Neither the scaling result nor the matched-grid behavior should be generalized to a setting where additional leaves respond differently.

The clean-only contrastive construction compares repeated deterministic computations on an unchanged record. All 2,382 usable clean records have zero scores, so every positive threshold has observed clean false-positive rate zero; this panel does not identify a unique deployment threshold. Across three seeds, the flat descriptive table-run ratio was 219/282 using 119 unique source-table identifiers. A post-hoc UID-cluster bootstrap gives a 95% interval of [0.7117, 0.8364]; the repeated table runs are not 282 independent source tables.

The per-seed contributions to the 219/282 ratio are 75/95, 76/97 and 68/90. The denominators refer to table appearances within each run; the same source table may contribute to more than one run. The bootstrap resamples unique source identifiers while retaining their repeated appearances, so its resampling unit matches that dependency. This uncertainty interval is post-hoc and conditional on the available source tables and three seeds; it should not be interpreted as a guarantee for future datasets or seeds. Equal weighting of source identifiers gives 0.7535 with interval [0.6835, 0.8207].

In a separate stage-aligned control, 72 source clusters contributed one injection each for mapping, retrieval and numeric processing. A leave-one-cluster-out nearest-centroid classifier on the full response vector attained macro-F1 and top-1 1.000. The three directly targeted leaves gave the same result; removing them reduced top-1 to 0.333 under the frozen tie-as-incorrect rule, with a 0.667 tie rate. The observed stage separation is attributable to explicit instrumentation, not to hierarchy alone. A nested FinQA probe [7] covered 89 rows from 30 report clusters; it changed program fields but did not recompute downstream result fields. Its zero detected and zero changed outcomes cannot estimate a failure rate for changed answers.

IV. FINRANK: SCORE SENSITIVITY AND DECISION STABILITY

FinRank ranks evidence from financial filings [4]. Under tie-as-positive scoring, a score tie counts for the gold passage; under strict-win scoring, it does not. The tie comparisons and materiality threshold were fixed before pair-level outcomes. For TF-IDF, hard/random accuracy changes from 77.756%/91.935% to 77.030%/90.850%; the random-minus-hard gap changes from 14.179 to 13.821 percentage points. For BM25, the corresponding hard/random accuracies are 74.780%/87.789% and 74.094%/86.760%; gaps change from 13.009 to 12.666 points. Random-negative accuracy moves by 1.084 percentage points for TF-IDF and 1.029 for BM25, exceeding the fixed 1.0-point threshold, while the gap remains positive in both systems.

Gaps are computed before display rounding. The comparison's qualitative direction is stable under these two policies; this does not establish stability for all decisions. A later source-informed identity analysis reproduces 442 hard-negative occurrences across 305 records sharing canonical text with another record's gold passage, and gold-passage loss in

33 records under the inspected metadata filter. These are post-hoc reproductions of known properties, not newly discovered benchmark defects. In-record and pairwise metrics reproduce exactly in the audited environment; some global and metadata-filtered results retain an unexplained reproduction gap.

The identity analysis also explains why text identity and record identity are different contracts. A pooled passage can occur in several records with different metadata. When the inspected implementation deduplicates text by first occurrence and retains that occurrence's metadata, a later record's gold text can be excluded by metadata filtering even though its text appeared in the pooled corpus. The reproduced counts describe that implementation and its released data, not the prevalence of this behavior in other retrieval systems. Exact in-record reproduction and the remaining global mismatch are reported separately because one does not resolve the other.

V. Retrieval Comparisons

We built five lexical configurations on BEIR SciFact and NFCorpus [5]: TF-IDF and BM25 parameter pairs (k1, b) of (0.9, 0.4), (1.2, 0.75), (0.5, 0.3) and (1.5, 0.6). They use the released corpora, qrels and 300/323 judged queries, respectively. The systems are our own runs, and the two datasets belong to one benchmark family. We compare system scores on the same queries so that statistical analysis is paired; each dataset has its own comparison family.

Our initial scoring implementation binarized graded relevance and used a different MAP denominator. Aligning it with the trec_eval contract corrected both definitions. Under graded nDCG@10, TF-IDF moved from second to third in one NFCorpus ranking; the separate denominator correction changed its example MAP@10 from approximately 0.2225 to 0.1193. This is a correction of our implementation, not evidence that the official leaderboard was wrong. For fixed rankings, trec_eval 10.0-rc3 agreed with 18,690 per-query nDCG, MAP and recall values within 1e-4; it does not validate tie-breaking policy.

The cross-check writes a strictly decreasing score for each fixed rank, so the reference evaluator receives the order selected by our run. It can test the metric values for that order, but cannot decide which document should win an equal-score tie. The maximum observed discrepancy was approximately 0.00005, consistent with four-decimal output precision. The executable used was trec_eval itself; the check was not a separate execution of the pytrec_eval Python binding. These distinctions make the reproducibility statement narrower and more useful than a general assertion that an entire retrieval pipeline has been independently reproduced.

For the five systems, 2,000 paired bootstrap resamples produced intervals excluding zero for 3/10 pairs on SciFact and 4/10 on NFCorpus. A separate two-sided paired sign-flip procedure with 2,000 Monte Carlo draws per pair and Holm correction supported 2/10 and 1/10, respectively. These are different inference procedures, so the count difference is not attributable to Holm correction alone. The inference depends on the relevant exchangeability or symmetry and query-independence assumptions; non-significance does not establish equality.

Separately from varying cutoff k, reversing document-ID tie order for one NFCorpus BM25 configuration at k=10 changed the ordered top ten for 36.5% of queries and top-ten membership for 25.7%. Mean nDCG@10 changed from 0.30453945 to 0.30449093, approximately 0.00005. Query-level changes can therefore be hidden by the aggregate in this setting; this is not an estimated benchmark-wide failure rate.

For an intentionally duplicated system and an intentionally degraded control, an exact-tie-aware point-estimate rule and the paired audit both passed both controls. The controls do not demonstrate that the audit outperforms the simpler rule. A subsequent BGE-small-en-v1.5 [8] exploration gave mean nDCG@10 of 0.7127 versus 0.6622 for BM25 on SciFact, and 0.3438 versus 0.3062 on NFCorpus. This is an exploratory retrieval result selected after the original analysis, not evidence that the audit improved a user decision or that lexical tie findings transfer to dense models.

The BGE comparison was later included with the five lexical runs in a separate six-system family of 15 pairs per dataset. With 200,000 Monte Carlo sign flips per pair and Holm correction within each dataset, the BGE-minus-BM25 nDCG@10 difference was +0.05049 on SciFact (adjusted p = 0.066000) and +0.03759 on NFCorpus (adjusted p = 0.015540). These post-hoc tests are not the original ten-pair family or independent confirmation. The saved dense outputs contain ranked document IDs rather than original dense scores, so they cannot establish dense-score tie frequencies. Numerical reproducibility of the tests does not establish their inferential assumptions.

The single BGE comparison originally used a paired bootstrap: the mean differences were 0.0505 [0.0137, 0.0891] on SciFact and 0.0376 [0.0154, 0.0608] on NFCorpus, uncorrected for a comparison family. It used normalized embeddings, the model's retrieval query prefix and a 512-token cap. A separate trec_eval execution agreed on 1,246 dense and BM25 per-query scores to the reference program's four-decimal print precision. The later 15-pair test answers a different question about multiplicity and must not be represented as a prospective verification of the selected BGE comparison.

VI. Discussion and Conclusion

The three cases show distinct ways in which an evaluation contract constrains a claim. In the staged evaluator, a rate difference coexists with identical ranks under a restricted score rescaling. In FinRank, a tested comparison retains direction as absolute scores change. In our BEIR runs, metric definitions, ties and statistical comparison procedures affect the interpretation of rankings.

These findings have limited scope: the first case uses controlled table perturbations, FinRank uses lexical baselines and has an unresolved reproduction gap, and the BEIR analyses are retrospective runs over two datasets with a post-hoc dense extension. Existing validity frameworks already cover broader audit principles [1], [2], [3]. Our contribution is a reproducible

set of case-specific observations and the distinction between numerical movement and supported interpretation. We recommend reporting the measurement object, scoring convention, comparison and uncertainty together; we do not claim a general audit guarantee or observed deployment benefit.

REFERENCES

[1] C. Ross et al., "What makes a good metric? Evaluating automatic metrics for text-to-image consistency," arXiv:2412.13989, 2024.

[2] W. Caban, "Measurement Without Validity: The Compounding Reliability Problem in Agentic AI Evaluation," arXiv:2608.00794, 2026.

[3] A. M. Bean et al., "Measuring what Matters: Construct Validity in Large Language Model Benchmarks," arXiv:2511.04703, 2025.

[4] S. Mansouri et al., "FinRank: An Evidence-Grounded Benchmark for Financial Question Answering and Retrieval over SEC Filings," arXiv:2608.07400, 2026.

[5] N. Thakur et al., "BEIR: A Heterogeneous Benchmark for Zero-shot Evaluation of Information Retrieval Models," NeurIPS Datasets and Benchmarks, 2021.

[6] F. Zhu et al., "TAT-QA: A Question Answering Benchmark on a Hybrid of Tabular and Textual Content in Finance," ACL-IJCNLP, 2021, doi: 10.18653/v1/2021.acl-long.254.

[7] Z. Chen et al., "FinQA: A Dataset of Numerical Reasoning over Financial Data," EMNLP, 2021, doi: 10.18653/v1/2021.emnlp-main.300.

[8] Beijing Academy of Artificial Intelligence, "bge-small-en-v1.5," model card, revision 5c38ec7c, https://huggingface.co/BAAI/bge-small-en-v1.5.

[9] H. Suh et al., "AgentSuite: Toward More Reliable Agent Evaluation with a Component-Based Benchmark Auditing Pipeline," ICML, PMLR 306:116300–116319, 2026.