




US 20190034926A1

(19) **United States**(12) **Patent Application Publication**
DAVIS(10) **Pub. No.: US 2019/0034926 A1**(43) **Pub. Date: Jan. 31, 2019**(54) **METHOD AND SYSTEM FOR
TRANSACTION PROCESSING WITH
COMPLETE CRYPTOGRAPHIC
AUDITABILITY**(52) **U.S. Cl.**
CPC **G06Q 20/3825** (2013.01); **G06Q 20/3827**
(2013.01)(71) Applicant: **Mastercard International
Incorporated**, Purchase, NY (US)(72) Inventor: **Steven Charles DAVIS**, Saint Peters,
MO (US)(73) Assignee: **Mastercard International
Incorporated**, Purchase, NY (US)(21) Appl. No.: **15/658,573**(22) Filed: **Jul. 25, 2017****Publication Classification**(51) **Int. Cl.**
G06Q 20/38 (2006.01)(57) **ABSTRACT**

A method for processing of a cryptographically auditable transaction includes: receiving payment data, wherein the payment data includes at least a primary account number; transmitting the primary account number to a computing system; receiving a confirmation associated with the primary account number from the computing system; transmitting a payment request to the computing system, wherein the payment request includes at least a reference value associated with a payment transaction; receiving an acceptance request from the computing system, wherein the acceptance request includes at least the reference value, an acceptance address, one or more fee values, and a first digital signature generated by a third party; generating a second digital signature using at least the acceptance address; and transmitting at least the second digital signature to the computing system.






FIG. 1




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5

600




FIG. 6




FIG. 7




FIG. 8

METHOD AND SYSTEM FOR TRANSACTION PROCESSING WITH COMPLETE CRYPTOGRAPHIC AUDITABILITY

FIELD

[0001] The present disclosure relates to the processing of electronic transactions with complete cryptographic auditability, specifically the use of a moderating system between two entities engaged in a transaction and a blockchain for complete auditability and transparency of the transaction for every involved party.

BACKGROUND

[0002] Entities engage in transactions for a variety of reasons, such as the use and/or purchase of goods or services. In many instances, an entity will keep a record of their transactions, such as for accounting purposes, or for dispute settlement between themselves and another entity. For instance, if the entity is accused of missing a payment, the entity can look at their record of transactions to find such a payment or lack thereof. However, such records often require management and upkeep by the entity themselves, or require the entity to hire a third party to maintain such records.

[0003] In addition, the management and maintenance of such records by individual entities can also result in two transacting entities having disputing records of a transaction. For instance, two parties in a transaction may each have records indicating a different amount paid between the two parties, where there may be no easy resolution for a payment dispute between the two, as each party may point to their own records for their position, but have no easy way to determine which party's record is accurate. In some cases, transacting entities may use a third party to keep records on a transaction, such as via the use of an escrow agent or other intermediary. These can be done using electronic records, such as an accounting program or programs, which often require accurate input of transaction details. Even when parts of this process are automated, such records may still be subject to tampering or inaccuracies from other sources and a transacting entity may have no ability to audit such records, particularly of each of the two or three parties involved. To do so would require accessing different computers, different, selected records perhaps kept in different formats, and designing a program complicated enough to check for a variety of irregularities and non-matching record elements.

[0004] Thus, there is a need for a technological solution whereby records may be kept for an electronic transaction between two entities that has complete cryptographic auditability to ensure auditability of the transaction by the involved entities, ensure that the transaction record is accurate as to the transaction as decided by each involved entity, and eliminate or strongly mitigate the possibility of the record being tampered with.

SUMMARY

[0005] The present disclosure provides a description of systems and methods for the processing of cryptographically auditable transactions. A transaction is agreed upon by two entities as parties thereof, where a third party is used to moderate the transaction. The transaction happening directly

between the two involved parties may minimize the need to rely on a moderator, which may reduce the data exchanged in the conducting of the transaction while still maintaining the benefits of a moderator. The moderator may provide a third party acknowledgement of a transaction for further verification thereof and may, in exemplary embodiments, act as a third party facilitator of settlement between the transacting entities, enabling transactions to be conducted more easily with less resources expended by the transacting entities. The use of a blockchain to store the data related to the transactions also provides additional benefits; in particular, transaction records stored therein cannot be tampered with without immediate detection, and the immutability of the blockchain provides for complete cryptographic auditability of every transaction by involved entities. As a result, entities may engage in transactions for which cryptographic auditability is maintained, while expending less resources and achieving faster processing than available in existing systems.

[0006] A method for processing of a cryptographically auditable transaction includes: receiving, by an input device of a processing server, payment data, wherein the payment data includes at least a primary account number; electronically transmitting, by a transmitting device of the processing server, the primary account number to a computing system; receiving, by a receiving device of the processing server, a confirmation associated with the primary account number from the computing system; electronically transmitting, by the transmitting device of the processing server, a payment request to the computing system, wherein the payment request includes at least a reference value associated with a payment transaction; receiving, by the receiving device of the processing server, an acceptance request from the computing system, wherein the acceptance request includes at least the reference value, an acceptance address, one or more fee values, and a first digital signature generated by a third party; generating, by a signing module of the processing server, a second digital signature using at least the acceptance address; and electronically transmitting, by the transmitting device of the processing server, at least the second digital signature to the computing system.

[0007] Another method for processing of a cryptographically auditable transaction includes: receiving, by a receiving device of a processing server, a payment request from a first computing system, wherein the payment request includes at least a reference value associated with a payment transaction; generating, by a signing module of the processing server, a first digital signature using at least the received payment request; electronically transmitting, by a transmitting device of the processing server, at least the first digital signature and the payment request to a second computing system; receiving, by the receiving device of the processing server, a confirmation message from the second computing system, wherein the confirmation message includes at least one or more fee values, a second digital signature, and an acceptance address; electronically transmitting, by the transmitting device of the processing server, an acceptance request to the first computing system, wherein the acceptance request includes at least the reference value, the one or more fee values, the second digital signature, and the acceptance address; receiving, by the receiving device of the processing server, an acceptance message from the first computing system, wherein the acceptance message includes at least a third digital signature; and electronically

transmitting, by the transmitting device of the processing server, a transaction value to a node associated with a blockchain network, wherein the transaction value includes at least the reference value, the acceptance address, and the third digital signature.

[0008] Yet another method for processing of a cryptographically auditable transaction includes: receiving, by a receiving device of a processing server, a payment request from a computing system, wherein the payment request includes at least a reference value associated with a payment transaction and a first digital signature; executing, by a querying module of the processing server, a first query to identify one or more fee values for the payment transaction and a second query to identify an acceptance address; generating, by a signing module of the processing server, a second digital signature; electronically transmitting, by a transmitting device of the processing server, at least the one or more fee values, the acceptance address, and the second digital signature to the computing system; receiving, by the receiving device of the processing server, blockchain data from a node associated with the blockchain network, wherein the blockchain data includes one or more blocks comprising a blockchain, each block being comprised of at least a block header and one or more transaction values, wherein each transaction value includes at least a transaction address, a transaction reference, and a transaction signature; executing, by the querying module of the processing server, a query on the received blockchain data to identify a specific transaction value where the included transaction address corresponds to the acceptance address; and verifying, by a verification module of the processing server, the specific transaction value based on at least a correspondence between the included transaction reference and the reference value.

[0009] A system for processing of a cryptographically auditable transaction includes: a signing module of a processing server; an input device of the processing server configured to receive payment data, wherein the payment data includes at least a primary account number; a transmitting device of the processing server configured to electronically transmit the primary account number to a computing system; and a receiving device of the processing server configured to receive a confirmation associated with the primary account number from the computing system, wherein the transmitting device of the processing server is further configured to electronically transmit a payment request to the computing system, wherein the payment request includes at least a reference value associated with a payment transaction, the receiving device of the processing server is further configured to receive an acceptance request from the computing system, wherein the acceptance request includes at least the reference value, an acceptance address, one or more fee values, and a first digital signature generated by a third party, the signing module of the processing server is configured to generate a second digital signature using at least the acceptance address, and the transmitting device of the processing server is configured to electronically transmit at least the second digital signature to the computing system.

[0010] Another system for processing of a cryptographically auditable transaction includes: a receiving device of a processing server configured to receive a payment request from a first computing system, wherein the payment request includes at least a reference value associated with a payment transaction; a signing module of the processing server

configured to generate a first digital signature using at least the received payment request; and a transmitting device of the processing server configured to electronically transmit at least the first digital signature and the payment request to a second computing system, wherein the receiving device of the processing server is further configured to receive a confirmation message from the second computing system, wherein the confirmation message includes at least one or more fee values, a second digital signature, and an acceptance address, the transmitting device of the processing server is further configured to electronically transmit an acceptance request to the first computing system, wherein the acceptance request includes at least the reference value, the one or more fee values, the second digital signature, and the acceptance address, the receiving device of the processing server is further configured to receive an acceptance message from the first computing system, wherein the acceptance message includes at least a third digital signature, and the transmitting device of the processing server is further configured to electronically transmit a transaction value to a node associated with a blockchain network, wherein the transaction value includes at least the reference value, the acceptance address, and the third digital signature.

[0011] Yet another system for processing of a cryptographically auditable transaction includes: a verification module of a processing server; a receiving device of the processing server configured to receive a payment request from a computing system, wherein the payment request includes at least a reference value associated with a payment transaction and a first digital signature; a querying module of the processing server configured to execute a first query to identify one or more fee values for the payment transaction and a second query to identify an acceptance address; a signing module of the processing server configured to generate a second digital signature; and a transmitting device of the processing server configured to electronically transmit at least the one or more fee values, the acceptance address, and the second digital signature to the computing system, wherein the receiving device of the processing server is further configured to receive blockchain data from a node associated with the blockchain network, wherein the blockchain data includes one or more blocks comprising a blockchain, each block being comprised of at least a block header and one or more transaction values, wherein each transaction value includes at least a transaction address, a transaction reference, and a transaction signature, the querying module of the processing server is further configured to execute a query on the received blockchain data to identify a specific transaction value where the included transaction address corresponds to the acceptance address, and the verification module of the processing server is configured to verify the specific transaction value based on at least a correspondence between the included transaction reference and the reference value.

BRIEF DESCRIPTION OF THE DRAWING FIGURES

[0012] The scope of the present disclosure is best understood from the following detailed description of exemplary embodiments when read in conjunction with the accompanying drawings. Included in the drawings are the following figures:

[0013] FIG. 1 is a block diagram illustrating a high level system architecture for the processing of a cryptographically

auditable transaction involving the use of a moderating system and blockchain in accordance with exemplary embodiments.

[0014] FIG. 2 is a block diagram illustrating a processing server for use in the system of FIG. 1 for the processing of cryptographically auditable transactions in accordance with exemplary embodiments.

[0015] FIG. 3 is a flow diagram illustrating a process for the identification and verification of an account to be used in a cryptographically auditable transaction in the system of FIG. 1 in accordance with exemplary embodiments.

[0016] FIGS. 4A and 4B are a flow diagram illustrating a process for the processing of a cryptographically auditable transaction in the system of FIG. 1 in accordance with exemplary embodiments.

[0017] FIGS. 5-7 are flow charts illustrating exemplary methods for processing cryptographically auditable transactions in accordance with exemplary embodiments.

[0018] FIG. 8 is a block diagram illustrating a computer system architecture in accordance with exemplary embodiments.

[0019] Further areas of applicability of the present disclosure will become apparent from the detailed description provided hereinafter. It should be understood that the detailed description of exemplary embodiments are intended for illustration purposes only and are, therefore, not intended to necessarily limit the scope of the disclosure.

DETAILED DESCRIPTION

Glossary of Terms

[0020] Blockchain—A public ledger of all transactions of a blockchain-based currency. One or more computing devices may comprise a blockchain network, which may be configured to process and record transactions as part of a block in the blockchain. Once a block is completed, the block is added to the blockchain and the transaction record thereby updated. In many instances, the blockchain may be a ledger of transactions in chronological order, or may be presented in any other order that may be suitable for use by the blockchain network. In some configurations, transactions recorded in the blockchain may include a destination address and a currency amount, such that the blockchain records how much currency is attributable to a specific address. In some instances, the transactions are financial and others not financial, or might include additional or different information, such as a source address, timestamp, etc. In some embodiments, a blockchain may also or alternatively include nearly any type of data as a form of transaction that is or needs to be placed in a distributed database that maintains a continuously growing list of data records hardened against tampering and revision, even by its operators, and may be confirmed and validated by the blockchain network through proof of work and/or any other suitable verification techniques associated therewith. In some cases, data regarding a given transaction may further include additional data that is not directly part of the transaction appended to transaction data. In some instances, the inclusion of such data in a blockchain may constitute a transaction. In such instances, a blockchain may not be directly associated with a specific digital, virtual, fiat, or other type of currency.

[0021] Transaction Account—A financial account that may be used to fund a transaction, such as a checking

account, savings account, credit account, virtual payment account, etc. A transaction account may be associated with a consumer, which may be any suitable type of entity associated with a payment account, which may include a person, family, company, corporation, governmental entity, etc. In some instances, a transaction account may be virtual, such as those accounts operated by PayPal®, etc.

[0022] Issuer—An entity that establishes (e.g., opens) a letter or line of credit in favor of a beneficiary, and honors drafts drawn by the beneficiary against the amount specified in the letter or line of credit. In many instances, the issuer may be a bank or other financial institution authorized to open lines of credit. In some instances, any entity that may extend a line of credit to a beneficiary may be considered an issuer. The line of credit opened by the issuer may be represented in the form of a payment account, and may be drawn on by the beneficiary via the use of a payment card. An issuer may also offer additional types of payment accounts to consumers as will be apparent to persons having skill in the relevant art, such as debit accounts, prepaid accounts, electronic wallet accounts, savings accounts, checking accounts, etc., and may provide consumers with physical or non-physical means for accessing and/or utilizing such an account, such as debit cards, prepaid cards, automated teller machine cards, electronic wallets, checks, etc.

[0023] Acquirer—An entity that may process payment card transactions on behalf of a merchant. The acquirer may be a bank or other financial institution authorized to process payment card transactions on a merchant's behalf. In many instances, the acquirer may open a line of credit with the merchant acting as a beneficiary. The acquirer may exchange funds with an issuer in instances where a consumer, which may be a beneficiary to a line of credit offered by the issuer, transacts via a payment card with a merchant that is represented by the acquirer.

System for the Processing of Cryptographically Auditable Transactions

[0024] FIG. 1 illustrates a system 100 for the processing of electronic transactions with complete cryptographic auditability between two transacting entities via the use of a moderating entity and blockchain.

[0025] The system 100 may involve an electronic transaction to be conducted between a purchasing entity 102 and a supplying entity 104. The supplying entity 104 may supply goods or services to the purchasing entity 102, for which the purchasing entity 102 makes a payment. The purchasing entity 102 may interact with a sending computing system 106 to make a payment to the supplying entity 104 in an amount agreed upon by the two entities. The sending computing system 106, discussed in more detail below, may be a computing system associated with a transaction account issued to the purchasing entity 102 that is specifically configured as discussed herein to initiate cryptographically auditable transactions. In some embodiments, the sending computing system 106 may be a part of an issuing financial institution, such as an issuing bank, that issues a transaction account to the purchasing entity 102 for use in funding electronic transactions.

[0026] The sending computing system 106 may receive payment data for use in making a payment as part of the electronic transaction involving the purchasing entity 102 and supplying entity 104. The payment data may include at

least a payment amount and a primary account number associated with a transaction account (e.g., a credit, debit or other payment card number, demand deposit number, or other form of account number issued to the supplying entity **104**) to which the payment is being made. In some cases, the payment data may also include an account number associated with the account issued to the purchasing entity **102**, from which payment is to be debited. In some embodiments, the sending computing system **106** may receive the payment data in a transaction message that is electronically transmitted to the sending computing system **106**, such as by the purchasing entity **102** or via another entity or system, such as via a point of sale device. The transaction message may be a specially formatted data message that is formatted pursuant to one or more standards governing the exchange of financial transaction messages, such as the International Organization of Standardization's ISO 8583 or ISO 20022 standards, where the payment data may be included in data elements stored therein.

[0027] Prior to initiating the process for payment to the supplying entity **104**, the sending computing system **106** may contact a receiving computing system **108** to verify the eligibility of the transaction account provided thereto for payment. The receiving computing system **108**, discussed in more detail below, may be a part of an acquiring financial institution, such as an acquiring bank, that issues the transaction account associated with the primary account number to the supplying entity **104** for the receipt of funds as part of the electronic transaction. The sending computing system **106** may establish a communication channel with the receiving computing system **108** using any suitable communication network and method. In some embodiments, the sending computing system **106** may possess communication data for contacting the receiving computing system **108**, which may be used in establishing the communication channel. For instance, the sending computing system **106** may identify the receiving computing system **108** based on the primary account number (e.g., using an entity identification number included therein or via a lookup table) and identify communication data associated therewith.

[0028] In other embodiments, a moderating computing system **110** may be used for identification of the receiving computing system **108**. The moderating computing system **110**, discussed in more detail below, may be a system of a third party entity configured to act as a moderator for transactions involving the sending computing system **106** and receiving computing system **108**. In such embodiments, the sending computing system **106** may provide the primary account number or data associated therewith (e.g., an entity identification number, issuer identification number, bank identification number, etc.) to the moderating computing system **110**. The moderating computing system **110** may identify the receiving computing system **108** associated therewith, such as via a lookup table, and provide the sending computing system **106** with communication data for establishing the communication channel with the receiving computing system **108**.

[0029] Once the communication channel is established, the sending computing system **106** may electronically transmit the primary account number supplied in the payment data to the receiving computing system **108**. The receiving computing system **108** may then identify if there is a transaction account associated with that primary account number, and if the transaction account is eligible for the

receipt of funds in a payment transaction. If there is no such transaction account or the transaction account is not eligible, the receiving computing system **108** may notify the sending computing system **106** accordingly, which may relay the message to the purchasing entity **102** and the transaction stopped. The purchasing entity **102** may then proceed to get a new account number from the supplying entity **104** or re-attempt the transaction using the original primary account number, such as to correct a typographical error in the account number. If the transaction account exists and is valid, the receiving computing system **108** may notify the sending computing system **106** accordingly, which may initiate the processing of the cryptographically auditable transaction.

[0030] The sending computing system **106** may first generate a payment request for the transaction. The payment request may be a request generated by the sending computing system **106** to indicate that payment, of the payment amount, is to be made to the transaction account associated with the primary account number. The payment request may include at least the payment data for the payment transaction. In one embodiment, the payment data may be formatted as a single reference value that is stored in the payment request. In such embodiments, the sending computing system **106** may generate a reference value of the payment data, such as via the application of a hashing algorithm to the payment data or use of abstract syntax notation one (ASN.1). The sending computing system **106** may then forward the payment request, including the reference value, to the receiving computing system **108** using the established communication channel. In some embodiments, the sending computing system **106** may also include a unique identifier in the payment request, which may be included in all communications between the sending computing system **106** and receiving computing system **108** associated with the transaction for identification thereof.

[0031] The receiving computing system **108** may receive the payment request and may verify the reference value included therein. Verification of the reference value may include the generation of a reference value by the receiving computing system **108** using payment data for the expected transaction (e.g., the same primary account number and payment amount as supplied by the supplying entity **104** based on the agreement with the purchasing entity **102** for the transaction), and comparison of the generated reference value to the reference value included in the payment request. If the verification fails, the receiving computing system **108** may notify the sending computing system **106** accordingly, and the transaction aborted. If the verification succeeds, then, in some embodiments, the receiving computing system **108** may provide a notification to the sending computing system **106** accordingly, which may include the reference value generated by the receiving computing system **108**.

[0032] Upon successful verification of the payment request, the receiving computing system **108** may notify the moderating computing system **110** of the transaction. The notification may be comprised of the payment request as received from the sending computing system **106** and a digital signature generated by the receiving computing system **108**. The digital signature may be generated via any suitable cryptographic algorithm, and may be generated via the use of a private key associated with the receiving computing system **108**, which may be part of a cryptographic key pair, where the moderating computing system

110 may possess the corresponding public key. In one embodiment, the digital signature may be generated via the signing of the payment request by the receiving computing system **108** using the private key.

[0033] The moderating computing system **110** may receive the signed payment request. In some embodiments, the moderating computing system **110** may be configured to verify the digital signature on the payment request. In such embodiments, the digital signature may be verified via use of the public key that corresponds to the private key used to generate the digital signature, which may be verified using any suitable algorithm associated therewith, which may vary based on algorithm used to generate the signature, the type of public key used, and the algorithm used to generate the key pair. If the verification fails, the moderating computing system **110** may notify the receiving computing system **108** and halt the processing of the transaction.

[0034] If the verification succeeds, then the moderating computing system **110** may store the signed payment request and may identify one or more fee values for fees to be paid (e.g., by the receiving computing system **108** and/or sending computing system **106**) for processing and settlement of the transaction. The moderating computing system **110** may also identify an acceptance address for the transaction. The acceptance address may be a unique value associated with the transaction, where the acceptance address may be used by each of the involved systems for identification of communications related to the transaction, which may also be used in the auditing thereof, as discussed in more detail below. The moderating computing system **110** may include the identified fee values and acceptance address in a message to be returned to the receiving computing system **108**. The moderating computing system **110** may be configured to digitally sign the message, where the digital signature may be generated using a private key of a cryptographic key pair associated with the moderating computing system **110**.

[0035] The receiving computing system **108** may receive the message from the moderating computing system **110**, including the one or more fee values, acceptance address, and digital signature. In some embodiments, the receiving computing system **108** may verify the digital signature, such as by using a public key corresponding to the private key used by the moderating computing system **110** (e.g., received by the receiving computing system **108** as part of a registration process with the moderating computing system **110**). The receiving computing system **108** may then generate an acceptance request. The acceptance request may be submitted to the sending computing system **106** via the established communication channel and include at least the reference value for the transaction, the acceptance address, the one or more fee values, and the moderating computing system's digital signature. In some instances, the receiving computing system **108** may add one or more additional fee values, such as for payment of fees to the receiving computing system **108** as part of the processing of the payment transaction.

[0036] The sending computing system **106** may receive the acceptance request and may verify the data included therein. For instance, the sending computing system **106** may verify the accuracy of the transaction reference value and verify the moderating computing system's digital signature, as discussed above. The sending computing system **106** may then determine if the acceptance request should be accepted or denied, such as based on the result of the

verification and the one or more fee values. For example, the sending computing system **106** may decline the transaction due to excess fees being charged, such as may exceed a pre-established agreement between the moderating computing system **110** (e.g., during a registration process) and/or the receiving computing system **108**, and/or between the purchasing entity **102** and supplying entity **104**.

[0037] If the sending computing system **106** agrees to the acceptance request, the sending computing system **106** may return an indication of agreement thereof to the receiving computing system **108**. The indication may include at least a digital signature generated by the sending computing system **106**, such as via the use of a private key of a cryptographic key pair associated with the sending computing system **106**. The digital signature may be generated on at least the transaction reference value and/or acceptance address, but may also, or alternatively, be generated on the one or more fee values to directly acknowledge agreement to pay the indicated fees. Such data may be included in a message that is digitally signed and then electronically transmitted to the receiving computing system **108** using the established communication channel.

[0038] The receiving computing system **108** may receive the signed message from the sending computing system **106**, which may indicate that the sending computing system **106** agrees to make payment for the payment amount and fee value(s) to the receiving computing system **108**. The receiving computing system **108** may then submit a transaction value to a blockchain network **112** for inclusion in a blockchain for confirmation of the transaction. The blockchain network **112** may be comprised of a plurality of nodes **114**, where the nodes **114** are each configured to generate new blocks for addition to the blockchain that are verified by other nodes **114** using traditional methods and systems that will be apparent to persons having skill in the relevant art. In some embodiments, the sending computing system **106**, receiving computing system **108**, and/or moderating computing system **110** may be a node **114**.

[0039] The transaction value submitted to a node **114** in the blockchain network **112** may include at least the reference value for the transaction, the acceptance address, and the sending computing system's digital signature. The transaction value may be included in a set of transaction values that are all included in a new block that is generated, verified, and added to the blockchain. The blockchain may be comprised of a plurality of blocks, where each block includes a block header and a set of transaction values. The block header may include a timestamp, a reference to a prior block, and a reference to the set of transaction values included in the respective block. In an exemplary embodiment, the reference to the prior block may refer to the block most recently added to the block prior to that respective block (e.g., identified via the timestamp included in its block header), and may be a hash value generated via the hashing of the block header in that most recently added block. The reference to the set of transaction values included in a block may similarly be generated via the hashing of the set of transaction values included in that block. In some cases, the reference may be the root of Merkle tree generated on the set of transaction values using one or more suitable hashing algorithms. The inclusion of the references in a block header may ensure immutability and cryptographic auditability of the blockchain; a modified transaction value would be immediately identified due to its resulting in an incorrect

reference for that block header, which would further result in an incorrect reference in the block header of every subsequent block added to the blockchain. Furthermore, the propagation of the blockchain across a plurality of nodes further prohibits the tampering of transaction values.

[0040] Once the transaction value for the transaction has been added to the blockchain, the sending computing system **106**, receiving computing system **108**, and moderating computing system **110** may each be able to verify the transaction value by verification of the transaction reference value and sending computing system's digital signature to ensure authenticity and accuracy of the transaction value. Once verified, the sending computing system **106** may debit the transaction account issued to the purchasing entity **102** and used for payment, and the receiving computing system **108** may credit the transaction account issued to the supplying entity **104** and associated with the primary account number.

[0041] Following processing of the transaction, settlement may be performed between the sending computing system **106** and the receiving computing system **108**. In some cases, net settlement may be performed, where the moderating computing system **110** may make an accounting of payments between all sending computing systems **106** and receiving computing systems **108** registered therewith over a period of time (e.g., daily) and may initiate settlement of net positions once the period expires, where each system may make payment to or receive payment from the moderating entity in accordance with their net positions. Methods for accounting of transactions over time and net settlement will be apparent to persons having skill in the relevant art.

[0042] In some embodiments, the moderating computing system **110** may be configured to verify its involvement in the processed transaction and inclusion thereof in settlement to be performed. In such embodiments, the moderating computing system **110** may be configured to generate a settlement acceptance. The settlement acceptance may include at least the transaction reference value, the acceptance address, and a digital signature generated by the moderating computing system **110**, which may be generated on the transaction reference value and acceptance address, or may be the digital signature previously generated by the moderating computing system **110**. The settlement acceptance may be submitted to a node **114** in the blockchain network **112** for addition thereto, which may then be verified by the sending computing system **106** and receiving computing system **108** for confirmation that settlement will be performed by the moderating computing system **110** (e.g., as opposed to the sending computing system **106** and receiving computing system **108** performing settlement independently, on a per-transaction basis).

[0043] The methods and systems discussed herein may enable two entities to engage in a payment transaction for which there is complete cryptographic auditability due to the use of digital signatures, the moderating computing system **110**, and the blockchain. The blockchain may provide each entity with the ability to verify transactions, where such data is also immutable to serve as a permanent record of transactions between each entity. In addition, as the blockchain only includes references to transactions, the transaction data may remain anonymous such that only parties involved in any transaction may be able to verify such data, and such that no entity may be able to identify entities involved in any transaction to which they are not a party. Thus, the blockchain serves as an immutable record that provides complete

cryptographic auditability to entities using the methods discussed herein, while maintaining complete privacy of transactions in which an entity is involved.

Processing Server

[0044] FIG. 2 illustrates an embodiment of a processing server **200** in the system **100**. It will be apparent to persons having skill in the relevant art that the embodiment of the processing server **200** illustrated in FIG. 2 is provided as illustration only and may not be exhaustive to all possible configurations of the processing server **200** suitable for performing the functions as discussed herein. For example, the computer system **800** illustrated in FIG. 8 and discussed in more detail below may be a suitable configuration of the processing server **200**. The processing server **200** may be part of or may comprise the sending computing system **106**, receiving computing system **108**, and/or the moderating computing system **110**. Accordingly, functions performed by each of the sending computing system **106**, receiving computing system **108**, and moderating computing system **110** may be performed by components of the processing server **200**, as discussed below, where each system may include or be comprised of a processing server **200** for the performance of the functions associated therewith.

[0045] The processing server **200** may include a receiving device **202**. The receiving device **202** may be configured to receive data over one or more networks via one or more network protocols. In some instances, the receiving device **202** may be configured to receive data from purchasing entities **102**, supplying entities **104**, sending computing systems **106**, receiving computing systems **108**, moderating computing systems **110**, nodes **114**, and other systems and entities via one or more communication methods, such as radio frequency, local area networks, wireless area networks, cellular communication networks, Bluetooth, the Internet, etc. In some embodiments, the receiving device **202** may be comprised of multiple devices, such as different receiving devices for receiving data over different networks, such as a first receiving device for receiving data over a local area network and a second receiving device for receiving data via the Internet. The receiving device **202** may receive electronically transmitted data signals, where data may be superimposed or otherwise encoded on the data signal and decoded, parsed, read, or otherwise obtained via receipt of the data signal by the receiving device **202**. In some instances, the receiving device **202** may include a parsing module for parsing the received data signal to obtain the data superimposed thereon. For example, the receiving device **202** may include a parser program configured to receive and transform the received data signal into usable input for the functions performed by the processing device to carry out the methods and systems described herein.

[0046] The receiving device **202** may be configured to receive data signals superimposed or otherwise encoded with payment data, which may be transaction messages formatted pursuant to one or more standards, such as the ISO 8583 or ISO 20022 standards, such as may be submitted by purchasing entities **102** and/or supplying entities **104**. The receiving device **202** may also be configured to receive data signals superimposed or otherwise encoded with account verification requests and confirmations, such as may be electronically transmitted by sending computing systems **106**, receiving computing systems **108**, or moderating computing systems **110**. The receiving device **202** may be further

configured to receive data signals electronically transmitted by sending computing systems **106**, which may be superimposed or otherwise encoded with payment requests and acceptance messages. The receiving device **202** may also be configured to receive data signals electronically transmitted by receiving computing systems **108**, which may be superimposed or otherwise encoded with payment confirmations, payment requests, and acceptance messages. The receiving device **202** may also be configured to receive data signals electronically transmitted by moderating computing systems **110**, which may be superimposed or otherwise encoded with responses to payment requests and data messages related to settlement of transactions. Receiving devices **202** may also be configured to receive data signals electronically transmitted by nodes **114**, which may be superimposed or otherwise encoded with blockchain data, such as for use in verification and auditing of transactions and settlement acceptances.

[0047] The processing server **200** may also include a communication module **204**. The communication module **204** may be configured to transmit data between modules, engines, databases, memories, and other components of the processing server **200** for use in performing the functions discussed herein. The communication module **204** may be comprised of one or more communication types and utilize various communication methods for communications within a computing device. For example, the communication module **204** may be comprised of a bus, contact pin connectors, wires, etc. In some embodiments, the communication module **204** may also be configured to communicate between internal components of the processing server **200** and external components of the processing server **200**, such as externally connected databases, display devices, input devices, etc. The processing server **200** may also include a processing device. The processing device may be configured to perform the functions of the processing server **200** discussed herein as will be apparent to persons having skill in the relevant art. In some embodiments, the processing device may include and/or be comprised of a plurality of engines and/or modules specially configured to perform one or more functions of the processing device, such as a querying module **216**, signing module **218**, generation module **220**, verification module **214**, etc. As used herein, the term “module” may be software or hardware particularly programmed to receive an input, perform one or more processes using the input, and provides an output. The input, output, and processes performed by various modules will be apparent to one skilled in the art based upon the present disclosure.

[0048] The processing server **200** may include an account database **206**. The account database **206** may be configured to store a plurality of account profiles **208** using a suitable data storage format and schema. The account database **206** may be a relational database that utilizes structured query language for the storage, identification, modifying, updating, accessing, etc. of structured data sets stored therein. Each account profile **208** may be a structured data set configured to store data related to one or more transaction accounts, where data included therein may be based on the functions performed by the processing server **200**. Account profiles **208** may include associated account numbers, balance and credit information, communication information, etc. For instance, the sending computing system **106** may store account profiles **208** for transaction account issued by

the sending computing system **106**, which may include balance and credit data, and may also store account profiles **208** for transaction accounts issued to receiving computing systems **108**, which may include communication data for establishing communication with the associated receiving computing system **108**.

[0049] The processing server **200** may also include or be otherwise interfaced with one or more input devices **210**. The input devices **210** may be internal to the processing server **200** or external to the processing server **200** and connected thereto via one or more connections (e.g., wired or wireless) for the transmission of data to and/or from. The input devices **210** may be configured to receive input from a user of the processing server **200**, which may be provided to another module or engine of the processing server **200** (e.g., via the communication module **204**) for processing accordingly. Input devices **210** may include any type of input device suitable for receiving input for the performing of the functions discussed herein, such as a keyboard, mouse, click wheel, scroll wheel, microphone, touch screen, track pad, camera, optical imager, etc. The input device **210** may be configured to, for example, receive input of payment data, such as primary account numbers, payment amounts, fee values, other account numbers, etc., which may be used in performing the functions of the processing server **200** as discussed herein.

[0050] The processing server **200** may include a querying module **216**. The querying module **216** may be configured to execute queries on databases to identify information. The querying module **216** may receive one or more data values or query strings, and may execute a query string based thereon on an indicated database, such as the account database **206**, to identify information stored therein. The querying module **216** may then output the identified information to an appropriate engine or module of the processing server **200** as necessary. The querying module **216** may, for example, execute a query on the account database to identify an account profile **208** for use in verifying transaction account eligibility, identifying a receiving computing system **108**, identifying communication data, etc.

[0051] The processing server **200** may also include a verification module **214**. The verification module **214** may be configured to perform data verifications for the processing server **200** in conjunction with the functions discussed herein. The verification module **214** may receive instructions as input, may verify data in accordance with the instructions, and may output results of the verifications to other modules or engines of the processing server **200**. In some cases, the input may include data to be used in the verifications. In other cases, the verification module **214** may be configured to identify (e.g., via instructing of the querying module **216**) data to be used in the verifications. The verification module **214** may be configured to, for example, verify digital signatures, transaction reference values, fee values, settlement acceptances, and acceptance addresses during the functions of the sending computing system **106**, receiving computing system **108**, and moderating computing system **110** as discussed herein.

[0052] The processing server **200** may also include a signing module **218**. The signing module **218** may be configured to generate digital signatures for use in performing the functions of the processing server **200** discussed herein. The signing module **218** may be configured to receive data to be signed as input, may generate a digital

signature for the data using a suitable algorithm or algorithms, and may output the digital signature to other modules or engines of the processing server **200**. In some embodiments, the signing module **218** may receive algorithms and/or cryptographic keys to use in the generation of digital signatures as input. In other embodiments, the signing module **218** may be configured to identify such data during the process of generating a digital signature, such as by instructing the querying module **216** to execute queries to identify data stored in the processing server **200**. The signing module **218** may be configured to generate digital signatures on payment requests, acceptance requests, and other data, such as for indication of acceptance of payment amounts and fees for cryptographically auditable transactions as discussed herein.

[0053] The processing server **200** may also include a generation module **220**. The generation module **220** may be configured to generate data for use in performing the functions of the processing server **200** as discussed herein. The generation module **220** may receive an instruction as input, may generate data as instructed, and may output the generated data to another module or engine of the processing server **200**. For example, the generation module **220** may be configured to generate payment requests, unique identifiers, transaction reference values, acceptance requests, acceptance addresses, payment acceptances, settlement acceptances, and other data and data messages used in performing the functions of the sending computing system **106**, receiving computing system **108**, and moderating computing system **110** as discussed herein.

[0054] The processing server **200** may also include a transmitting device **222**. The transmitting device **222** may be configured to transmit data over one or more networks via one or more network protocols. In some instances, the transmitting device **222** may be configured to transmit data to purchasing entities **102**, supplying entities **104**, sending computing systems **106**, receiving computing systems **108**, moderating computing systems **110**, nodes **114**, and other entities via one or more communication methods, local area networks, wireless area networks, cellular communication, Bluetooth, radio frequency, the Internet, etc. In some embodiments, the transmitting device **222** may be comprised of multiple devices, such as different transmitting devices for transmitting data over different networks, such as a first transmitting device for transmitting data over a local area network and a second transmitting device for transmitting data via the Internet. The transmitting device **222** may electronically transmit data signals that have data superimposed that may be parsed by a receiving computing device. In some instances, the transmitting device **222** may include one or more modules for superimposing, encoding, or otherwise formatting data into data signals suitable for transmission.

[0055] The transmitting device **222** may be configured to electronically transmit data signals superimposed or otherwise encoded with account verification requests and confirmations, such as may be electronically transmitted by sending computing systems **106**, receiving computing systems **108**, or moderating computing systems **110**. The transmitting device **222** may be further configured to electronically transmit data signals from sending computing systems **106**, which may be superimposed or otherwise encoded with payment requests and acceptance messages. The transmitting device **222** may also be configured to electronically

transmit data signals from receiving computing systems **108**, which may be superimposed or otherwise encoded with payment confirmations, payment requests, and acceptance messages. The transmitting device **222** may also be configured to electronically transmit data signals from moderating computing systems **110**, which may be superimposed or otherwise encoded with responses to payment requests and data messages related to settlement of transactions. Transmitting devices **222** may also be configured to electronically transmit data signals to nodes **114**, which may be superimposed or otherwise encoded with transaction values and/or settlement acceptance messages for addition to the blockchain associated therewith.

[0056] The processing server **200** may also include a memory **224**. The memory **224** may be configured to store data for use by the processing server **200** in performing the functions discussed herein, such as public and private keys, symmetric keys, etc. The memory **224** may be configured to store data using suitable data formatting methods and schema and may be any suitable type of memory, such as read-only memory, random access memory, etc. The memory **224** may include, for example, encryption keys and algorithms, communication protocols and standards, data formatting standards and protocols, program code for modules and application programs of the processing device, and other data that may be suitable for use by the processing server **200** in the performance of the functions disclosed herein as will be apparent to persons having skill in the relevant art. In some embodiments, the memory **224** may be comprised of or may otherwise include a relational database that utilizes structured query language for the storage, identification, modifying, updating, accessing, etc. of structured data sets stored therein. The memory **224** may be configured to store, for example, blockchain data, lookup tables for receiving computing systems **108** and communication data, encryption algorithms for generating cryptographic key pairs or digital signatures, private and public keys, etc.

Process for Identification and Confirmation of a Transaction Account

[0057] FIG. 3 illustrates a process in the system **100** for the identification of a transaction account for use in receiving funds in the cryptographically auditable transaction and confirmation of eligibility thereof.

[0058] In step **302**, the receiving device **202** and/or input device **210** of the sending computing system **106** may receive payment data for a proposed transaction, where the payment data includes at least a primary account number to which payment is to be made. In step **304**, the querying module **216** of the sending computing system **106** may execute a query on an account database **206** of the sending computing system **106** or other storage to identify a receiving entity associated with the primary account number. The sending computing system **106** may be able to successfully identify the entity, but may not have a current routing number associated with the receiving computing system **108** of the entity for use in establishing communication therewith.

[0059] In step **306**, the transmitting device **222** of the sending computing system **106** may electronically transmit a routing number request to the moderating computing system **110**. The routing number request may include the primary account number and/or identification of the receiving entity. In step **308**, the receiving device **202** of the

moderating computing system 110 may receive the routing number request. In step 310, the querying module 216 of the moderating computing system 110 may execute a query on an account database 206 or other storage of the moderating computing system 110 to identify a current routing number for the receiving entity. In step 312, the transmitting device 222 of the moderating computing system 110 may electronically transmit the routing number to the sending computing system 106.

[0060] In step 314, the receiving device 202 of the sending computing system 106 may receive the routing number. In step 316, the transmitting device 222 of the sending computing system 106 may electronically transmit a request for account verification to the receiving computing system 108. The request for account verification may include at least the primary account number supplied as part of the payment data, and may be submitted to the receiving computing system 108 using the routing number received from the moderating computing system 110. In some instances, the sending computing system 106 may establish a direct communication channel with the receiving computing system 108 using the routing number, through which the request for account verification may be transmitted. In step 318, the receiving device 202 of the receiving computing system 108 may receive the account verification request.

[0061] In step 320, the receiving computing system 108 may determine if the transaction account associated with the primary account number is eligible for receipt of funds via a cryptographically auditable transaction. The querying module 216 of the receiving computing system 108 may execute a query on an account database 206 stored therein and identify an account profile 208 that includes the primary account number. The verification module 214 of the receiving computing system 108 may verify that the transaction account related thereto is eligible for use in receiving funds. In step 322, the transmitting device 222 of the receiving computing system 108 may electronically transmit a confirmation message to the sending computing system 106, which may be received by a receiving device 202 thereof, in step 324. The confirmation message may indicate that the transaction account associated with the primary account number is eligible to receive funds, such that the cryptographically auditable transaction may proceed for processing.

Processing of a Cryptographically Auditable Transaction

[0062] FIGS. 4A and 4B illustrate a process for the processing of a cryptographically auditable transaction involving a moderating entity and the use of a blockchain in the system 100.

[0063] In step 402, the generation module 220 of the sending computing system 106 may generate a reference value for a transaction to be processed. The reference value may be generated on payment data received for the transaction, and may be generated via the application of one or more hashing algorithms to the payment data, transformation of the payment data using standardized rules, or other suitable method. The payment data may include at least a primary account number to which payment is to be made, a payment amount, and any other data suitable for use in the processing and settlement of a transaction, such as an account number from which payment is to be made, transaction time and/or date, consumer data, product data, purchase order data, invoice data, offer data, reward data,

loyalty data, geographic location, etc. In step 404, the generation module 220 of the sending computing system 106 may generate a payment request, which may include at least the generated reference value.

[0064] In step 406, the transmitting device 222 of the sending computing system 106 may electronically transmit the generated payment request to the receiving computing system 108 using a communication channel established therewith. In step 408, the receiving device 202 of the receiving computing system 108 may receive the payment request. In some embodiments, the receiving computing system 108 may be configured to acknowledge receipt of the payment request, by returning a response message to the sending computing system 106. In step 410, the signing module 218 of the receiving computing system 108 may generate a digital signature on the payment request using a private key associated with the receiving computing system 108. In step 412, the transmitting device 222 of the receiving computing system 108 may electronically transmit the signed payment request to the moderating computing system 110.

[0065] In step 414, the receiving device 202 of the moderating computing system 110 may receive the signed payment request. In some embodiments, a verification module 214 of the moderating computing system 110 may be used to verify the digital signature on the payment request, such as using a public key associated with the receiving computing system 108 and corresponding to the private key used to generate the digital signature. In step 416, the querying module 216 of the moderating computing system 110 may identify one or more fee values for processing the transaction, which may be based on the payment data for the transaction, entities involved in the transaction, or other criteria that will be apparent to persons having skill in the relevant art. In step 418, the moderating computing system 110 may identify an acceptance address for unique association with the transaction, such as may be identified via a query executed by the querying module 216 of the moderating computing system 110 or generated by the generation module 220 of the moderating computing system 110.

[0066] In step 420, the signing module 218 of the moderating computing system 110 may generate a digital signature, which may be generated on at least the identified fee values, and may be generated on a message that includes the identified fee values, acceptance address, and transaction reference value. The digital signature may be generated using a private key associated with the moderating computing system 110, such as may be queried (e.g., by the moderating computing system's querying module 216) from a memory 224 of the moderating computing system 110. In step 422, the transmitting device 222 of the moderating computing system 110 may return transaction data to the receiving computing system 108, which may be comprised of at least the identified fee values, acceptance address, and the generated digital signature.

[0067] In step 424, the receiving device 202 of the receiving computing system 108 may receive the transaction data from the moderating computing system 110. In step 426, the transmitting device 222 of the receiving computing system 108 may electronically transmit an acceptance request to the sending computing system 106. The acceptance request may include at least the transaction reference value, the one or more fee values, the acceptance address, and the moderating computing system's digital signature. In some cases, the

receiving computing system **108** may verify the moderating computing system's digital signature prior to transmission of the acceptance request. In step **428**, the receiving device **202** of the sending computing system **106** may receive the acceptance request. The sending computing system **106** may then (e.g., using the verification module **214** thereof) verify that the transaction should proceed, such as by confirming the data included in the acceptance request (e.g., ensuring the transaction reference value is correct, checking for excess or unknown fees, verifying the moderating computing system's digital signature, etc.).

[0068] In step **430**, signing module **218** of the sending computing system **106** may generate a digital signature, which may be generated on at least the identified fee values, and may be generated on the acceptance request. The digital signature may be generated using a private key associated with the sending computing system **106**, such as may be queried (e.g., by the sending computing system's querying module **216**) from a memory **224** of the sending computing system **106**. In step **432**, the transmitting device **222** of the sending computing system **106** may electronically transmit an acceptance message to the receiving computing system **108**. The acceptance message may include at least the acceptance address and the sending computing system's digital signature.

[0069] In step **434**, the receiving device **202** of the receiving computing system **108** may receive the acceptance message from the sending computing system **106**. In step **436**, the generation module **220** of the receiving computing system **108** may generate a transaction value for the transaction. The transaction value may be formatted in compliance with any rules or standards set forth by the blockchain network **112** and may include at least the reference value for the transaction, the acceptance address, and the digital signature generated by the sending computing system **106**. In step **438**, the transmitting device **222** of the receiving computing system **108** may electronically transmit the transaction value to a node **114** associated with the blockchain network **112** for addition thereto using standard methods and systems. Each of the sending computing system **106**, receiving computing system **108**, and moderating computing system **110** may then be free to identify the transaction value in the blockchain (e.g., via the acceptance address and/or transaction reference value) and verify the data included therein. The sending computing system **106** and receiving computing system **108** may settle their respective transaction accounts accordingly, and the moderating computing system **110** may account for the transaction when performing net settlement for all associated entities.

First Exemplary Method for Processing of a Cryptographically Auditable Transaction

[0070] FIG. 5 illustrates a method **500** for the processing of a cryptographically auditable transaction including the generation and submission of a payment request from an entity associated with a transaction account used for funding of the transaction.

[0071] In step **502**, payment data may be received by an input device (e.g., the input device **210**) of a processing server (e.g., a processing server **200** comprising the sending computing system **106**), wherein the payment data includes at least a primary account number. In step **504**, the primary account number may be electronically transmitted by a transmitting device (e.g., the transmitting device **222**) of the

processing server to a computing system (e.g., the receiving computing system **108**). In step **506**, a confirmation associated with the primary account number may be received by a receiving device (e.g., the receiving device **202**) of the processing server from the computing system.

[0072] In step **508**, a payment request may be electronically transmitted by the transmitting device of the processing server to the computing system, wherein the payment request includes at least a reference value associated with a payment transaction. In step **510**, an acceptance request may be received from the computing system by the receiving device of the processing server, wherein the acceptance request includes at least the reference value, an acceptance address, one or more fee values, and a first digital signature generated by a third party (e.g., the moderating computing system **110**).

[0073] In step **512**, a second signature may be generated by a signing module (e.g., the signing module **218**) of the processing server using at least the acceptance address. In step **514**, at least the second digital signature may be electronically transmitted to the computing system by the transmitting device of the processing server.

[0074] In one embodiment, the method **500** may further include: receiving, by the receiving device of the processing server, a transaction message associated with the payment transaction, wherein the transaction message is formatted based on one or more standards and includes at least a plurality of data elements including at least a first data element configured to store the primary account number; and generating, by a hashing module (e.g., the generation module **220**) of the processing server, the reference value based on application of one or more hashing algorithms to the received transaction message. In some embodiments, the method **500** may also include receiving, by the receiving device of the processing server, blockchain data from a node (e.g., a node **114**) associated with a blockchain network (e.g., the blockchain network **112**), wherein the blockchain data includes one or more blocks comprising a blockchain, each block being comprised of at least a block header and one or more transaction values, wherein each transaction value includes at least a transaction address, a transaction reference, and a transaction signature; executing, by a querying module (e.g., the querying module **216**) of the processing server, a query on the received blockchain data to identify a specific transaction value where the included transaction address corresponds to the acceptance address; and verifying, by a verification module (e.g., the verification module **214**) of the processing server, the specific transaction value based on at least a correspondence between the included transaction reference and the reference value and a correspondence between the included transaction signature and the second digital signature.

Second Exemplary Method for Processing of a Cryptographically Auditable Transaction

[0075] FIG. 6 illustrates a method **600** for the processing of a cryptographically auditable transaction including the receipt and processing of a payment request by an entity associated with a transaction account used for the receipt of funds in the transaction.

[0076] In step **602**, a payment request may be received by a receiving device (e.g., the receiving device **202**) of a processing server (e.g., a processing server **200** comprising the receiving computing system **108**) from a first computing

system (e.g., the sending computing system 106) wherein the payment request includes at least a reference value associated with a payment transaction. In step 604, a first digital signature may be generated by a signing module (e.g., the signing module 218) of the processing server using at least the received payment request. In step 606, at least the first digital signature and the payment request may be electronically transmitted by a transmitting device (e.g., the transmitting device 222) of the processing server to a second computing system (e.g., the moderating computing system 110).

[0077] In step 608, a confirmation message may be received from the second computing system by the receiving device of the processing server, wherein the confirmation message includes at least one or more fee values, a second digital signature, and an acceptance address. In step 610, an acceptance request may be electronically transmitted to the first computing system by the transmitting device of the processing server, wherein the acceptance request includes at least the reference value, the one or more fee values, the second digital signature, and the acceptance address.

[0078] In step 612, an acceptance message may be received from the first computing system by the receiving device of the processing server, wherein the acceptance message includes at least a third digital signature. In step 614, a transaction value may be electronically transmitted by the transmitting device of the processing server to a node (e.g., a node 114) associated with a blockchain network (e.g., the blockchain network 112), wherein the transaction value includes at least the reference value, the acceptance address, and the third digital signature.

[0079] In one embodiment, the method 600 may further include: receiving, by the receiving device of the processing server, blockchain data from a node associated with the blockchain network, wherein the blockchain data includes one or more blocks comprising a blockchain, each block being comprised of at least a block header and one or more transaction values, wherein each transaction value includes at least a transaction address, a transaction reference, and a transaction signature; executing, by a querying module (e.g., the querying module 216) of the processing server, a query on the received blockchain data to identify a specific transaction value where the included transaction address corresponds to the acceptance address; and verifying, by a verification module (e.g., the verification module 214) of the processing server, the specific transaction value based on at least a correspondence between the included transaction reference and the reference value and a correspondence between the included transaction signature and the third digital signature. In some embodiments, the method 600 may also include: storing, in an account database (e.g., the account database 206) of the processing server, a plurality of account profiles (e.g., account profiles 208), wherein each account profile includes a structured data set related to a transaction account including at least a primary account number; receiving, by the receiving device of the processing server, a verification request from the first computing system, wherein the verification request includes at least a specific account number; verifying, by the verification module of the processing server, an account profile of the plurality of account profiles where the included primary account number corresponds to the specific account number; and electronically transmitting, by the transmitting device of

the processing server, an indication of successful verification to the first computing system.

Third Exemplary Method for Processing of a Cryptographically Auditable Transaction

[0080] FIG. 7 illustrates a method 700 for the processing of a cryptographically auditable transaction including the processing of data associated therewith by a third party, moderating entity.

[0081] In step 702, a payment request may be received by a receiving device (e.g., the receiving device 202) of a processing server (e.g., a processing server 200 comprising the moderating computing system 110) from a computing system (e.g., the receiving computing system 108), wherein the payment request includes at least a reference value associated with a payment transaction and a first digital signature. In step 704, a querying module (e.g., the querying module 216) of the processing server may execute a first query to identify one or more fee values for the payment transaction and a second query to identify an acceptance address. In step 706, a second digital signature may be generated by a signing module (e.g., the signing module 218) of the processing server.

[0082] In step 708, at least the one or more fee values, the acceptance address, and the second digital signature may be electronically transmitted by a transmitting device (e.g., the transmitting device 222) of the processing server to the computing system. In step 710, the receiving device of the processing server may receive blockchain data from a node (e.g., a node 114) associated with a blockchain network (e.g., the blockchain network 112), wherein the blockchain data includes one or more blocks comprising a blockchain, each block being comprised of at least a block header and one or more transaction values, wherein each transaction value includes at least a transaction address, a transaction reference, and a transaction signature.

[0083] In step 712, a query may be executed on the received blockchain data by the querying module of the processing server to identify a specific transaction value where the included transaction address corresponds to the acceptance address. In step 714, the specific transaction value may be verified by a verification module (e.g., the verification module 214) of the processing server based on at least a correspondence between the included transaction reference and the reference value. In one embodiment, the method 700 may further include: generating, by a generation module (e.g., the generation module 220) of the processing server, an acceptance entry, wherein the acceptance entry includes at least the acceptance address, the reference value, and the second digital signature; and electronically transmitting, by the transmitting device of the processing server, the generated acceptance entry to a node associated with the blockchain network.

Computer System Architecture

[0084] FIG. 8 illustrates a computer system 800 in which embodiments of the present disclosure, or portions thereof, may be implemented as computer-readable code. For example, the sending computing system 106, receiving computing system 108, and moderating computing system 110 of FIG. 1 may be implemented in the computer system 800 using hardware, software, firmware, non-transitory computer readable media having instructions stored thereon,

or a combination thereof and may be implemented in one or more computer systems or other processing systems. Hardware, software, or any combination thereof may embody modules and components used to implement the methods of FIGS. 3, 4A, 4B, and 5-7.

[0085] If programmable logic is used, such logic may execute on a commercially available processing platform configured by executable software code to become a specific purpose computer or a special purpose device (e.g., programmable logic array, application-specific integrated circuit, etc.). A person having ordinary skill in the art may appreciate that embodiments of the disclosed subject matter can be practiced with various computer system configurations, including multi-core multiprocessor systems, minicomputers, mainframe computers, computers linked or clustered with distributed functions, as well as pervasive or miniature computers that may be embedded into virtually any device. For instance, at least one processor device and a memory may be used to implement the above described embodiments.

[0086] A processor unit or device as discussed herein may be a single processor, a plurality of processors, or combinations thereof. Processor devices may have one or more processor “cores.” The terms “computer program medium,” “non-transitory computer readable medium,” and “computer usable medium” as discussed herein are used to generally refer to tangible media such as a removable storage unit **818**, a removable storage unit **822**, and a hard disk installed in hard disk drive **812**.

[0087] Various embodiments of the present disclosure are described in terms of this example computer system **800**. After reading this description, it will become apparent to a person skilled in the relevant art how to implement the present disclosure using other computer systems and/or computer architectures. Although operations may be described as a sequential process, some of the operations may in fact be performed in parallel, concurrently, and/or in a distributed environment, and with program code stored locally or remotely for access by single or multi-processor machines. In addition, in some embodiments the order of operations may be rearranged without departing from the spirit of the disclosed subject matter.

[0088] Processor device **804** may be a special purpose or a general purpose processor device specifically configured to perform the functions discussed herein. The processor device **804** may be connected to a communications infrastructure **806**, such as a bus, message queue, network, multi-core message-passing scheme, etc. The network may be any network suitable for performing the functions as disclosed herein and may include a local area network (LAN), a wide area network (WAN), a wireless network (e.g., WiFi), a mobile communication network, a satellite network, the Internet, fiber optic, coaxial cable, infrared, radio frequency (RF), or any combination thereof. Other suitable network types and configurations will be apparent to persons having skill in the relevant art. The computer system **800** may also include a main memory **808** (e.g., random access memory, read-only memory, etc.), and may also include a secondary memory **810**. The secondary memory **810** may include the hard disk drive **812** and a removable storage drive **814**, such as a floppy disk drive, a magnetic tape drive, an optical disk drive, a flash memory, etc.

[0089] The removable storage drive **814** may read from and/or write to the removable storage unit **818** in a well-

known manner. The removable storage unit **818** may include a removable storage media that may be read by and written to by the removable storage drive **814**. For example, if the removable storage drive **814** is a floppy disk drive or universal serial bus port, the removable storage unit **818** may be a floppy disk or portable flash drive, respectively. In one embodiment, the removable storage unit **818** may be non-transitory computer readable recording media.

[0090] In some embodiments, the secondary memory **810** may include alternative means for allowing computer programs or other instructions to be loaded into the computer system **800**, for example, the removable storage unit **822** and an interface **820**. Examples of such means may include a program cartridge and cartridge interface (e.g., as found in video game systems), a removable memory chip (e.g., EEPROM, PROM, etc.) and associated socket, and other removable storage units **822** and interfaces **820** as will be apparent to persons having skill in the relevant art.

[0091] Data stored in the computer system **800** (e.g., in the main memory **808** and/or the secondary memory **810**) may be stored on any type of suitable computer readable media, such as optical storage (e.g., a compact disc, digital versatile disc, Blu-ray disc, etc.) or magnetic tape storage (e.g., a hard disk drive). The data may be configured in any type of suitable database configuration, such as a relational database, a structured query language (SQL) database, a distributed database, an object database, etc. Suitable configurations and storage types will be apparent to persons having skill in the relevant art.

[0092] The computer system **800** may also include a communications interface **824**. The communications interface **824** may be configured to allow software and data to be transferred between the computer system **800** and external devices. Exemplary communications interfaces **824** may include a modem, a network interface (e.g., an Ethernet card), a communications port, a PCMCIA slot and card, etc. Software and data transferred via the communications interface **824** may be in the form of signals, which may be electronic, electromagnetic, optical, or other signals as will be apparent to persons having skill in the relevant art. The signals may travel via a communications path **826**, which may be configured to carry the signals and may be implemented using wire, cable, fiber optics, a phone line, a cellular phone link, a radio frequency link, etc.

[0093] The computer system **800** may further include a display interface **802**. The display interface **802** may be configured to allow data to be transferred between the computer system **800** and external display **830**. Exemplary display interfaces **802** may include high-definition multimedia interface (HDMI), digital visual interface (DVI), video graphics array (VGA), etc. The display **830** may be any suitable type of display for displaying data transmitted via the display interface **802** of the computer system **800**, including a cathode ray tube (CRT) display, liquid crystal display (LCD), light-emitting diode (LED) display, capacitive touch display, thin-film transistor (TFT) display, etc.

[0094] Computer program medium and computer usable medium may refer to memories, such as the main memory **808** and secondary memory **810**, which may be memory semiconductors (e.g., DRAMs, etc.). These computer program products may be means for providing software to the computer system **800**. Computer programs (e.g., computer control logic) may be stored in the main memory **808** and/or the secondary memory **810**. Computer programs may also

be received via the communications interface 824. Such computer programs, when executed, may enable computer system 800 to implement the present methods as discussed herein. In particular, the computer programs, when executed, may enable processor device 804 to implement the methods illustrated by FIGS. 3, 4A, 4B, and 5-7, as discussed herein. Accordingly, such computer programs may represent controllers of the computer system 800. Where the present disclosure is implemented using software, the software may be stored in a computer program product and loaded into the computer system 800 using the removable storage drive 814, interface 820, and hard disk drive 812, or communications interface 824.

[0095] The processor device 804 may comprise one or more modules or engines configured to perform the functions of the computer system 800. Each of the modules or engines may be implemented using hardware and, in some instances, may also utilize software, such as corresponding to program code and/or programs stored in the main memory 808 or secondary memory 810. In such instances, program code may be compiled by the processor device 804 (e.g., by a compiling module or engine) prior to execution by the hardware of the computer system 800. For example, the program code may be source code written in a programming language that is translated into a lower level language, such as assembly language or machine code, for execution by the processor device 804 and/or any additional hardware components of the computer system 800. The process of compiling may include the use of lexical analysis, preprocessing, parsing, semantic analysis, syntax-directed translation, code generation, code optimization, and any other techniques that may be suitable for translation of program code into a lower level language suitable for controlling the computer system 800 to perform the functions disclosed herein. It will be apparent to persons having skill in the relevant art that such processes result in the computer system 800 being a specially configured computer system 800 uniquely programmed to perform the functions discussed above.

[0096] Techniques consistent with the present disclosure provide, among other features, systems and methods for processing cryptographically auditable transactions. While various exemplary embodiments of the disclosed system and method have been described above it should be understood that they have been presented for purposes of example only, not limitations. It is not exhaustive and does not limit the disclosure to the precise form disclosed. Modifications and variations are possible in light of the above teachings or may be acquired from practicing of the disclosure, without departing from the breadth or scope.

What is claimed is:

1. A method for processing of a cryptographically auditable transaction, comprising:

receiving, by an input device of a processing server, payment data, wherein the payment data includes at least a primary account number;

electronically transmitting, by a transmitting device of the processing server, the primary account number to a computing system;

receiving, by a receiving device of the processing server, a confirmation associated with the primary account number from the computing system;

electronically transmitting, by the transmitting device of the processing server, a payment request to the com-

puting system, wherein the payment request includes at least a reference value associated with a payment transaction;

receiving, by the receiving device of the processing server, an acceptance request from the computing system, wherein the acceptance request includes at least the reference value, an acceptance address, one or more fee values, and a first digital signature generated by a third party;

generating, by a signing module of the processing server, a second digital signature using at least the acceptance address; and

electronically transmitting, by the transmitting device of the processing server, at least the second digital signature to the computing system.

2. The method of claim 1, further comprising:

receiving, by the receiving device of the processing server, a transaction message associated with the payment transaction, wherein the transaction message is formatted based on one or more standards and includes at least a plurality of data elements including at least a first data element configured to store the primary account number; and

generating, by a hashing module of the processing server, the reference value based on application of one or more hashing algorithms to the received transaction message.

3. The method of claim 1, further comprising:

receiving, by the receiving device of the processing server, blockchain data from a node associated with a blockchain network, wherein the blockchain data includes one or more blocks comprising a blockchain, each block being comprised of at least a block header and one or more transaction values, wherein each transaction value includes at least a transaction address, a transaction reference, and a transaction signature;

executing, by a querying module of the processing server, a query on the received blockchain data to identify a specific transaction value where the included transaction address corresponds to the acceptance address; and

verifying, by a verification module of the processing server, the specific transaction value based on at least a correspondence between the included transaction reference and the reference value and a correspondence between the included transaction signature and the second digital signature.

4. A method for processing of a cryptographically auditable transaction, comprising:

receiving, by a receiving device of a processing server, a payment request from a first computing system, wherein the payment request includes at least a reference value associated with a payment transaction;

generating, by a signing module of the processing server, a first digital signature using at least the received payment request;

electronically transmitting, by a transmitting device of the processing server, at least the first digital signature and the payment request to a second computing system;

receiving, by the receiving device of the processing server, a confirmation message from the second computing system, wherein the confirmation message includes at least one or more fee values, a second digital signature, and an acceptance address;

electronically transmitting, by the transmitting device of the processing server, an acceptance request to the first

- computing system, wherein the acceptance request includes at least the reference value, the one or more fee values, the second digital signature, and the acceptance address;
- receiving, by the receiving device of the processing server, an acceptance message from the first computing system, wherein the acceptance message includes at least a third digital signature; and
- electronically transmitting, by the transmitting device of the processing server, a transaction value to a node associated with a blockchain network, wherein the transaction value includes at least the reference value, the acceptance address, and the third digital signature.
5. The method of claim 4, comprising:
- receiving, by the receiving device of the processing server, blockchain data from a node associated with the blockchain network, wherein the blockchain data includes one or more blocks comprising a blockchain, each block being comprised of at least a block header and one or more transaction values, wherein each transaction value includes at least a transaction address, a transaction reference, and a transaction signature;
- executing, by a querying module of the processing server, a query on the received blockchain data to identify a specific transaction value where the included transaction address corresponds to the acceptance address; and
- verifying, by a verification module of the processing server, the specific transaction value based on at least a correspondence between the included transaction reference and the reference value and a correspondence between the included transaction signature and the third digital signature.
6. The method of claim 4, further comprising:
- storing, in an account database of the processing server, a plurality of account profiles, wherein each account profile includes a structured data set related to a transaction account including at least a primary account number;
- receiving, by the receiving device of the processing server, a verification request from the first computing system, wherein the verification request includes at least a specific account number;
- verifying, by a verification module of the processing server, an account profile of the plurality of account profiles where the included primary account number corresponds to the specific account number; and
- electronically transmitting, by the transmitting device of the processing server, an indication of successful verification to the first computing system.
7. A method for processing of a cryptographically auditable transaction, comprising:
- receiving, by a receiving device of a processing server, a payment request from a computing system, wherein the payment request includes at least a reference value associated with a payment transaction and a first digital signature;
- executing, by a querying module of the processing server, a first query to identify one or more fee values for the payment transaction and a second query to identify an acceptance address;
- generating, by a signing module of the processing server, a second digital signature;
- electronically transmitting, by a transmitting device of the processing server, at least the one or more fee values, the acceptance address, and the second digital signature to the computing system;
- receiving, by the receiving device of the processing server, blockchain data from a node associated with the blockchain network, wherein the blockchain data includes one or more blocks comprising a blockchain, each block being comprised of at least a block header and one or more transaction values, wherein each transaction value includes at least a transaction address, a transaction reference, and a transaction signature;
- executing, by the querying module of the processing server, a query on the received blockchain data to identify a specific transaction value where the included transaction address corresponds to the acceptance address; and
- verifying, by a verification module of the processing server, the specific transaction value based on at least a correspondence between the included transaction reference and the reference value.
8. The method of claim 7, further comprising:
- generating, by a generation module of the processing server, an acceptance entry, wherein the acceptance entry includes at least the acceptance address, the reference value, and the second digital signature; and
- electronically transmitting, by the transmitting device of the processing server, the generated acceptance entry to a node associated with the blockchain network.
9. A system for processing of a cryptographically auditable transaction, comprising:
- a signing module of a processing server;
- an input device of the processing server configured to receive payment data, wherein the payment data includes at least a primary account number;
- a transmitting device of the processing server configured to electronically transmit the primary account number to a computing system; and
- a receiving device of the processing server configured to receive a confirmation associated with the primary account number from the computing system, wherein the transmitting device of the processing server is further configured to electronically transmit a payment request to the computing system, wherein the payment request includes at least a reference value associated with a payment transaction;
- the receiving device of the processing server is further configured to receive an acceptance request from the computing system, wherein the acceptance request includes at least the reference value, an acceptance address, one or more fee values, and a first digital signature generated by a third party;
- the signing module of the processing server is configured to generate a second digital signature using at least the acceptance address, and
- the transmitting device of the processing server is configured to electronically transmit at least the second digital signature to the computing system.
10. The system of claim 9, further comprising:
- a hashing module of the processing server, wherein the receiving device of the processing server is further configured to receive a transaction message associated with the payment transaction, wherein the transaction message is formatted based on one or more standards

and includes at least a plurality of data elements including at least a first data element configured to store the primary account number, and

the hashing module of the processing server is configured to generate the reference value based on application of one or more hashing algorithms to the received transaction message.

11. The system of claim 9, further comprising:

a querying module of the processing server; and

a verification module of the processing server, wherein

the receiving device of the processing server is further configured to receive blockchain data from a node associated with a blockchain network, wherein the blockchain data includes one or more blocks comprising a blockchain, each block being comprised of at least a block header and one or more transaction values, wherein each transaction value includes at least a transaction address, a transaction reference, and a transaction signature,

the querying module of the processing server is configured to execute a query on the received blockchain data to identify a specific transaction value where the included transaction address corresponds to the acceptance address, and

the verification module of the processing server is configured to verify the specific transaction value based on at least a correspondence between the included transaction reference and the reference value and a correspondence between the included transaction signature and the second digital signature.

12. A system for processing of a cryptographically auditable transaction, comprising:

a receiving device of a processing server configured to receive a payment request from a first computing system, wherein the payment request includes at least a reference value associated with a payment transaction;

a signing module of the processing server configured to generate a first digital signature using at least the received payment request; and

a transmitting device of the processing server configured to electronically transmit at least the first digital signature and the payment request to a second computing system, wherein

the receiving device of the processing server is further configured to receive a confirmation message from the second computing system, wherein the confirmation message includes at least one or more fee values, a second digital signature, and an acceptance address;

the transmitting device of the processing server is further configured to electronically transmit an acceptance request to the first computing system, wherein the acceptance request includes at least the reference value, the one or more fee values, the second digital signature, and the acceptance address;

the receiving device of the processing server is further configured to receive an acceptance message from the first computing system, wherein the acceptance message includes at least a third digital signature; and

the transmitting device of the processing server is further configured to electronically transmit a transaction value to a node associated with a blockchain network,

wherein the transaction value includes at least the reference value, the acceptance address, and the third digital signature.

13. The system of claim 12, comprising:

a querying module of the processing server; and

a verification module of the processing server, wherein the receiving device of the processing server is further configured to receive blockchain data from a node associated with the blockchain network, wherein the blockchain data includes one or more blocks comprising a blockchain, each block being comprised of at least a block header and one or more transaction values, wherein each transaction value includes at least a transaction address, a transaction reference, and a transaction signature,

the querying module of the processing server is configured to execute a query on the received blockchain data to identify a specific transaction value where the included transaction address corresponds to the acceptance address, and

the verification module of the processing server is configured to verify the specific transaction value based on at least a correspondence between the included transaction reference and the reference value and a correspondence between the included transaction signature and the third digital signature.

14. The system of claim 12, further comprising:

a verification module of the processing server; and

an account database of the processing server configured to store a plurality of account profiles, wherein each account profile includes a structured data set related to a transaction account including at least a primary account number, wherein

the receiving device of the processing server is further configured to receive a verification request from the first computing system, wherein the verification request includes at least a specific account number,

the verification module of the processing server is configured to verify an account profile of the plurality of account profiles where the included primary account number corresponds to the specific account number, and

the transmitting device of the processing server is further configured to electronically transmit an indication of successful verification to the first computing system.

15. A system for processing of a cryptographically auditable transaction, comprising:

a verification module of a processing server;

a receiving device of the processing server configured to receive a payment request from a computing system, wherein the payment request includes at least a reference value associated with a payment transaction and a first digital signature;

a querying module of the processing server configured to execute a first query to identify one or more fee values for the payment transaction and a second query to identify an acceptance address;

a signing module of the processing server configured to generate a second digital signature; and

a transmitting device of the processing server configured to electronically transmit at least the one or more fee values, the acceptance address, and the second digital signature to the computing system, wherein

the receiving device of the processing server is further configured to receive blockchain data from a node associated with the blockchain network, wherein the blockchain data includes one or more blocks comprising a blockchain, each block being comprised of at least a block header and one or more transaction values, wherein each transaction value includes at least a transaction address, a transaction reference, and a transaction signature;

the querying module of the processing server is further configured to execute a query on the received blockchain data to identify a specific transaction value where the included transaction address corresponds to the acceptance address, and

the verification module of the processing server is configured to verify the specific transaction value based on at least a correspondence between the included transaction reference and the reference value.

16. The system of claim **15**, further comprising:

a generation module of the processing server configured to generate an acceptance entry, wherein the acceptance entry includes at least the acceptance address, the reference value, and the second digital signature, wherein

the transmitting device of the processing server is further configured to electronically transmit the generated acceptance entry to a node associated with the blockchain network.

* * * * *