

TLAMATINI

Complete Project Dossier: what the system does, how it works, how to use it, complete tracked file tree, and effective line inventory



Measure	Value
Generated	May 14, 2026 05:19 PM UTC-0600
Current HEAD	e1d93ab - Added Browse buttons to new dialogs of menu DB entry, by Tlamatini's-AutoBot.
Tracked files	436
Workflow agents	60
Total effective lines	92,274
Total physical text lines	125,137

1. What Tlamatini Is

- Tlamatini is a local-first AI developer assistant built with Django, Django Channels, LangChain, LangGraph, FAISS/BM25 retrieval, and a large in-repository agent application.
- It combines a browser chat surface, a Retrieval-Augmented Generation stack, a Multi-Turn tool executor, MCP-backed context providers, wrapped chat-agent runtimes, and a visual Agentic Control Panel for workflow design.
- The platform is designed for development operations: codebase analysis, file and directory context, command execution, Python execution, screenshots, web/search helpers, notifications, DevOps tools, local model operation, and Windows packaging.

What the system does

- Answers codebase questions with loaded file or directory context.
- Uses hybrid retrieval to extract metadata, split content, rank source chunks, and respect context budgets.
- Gives operators GUI-first database maintenance through the new DB dropdown for backup and staged database replacement.
- Warns GPU-host operators before a directory-context load is likely to saturate VRAM and degrade embedding throughput.
- Runs checked Multi-Turn requests through request-scoped planning, capability selection, tool calls, observations, monitoring, and final synthesis.
- Launches wrapped copies of selected workflow agents in isolated runtime folders without mutating templates.
- Lets users design, validate, save, pause, resume, and stop visual workflows through the Agentic Control Panel.
- Turns successful Multi-Turn tool executions into starter `.flw` workflows that can be inspected and validated in ACP.
- Packages the project into a distributable Windows release with installer and uninstaller tooling.

How it works

- Browser UI sends chat and workflow requests through Django views and Channels WebSockets.
- RAG chains load selected file/directory context, retrieve relevant chunks, and build answer prompts.
- DB-menu actions validate directories or SQLite files in the browser, then call Django views that either copy the live database out or stage a replacement into `DB/ToLoad/db.sqlite3`.
- Before a heavy directory embedding run on supported NVIDIA hosts, a fail-open pre-flight guard can estimate VRAM pressure and surface a non-blocking warning in chat.
- When Multi-Turn is enabled, the global planner selects context and tool stages before the executor binds only the relevant tools.
- Tool calls execute in the backend, append observations, and may create wrapped runtime copies under `agent/agents/pools/_chat_runs_`.
- On the next full start-up, `manage.py` can swap a staged database into place before Django imports, while archiving the previous live database under `DB/Older/<timestamp>`.
- ACP flows deploy session-scoped pool instances, wire config values, validate NxN graph rules, and execute through Starter-driven flow semantics.
- Build scripts collect static assets, bundle Django/Python resources, add agent templates, and assemble `pkg.zip`, `Uninstaller.exe`, and `dist/Tlamatini_Release`.

2. Architecture Layers

Layer	Role
Browser interfaces	Chat page plus Agentic Control Panel templates and JavaScript modules.
Django/Channels	Authentication, views, WebSockets, session state, message persistence, and ASGI startup.
RAG and context	Metadata extraction, text splitting, FAISS/BM25 retrieval, context budgeting, and fallback behavior.
Multi-Turn engine	Capability registry, global execution planner, explicit tool loop, answer parsing, and answer-success classification.
Tools and agents	Core tools, MCP context providers, wrapped chat-agent launchers, and the current 60 visual workflow agent templates.
Packaging	PyInstaller build scripts, shortcut registration, `.flw` association, installer, uninstaller, and release folder assembly.

Design principles

- Evidence-first answers: Tlamatini grounds responses in selected project context and hybrid retrieval rather than freeform model memory.
- Explicit orchestration: checked Multi-Turn uses a visible tool loop, capability scoring, and staged planning instead of a single opaque call.
- Operational reversibility: risky changes such as database replacement are staged, archived, and delayed to the only safe window instead of hot-swapped mid-session.
- Fail-open diagnostics: GPU pressure probes and session-restore safeguards warn early without breaking CPU-only or degraded environments.
- Runtime isolation: wrapped chat-agent copies run in session-scoped folders so template agents remain pristine while live runs stay inspectable.
- Operator truth over vibes: Exec Report tables, tlamatini.log, skill audits, and ACPX transcripts make the system auditable after execution.

3. Installation, Configuration, and Everyday Use

Installation essentials

- Python 3.12.10 is the strongly recommended source-mode version in the README, and the codebase has been tested most deeply there.
- Source installs require a clone, virtual environment, dependency install from `requirements.txt`, migrations, a superuser, static collection, and then the web server.
- You can run either the checked-in cloud/back-end defaults from `Tlmatini/agent/config.json` or a local Ollama-backed configuration with matching model names.
- Packaged Windows installs create a default `user / changeme` account; manual source installs use your own `createsuperuser` account instead.

Configuration essentials

- Source mode resolves `Tlmatini/agent/config.json`; frozen builds resolve `config.json` next to the executable; `CONFIG\_PATH` overrides both.
- Core keys include `embedding-model`, `chained-model`, `ollama\_base\_url`, `ollama\_token`, `enable\_unified\_agent`, `unified\_agent\_model`, and `unified\_agent\_max\_iterations`.
- The chat-side Config -> Models and Config -> URLs dialogs are now first-class configuration surfaces, and they can explicitly ask the operator to reconnect when saved values change live-session assumptions.
- The separate DB dropdown is not a config editor: it is a maintenance surface for copying the live SQLite database out or staging a replacement for the next full start-up.
- Multi-Turn is toggled from the chat toolbar, but it depends on the unified-agent configuration and the selected model/base-url pairing being valid.
- Image interpretation can run through Claude-backed cloud paths or Qwen/Ollama-backed local paths, and remote Ollama can be protected with a bearer token.

DB menu and database swap-in

- The new DB dropdown gives operators two GUI-first maintenance paths: `Backup database` copies the live SQLite file out, and `Set DB` stages a chosen `db.sqlite3` for the next full start-up.
- Both dialogs are live-validated in the browser and now expose Browse buttons that open native host-side pickers for folders or `db.sqlite3` files.
- Backup is read-only and uses the currently live database path; Set DB never hot-swaps the file mid-session because Django already holds SQLite open.
- Set DB writes the selected file to `DB/ToLoad/db.sqlite3`; the real swap happens only at the top of `manage.py` before Django imports anything.
- When that swap runs, the previous live database is moved into `DB/Older/<timestamp>/db.sqlite3`, creating a built-in rollback trail instead of overwriting history.
- Reconnect is not enough for this path: the operator must fully restart Tlmatini so the pre-Django swap window opens again.
- If the staged file is bad or locked, startup fails open: Tlmatini logs the error and continues with the previous live database.

How to use it

- Run from source: create a virtual environment, install requirements, migrate, create a superuser, collect static files, and start Django.
- Open `/agent/` for chat. Load a file or directory context before asking codebase-specific questions.
- Keep Multi-Turn unchecked for direct Q&A; enable Multi-Turn for tasks that need tools, wrapped agents, monitoring, or workflow seeding.

- Use the DB dropdown when you need a safe database snapshot or want to stage a different `db.sqlite3` for the next start-up without hot-swapping the live SQLite file.
- Open `/agentic\_control\_panel/` to drag agents, connect them, configure each node, validate, start, pause/resume, stop, and save `.flw` workflows.
- Use `python build.py`, `python build\_uninstaller.py`, and `python build\_installer.py` only when producing a packaged Windows release.

Source-mode bootstrap commands

```
python -m venv venv
venv\Scripts\activate
pip install -r requirements.txt
python Tlamatini/manage.py migrate
python Tlamatini/manage.py createsuperuser
python Tlamatini/manage.py collectstatic --noinput
python Tlamatini/manage.py runserver --noreload
```

4. Ollama Setup Without Administrative Rights

- Open a normal PowerShell window, not an elevated one, for the safest no-admin Windows installation path.
- Install into `%LOCALAPPDATA%\Programs\Ollama` with the official PowerShell installer script and then reopen PowerShell so PATH updates are visible.
- Verify the CLI with `ollama --version`, start `ollama serve` if the background service is not already active, and confirm `http://127.0.0.1:11434/api/tags` responds.
- Pull the default repository model tags exactly as written if you want the shipped config and agent templates to work unchanged.

No-admin Ollama commands and default model pulls

```
$env:OLLAMA_INSTALL_DIR = "$env:LOCALAPPDATA\Programs\ollama"
irm https://ollama.com/install.ps1 | iex
ollama --version
ollama serve
Invoke-WebRequest http://127.0.0.1:11434/api/tags -UseBasicParsing
ollama pull qwen3-embedding:8b
ollama pull glm-5:cloud
ollama pull qwen3.5:cloud
ollama pull gpt-oss:120b-cloud
ollama pull qwen3.5:397b-cloud
ollama pull llama3.2-vision:11b
```

5. Runtime, Release, and Operator Diagnostics

Running the application

- Development server: ``python Tlamatini/manage.py runserver --noreload``.
- Preferred async/dev bootstrap: ``python Tlamatini/manage.py startserver``, which starts MCP services before the Django server.
- Production-style ASGI endpoint: ``daphne -b 127.0.0.1 -p 8000 tlamatini.asgi:application``.
- Current startup also re-applies GPU-performance / Ollama-pinning hooks in the background on supported NVIDIA Windows hosts, so restart-time behavior stays closer to the tuned development baseline.
- That same early startup window is also where a staged ``DB/ToLoad/db.sqlite3`` file is promoted into the live database path, before Django opens SQLite.
- Startup cleans pool state, repopulates the agent registry, launches MCP metrics/file-search servers, and then serves HTTP plus WebSocket traffic.

Embedding-memory pre-flight guard

- README and BookOfTlamatini now document an embedding-memory pre-flight guard for GPU hosts before a directory-context load starts its FAISS embedding burst.
- On supported NVIDIA hosts it estimates embedding-model VRAM pressure, and when the projected load is too high it emits a non-blocking warning chat bubble instead of silently letting RAM<->VRAM thrash surprise the operator.
- CPU-only, AMD, and Apple-Silicon hosts stay fail-open: the guard becomes a no-op when the NVIDIA probe does not apply.
- The practical operator response is straightforward: switch to a smaller embedding model, reconnect if needed, or proceed knowingly with the heavier model.

Reconnect and restart safeguards

- Config -> Models and Config -> URLs dialogs now track their pre-edit baseline and can show a reconnect-required dialog when the saved values change what the live chat session should trust.
- The restored-session autoload path now buffers early WebSocket frames so context-loading spinners and disabled-input state are not lost during automatic reconnect/restore flows.
- Startup and restart behavior now also re-apply GPU performance and Ollama keep-alive hooks in the background on supported NVIDIA Windows hosts, improving warm-model readiness without blocking Django boot.

Release pipeline

- Release production is a three-step pipeline: ``build.py`` -> ``build_uninstaller.py`` -> ``build_installer.py``.
- The final distributable is the full ``dist/Tlamatini_Release/`` folder, not a stray executable copied outside its payload.
- Current ``build.py`` treats ``README.md`` and ``jd-cli/`` as required post-build assets and fails hard if those payloads are missing.
- Bundled support scripts cover shortcut creation/removal, ``.flw`` association, the PowerShell launcher, and Windows-specific installer ergonomics.

Exec Report

- Exec Report is a Multi-Turn-only transparency layer that appends one operation table per state-changing agent family to the final answer.
- Rows are recorded from the live tool-call stream rather than guessed from the LLM prose, so the report is the operational ground truth.
- Each row receives a SUCCESS/FAILURE verdict from raw tool returns, making long installs, deployments, and remediations inspectable after the fact.

ACPX and skills

- ACPX lets Tlamatini spawn external coding-agent CLIs such as Codex, Claude Code, Cursor, Gemini, Qwen, and others as managed child processes.
- It pairs those agents with markdown-driven `SKILL.md` packages, validated I/O contracts, permission gating, and append-only audit logs.
- Transport-aware drain rules and bounded event bodies reduce latency while protecting the LLM context budget during external-agent relays.
- The operator-facing references are `README.md` and `ACPX.md`, while the implementation lives under `agent/acpx/`, `agent/skills/`, and `agent/skills\_pkg/`.

Application log

- The built-in `tlamatini.log` file captures both stdout and stderr through a tee stream initialized in `manage.py` before Django starts.
- In source mode the log sits next to `manage.py`; in frozen mode it lives next to the executable.
- Immediate flush behavior makes the log the primary forensic artifact for startup problems, warnings, tracebacks, and runtime diagnostics.

6. Agent Catalog and Runtime Model

Tlmatini currently exposes 60 workflow-agent templates.

Category	Representative agents
Control	starter, ender, stopper, cleaner, barrier, flowbacker
Execution and files	executer, pythonxer, pser, file_creator, file_extractor, file_interpreter, mover, deleter
DevOps and infra	gitter, dockerer, kubernetes, jenkinser, ssher, scper
Data and APIs	sqler, mongoxer, apirer, crawler, googler
Monitoring and routing	monitor_log, monitor_netstat, flowhypervisor, forker, asker, counter, and, or
Communication	notifier, emailer, recmailer, telegramer, telegramrx, whatsapper
Security and media	kyber_keygen, kyber_cipher, kyber_decipher, image_interpreter, shoter, j_decompiler
Workflow intelligence	flowcreator, gatewayer, gateway_relayer, node_manager, parametrizer, prompter, summarizer

All workflow agents follow a common deployment pattern: template directory, YAML configuration, session-scoped pool copy, PID/status/log files, target/source wiring, and optional reanimation state.

7. Repository Facts and Git Changes

Metric	Value
Tracked files in git	436
Workflow agents	60
Django migrations	82
Frontend JavaScript modules	27
Frontend CSS files	5
HTML templates	4
Python requirements	62
Binary/asset tracked files skipped from line count	15

Latest commits

Date	Commit	Subject
2026-05-14	e1d93ab	Added Browse buttons to new dialogs of menu DB entry, by Tlamatini's-AutoBot.
2026-05-14	1c38970	Updating documentation, by Tlamatini's-AutoBot.
2026-05-14	70a6cd8	Implemented the new menu DB, to backup and restore databases of Tlamatini, by Tlamatini's-AutoBot.
2026-05-14	47df564	Tlamatini's operation database backup mechanics, by Tlamatini's-AutoBot.
2026-05-13	b73ee03	Enabling J-Decompiler as Multi-turn agent, by Tlamatini's-AutoBot.
2026-05-12	d7509c9	Update README.md
2026-05-12	65319a6	Adding the reference to a new video!, by angelahack1
2026-05-12	fc76275	Adding additional info about cloud models aand how to anable them by plans in Ollama.com, by Tlamatini's-AutoBot.
2026-05-12	ad6becb	Changing to Nomic-Embed-Text:latest as default embedding model, by Tlamatini's-AutoBot.
2026-05-12	314ff7b	Hiding Config meenu entries while in long-runing operations, by Tlamatini's-AutoBot.

Git changes from the last 2 days

- Today's operator-facing work is dominated by the new DB dropdown: backup, Set DB staging for the next start-up, startup swap-in/rollback mechanics, and native Browse buttons on both dialogs.
- The current Git window still shows the flow compiler / agent-contract direction influencing how chat-created and ACP-created workflows converge.
- Multi-Turn behavior kept evolving across the period through quota tuning, execution-table persistence, autonomous-action improvements, and broader tool enablement.
- Documentation itself changed during the last 2 days, so the regenerated dossier is part of the tracked operator surface rather than an external afterthought.

2-day commit appendix 1 of 1

Date	Commit	Subject
2026-05-14	e1d93ab	Added Browse buttons to new dialogs of menu DB entry, by Tlamatini's-AutoBot.
2026-05-14	1c38970	Updating documentation, by Tlamatini's-AutoBot.
2026-05-14	70a6cd8	Implemented the new menu DB, to backup and restore databases of Tlamatini, by Tlamatini's-AutoBot.
2026-05-14	47df564	Tlamatini's operation database backup mechanics, by Tlamatini's-AutoBot.
2026-05-13	b73ee03	Enabling J-Decompiler as Multi-turn agent, by Tlamatini's-AutoBot.
2026-05-12	d7509c9	Update README.md
2026-05-12	65319a6	Adding the reference to a new video!, by angelahack1

8. Effective Line Inventory by Language

Methodology: tracked text files only. Blank lines and comment-only lines are excluded. Python counts also remove module, class, and function docstrings detected through AST parsing.

Language	Files	Effective lines	Total lines	Share
Python	250	61,408	85,340	66.5%
JavaScript	27	12,330	15,560	13.4%
Markdown	49	10,790	13,803	11.7%
CSS	5	3,027	3,793	3.3%
YAML	64	1,342	2,639	1.5%
Other text	3	780	957	0.8%
HTML	4	780	798	0.8%
PowerShell	5	506	752	0.5%
Prompt template	2	403	477	0.4%
JSON	5	383	383	0.4%
JavaScript module	1	377	444	0.4%
Text	4	115	134	0.1%
Protocol Buffers	1	20	33	0.0%
Batch	1	13	24	0.0%

Total effective lines: 92,274

9. Largest Effective Source Files

Path	Language	Effective	Total
Tlmatini/agent/views.py	Python	6,622	9,561
Tlmatini/agent/tests.py	Python	3,886	4,963
Tlmatini/agent/tools.py	Python	2,201	3,094
Tlmatini/agent/agents/flowcreator/agent_skill.md	Markdown	1,778	1,981
BookOfTlmatini.md	Markdown	1,662	2,328
Tlmatini/agent/static/agent/css/agent_control_panel.css	CSS	1,631	2,140
Tlmatini/agent/doc_generation/complete_project_docs.py	Python	1,346	1,531
Tlmatini/agent/static/agent/js/agent_page_init.js	JavaScript	1,306	1,503
Tlmatini/agent/static/agent/js/acp-canvas-core.js	JavaScript	1,256	1,566
Tlmatini/agent/static/agent/css/agent_page.css	CSS	1,143	1,362
Tlmatini/agent/consumers.py	Python	1,121	1,350
Tlmatini/agent/static/agent/js/acp-agent-connectors.js	JavaScript	1,073	1,211
Tlmatini/agent/agents/whatstlmatini/whatstlmatini.py	Python	1,044	1,300
Tlmatini/agent/static/agent/js/acp-control-buttons.js	JavaScript	1,036	1,344
Tlmatini/agent/acpx/tests.py	Python	1,035	1,299
Tlmatini/agent/static/agent/js/agent_page_chat.js	JavaScript	971	1,345
README.md	Markdown	921	1,285
KIMI.md	Markdown	915	1,088
Tlmatini/agent/static/agent/js/canvas_item_dialog.js	JavaScript	898	1,165
Tlmatini/agent/agents/teletlmatini/teletlmatini.py	Python	888	1,147
Tlmatini/agent/agents/crawler/crawler.py	Python	881	1,261
Tlmatini/agent/static/agent/js/acp-canvas-undo.js	JavaScript	805	916
Tlmatini/agent/acpx/runtime.py	Python	798	1,087
Tlmatini/agent/agents/parametrizer/parametrizer.py	Python	794	1,118
Tlmatini/agent/static/agent/js/agent_page_dialogs.js	JavaScript	761	932

10. Complete Tracked File Tree (Repository Appendix)

Tree appendix 1 of 8

```
Tlamatini/
|-- .gitignore
|-- _acpx_pipeline_demo_report.md
|-- ACPX.md
|-- agents_descriptions.md
|-- BookOfTlamatini.md
|-- build.py
|-- build_installer.py
|-- build_uninstaller.py
|-- CLAUDE.md
|-- CreateShortcut.json
|-- CreateShortcut.ps1
|-- eslint.config.mjs
|-- install.py
|-- KIMI.md
|-- LICENSE
|-- OllamaPricing.png
|-- package.json
|-- pnpm-lock.yaml
|-- prompt_example_2_create_agent.txt
|-- README.md
|-- regen_secrets.py
|-- register_flw.ps1
|-- RemoveShortcut.ps1
|-- requirements.txt
|-- Tlamatini.ico
|-- Tlamatini.jpg
|-- Tlamatini.ps1
|-- tlamatini_app_summary.pdf
|-- Tlamatini_eXtended_Artificial_Intelligence_Humanly_Tempered.pptx
|-- uninstall.py
|-- unregister_flw.ps1
|-- .codex/
|   |-- skills/
|   |   |-- full-project-pdf-dossier/
|   |   |   |-- SKILL.md
|   |   |-- overlap-safe-pptx-dossier/
|   |   |   |-- SKILL.md
|   |-- .github/
|   |   |-- workflows/
|   |   |   |-- name-guard.yml
|   |-- docs/
|   |   |-- claude/
|   |   |   |-- acpx.md
|   |   |   |-- agents.md
|   |   |   |-- architecture.md
|   |   |   |-- exec-report.md
|   |   |   |-- frontend.md
|   |   |   |-- gotchas.md
|   |   |   |-- INDEX.md
|   |   |   |-- mcp-tools.md
|   |   |   |-- multi-turn.md
|   |-- pyinstaller_hooks/
|   |   |-- hook-numpy.py
|   |-- Tlamatini/
|   |   |-- cat_art.py
|   |   |-- manage.py
|   |   |-- .agents/
|   |   |   |-- workflows/
|   |   |   |   |-- create_new_agent.md
|   |   |-- .mcps/
|   |   |   |-- create_new_mcp.md
|   |   |-- agent/
|   |   |   |-- __init__.py
|   |   |   |-- admin.py
|   |   |   |-- apps.py
|   |   |   |-- capability_registry.py
|   |   |   |-- chain_files_search_lcel.py
|   |   |   |-- chain_system_lcel.py
|   |   |   |-- chat_agent_registry.py
|   |   |   |-- chat_agent_runtime.py
|   |   |   |-- chat_history_loader.py
|   |   |   |-- command_togen_pb2.txt
|   |   |   |-- config.json
|   |   |   |-- config_loader.py
|   |   |   |-- constants.py
```

Tree appendix 2 of 8

```
-- consumers.py
-- embedding_memory_guard.py
-- filesearch.proto
-- filesearch_pb2.py
-- filesearch_pb2_grpc.py
-- global_execution_planner.py
-- global_state.py
-- gpu_perf.py
-- inet_determiner.py
-- mcp_agent.py
-- mcp_files_search_client.py
-- mcp_files_search_server.py
-- mcp_system_client.py
-- mcp_system_server.py
-- models.py
-- path_guard.py
-- prompt.pmt
-- rag_enhancements.py
-- routing.py
-- test_embedding_memory_guard.py
-- test_flow_contracts.py
-- test_password_quoting.py
-- tests.py
-- tools.py
-- urls.py
-- views.py
-- web_search_llm.py
-- acpx/
|   |-- __init__.py
|   |-- agent_registry.py
|   |-- config.py
|   |-- permissions.py
|   |-- runtime.py
|   |-- service.py
|   |-- session_store.py
|   |-- tests.py
|   |-- tools.py
|   |-- windows_spawn.py
-- agents/
|   |-- acpxer/
|   |   |-- acpxer.py
|   |   |-- config.yaml
|   |-- and/
|   |   |-- and.py
|   |   |-- config.yaml
|   |-- apirer/
|   |   |-- apirer.py
|   |   |-- config.yaml
|   |-- asker/
|   |   |-- asker.py
|   |   |-- config.yaml
|   |-- barrier/
|   |   |-- barrier.py
|   |   |-- config.yaml
|   |   |-- test_barrier.py
|   |-- cleaner/
|   |   |-- __init__.py
|   |   |-- cleaner.py
|   |   |-- config.yaml
|   |-- counter/
|   |   |-- config.yaml
|   |   |-- counter.py
|   |-- crawler/
|   |   |-- config.yaml
|   |   |-- crawler.py
|   |-- croner/
|   |   |-- config.yaml
|   |   |-- croner.py
|   |-- deleter/
|   |   |-- config.yaml
|   |   |-- deleter.py
|   |-- dockerer/
|   |   |-- config.yaml
|   |   |-- dockerer.py
|   |-- emailer/
|   |   |-- config.yaml
```

Tree appendix 3 of 8

```
-- emitter.py
-- ender/
| |-- config.yaml
| |-- ender.py
-- executor/
| |-- config.yaml
| |-- executor.py
-- file_creator/
| |-- config.yaml
| |-- file_creator.py
-- file_extractor/
| |-- config.yaml
| |-- file_extractor.py
-- file_interpreter/
| |-- config.yaml
| |-- file_interpreter.py
-- flowbacker/
| |-- config.yaml
| |-- flowbacker.py
-- flowcreator/
| |-- agentic_skill.md
| |-- config.yaml
| |-- flowcreator.py
-- flowhypervisor/
| |-- config.yaml
| |-- flowhypervisor.py
| |-- hypervisor_alert.wav
| |-- monitoring-prompt.pmt
-- forker/
| |-- config.yaml
| |-- forker.py
-- gateway_relayer/
| |-- config.yaml
| |-- gateway_relayer.md
| |-- gateway_relayer.py
-- gatewayer/
| |-- config.yaml
| |-- gatewayer.md
| |-- gatewayer.py
| |-- gatewayer_explanation.md
-- gitter/
| |-- config.yaml
| |-- gitter.py
-- googler/
| |-- config.yaml
| |-- googler.py
-- image_interpreter/
| |-- config.yaml
| |-- image_interpreter.py
-- j_decompiler/
| |-- config.yaml
| |-- j_decompiler.py
-- jenkinsr/
| |-- config.yaml
| |-- jenkinsr.py
-- keyboarder/
| |-- config.yaml
| |-- keyboarder.py
-- kubernetes/
| |-- config.yaml
| |-- kubernetes.py
-- kyber_cipher/
| |-- config.yaml
| |-- kyber_cipher.py
-- kyber_decipher/
| |-- config.yaml
| |-- kyber_decipher.py
-- kyber_keygen/
| |-- config.yaml
| |-- kyber_keygen.py
-- mongoxer/
| |-- config.yaml
| |-- mongoxer.py
-- monitor_log/
| |-- config.yaml
| |-- monitor_log.py
```

Tree appendix 4 of 8

```
-- monitor_netstat/
| |-- config.yaml
| |-- monitor_netstat.py
-- mouser/
| |-- config.yaml
| |-- mouser.py
-- mover/
| |-- config.yaml
| |-- mover.py
-- node_manager/
| |-- config.yaml
| |-- node_manager.md
| |-- node_manager.py
| |-- nodes_example.json
| |-- nodes_example.yaml
-- notifier/
| |-- config.yaml
| |-- notifier.py
-- or/
| |-- config.yaml
| |-- or.py
-- parametrizer/
| |-- config.yaml
| |-- parametrizer.py
-- prompter/
| |-- config.yaml
| |-- prompter.py
-- psr/
| |-- config.yaml
| |-- psr.py
-- pythonxer/
| |-- config.yaml
| |-- pythonxer.py
-- raiser/
| |-- config.yaml
| |-- raiser.py
-- recmailer/
| |-- config.yaml
| |-- recmailer.py
-- scper/
| |-- config.yaml
| |-- scper.py
-- shoter/
| |-- config.yaml
| |-- shoter.py
-- sleeper/
| |-- config.yaml
| |-- sleeper.py
-- sqler/
| |-- config.yaml
| |-- sqler.py
-- ssher/
| |-- config.yaml
| |-- ssher.py
-- starter/
| |-- config.yaml
| |-- starter.py
-- stopper/
| |-- config.yaml
| |-- stopper.py
-- summarizer/
| |-- config.yaml
| |-- summarizer.py
-- telegramer/
| |-- config.yaml
| |-- telegramer.py
-- telegramrx/
| |-- config.yaml
| |-- telegramrx.py
-- teletlatamini/
| |-- config.yaml
| |-- teletlatamini.py
-- whatsapper/
| |-- config.yaml
| |-- whatsapper.py
-- whatstlatamini/
```


Tree appendix 5 of 8

```
-- config.yaml
-- whatstlamatini.py
-- doc_generation/
|-- complete_project_docs.py
|-- markdown_to_pdf.py
|-- refresh_project_docs.py
|-- test_output.pdf
-- images/
|-- mockup.jpg
|-- TlamatiniAbout.jpg
|-- XAIHT-Tlamatini.mp4
-- imaging/
|-- converter.py
|-- image_interpreter.py
|-- screenshot.py
-- management/
|-- __init__.py
|-- commands/
|   |-- acpx_lint.py
|   |-- startserver.py
-- migrations/
|-- 0001_initial.py
|-- 0002_populate_db.py
|-- 0003_add_cleaner.py
|-- 0004_add_deleter.py
|-- 0005_add_executer.py
|-- 0006_add_notifier.py
|-- 0007_add_stopper.py
|-- 0008_add_recmailer.py
|-- 0009_add_whatsapper.py
|-- 0010_add_pythoex.py
|-- 0011_add_asker.py
|-- 0012_repopulate_all_agents.py
|-- 0013_add_forker.py
|-- 0014_repopulate_all_agents.py
|-- 0015_add_shoter.py
|-- 0016_repopulate_all_agents.py
|-- 0017_add_ssher.py
|-- 0018_repopulate_all_agents.py
|-- 0019_add_scper.py
|-- 0020_repopulate_all_agents.py
|-- 0021_add_telegramrx.py
|-- 0022_repopulate_all_agents.py
|-- 0023_add_mongoxer.py
|-- 0024_repopulate_all_agents.py
|-- 0025_add_telegramer.py
|-- 0026_repopulate_all_agents.py
|-- 0027_add_sqler.py
|-- 0028_repopulate_all_agents.py
|-- 0029_add_prompter.py
|-- 0030_repopulate_all_agents.py
|-- 0031_add_flowcreator.py
|-- 0032_repopulate_all_agents.py
|-- 0033_add_gitter.py
|-- 0034_add_dockerer.py
|-- 0035_add_pser.py
|-- 0036_add_kubernereter.py
|-- 0037_add_apirer.py
|-- 0038_add_jenkinser.py
|-- 0039_add_crawler.py
|-- 0040_add_summarizer.py
|-- 0041_add_flowhypervisor.py
|-- 0042_add_mouser.py
|-- 0043_agentmessage_conversation_user.py
|-- 0044_add_counter.py
|-- 0045_add_file_interpreter.py
|-- 0046_add_image_interpreter.py
|-- 0047_add_gatewayer.py
|-- 0048_add_gateway_relayer.py
|-- 0049_add_node_manager.py
|-- 0050_add_file_creator.py
|-- 0051_add_file_extractor.py
|-- 0052_add_kyber_keygen.py
|-- 0053_add_kyber_cipher.py
|-- 0054_add_kyber_decipher.py
|-- 0055_fix_kyber_cipher_names.py
```

Tree appendix 6 of 8

```
-- 0056_add_parametrizer.py
-- 0057_add_flowbacker.py
-- 0058_add_barrier.py
-- 0059_add_j_decompiler.py
-- 0060_add_agent_parametrizer_tool.py
-- 0061_add_agent_starter_tool.py
-- 0062_sync_agent_control_tools_and_prompts.py
-- 0063_add_agent_parametrizer_prompt.py
-- 0064_add_chat_agent_run_model.py
-- 0065_add_chat_wrapped_agent_tools.py
-- 0066_add_keyboarder.py
-- 0067_add_multi_turn_demo_prompts.py
-- 0068_add_googler_tool.py
-- 0069_add_googler_agent.py
-- 0070_add_teletlamatini.py
-- 0071_acpx_skills.py
-- 0072_add_acpx_demo_prompts.py
-- 0073_acpx_demo_gemini_uplift.py
-- 0074_simplify_demo_prompts.py
-- 0075_add_acpx_tool_surface.py
-- 0076_add_acpxer.py
-- 0077_add_whatstlamatini.py
-- 0078_add_chat_agent_keyboarder_tool.py
-- 0079_add_chat_agent_mouser_tool.py
-- 0080_add_chat_agent_sleeper_tool.py
-- 0081_add_window_present_and_run_wait_tools.py
-- 0082_add_chat_agent_j_decompiler_tool.py
-- __init__.py
-- monitors/
--   monitor_sql.py
-- opus_client/
--   claudie_opus_client.py
--   examples.py
--   README.md
-- rag/
--   __init__.py
--   config.py
--   factory.py
--   interaction.py
--   interface.py
--   loaders.py
--   prompts.py
--   retrieval.py
--   splitters.py
--   utils.py
--   chains/
--     base.py
--     basic.py
--     history_aware.py
--     unified.py
-- services/
--   __init__.py
--   agent_contracts.py
--   agent_paths.py
--   answer_analyzer.py
--   filesystem.py
--   flow_compiler.py
--   flow_spec.py
--   response_parser.py
-- skills/
--   __init__.py
--   frontmatter.py
--   harness.py
--   io_contract.py
--   registry.py
-- skills_pkg/
--   _meta/
--     lint.py
--     schema.json
--   acp_router/
--     SKILL.md
--   github/
--     SKILL.md
--   gmail/
--     SKILL.md
--   hello_world/
```

Tree appendix 7 of 8

```
-- -- SKILL.md
-- jira/
-- -- SKILL.md
-- notion/
-- -- SKILL.md
-- setup_new_acpx_key/
-- -- SKILL.md
-- skill_creator/
-- |-- SKILL.md
-- -- scripts/
-- -- -- quick_validate.py
-- slack/
-- -- SKILL.md
-- summarize/
-- -- SKILL.md
-- tlamatini_allowed_hosts_tighten/
-- -- SKILL.md
-- tlamatini_csrf_exempt_audit/
-- -- SKILL.md
-- tlamatini_exec_report_row_adder/
-- -- SKILL.md
-- tlamatini_flow_from_objective/
-- -- SKILL.md
-- tlamatini_flw_doctor/
-- -- SKILL.md
-- tlamatini_new_acp_agent/
-- -- SKILL.md
-- tlamatini_planner_trace_replay/
-- -- SKILL.md
-- tlamatini_static_version_bumper/
-- -- SKILL.md
-- todoist/
-- -- SKILL.md
-- trello/
-- -- SKILL.md
-- weather/
-- -- SKILL.md
-- static/
-- -- agent/
-- -- -- css/
-- -- -- -- agent_page.css
-- -- -- -- agentic_control_panel.css
-- -- -- -- login.css
-- -- -- -- tools_dialog.css
-- -- -- -- welcome.css
-- -- -- img/
-- -- -- -- spinner.svg
-- -- -- -- Tlamatini.ico
-- -- -- js/
-- -- -- -- acp-agent-connectors.js
-- -- -- -- acp-canvas-core.js
-- -- -- -- acp-canvas-undo.js
-- -- -- -- acp-control-buttons.js
-- -- -- -- acp-file-io.js
-- -- -- -- acp-flow-snapshot.js
-- -- -- -- acp-globals.js
-- -- -- -- acp-layout.js
-- -- -- -- acp-parametrizer-dialog.js
-- -- -- -- acp-running-state.js
-- -- -- -- acp-session.js
-- -- -- -- acp-undo-manager.js
-- -- -- -- acp-validate.js
-- -- -- -- agent_page_canvas.js
-- -- -- -- agent_page_chat.js
-- -- -- -- agent_page_context.js
-- -- -- -- agent_page_dialogs.js
-- -- -- -- agent_page_init.js
-- -- -- -- agent_page_layout.js
-- -- -- -- agent_page_state.js
-- -- -- -- agent_page_ui.js
-- -- -- -- agentic_control_panel.js
-- -- -- -- canvas_item_dialog.js
-- -- -- -- chat_page_runtime_poller.js
-- -- -- -- contextual_menus.js
-- -- -- -- shared-runtime-dialogs.js
-- -- -- -- tools_dialog.js
```

Tree appendix 8 of 8

```
| | | |-- sounds/  
| | | | |-- hypervisor_alert.wav  
| | | | |-- notification.wav  
| | | |-- video/  
| | | | |-- XAIHT-Tlamatini.mp4  
|-- telegram/  
| |-- AztecTlamatini.txt  
| |-- config.yaml  
| |-- telegram_receiver.py  
-- templates/  
  |-- agent/  
    |-- agent_page.html  
    |-- agentic_control_panel.html  
    |-- login.html  
    |-- welcome.html  
  
-- DB/  
  |-- Older/  
  | |-- README.md  
  |-- ToLoad/  
  | |-- README.md  
  
-- jd-cli/  
  |-- jd-cli.bat  
  |-- jd-cli.jar  
  
-- tlamatini/  
  |-- __init__.py  
  |-- asgi.py  
  |-- context_processors.py  
  |-- logging_filters.py  
  |-- middleware.py  
  |-- settings.py  
  |-- urls.py  
  |-- wsgi.py
```