

TLAMATINI

Complete Project Dossier: what the system does, how it works, how to use it, complete tracked file tree, and effective line inventory



Measure	Value
Generated	May 16, 2026 08:48 AM UTC-0600
Current HEAD	c0a1bf4 - Updating documentation, by angelahack1
Resolved version	1.1.1 (git)
Tracked files	445
Workflow agents	61
Total effective lines	94,350
Total physical text lines	128,213

1. What Tlamatini Is

- Tlamatini is a local-first AI developer assistant built with Django, Django Channels, LangChain, LangGraph, FAISS/BM25 retrieval, and a large in-repository agent application.
- It combines a browser chat surface, a Retrieval-Augmented Generation stack, a Multi-Turn tool executor, MCP-backed context providers, wrapped chat-agent runtimes, and a visual Agentic Control Panel for workflow design.
- The platform is designed for development operations: codebase analysis, file and directory context, command execution, Python execution, screenshots, web/search helpers, notifications, DevOps tools, local model operation, and Windows packaging.

What the system does

- Answers codebase questions with loaded file or directory context.
- Uses hybrid retrieval to extract metadata, split content, rank source chunks, and respect context budgets.
- Gives operators GUI-first database maintenance through the new DB dropdown for backup and staged database replacement.
- Warns GPU-host operators before a directory-context load is likely to saturate VRAM and degrade embedding throughput.
- Exposes a coherent versioning surface across builds, runtime UI, logs, and an open health-check endpoint.
- Runs checked Multi-Turn requests through request-scoped planning, capability selection, tool calls, observations, monitoring, and final synthesis.
- Launches wrapped copies of selected workflow agents in isolated runtime folders without mutating templates.
- Lets users design, validate, save, pause, resume, and stop visual workflows through the Agentic Control Panel.
- Turns successful Multi-Turn tool executions into starter `.flw` workflows that can be inspected and validated in ACP.
- Packages the project into a distributable Windows release with installer and uninstaller tooling.

How it works

- Browser UI sends chat and workflow requests through Django views and Channels WebSockets.
- RAG chains load selected file/directory context, retrieve relevant chunks, and build answer prompts.
- DB-menu actions validate directories or SQLite files in the browser, then call Django views that either copy the live database out or stage a replacement into `DB/ToLoad/db.sqlite3`.
- Before a heavy directory embedding run on supported NVIDIA hosts, a fail-open pre-flight guard can estimate VRAM pressure and surface a non-blocking warning in chat.
- Version resolution now flows through git tags, a runtime resolver module, generated build artefacts, and an open `/agent/version/` endpoint.
- When Multi-Turn is enabled, the global planner selects context and tool stages before the executor binds only the relevant tools, including wrapped deterministic agents such as De-Compressor.
- Tool calls execute in the backend, append observations, and may create wrapped runtime copies under `agent/agents/pools/_chat_runs_`.
- On the next full start-up, `manage.py` can swap a staged database into place before Django imports, while archiving the previous live database under `DB/Older/<timestamp>`.
- ACP flows deploy session-scoped pool instances, wire config values, validate NxN graph rules, and execute through Starter-driven flow semantics.
- Build scripts collect static assets, bundle Django/Python resources, add agent templates, and assemble `pkg.zip`, `Uninstaller.exe`, and `dist/Tlamatini_Release/`.

2. Architecture Layers

Layer	Role
Browser interfaces	Chat page plus Agentic Control Panel templates and JavaScript modules.
Django/Channels	Authentication, views, WebSockets, session state, message persistence, and ASGI startup.
RAG and context	Metadata extraction, text splitting, FAISS/BM25 retrieval, context budgeting, and fallback behavior.
Multi-Turn engine	Capability registry, global execution planner, explicit tool loop, answer parsing, and answer-success classification.
Tools and agents	Core tools, MCP context providers, wrapped chat-agent launchers, and the current visual workflow agent templates.
Packaging	PyInstaller build scripts, shortcut registration, `.flw` association, installer, uninstaller, and release folder assembly.

Design principles

- Evidence-first answers: Tlamatini grounds responses in selected project context and hybrid retrieval rather than freeform model memory.
- Explicit orchestration: checked Multi-Turn uses a visible tool loop, capability scoring, and staged planning instead of a single opaque call.
- Operational reversibility: risky changes such as database replacement are staged, archived, and delayed to the only safe window instead of hot-swapped mid-session.
- Fail-open diagnostics: GPU pressure probes and session-restore safeguards warn early without breaking CPU-only or degraded environments.
- Runtime isolation: wrapped chat-agent copies run in session-scoped folders so template agents remain pristine while live runs stay inspectable.
- Operator truth over vibes: Exec Report tables, tlamatini.log, skill audits, and ACPX transcripts make the system auditable after execution.

3. Installation, Configuration, and Everyday Use

Installation essentials

- Python 3.12.10 is the strongly recommended source-mode version in the README, and the codebase has been tested most deeply there.
- Source installs require a clone, virtual environment, dependency install from `requirements.txt`, migrations, a superuser, static collection, and then the web server.
- You can run either the checked-in cloud/back-end defaults from `Tlmatini/agent/config.json` or a local Ollama-backed configuration with matching model names.
- Packaged Windows installs create a default `user / changeme` account; manual source installs use your own `createsuperuser` account instead.

Configuration essentials

- Source mode resolves `Tlmatini/agent/config.json`; frozen builds resolve `config.json` next to the executable; `CONFIG\_PATH` overrides both.
- Core keys include `embedding-model`, `chained-model`, `ollama\_base\_url`, `ollama\_token`, `enable\_unified\_agent`, `unified\_agent\_model`, and `unified\_agent\_max\_iterations`.
- The chat-side Config -> Models and Config -> URLs dialogs are now first-class configuration surfaces, and they can explicitly ask the operator to reconnect when saved values change live-session assumptions.
- The separate DB dropdown is not a config editor: it is a maintenance surface for copying the live SQLite database out or staging a replacement for the next full start-up.
- Multi-Turn is toggled from the chat toolbar, but it depends on the unified-agent configuration and the selected model/base-url pairing being valid.
- Image interpretation can run through Claude-backed cloud paths or Qwen/Ollama-backed local paths, and remote Ollama can be protected with a bearer token.

DB menu and database swap-in

- The new DB dropdown gives operators two GUI-first maintenance paths: `Backup database` copies the live SQLite file out, and `Set DB` stages a chosen `db.sqlite3` for the next full start-up.
- Both dialogs are live-validated in the browser and now expose Browse buttons that open native host-side pickers for folders or `db.sqlite3` files.
- Backup is read-only and uses the currently live database path; Set DB never hot-swaps the file mid-session because Django already holds SQLite open.
- Set DB writes the selected file to `DB/ToLoad/db.sqlite3`; the real swap happens only at the top of `manage.py` before Django imports anything.
- When that swap runs, the previous live database is moved into `DB/Older/<timestamp>/db.sqlite3`, creating a built-in rollback trail instead of overwriting history.
- Reconnect is not enough for this path: the operator must fully restart Tlmatini so the pre-Django swap window opens again.
- If the staged file is bad or locked, startup fails open: Tlmatini logs the error and continues with the previous live database.

Versioning system

- Tlmatini now follows Semantic Versioning 2.0.0 with git tags as the single source of truth: you tag, then you build, instead of hand-editing version strings across files.
- The build path resolves a version once and propagates it into generated runtime metadata, Win32 VERSIONINFO resources, and the release-folder naming convention.
- On untagged commits the resolver falls back honestly to a git-derived development version instead of failing the build or lying about the release state.

Version surfaces

- Operators can now see the running version in the About dialog, the startup banner, the open ``GET /agent/version/`` health-check endpoint, and Windows file properties on the built executables.
- The runtime resolver lives in ``Tlmatini/agent/version.py``, while the build-oriented coordination logic lives in the repo-root ``versioning.py`` and the longer policy notes live in ``VERSIONING.md``.
- Build overrides are supported in a predictable order: CLI ``--version``, then ``TLMATINI_VERSION``, then `git describe`, then the sentinel ``0.0.0+unknown``.

De-Compressor agent

- De-Compressor is the new 61st workflow agent: a deterministic archive worker that can either compress or decompress depending on which side exposes a recognized archive extension.
- Supported archive families are ``.gz``, ``.zip``, ``.7z``, ``.tar.gz``, and ``.gz.tar``; file-to-folder extraction and file-or-directory packing are both documented in the README and Book.
- Password handling is explicit: ``passwordless=true`` skips it, while ``passwordless=false`` requires the ``DE_COMPRESSER_PWD`` environment variable and fails fast if the secret is missing.

De-Compressor integration and fallback behavior

- The agent is reachable from both operator surfaces: ACP canvas nodes wire through dedicated connection-update views, and checked Multi-Turn can invoke it through ``chat_agent_de_compressor``.
- Format engines are practical rather than magical: `stdlib `gzip`` and ``zipfile`` cover core cases, ``7z`` is preferred for encrypted ``7z`` or ``zip``, and ``py7zr`` was added to ``requirements.txt`` as the Python fallback.
- Every run emits an ``INI_SECTION_DE_COMPRESSER<<< ... >>>END_SECTION_DE_COMPRESSER`` block and still triggers ``target_agents``, so downstream Parametrizer or Raiser logic can branch on ``success=true|false`` instead of guessing from prose.

How to use it

- Run from source: create a virtual environment, install requirements, migrate, create a superuser, collect static files, and start Django.
- Open ``/agent/`` for chat. Load a file or directory context before asking codebase-specific questions.
- Keep Multi-Turn unchecked for direct Q&A; enable Multi-Turn for tasks that need tools, wrapped agents, monitoring, or workflow seeding.
- Archive jobs can now be described directly in Multi-Turn or modeled visually in ACP: De-Compressor infers compress vs decompress from the ``input`` or ``output`` extension.
- Use the DB dropdown when you need a safe database snapshot or want to stage a different ``db.sqlite3`` for the next start-up without hot-swapping the live SQLite file.
- Open ``/agentic_control_panel/`` to drag agents, connect them, configure each node, validate, start, pause/resume, stop, and save ``.flw`` workflows.
- Use ``python build.py``, ``python build_uninstaller.py``, and ``python build_installer.py`` only when producing a packaged Windows release.

Source-mode bootstrap commands

```
python -m venv venv
venv\Scripts\activate
pip install -r requirements.txt
python Tlmatini/manage.py migrate
python Tlmatini/manage.py createsuperuser
python Tlmatini/manage.py collectstatic --noinput
python Tlmatini/manage.py runserver --noreload
```

4. Ollama Setup Without Administrative Rights

- Open a normal PowerShell window, not an elevated one, for the safest no-admin Windows installation path.
- Install into `%LOCALAPPDATA%\Programs\Ollama` with the official PowerShell installer script and then reopen PowerShell so PATH updates are visible.
- Verify the CLI with `ollama --version`, start `ollama serve` if the background service is not already active, and confirm `http://127.0.0.1:11434/api/tags` responds.
- Pull the default repository model tags exactly as written if you want the shipped config and agent templates to work unchanged.

No-admin Ollama commands and default model pulls

```
$env:OLLAMA_INSTALL_DIR = "$env:LOCALAPPDATA\Programs\ollama"
irm https://ollama.com/install.ps1 | iex
ollama --version
ollama serve
Invoke-WebRequest http://127.0.0.1:11434/api/tags -UseBasicParsing
ollama pull qwen3-embedding:8b
ollama pull glm-5:cloud
ollama pull qwen3.5:cloud
ollama pull gpt-oss:120b-cloud
ollama pull qwen3.5:397b-cloud
ollama pull llama3.2-vision:11b
```

5. Runtime, Release, and Operator Diagnostics

Running the application

- Development server: ``python Tlamatini/manage.py runserver --noreload``.
- Preferred async/dev bootstrap: ``python Tlamatini/manage.py startserver``, which starts MCP services before the Django server.
- Production-style ASGI endpoint: ``daphne -b 127.0.0.1 -p 8000 tlamatini.asgi:application``.
- Current startup also re-applies GPU-performance / Ollama-pinning hooks in the background on supported NVIDIA Windows hosts, so restart-time behavior stays closer to the tuned development baseline.
- That same early startup window is also where a staged ``DB/ToLoad/db.sqlite3`` file is promoted into the live database path, before Django opens SQLite.
- Startup now also prints a ``--- [VERSION] Tlamatini ...`` banner, making the running build visible in both the console and ``tlamatini.log`` without an HTTP call.
- Startup cleans pool state, repopulates the agent registry, launches MCP metrics/file-search servers, and then serves HTTP plus WebSocket traffic.

Embedding-memory pre-flight guard

- README and BookOfTlamatini now document an embedding-memory pre-flight guard for GPU hosts before a directory-context load starts its FAISS embedding burst.
- On supported NVIDIA hosts it estimates embedding-model VRAM pressure, and when the projected load is too high it emits a non-blocking warning chat bubble instead of silently letting RAM<->VRAM thrash surprise the operator.
- CPU-only, AMD, and Apple-Silicon hosts stay fail-open: the guard becomes a no-op when the NVIDIA probe does not apply.
- The practical operator response is straightforward: switch to a smaller embedding model, reconnect if needed, or proceed knowingly with the heavier model.

Reconnect and restart safeguards

- Config -> Models and Config -> URLs dialogs now track their pre-edit baseline and can show a reconnect-required dialog when the saved values change what the live chat session should trust.
- The restored-session autoload path now buffers early WebSocket frames so context-loading spinners and disabled-input state are not lost during automatic reconnect/restore flows.
- Startup and restart behavior now also re-apply GPU performance and Ollama keep-alive hooks in the background on supported NVIDIA Windows hosts, improving warm-model readiness without blocking Django boot.

Release pipeline

- Release production is a three-step pipeline: ``build.py`` -> ``build_uninstaller.py`` -> ``build_installer.py``.
- The final distributable is the full ``dist/Tlamatini_Release/`` folder, not a stray executable copied outside its payload.
- Current ``build.py`` treats ``README.md`` and ``jd-cli/`` as required post-build assets and fails hard if those payloads are missing.
- Bundled support scripts cover shortcut creation/removal, ``flw`` association, the PowerShell launcher, and Windows-specific installer ergonomics.

Exec Report

- Exec Report is a Multi-Turn-only transparency layer that appends one operation table per state-changing agent family to the final answer.
- Rows are recorded from the live tool-call stream rather than guessed from the LLM prose, so the report is the operational ground truth.

- Each row receives a SUCCESS/FAILURE verdict from raw tool returns, making long installs, deployments, and remediations inspectable after the fact.

ACPX and skills

- ACPX lets Tlmatini spawn external coding-agent CLIs such as Codex, Claude Code, Cursor, Gemini, Qwen, and others as managed child processes.
- It pairs those agents with markdown-driven `SKILL.md` packages, validated I/O contracts, permission gating, and append-only audit logs.
- Transport-aware drain rules and bounded event bodies reduce latency while protecting the LLM context budget during external-agent relays.
- The operator-facing references are `README.md` and `ACPX.md`, while the implementation lives under `agent/acpx/`, `agent/skills/`, and `agent/skills\_pkg/`.

Application log

- The built-in `tlmatini.log` file captures both stdout and stderr through a tee stream initialized in `manage.py` before Django starts.
- In source mode the log sits next to `manage.py`; in frozen mode it lives next to the executable.
- Immediate flush behavior makes the log the primary forensic artifact for startup problems, warnings, tracebacks, and runtime diagnostics.

6. Agent Catalog and Runtime Model

Tlmatini currently exposes 61 workflow-agent templates.

Category	Representative agents
Control	starter, ender, stopper, cleaner, barrier, flowbacker
Execution and files	executer, pythonxer, pser, file_creator, file_extractor, file_interpreter, de_compressor, mover, deleter
DevOps and infra	gitter, dockerer, kubernetes, jenkinser, ssher, scper
Data and APIs	sqler, mongoxer, apirer, crawler, googler
Monitoring and routing	monitor_log, monitor_netstat, flowhypervisor, forker, asker, counter, and, or
Communication	notifier, emailer, recmailer, telegramer, telegramrx, whatsapper
Security and media	kyber_keygen, kyber_cipher, kyber_decipher, image_interpreter, shoter, j_decompiler
Workflow intelligence	flowcreator, gatewayer, gateway_relayer, node_manager, parametrizer, prompter, summarizer

All workflow agents follow a common deployment pattern: template directory, YAML configuration, session-scoped pool copy, PID/status/log files, target/source wiring, and optional reanimation state.

De-Compressor spotlight

- De-Compressor is the new 61st workflow agent: a deterministic archive worker that can either compress or decompress depending on which side exposes a recognized archive extension.
- Supported archive families are `.gz``, `.zip``, `.7z``, `.tar.gz``, and `.gz.tar``; file-to-folder extraction and file-or-directory packing are both documented in the README and Book.
- Password handling is explicit: ``passwordless=true`` skips it, while ``passwordless=false`` requires the ``DE_COMPRESSER_PWD`` environment variable and fails fast if the secret is missing.
- The agent is reachable from both operator surfaces: ACP canvas nodes wire through dedicated connection-update views, and checked Multi-Turn can invoke it through ``chat_agent_de_compressor``.
- Format engines are practical rather than magical: `stdlib`gzzip`` and ``zipfile`` cover core cases, ``7z`` is preferred for encrypted ``7z`` or ``zip``, and ``py7zr`` was added to ``requirements.txt`` as the Python fallback.
- Every run emits an ``INI_SECTION_DE_COMPRESSER<<< ... >>>END_SECTION_DE_COMPRESSER`` block and still triggers ``target_agents``, so downstream Parametrizer or Raiser logic can branch on ``success=true|false`` instead of guessing from prose.

7. Repository Facts and Git Changes

Metric	Value
Tracked files in git	445
Workflow agents	61
Django migrations	84
Frontend JavaScript modules	27
Frontend CSS files	5
HTML templates	4
Python requirements	63
Binary/asset tracked files skipped from line count	15
Resolved version	1.1.1
Version source	git

Latest commits

Date	Commit	Subject
2026-05-15	c0a1bf4	Updating documentation, by angelahack1
2026-05-15	0adcd1f	Patched requirements.txt due to new De-Compressor agent, by angelahack1
2026-05-15	2002314	De-Compressor agent and added to multi-turn, by angelahack1
2026-05-15	d2da4a4	Updating and linting, by Tlamatini's-AutoBot.
2026-05-15	382e1a1	Implementing the professional way every worldwide system is generated, by angelahack1
2026-05-14	0da6424	Updating visual documentation pdf, pptx, by Tlamatini's-AutoBot.
2026-05-14	e1d93ab	Added Browse buttons to new dialogs of menu DB entry, by Tlamatini's-AutoBot.
2026-05-14	1c38970	Updating documentation, by Tlamatini's-AutoBot.
2026-05-14	70a6cd8	Implemented the new menu DB, to backup and restore databases of Tlamatini, by Tlamatini's-AutoBot.
2026-05-14	47df564	Tlamatini's operation database backup mechanics, by Tlamatini's-AutoBot.

Git changes from today

- Git history today shows focused maintenance across the operator surface, release mechanics, and runtime behavior.

8. Effective Line Inventory by Language

Methodology: tracked text files only. Blank lines and comment-only lines are excluded. Python counts also remove module, class, and function docstrings detected through AST parsing.

Language	Files	Effective lines	Total lines	Share
Python	256	62,993	87,721	66.8%
JavaScript	27	12,375	15,612	13.1%
Markdown	50	11,165	14,323	11.8%
CSS	5	3,043	3,831	3.2%
YAML	65	1,347	2,665	1.4%
Other text	3	789	967	0.8%
HTML	4	780	798	0.8%
PowerShell	5	506	752	0.5%
Prompt template	2	409	483	0.4%
JSON	5	383	383	0.4%
JavaScript module	1	377	444	0.4%
Text	5	150	177	0.2%
Protocol Buffers	1	20	33	0.0%
Batch	1	13	24	0.0%

Total effective lines: 94,350

9. Largest Effective Source Files

Path	Language	Effective	Total
Tlmatini/agent/views.py	Python	6,690	9,661
Tlmatini/agent/tests.py	Python	3,886	4,963
Tlmatini/agent/tools.py	Python	2,201	3,094
Tlmatini/agent/agents/flowcreator/agentic_skill.md	Markdown	1,797	2,001
BookOfTlmatini.md	Markdown	1,707	2,395
Tlmatini/agent/static/agent/css/agentic_control_panel.css	CSS	1,641	2,167
Tlmatini/agent/doc_generation/complete_project_docs.py	Python	1,469	1,664
Tlmatini/agent/static/agent/js/agent_page_init.js	JavaScript	1,306	1,503
Tlmatini/agent/static/agent/js/acp-canvas-core.js	JavaScript	1,263	1,573
Tlmatini/agent/static/agent/css/agent_page.css	CSS	1,149	1,373
Tlmatini/agent/consumers.py	Python	1,121	1,350
Tlmatini/agent/static/agent/js/acp-agent-connectors.js	JavaScript	1,091	1,230
Tlmatini/agent/agents/whatstlmatini/whatstlmatini.py	Python	1,044	1,300
Tlmatini/agent/static/agent/js/acp-control-buttons.js	JavaScript	1,036	1,344
Tlmatini/agent/acpx/tests.py	Python	1,035	1,299
Tlmatini/agent/static/agent/js/agent_page_chat.js	JavaScript	977	1,357
README.md	Markdown	973	1,357
KIMI.md	Markdown	915	1,088
Tlmatini/agent/static/agent/js/canvas_item_dialog.js	JavaScript	898	1,165
Tlmatini/agent/agents/teletlmatini/teletlmatini.py	Python	888	1,147
Tlmatini/agent/agents/crawler/crawler.py	Python	881	1,261
Tlmatini/agent/static/agent/js/acp-canvas-undo.js	JavaScript	817	928
Tlmatini/agent/acpx/runtime.py	Python	798	1,087
Tlmatini/agent/agents/parametrizer/parametrizer.py	Python	794	1,118
Tlmatini/agent/static/agent/js/agent_page_dialogs.js	JavaScript	761	932

10. Complete Tracked File Tree (Repository Appendix)

Tree appendix 1 of 8

```
Tlamatini/
|-- .gitignore
|-- _acpx_pipeline_demo_report.md
|-- ACPX.md
|-- agents_descriptions.md
|-- BookOfTlamatini.md
|-- build.py
|-- build_installer.py
|-- build_uninstaller.py
|-- CLAUDE.md
|-- CreateShortcut.json
|-- CreateShortcut.ps1
|-- eslint.config.mjs
|-- example_of_prompt_to_make_de-compressor_agent.txt
|-- install.py
|-- KIMI.md
|-- LICENSE
|-- OllamaPricing.png
|-- package.json
|-- pnpm-lock.yaml
|-- prompt_example_2_create_agent.txt
|-- README.md
|-- regen_secrets.py
|-- register_flw.ps1
|-- RemoveShortcut.ps1
|-- requirements.txt
|-- Tlamatini.ico
|-- Tlamatini.jpg
|-- Tlamatini.ps1
|-- tlamatini_app_summary.pdf
|-- Tlamatini_extended_Artificial_Intelligence_Humanly_Tempered.pptx
|-- uninstall.py
|-- unregister_flw.ps1
|-- VERSIONING.md
|-- versioning.py
|-- .codex/
|   |-- skills/
|   |   |-- full-project-pdf-dossier/
|   |   |   |-- SKILL.md
|   |   |-- overlap-safe-pptx-dossier/
|   |   |   |-- SKILL.md
|   |-- .github/
|   |   |-- workflows/
|   |   |   |-- name-guard.yml
|   |-- docs/
|   |   |-- claude/
|   |   |   |-- acpx.md
|   |   |   |-- agents.md
|   |   |   |-- architecture.md
|   |   |   |-- exec-report.md
|   |   |   |-- frontend.md
|   |   |   |-- gotchas.md
|   |   |   |-- INDEX.md
|   |   |   |-- mcp-tools.md
|   |   |   |-- multi-turn.md
|   |-- pyinstaller_hooks/
|   |   |-- hook-numpy.py
|-- Tlamatini/
|   |-- cat_art.py
|   |-- manage.py
|   |-- .agents/
|   |   |-- workflows/
|   |   |   |-- create_new_agent.md
|   |-- .mcps/
|   |   |-- create_new_mcp.md
|   |-- agent/
|   |   |-- __init__.py
|   |   |-- admin.py
|   |   |-- apps.py
|   |   |-- capability_registry.py
|   |   |-- chain_files_search_lcel.py
|   |   |-- chain_system_lcel.py
|   |   |-- chat_agent_registry.py
|   |   |-- chat_agent_runtime.py
|   |   |-- chat_history_loader.py
|   |   |-- command_togen_pb2.txt
```

Tree appendix 2 of 8

```
-- config.json
-- config_loader.py
-- constants.py
-- consumers.py
-- embedding_memory_guard.py
-- filesearch.proto
-- filesearch_pb2.py
-- filesearch_pb2_grpc.py
-- global_execution_planner.py
-- global_state.py
-- gpu_perf.py
-- inet_determiner.py
-- mcp_agent.py
-- mcp_files_search_client.py
-- mcp_files_search_server.py
-- mcp_system_client.py
-- mcp_system_server.py
-- models.py
-- path_guard.py
-- prompt.pmt
-- rag_enhancements.py
-- routing.py
-- test_de_compressor.py
-- test_embedding_memory_guard.py
-- test_flow_contracts.py
-- test_password_quoting.py
-- tests.py
-- tools.py
-- urls.py
-- version.py
-- views.py
-- web_search_llm.py
-- acpx/
|   -- __init__.py
|   -- agent_registry.py
|   -- config.py
|   -- permissions.py
|   -- runtime.py
|   -- service.py
|   -- session_store.py
|   -- tests.py
|   -- tools.py
|   -- windows_spawn.py
-- agents/
|   -- acpxer/
|   |   -- acpxer.py
|   |   -- config.yaml
|   -- and/
|   |   -- and.py
|   |   -- config.yaml
|   -- apirer/
|   |   -- apirer.py
|   |   -- config.yaml
|   -- asker/
|   |   -- asker.py
|   |   -- config.yaml
|   -- barrier/
|   |   -- barrier.py
|   |   -- config.yaml
|   |   -- test_barrier.py
|   -- cleaner/
|   |   -- __init__.py
|   |   -- cleaner.py
|   |   -- config.yaml
|   -- counter/
|   |   -- config.yaml
|   |   -- counter.py
|   -- crawler/
|   |   -- config.yaml
|   |   -- crawler.py
|   -- croner/
|   |   -- config.yaml
|   |   -- croner.py
|   -- de_compressor/
|   |   -- config.yaml
|   |   -- de_compressor.py
```

Tree appendix 3 of 8

```
-- deleter/
|-- config.yaml
|-- deleter.py
-- dockerer/
|-- config.yaml
|-- dockerer.py
-- emailer/
|-- config.yaml
|-- emailer.py
-- ender/
|-- config.yaml
|-- ender.py
-- executer/
|-- config.yaml
|-- executer.py
-- file_creator/
|-- config.yaml
|-- file_creator.py
-- file_extractor/
|-- config.yaml
|-- file_extractor.py
-- file_interpreter/
|-- config.yaml
|-- file_interpreter.py
-- flowbacker/
|-- config.yaml
|-- flowbacker.py
-- flowcreator/
|-- agentic_skill.md
|-- config.yaml
|-- flowcreator.py
-- flowhypervisor/
|-- config.yaml
|-- flowhypervisor.py
|-- hypervisor_alert.wav
|-- monitoring-prompt.pmt
-- forker/
|-- config.yaml
|-- forker.py
-- gateway_relayer/
|-- config.yaml
|-- gateway_relayer.md
|-- gateway_relayer.py
-- gatewayer/
|-- config.yaml
|-- gatewayer.md
|-- gatewayer.py
|-- gatewayer_explanation.md
-- gitter/
|-- config.yaml
|-- gitter.py
-- googler/
|-- config.yaml
|-- googler.py
-- image_interpreter/
|-- config.yaml
|-- image_interpreter.py
-- j_decompiler/
|-- config.yaml
|-- j_decompiler.py
-- jenkinser/
|-- config.yaml
|-- jenkinser.py
-- keyboarder/
|-- config.yaml
|-- keyboarder.py
-- kubernereter/
|-- config.yaml
|-- kubernereter.py
-- kyber_cipher/
|-- config.yaml
|-- kyber_cipher.py
-- kyber_decipher/
|-- config.yaml
|-- kyber_decipher.py
-- kyber_keygen/
```

Tree appendix 4 of 8

```
-- config.yaml
-- kyber_keygen.py
-- mongoxer/
|-- config.yaml
|-- mongoxer.py
-- monitor_log/
|-- config.yaml
|-- monitor_log.py
-- monitor_netstat/
|-- config.yaml
|-- monitor_netstat.py
-- mouser/
|-- config.yaml
|-- mouser.py
-- mover/
|-- config.yaml
|-- mover.py
-- node_manager/
|-- config.yaml
|-- node_manager.md
|-- node_manager.py
|-- nodes_example.json
|-- nodes_example.yaml
-- notifier/
|-- config.yaml
|-- notifier.py
-- or/
|-- config.yaml
|-- or.py
-- parametrizer/
|-- config.yaml
|-- parametrizer.py
-- prompter/
|-- config.yaml
|-- prompter.py
-- pser/
|-- config.yaml
|-- pser.py
-- pythonxer/
|-- config.yaml
|-- pythonxer.py
-- raiser/
|-- config.yaml
|-- raiser.py
-- recmailer/
|-- config.yaml
|-- recmailer.py
-- scper/
|-- config.yaml
|-- scper.py
-- shoter/
|-- config.yaml
|-- shoter.py
-- sleeper/
|-- config.yaml
|-- sleeper.py
-- sqler/
|-- config.yaml
|-- sqler.py
-- ssher/
|-- config.yaml
|-- ssher.py
-- starter/
|-- config.yaml
|-- starter.py
-- stopper/
|-- config.yaml
|-- stopper.py
-- summarizer/
|-- config.yaml
|-- summarizer.py
-- telegramer/
|-- config.yaml
|-- telegramer.py
-- telegramrx/
|-- config.yaml
```

Tree appendix 5 of 8

```
| | | | | `-- telegramrx.py
| | | | | -- teletlamatini/
| | | | | |-- config.yaml
| | | | | `-- teletlamatini.py
| | | | | -- whatsapper/
| | | | | |-- config.yaml
| | | | | `-- whatsapper.py
| | | | | -- whatstlamatini/
| | | | | |-- config.yaml
| | | | | `-- whatstlamatini.py
| | | | -- doc_generation/
| | | | |-- complete_project_docs.py
| | | | |-- markdown_to_pdf.py
| | | | |-- refresh_project_docs.py
| | | | | `-- test_output.pdf
| | | | -- images/
| | | | |-- mockup.jpg
| | | | |-- TlamatiniAbout.jpg
| | | | | `-- XAIHT-Tlamatini.mp4
| | | | -- imaging/
| | | | |-- converter.py
| | | | |-- image_interpreter.py
| | | | | `-- screenshot.py
| | | | -- management/
| | | | |-- __init__.py
| | | | | `-- commands/
| | | | | |-- acpx_lint.py
| | | | | `-- startserver.py
| | | | -- migrations/
| | | | |-- 0001_initial.py
| | | | |-- 0002_populate_db.py
| | | | |-- 0003_add_cleaner.py
| | | | |-- 0004_add_deleter.py
| | | | |-- 0005_add_executer.py
| | | | |-- 0006_add_notifier.py
| | | | |-- 0007_add_stopper.py
| | | | |-- 0008_add_recmailer.py
| | | | |-- 0009_add_whatsapper.py
| | | | |-- 0010_add_pythonxer.py
| | | | |-- 0011_add_asker.py
| | | | |-- 0012_repopulate_all_agents.py
| | | | |-- 0013_add_forker.py
| | | | |-- 0014_repopulate_all_agents.py
| | | | |-- 0015_add_shoter.py
| | | | |-- 0016_repopulate_all_agents.py
| | | | |-- 0017_add_ssher.py
| | | | |-- 0018_repopulate_all_agents.py
| | | | |-- 0019_add_scper.py
| | | | |-- 0020_repopulate_all_agents.py
| | | | |-- 0021_add_telegramrx.py
| | | | |-- 0022_repopulate_all_agents.py
| | | | |-- 0023_add_mongoxer.py
| | | | |-- 0024_repopulate_all_agents.py
| | | | |-- 0025_add_telegramer.py
| | | | |-- 0026_repopulate_all_agents.py
| | | | |-- 0027_add_sqler.py
| | | | |-- 0028_repopulate_all_agents.py
| | | | |-- 0029_add_prompter.py
| | | | |-- 0030_repopulate_all_agents.py
| | | | |-- 0031_add_flowcreator.py
| | | | |-- 0032_repopulate_all_agents.py
| | | | |-- 0033_add_gitter.py
| | | | |-- 0034_add_dockerer.py
| | | | |-- 0035_add_pser.py
| | | | |-- 0036_add_kuberneter.py
| | | | |-- 0037_add_apirer.py
| | | | |-- 0038_add_jenkinser.py
| | | | |-- 0039_add_crawler.py
| | | | |-- 0040_add_summarizer.py
| | | | |-- 0041_add_flowhypervisor.py
| | | | |-- 0042_add_mouser.py
| | | | |-- 0043_agentmessage_conversation_user.py
| | | | |-- 0044_add_counter.py
| | | | |-- 0045_add_file_interpreter.py
| | | | |-- 0046_add_image_interpreter.py
| | | | |-- 0047_add_gatewayer.py
```

Tree appendix 6 of 8

```
-- 0048_add_gateway_relayer.py
-- 0049_add_node_manager.py
-- 0050_add_file_creator.py
-- 0051_add_file_extractor.py
-- 0052_add_kyber_keygen.py
-- 0053_add_kyber_cipher.py
-- 0054_add_kyber_decipher.py
-- 0055_fix_kyber_cipher_names.py
-- 0056_add_parametrizer.py
-- 0057_add_flowbacker.py
-- 0058_add_barrier.py
-- 0059_add_j_decompiler.py
-- 0060_add_agent_parametrizer_tool.py
-- 0061_add_agent_starter_tool.py
-- 0062_sync_agent_control_tools_and_prompts.py
-- 0063_add_agent_parametrizer_prompt.py
-- 0064_add_chat_agent_run_model.py
-- 0065_add_chat_wrapped_agent_tools.py
-- 0066_add_keyboarder.py
-- 0067_add_multi_turn_demo_prompts.py
-- 0068_add_googler_tool.py
-- 0069_add_googler_agent.py
-- 0070_add_teletlamatini.py
-- 0071_acpx_skills.py
-- 0072_add_acpx_demo_prompts.py
-- 0073_acpx_demo_gemini_uplift.py
-- 0074_simplify_demo_prompts.py
-- 0075_add_acpx_tool_surface.py
-- 0076_add_acpxer.py
-- 0077_add_whatstlamatini.py
-- 0078_add_chat_agent_keyboarder_tool.py
-- 0079_add_chat_agent_mouser_tool.py
-- 0080_add_chat_agent_sleeper_tool.py
-- 0081_add_window_present_and_run_wait_tools.py
-- 0082_add_chat_agent_j_decompiler_tool.py
-- 0083_add_de_compressor.py
-- 0084_add_chat_agent_de_compressor_tool.py
-- __init__.py
-- monitors/
--   -- monitor_sql.py
-- opus_client/
--   -- claude_opus_client.py
--   -- examples.py
--   -- README.md
-- rag/
--   -- __init__.py
--   -- config.py
--   -- factory.py
--   -- interaction.py
--   -- interface.py
--   -- loaders.py
--   -- prompts.py
--   -- retrieval.py
--   -- splitters.py
--   -- utils.py
--   -- chains/
--     -- base.py
--     -- basic.py
--     -- history_aware.py
--     -- unified.py
-- services/
--   -- __init__.py
--   -- agent_contracts.py
--   -- agent_paths.py
--   -- answer_analyzer.py
--   -- filesystem.py
--   -- flow_compiler.py
--   -- flow_spec.py
--   -- response_parser.py
-- skills/
--   -- __init__.py
--   -- frontmatter.py
--   -- harness.py
--   -- io_contract.py
--   -- registry.py
-- skills_pkg/
```

Tree appendix 7 of 8

```
-- _meta/
|   |-- lint.py
|   |-- schema.json
-- acp_router/
|   |-- SKILL.md
-- github/
|   |-- SKILL.md
-- gmail/
|   |-- SKILL.md
-- hello_world/
|   |-- SKILL.md
-- jira/
|   |-- SKILL.md
-- notion/
|   |-- SKILL.md
-- setup_new_acpx_key/
|   |-- SKILL.md
-- skill_creator/
|   |-- SKILL.md
|   |-- scripts/
|   |   |-- quick_validate.py
-- slack/
|   |-- SKILL.md
-- summarize/
|   |-- SKILL.md
-- tlamatini_allowed_hosts_tighten/
|   |-- SKILL.md
-- tlamatini_csrf_exempt_audit/
|   |-- SKILL.md
-- tlamatini_exec_report_row_adder/
|   |-- SKILL.md
-- tlamatini_flow_from_objective/
|   |-- SKILL.md
-- tlamatini_flw_doctor/
|   |-- SKILL.md
-- tlamatini_new_acp_agent/
|   |-- SKILL.md
-- tlamatini_planner_trace_replay/
|   |-- SKILL.md
-- tlamatini_static_version_bumper/
|   |-- SKILL.md
-- todoist/
|   |-- SKILL.md
-- trello/
|   |-- SKILL.md
-- weather/
|   |-- SKILL.md
-- static/
|   |-- agent/
|   |   |-- css/
|   |   |   |-- agent_page.css
|   |   |   |-- agentic_control_panel.css
|   |   |   |-- login.css
|   |   |   |-- tools_dialog.css
|   |   |   |-- welcome.css
|   |   |-- img/
|   |   |   |-- spinner.svg
|   |   |   |-- Tlamatini.ico
|   |   |-- js/
|   |   |   |-- acp-agent-connectors.js
|   |   |   |-- acp-canvas-core.js
|   |   |   |-- acp-canvas-undo.js
|   |   |   |-- acp-control-buttons.js
|   |   |   |-- acp-file-io.js
|   |   |   |-- acp-flow-snapshot.js
|   |   |   |-- acp-globals.js
|   |   |   |-- acp-layout.js
|   |   |   |-- acp-parametrizer-dialog.js
|   |   |   |-- acp-running-state.js
|   |   |   |-- acp-session.js
|   |   |   |-- acp-undo-manager.js
|   |   |   |-- acp-validate.js
|   |   |   |-- agent_page_canvas.js
|   |   |   |-- agent_page_chat.js
|   |   |   |-- agent_page_context.js
|   |   |   |-- agent_page_dialogs.js
```

Tree appendix 8 of 8

```
| | | |-- agent_page_init.js  
| | | |-- agent_page_layout.js  
| | | |-- agent_page_state.js  
| | | |-- agent_page_ui.js  
| | | |-- agentic_control_panel.js  
| | | |-- canvas_item_dialog.js  
| | | |-- chat_page_runtime_poller.js  
| | | |-- contextual_menus.js  
| | | |-- shared-runtime-dialogs.js  
| | | |-- tools_dialog.js  
| | |-- sounds/  
| | | |-- hypervisor_alert.wav  
| | | |-- notification.wav  
| |-- video/  
|   |-- XAIHT-Tlamatini.mp4  
  
|-- telegram/  
|   |-- AztecTlamatini.txt  
|   |-- config.yaml  
|   |-- telegram_receiver.py  
-- templates/  
    |-- agent/  
        |-- agent_page.html  
        |-- agentic_control_panel.html  
        |-- login.html  
        |-- welcome.html  
  
-- DB/  
|   |-- Older/  
|       |-- README.md  
|   -- ToLoad/  
      |-- README.md  
  
-- jd-cli/  
|   |-- jd-cli.bat  
|   |-- jd-cli.jar  
  
-- tlamatini/  
|   |-- __init__.py  
|   |-- asgi.py  
|   |-- context_processors.py  
|   |-- logging_filters.py  
|   |-- middleware.py  
|   |-- settings.py  
|   |-- urls.py  
|   -- wsgi.py
```