

TLAMATINI

Complete Project Dossier: what the system does, how it works, how to use Tlamatini, complete repository file tree, and effective line inventory



Measure	Value
Generated	August 29, 2026 10:32 AM UTC-0600
Current HEAD	64b29725 - Trying to fix the starting runtime error at installed Tlamatini, by angelahack1
Resolved version	1.50.4 (git)
Repository inventory files	1030
Tracked files	1030
Git-unignored working-tree additions	0
Workflow agents	88
Multi-Turn tools	108
Skills	29
Total effective lines	226,230
Total physical text lines	322,716

1. What Tlamatini Is

- Tlamatini is a self-hosted AI developer assistant (cloud LLMs by default; the app and RAG run locally) built with Django, Django Channels, LangChain, LangGraph, FAISS/BM25 retrieval, and a large in-repository agent application.
- She combines a browser chat surface, a Retrieval-Augmented Generation stack, a Multi-Turn tool executor, MCP-backed context providers, wrapped chat-agent runtimes, and a visual Agentic Control Panel for workflow design.
- She is designed for development operations: codebase analysis, file and directory context, deterministic file discovery/search/editing, command execution, Python execution, screenshots, web/search helpers, notifications and attention routing, DevOps tools, authorized cyber-security assessment, local model operation, Windows packaging and uninstall registration, first-person self-knowledge about her own runtime, and embedded-firmware control for STM32, ESP32-class, Arduino-class, and ESPHome smart-home boards.

Agent-directory disclaimer: user jurisdiction and responsibility

- Every agent in ``Tlamatini/agent/agents/`` is intentionally plain Python so the user can read, audit, edit, restrict, or disable its operating code. This transparency is a user-control mechanism, not a warranty that an agent is secure or suitable for a particular environment.
- Agents have no independent authority or jurisdiction. The user alone decides whether, where, how, and with which permissions an agent runs; enabling, configuring, modifying, chaining, or executing it places that execution under the user's control and jurisdiction.
- The user is responsible for code/config review, least-privilege secrets and credentials, authorized files and targets, browsers, shells, APIs, external MCPs, machines, hardware, downstream systems, supervision, and compliance with applicable law, policy, license, contract, and authorization.
- By running an agent, the user accepts responsibility for its actions and consequences. To the fullest extent permitted by applicable law, security breaches, data exposure or loss, unauthorized actions, credential leaks, unsafe automation, violations, compromise, device damage, financial loss, or other harm arising from use are the responsibility of the user who runs it.
- Tlamatini's orchestration, documentation, examples, and guardrails do not authorize third-party access and cannot replace the user's security review, permission controls, monitoring, or legal compliance.

Enable Tlamatini as a Blue-hat agent

- The ``security/`` directory is an administrator-operated Windows defensive toolkit, not a new chat tool or database-backed workflow Agent row. Tlamatini helps collect and respond to signals only on systems the operator owns or is explicitly authorized to defend.
- The six shipped assets are ``README.md``, ``enable_tlamatini_v2.bat``, ``tlamatini_whitelist_v2.ps1``, ``run_defender.bat``, ``tlamatini_defender.ps1``, and ``automated_tests_of_security_assets.py``; runtime evidence is written under git-ignored ``security_logs/``.
- Use the safe sequence validate -> record a Windows baseline -> enable -> restart -> run detect-only -> investigate -> arm only when justified. There is no bundled rollback script, so Defender, ASR, CFA, firewall, execution-policy, audit-policy, and Security-log state must be recorded before elevation.
- The visible non-destructive harness parses both PowerShell files, exercises the self-safe classifier, validates official ASR/audit GUIDs, watch timing, UAC path handling, launcher failure propagation, Shoter capture, and headed-browser proof. The audited run passed 40/40 checks, but it does not apply Windows policy or execute an armed sweep.
- Enablement keeps core Defender/firewall services running but deliberately adds the Tlamatini root and selected executables to Defender exclusions, allows ``Tlamatini.exe`` through Controlled Folder Access, moves six selected ASR rules to action 6 (Audit), sets current-user PowerShell to RemoteSigned, and creates broad outbound application rules.
- The ASR rules cover Office child processes, LSASS credential stealing, WMI event-subscription persistence, email/webmail executables, untrusted or unsigned USB processes, and PSEXEC/WMI child processes. The script uses Microsoft's published IDs and reads Defender's effective ID/action arrays back before reporting success.
- Audit setup uses stable subcategory GUIDs for Logon, Credential Validation, Process Creation, Sensitive Privilege Use, and User Account Management, and checks every ``auditpol`` exit code. Command-line event 4688 and PowerShell Script Block Logging improve evidence but can record sensitive arguments.

- The ten monitor families are Defender health, logons, established TCP/listeners, processes, scheduled tasks, services, registry persistence, recently changed critical files, ransomware/recovery tampering, and account/administrator-group events.
- Detect-only logs ``WOULD BLOCK`` and ``WOULD KILL``. Default armed mode may add persistent inbound/outbound firewall blocks after repeated non-local failed logons and may force-stop known attacker-tool process-name matches; most other findings alert only.
- Dual-use names alert unless ``-Aggressive`` is supplied. Recognized Tlamatini paths are protected from auto-kill, but that is only a path-prefix check, not signature or provenance proof; malicious content inside an excluded/self path can inherit a blind spot.
- Watch mode is a foreground loop with ``-IntervalSeconds`` constrained to 5..86400. It is not a service or scheduled task, and ``run_defender.bat`` deliberately selects one default armed sweep, so baseline runs should invoke the PowerShell script directly with ``-DetectOnly``.
- ``alerts.log`` and ``monitor.log`` append sensitive usernames, IP addresses, paths, command lines, task/registry details, and response records without built-in rotation, deduplication, automatic unblock, or SIEM forwarding. Treat every severity as triage priority, not certainty.
- The batch launchers preserve paths containing spaces through UAC and propagate PowerShell failures. ``build.py`` ships the security source while excluding logs; self-modify snapshots likewise prune ``security_logs/`` so screenshots and host telemetry are not published.

What the system does

- Answers codebase questions with loaded file or directory context.
- Uses hybrid retrieval to extract metadata, split content, rank source chunks, and respect context budgets.
- Can discover files by glob pattern, search their contents by regex through Grepper's BOM-first UTF-8/16/32 and cp1252/Latin-1 decoder while skipping genuine binary data, and make surgical in-place replacements through Editor.
- Can connect to external MCP servers declared in ``external_mcps.json``, expose their remote tools to Multi-Turn under the ``ext__<server>__<tool>`` naming convention, and supervise those connections through ten status / reconnect / doctor / runtime / import / list / call / activate / wait helpers.
- Ships official Memory and Sequential-Thinking MCP catalog defaults in every install, both inactive, and can provision a private per-user Node/npm/npn/pnpm or uv/uvx runtime without admin access or system-PATH changes.
- Gives operators GUI-first database maintenance through the new DB dropdown for backup and staged database replacement.
- Makes those SQLite operations WAL-safe: online backup reads through committed WAL pages, creates a self-contained destination, verifies it with ``quick_check``, and keeps sidecars attached to the database they belong to.
- Can measure this machine's Internet connection through NetSpeed-Calculator, reporting throughput with confidence intervals, latency, jitter, loss, bufferbloat grade, and provider heterogeneity instead of trusting one speed-test endpoint.
- Lets operators manage provider secrets from the browser through the Config -> Access Keys Wizard instead of hand-editing ``config.json``.
- Can drive Blender through the Blenderer agent, using the official Blender MCP add-on socket to inspect scenes, mutate objects and materials, run raw code, and automate renders from chat or the workflow canvas.
- Can pause before every state-changing Multi-Turn execution and ask the operator to approve or deny that exact step through the Ask Execs checkbox.
- Can raise a Windows attention signal when the browser needs the operator: Ask Execs prompts and Notifier events can flash Tlamatini's own taskbar presence and leave an uppercase banner in ``tlamatini.log``.
- Registers packaged installs in Windows ``Installed apps`` / ``Programs and Features`` with a real uninstall entry, so the release behaves like a normal installed application instead of only a shortcut bundle.
- Can update packaged installs in place through About -> Check for updates: she checks the latest GitHub release, stages the download, swaps locked files externally, and preserves operator state such as ``config.json``, the database, and content.
- Hardens generated files: File-Creator's bulk-write path now preserves long content byte-complete even when it contains heavy quoting or semicolon-rich source text.

- Warns GPU-host operators before a directory-context load is likely to saturate VRAM and degrade embedding throughput.
- Exposes a coherent versioning surface across builds, runtime UI, logs, and an open health-check endpoint.
- Carries a first-person self-knowledge map so she can answer more accurately about her own architecture, ports, runtime modes, pages, and capabilities.
- Can command Kali Linux offensive-security tooling through MCP-Kali-Server for authorized recon, enumeration, web scanning, and assessment workflows.
- Can run local authorized nmap reconnaissance through Nmapper, a use-only bridge that resolves a user-installed nmap, defaults to unprivileged TCP connect scanning, refuses unsafe/missing prerequisites gracefully, and never bundles or redistributes nmap.
- Can support operator-controlled Windows Blue-hat monitoring through the host-side ``security/`` toolkit, with persistent enablement tradeoffs, detect-only baselining, ten signal families, bounded armed response, and explicit evidence/privacy limits.
- Can diagnose an external MCP before the first live connection through the MCP Doctor agent and wrapped ``chat_agent_mcp_doctor`` tool, checking transport, runtime requirements, PATH availability, placeholder secrets, and the next operator step.
- Can scaffold, author, build, flash, reset, and observe STM32 firmware through STM32er: the template-MCP path remains for STM32F407, while released ``v1.42.0`` adds a PlatformIO path for supported boards from Blue Pill/F1 through mainstream F/G/L/H7/U5/WB families, with fail-safe preflight before hardware mutation.
- Can scaffold, author, build, upload, and monitor ESP32-class firmware through ESP32er and PlatformIO Core, with zero-config bootstrap and a serial-aware preflight before hardware mutation.
- Can author YAML-based smart-home firmware through ESPHomer and ESPHome, including zero-config bootstrap, device-config generation, validation, compile, USB/OTA upload, and bounded log observation for ESP32 / ESP8266 / RP2040 / BK72xx devices.
- Can play media on the operator's machine: an audio file to the speakers through AudioPlayer (soundfile + sounddevice — volume in percent and a time-played budget that truncates a longer file or loops a shorter one), or a video file with audio on a chosen display through VideoPlayer (ffpyplayer, whose wheel bundles ffmpeg + SDL, plus an OpenCV window — display, volume, the same truncate/loop time budget, window size, and fullscreen); both are observational/output and ship on the canvas and as wrapped chat tools.
- Can SPEAK and LISTEN: Talker (text-to-speech) renders input_text to a 24 kHz WAV through an Ollama neural TTS model (default Orpheus-3b-FT) and is female-voice-only by design, while Whisperer (speech-to-text) records the microphone itself or transcribes a file via faster-whisper locally (NVIDIA-GPU auto-detect with an always-present CPU fallback) or a cloud Whisper API; both light a zero-latency console REC indicator driven by the live audio stream and are observational/output, on the canvas and as wrapped chat tools.
- Can manage real desktop windows by title: focus them, tile them, resize them, list them, and close them deterministically through Win32 calls.
- Can search with Googler through four plain-HTTP server-rendered routes first and, if empty, visible installed Chrome/bundled Chromium across seven browser routes, using bounded retries, manual query operators or a visual/pool structured dork builder, and URL-only output for indexed-file workflows.
- Can drive a real Playwright browser through scripted interactive steps for logins, forms, assertions, downloads, extraction, and end-to-end UI checks.
- Can drive a live Unreal Engine 5 editor through the Unreal MCP plugin, from either Multi-Turn chat or the visual workflow canvas.
- Actively reaps orphaned Windows console-host and pool-child processes so long Multi-Turn or ACPX sessions do not leave misleading Tlamatini-icon ghosts in Task Manager.
- Can autonomously kill only genuinely hung shell-wrapper subtrees through a boot-time command watchdog that measures CPU and I/O progress instead of guessing from elapsed time.
- Runs checked Multi-Turn requests through request-scoped planning, capability selection, tool calls, observations, monitoring, and final synthesis.
- Can optionally inspect and modify her own bundled source tree in self-modify builds after verifying that ``TlamatiniSourceCode/`` is actually present.

- Launches wrapped copies of selected workflow agents in isolated runtime folders without mutating templates.
- Lets users design, validate, save, pause, resume, and stop visual workflows through the Agentic Control Panel.
- Turns successful Multi-Turn tool executions into starter `.flow` workflows that can be inspected and validated in ACP.
- Packages the project into a distributable Windows release with installer and uninstaller tooling.

How it works

- Browser UI sends chat and workflow requests through Django views and Channels WebSockets.
- RAG chains load selected file/directory context, retrieve relevant chunks, and build answer prompts.
- DB-menu actions validate directories or SQLite files in the browser, then call Django views that use `sqlite_copy.consistent_copy()` to read through WAL, create a self-contained checked destination, and either back it up or stage it under `DB/ToLoad/db.sqlite3`.
- Config -> Access Keys Wizard reads masked provider-key status from the backend and persists only the edited secrets, keeping the browser flow honest without dumping live values back to the page.
- The file-navigation and file-edit trio sits above raw shell execution: Globber enumerates matching files, Grepper decodes BOM-marked UTF-8/16/32 before cp1252/Latin-1 fallbacks while pruning genuine binary/noisy trees, and Editor performs byte-exact in-place replacements without rewriting an entire file.
- External MCP connectivity is catalog-driven: `external_mcps.json` stores preserved Claude-style `mcpServers` state, `external_mcp_defaults.py` seeds inactive Memory/Sequential-Thinking defaults with edit/tombstone semantics, `runtime_provisioner.py` resolves or privately provisions npx/uvx managers, and `external_mcp_manager.py` negotiates stdio / streamable-HTTP / SSE / WebSocket before healthy remote tools become `ext__<server>__<tool>` planner entries.
- The `adding-external-mcp` skill applies that machinery in one guarded sequence: classify transport, import secret-separated configuration, diagnose, activate only on intent, wait for healthy tools, inspect status/list output, then call.
- The MCP Doctor path is intentionally safer than a live connect: it reads the configured server entry, validates transport shape, runtime commands, PATH/toolchain presence, placeholder secrets, and docs/source URLs, then returns an onboarding diagnosis without consuming the server's real tool surface.
- Blenderer opens the official Blender MCP add-on TCP socket (default `localhost:9876`), sends one action payload or raw code-execution request, and returns the structured result through the same wrapped-tool / canvas contract used by the rest of the agent catalog.
- When Ask Execs is enabled, the synchronous Multi-Turn executor stops before each state-changing tool call, emits an `exec_permission_request`, and waits on `ExecPermissionBroker` until the browser sends Proceed or Deny.
- When the browser surfaces an Ask Execs prompt or a Notifier event, JavaScript can POST to `/agent/flash_window/`; the backend then best-effort flashes the `Tlaminini.exe` console/taskbar window through `window_flash.py` and prints an uppercase attention banner for the log.
- Installer-time registration writes a per-user HKCU Add/Remove Programs entry pointing at `Uninstaller.exe`, and frozen startup re-checks that entry through `windows_app_registration.self_heal_for_frozen()` so older installs retroactively appear in Windows' uninstall surfaces.
- In-app self-update uses Django views plus `self_update.py` to check GitHub releases, download and stage the selected package, then hand off the locked-file swap to `apply_update.ps1`; the preserve contract retains operator state and `Uninstaller.exe` before relaunch.
- Frozen-build hardening now verifies media dependencies during packaging too: `build.py` embeds numpy and OpenCV in both shipped Python runtimes and refuses to produce a release if those imports are missing.
- Before a heavy directory embedding run on supported NVIDIA hosts, a fail-open pre-flight guard can estimate VRAM pressure and surface a non-blocking warning in chat.
- Version resolution now flows through git tags, a runtime resolver module, generated build artefacts, and an open `/agent/version/` endpoint.
- A first-person self-knowledge file (`Tlaminini.md`) is injected into prompt construction for all chains, but loaded user context still outranks that self-reference when the request is a generic summary of the provided project.

- When Multi-Turn is enabled, the global planner selects context and tool stages before the executor binds only the relevant tools, including wrapped deterministic agents such as De-Compressor.
- Optional self-modify builds bundle ``TlmatiniSourceCode/``; ``copy_source_assets.py`` generates that snapshot with rebuild instructions and redacted secrets, and prompt rules require her to verify that directory exists before claiming she can inspect or change her own code.
- The Kalier path talks directly to the MCP-Kali-Server Flask API over HTTP with Python-stdlib ``urllib``, auto-seeding the default box from ``kali_server_url`` in Config -> URLs before any one-off per-call override is applied, and captures one atomic ``INI_SECTION_KALIER`` block per run.
- The Nmaper path resolves a user-installed ``nmap`` from explicit config, PATH, Program Files, or ``%LOCALAPPDATA%``, constructs one safe scan action, captures XML plus normal output, parses hosts/open ports with the standard library, and emits one atomic ``INI_SECTION_NMAPPER`` block for Parametrizer/Forker routing.
- The NetSpeed-Calculator path opens parallel keyless-provider streams, drops the slow-start warmup, samples byte derivatives, rejects outliers, computes Student-t intervals, and pools provider estimates with inverse-variance or DerSimonian-Laird random effects; ``validate`` and ``providers`` are read-only, while throughput actions are metered tier-D work.
- The STM32er path spawns the STM32 Template Project MCP stdio server, performs the MCP initialize handshake, runs exactly one requested tool or composite action, and emits one atomic ``INI_SECTION_STM32ER`` block with the result, project directory, and stage metadata.
- Before any flash-capable STM32er action, a critical-mission preflight validates the arm-none-eabi toolchain, STM32CubeIDE, programmer path, ST-LINK presence, and STM32F-family match; compile-only steps can run boardless, but unsafe hardware mutations are refused fail-safe.
- The ESP32er path resolves or bootstraps PlatformIO Core, invokes ``pio`` subcommands directly with Python-stdlib process control, validates project and serial-port readiness, and emits one atomic ``INI_SECTION_ESP32ER`` block with stage, project, port, and stdout/stderr payloads.
- The ESPHomer path resolves or bootstraps the ``esphome`` CLI, can generate a minimal valid YAML device config headlessly, validates either a serial board or OTA host before upload/log actions, and emits one atomic ``INI_SECTION_ESPHOMER`` block with action, config path, stage, and captured CLI output.
- The Windower path uses Win32 APIs plus the cross-process ``AttachThreadInput`` focus-transfer dance to locate windows by title and apply one lifecycle action while still returning structured geometry/state fields.
- The Playwrighter path loads a declarative step list, drives Playwright against Chromium/Firefox/WebKit, and emits one atomic ``INI_SECTION_PLAYWRIGHTER`` block with status, assertions, extracted values, and the final URL.
- The Unreal path opens a TCP socket to the Unreal MCP plugin, sends one ``{"type": "command", "params": {...}}`` payload, captures the JSON reply, and emits one ``INI_SECTION_UNREALER`` block for downstream logic.
- A boot-time command watchdog samples CPU time and I/O bytes across shell-interpreter subtrees and reaps only the ones that stay idle past the grace-and-streak window, protecting healthy long-running commands while rescuing wedged prompt waits.
- After spawn-capable tool calls and again after the final answer, the orphan reaper can sweep dead descendants, orphaned ``conhost.exe`` companions, and stale pool-linked processes without ever raising into the chat path.
- Tool calls execute in the backend, append observations, and may create wrapped runtime copies under ``agent/agents/pools/_chat_runs_``.
- On the next full start-up, ``manage.py`` archives the previous database with its WAL/SHM/journal sidecars under ``DB/Older/<timestamp>``, clears stale destination sidecars, and only then promotes the verified staged database before Django imports.
- ACP flows deploy session-scoped pool instances, wire config values, validate NxN graph rules, and execute through Starter-driven flow semantics.
- Build scripts collect static assets, bundle Django/Python resources, add agent templates, and assemble ``pkg.zip``, ``Uninstaller.exe``, and ``dist/Tlmatini_Release/``; ``build.py --self-modify`` additionally injects the generated source snapshot, while the explicit private builder can synchronize same-machine contacts into gitignored private staging without exposing them in public output.

2. Architecture Layers

Layer	Role
Browser interfaces	Chat page plus Agentic Control Panel templates and JavaScript modules.
Django/Channels	Authentication, views, WebSockets, session state, message persistence, and ASGI startup.
RAG and context	Metadata extraction, text splitting, FAISS/BM25 retrieval, context budgeting, and fallback behavior.
Multi-Turn engine	Capability registry, global execution planner, explicit tool loop, answer parsing, and answer-success classification.
Tools and agents	Core tools, MCP context providers, wrapped chat-agent launchers, and the current visual workflow agent templates.
Packaging	PyInstaller build scripts, shortcut registration, `.flw` association, installer, uninstaller, and release folder assembly.

Design principles

- Evidence-first answers: Tlamatini grounds responses in selected project context and hybrid retrieval rather than freeform model memory.
- Explicit orchestration: checked Multi-Turn uses a visible tool loop, capability scoring, and staged planning instead of a single opaque call.
- Operational reversibility: risky changes such as database replacement are staged, archived, and delayed to the only safe window instead of hot-swapped mid-session.
- Fail-open diagnostics: GPU pressure probes and session-restore safeguards warn early without breaking CPU-only or degraded environments.
- Runtime isolation: wrapped chat-agent copies run in session-scoped folders so template agents remain pristine while live runs stay inspectable.
- Self-knowledge with scope discipline: she can talk accurately about herself without letting self-reference override a user-loaded project context.
- Operator truth over vibes: Exec Report tables, tlamatini.log, skill audits, and ACPX transcripts make the system auditable after execution.

3. Installation, Configuration, and Everyday Use

Start here - the easiest path

- BookOfTlmatini now leads with a five-step onboarding path because the easiest way to succeed with Tlmatini is to treat setup as one guided sequence instead of reading the whole handbook first.
- Recommended path for most operators: install the packaged release from GitHub Releases, launch the Start-menu shortcut, and let the bundled Python 3.12.10 plus dependencies carry the runtime without asking the user to install Python manually.
- Developer path stays available: clone the repo, create a virtual environment, install `requirements.txt`, run migrations, and start Django with `python Tlmatini/manage.py runserver` (the `--noreload` flag is optional since 2026-07-11 — plain `runserver` now boots clean and auto-reloads).
- Before pulling the shipped `:cloud` model tags, activate Ollama Pro or higher and run `ollama signin`; this is an operating requirement for the complete intended workload, not a sponsorship or affiliate relationship.
- After the app opens, the first in-app surfaces that matter are `Config -> Models`, `Config -> URLs`, and `Config -> Access Keys Wizard`; those now form the real beginner path, not manual JSON editing.
- For ordinary question-answering keep Multi-Turn off; turn it on only when you want Tlmatini to execute tools, wrapped agents, or remote MCP capabilities instead of answering directly.

Installation essentials

- The easiest path for most users is the packaged installer from GitHub Releases: no manual Python install is required because the release already carries Python 3.12.10 and the project dependencies.
- For Tlmatini's complete intended cloud-model workload, activate Ollama Pro or a higher plan such as Max and sign in with the Ollama CLI. Free/local-only operation is a limited compatibility path, not the documented full-workload baseline; verify current plan pricing and limits on Ollama's official site.
- Source mode remains the developer path: clone the repo, create a virtual environment, install `requirements.txt`, run migrations, create a superuser, collect static files, and then launch Django.
- Packaged Windows installs open the browser at `http://127.0.0.1:8000/` and create the default `user / changeme` login; manual source installs use your own `createsuperuser` account instead.
- Port 8000 is only the default: `config.json`'s `django\_port` moves the web UI to any free port on every launch path, which is the fix when Windows or Hyper-V has RESERVED port 8000 and startup fails with `WinError 10013`.
- When a newer packaged release exists, the intended upgrade path is in-app: `About -> Check for updates`, not manual folder replacement.
- You can run either the checked-in cloud/back-end defaults from `Tlmatini/agent/config.json` or a local/remote Ollama-backed configuration with matching model names.

First configuration screens

- Three new onboarding screenshots now anchor the first-run path: `Tlmatini/agent/images/MenuConfig.jpg`, `ConfigureModels.jpg`, and `ACPXKeysConfigureWizard.jpg`.
- `Config -> Models` is the place where operators map embedding, chat, vision, and auxiliary model names to what Ollama actually exposes on the host machine.
- `Config -> Access Keys Wizard` now carries an especially important rule: a localhost Ollama usually needs no Ollama token, while a remote Ollama endpoint may require one.
- Saved model, URL, or credential changes can invalidate the assumptions of the current session, so reconnecting after major Config edits is now part of the honest operator guidance.

Configuration essentials

- Source mode resolves `Tlmatini/agent/config.json`; frozen builds resolve `config.json` next to the executable; `CONFIG\_PATH` overrides both.

- Core keys include ``embedding-model``, ``chained-model``, ``ollama_base_url``, ``ollama_token``, ``enable_unified_agent``, ``unified_agent_model``, and ``unified_agent_max_iterations``.
- The checked-in default model baseline moved again in the recent Git window: the shared config now favors ``glm-5.2:cloud``, so source or frozen installs that keep the shipped config should be documented as cloud-first unless the operator intentionally swaps models.
- URL configuration now also includes ``kali_server_url``, the STM32er bootstrap fields ``stm32_mcp_server_script``, ``stm32_mcp_python``, ``stm32_template_dir``, ``stm32_ide_root``, ``stm32_mcp_repo_url``, and ``stm32_mcp_install_dir``, plus ESP32er's ``pio_executable`` and ``pio_core_dir``, all edited from ``Config -> URLs`` and inherited automatically by the chat-side wrapped tools.
- Credential configuration is no longer hand-edit-only: Config -> Access Keys Wizard provides a browser-side path for ACPX, provider secrets, unified messaging, and Security Recon (ProjectDiscovery) keys such as ``pdcg_api_key`` while preserving masked status in the UI.
- The chat-side Config -> Models and Config -> URLs dialogs are now first-class configuration surfaces, and they can explicitly ask the operator to reconnect when saved values change live-session assumptions.
- The separate DB dropdown is not a config editor: it is a maintenance surface for copying the live SQLite database out or staging a replacement for the next full start-up.
- Multi-Turn is toggled from the chat toolbar, but it depends on the unified-agent configuration and the selected model/base-url pairing being valid; the current default iteration ceiling is 4096, and Ask Execs only becomes available when Multi-Turn itself is on.
- Image-Interpreter now uses three model slots from Config -> Models: ``image_interpreter_model`` for the first forensic interpreter, ``image_interpreter_model_2`` for the second holistic interpreter, and ``image_merging_model`` for the final report merger.

DB menu and database swap-in

- The DB dropdown gives operators two GUI-first maintenance paths: ``Backup database`` creates a WAL-consistent verified snapshot, and ``Set DB`` stages a WAL-consistent chosen database for the next full start-up.
- Both dialogs are live-validated in the browser and now expose Browse buttons that open native host-side pickers for folders or ``db.sqlite3`` files.
- Both paths use ``sqlite_copy.consistent_copy()``: SQLite's online backup API reads through committed WAL pages, the destination switches to DELETE journal mode, and ``PRAGMA quick_check`` must pass before success. Set DB never hot-swaps mid-session because Django already holds SQLite open.
- Set DB writes a verified self-contained copy to ``DB/ToLoad/db.sqlite3``; the real swap happens only at the top of ``manage.py`` before Django imports anything.
- When that swap runs, the previous live database and its ``-wal`/`-shm`/`-journal`` family move into ``DB/Older/<timestamp>``, creating a rollback trail instead of overwriting history.
- Stale sidecars beside the destination are removed before promotion so SQLite can never replay pages belonging to the previous database over the newly selected file.
- Reconnect is not enough for this path: the operator must fully restart Tlmatini so the pre-Django swap window opens again.
- Copy verification is fail-safe: an unreadable, inconsistent, or unchecked result is reported as failure rather than called a backup. Startup preserves the previous live database if promotion cannot complete safely.

Versioning system

- Tlmatini now follows Semantic Versioning 2.0.0 with git tags as the single source of truth: you tag, then you build, instead of hand-editing version strings across files.
- The build path resolves a version once and propagates it into generated runtime metadata, Win32 VERSIONINFO resources, and the release-folder naming convention.
- Git resolves the current release as ``TLMATINI_VERSION=1.50.4``, matching the newest annotated ``v1.50.4`` tag at aligned local/remote HEAD rather than inventing a separate build identity.

Version surfaces

- Operators can now see the running version in the About dialog, the startup banner, the open ``GET /agent/version/`` health-check endpoint, and Windows file properties on the built executables.
- Packaged installs also project the same release identity into Windows' Installed-apps metadata through the ARP ``DisplayVersion`` field, so the uninstall surface and the binaries agree on the version being removed.
- The runtime resolver lives in ``Tlmatini/agent/version.py``, while the build-oriented coordination logic lives in the repo-root ``versioning.py`` and the longer policy notes live in ``VERSIONING.md``.
- Build overrides are supported in a predictable order: CLI ``--version``, then ``TLMATINI_VERSION``, then git describe, then the sentinel ``0.0.0+unknown``.

Current release focus in 1.50.4

- ``v1.50.4`` is the current annotated release, and the tag plus aligned local ``origin/main`` HEAD all resolve to ``64b29725``. It root-fixes installed-runtime startup by excluding optional Transformers from the frozen Django process, preventing its guarded token-counter fallback from loading 248 Transformers and 663 Torch submodules; carried Python still keeps Torch for Talker. Runtime identity stays Git/build-derived, and this generator creates no tag, commit, or push.
- NetSpeed-Calculator is workflow agent 88 and wrapped launcher 66. It measures download, upload, latency, jitter, loss, and bufferbloat across keyless providers, discards slow start, samples $d(\text{bytes})/dt$, rejects outliers, publishes Student-t confidence intervals, and uses fixed/random-effects fusion with Cochran Q and I-squared. Full runs commonly transfer 100-200 MB and are Ask-Execs tier D.
- Googler's structured dork compiler enforces no-space operators, exact quoting, uppercase parenthesized OR groups, exclusions, presets/aliases, and ``links_only`` file discovery; its pool runtime tries four plain-HTTP routes first, then seven browser routes with bounded retries. `v1.50.3` unescapes HTML entities, decodes Bing ``ck/a`` Base64URL targets, and filters Mojeek self-promotional links. External MCP onboarding and Deep Internet Research prompt 118 remain carried.
- Complete operation now documents Ollama Pro or higher as the intended minimum service tier for the shipped cloud-model workload. The private builder synchronizes same-machine contact sources into gitignored ``contacts.private.json``, while public builds and self-modify snapshots remain contact-empty.
- ``agent/agent_verdict.py`` now owns the CLOSED ``KNOWN_STATUSES`` union of five disjoint sets: ``DIAGNOSTIC_COMPLETED_STATUSES``, ``WORK_COMPLETED_STATUSES``, ``WORK_DEGRADED_STATUSES``, ``WORK_NOT_DONE_STATUSES``, and ``AGENT_ERROR_STATUSES``. The first two are green; the last three are red. R8b remains fail-open for unknown runtime input, while ``agent/test_status_vocabulary.py`` rejects unknown literals before release.
- Grepper detects BOM-marked UTF-8/16/32 before cp1252/Latin-1 fallbacks and before the NUL-byte binary test. The self-report outranks process exit code; Kubernetes emits ``returncode``, ``success``, and semantic ``status: ok|failed``. Source-derived tests stop status, supervisor, prompt, and catalog drift.
- ``agent/sqlite_copy.py`` routes Backup DB, Set DB, and pre-Django hot-swap through SQLite's online backup API. Destinations become self-contained DELETE-journal files, must pass ``PRAGMA quick_check``, and keep or clear WAL/SHM/journal sidecars in the correct order before promotion.
- Frontend dialogs now share one visual language through ``dialog_theme.css`` and one fail-open dismissal contract through ``dialog_policy.js``: an outside click never dismisses, while Escape finds the topmost open dialog and invokes that dialog's own X/Cancel path so permission denials, confirmation-false results, and scroll-lock cleanup remain intact. A sealed downloading updater is the single exception and refuses Escape/reload shortcuts. ``tlmAlert`` / ``tlmConfirm`` replace the remaining native pop-ups inside Contacts and External MCP dialogs, while ``release_notes_renderer.js`` safely renders update notes.
- The ``v1.48.16`` build proof names fail-open imports explicitly with hidden-import flags, opens the PyInstaller archive it just produced, and aborts if any of seven required ``agent.*`` modules is genuinely absent. Unreadable archive formats warn rather than fabricate failure, but a readable archive missing a required module cannot ship.
- Long operations use ``LONG_OPERATION_DISABLED_MENU_BUTTONS`` as the single Open/Save/Context/MCPs/Skills/External/Config/DB/Reconnect lock list; disable/restore paths preserve ``data-bs-toggle``, while only Check for Updates and Configure Agents receive the targeted extra lock. Application logging now attributes output by user, request, stream, and source line.
- Shoter now captures the whole desktop by default so secondary-monitor evidence is not silently lost, accepts a basename-sanitized exact filename for report workflows, falls back to primary-screen capture when ``all_screens`` is unsupported, and emits the resolved capture settings in its structured result.

- PDFer now localizes its own footer/fallback-title labels through ``document_language`` and forces optional Ollama polish to preserve the source language. External-MCP catalog refinements pin active services first, keep them alphabetized, add active/catalog headings, and preserve focus after rerendering.
- The binary-content guard, PDFer, LaTeXer repair ladder, FlowCreator, prompt grammar, recon free-run, STM32er PlatformIO/camera demos, and External-MCP structured-result delivery remain carried behavior rather than disappearing behind the latest changes.
- The private External-MCP runtime, inactive Memory/Sequential-Thinking defaults, tombstones, persistent Memory state, secret-separated catalogs, nested-diagram restoration, Mover/Deleter placement guard, and updater preservation remain carried from the v1.48.14-v1.48.17 lineage.
- The categorized prompt catalog, per-user Hard Cancel epochs, path-native screenshot paste/drop, configurable port, FlowPills discovery, Unreal scaffold, self-healing, robotic loop, firmware/media agents, External MCPs, ACPX skills, and deterministic file tools remain part of the complete product rather than being reduced to a latest-changes summary.
- README.md and BookOfTlmatini.md retain the complete MIT-licensed installation, Ollama setup, architecture, everyday-use, agent, and responsibility narrative. The plain-Python agent disclaimer is explicit: transparency enables user control but is not a security warranty, and authorization, review, permissions, and consequences remain the operator's responsibility.
- README.md and BookOfTlmatini.md remain the complete content baselines, while Git is the version source of truth: annotated release ``v1.50.4`` and aligned local/remote HEAD all resolve to ``64b29725``. The generated facts are source-derived: 88 agents, 66 wrapped launchers, 108 built-in Multi-Turn tools, 29 skills, and 197 migrations before documentation edits change line totals.
- The inventory is rebuilt from Git-tracked plus Git-unignored files without reproducing credentials, endpoints, private values, or machine-specific configuration. This generation pass does not stage, commit, or push anything.
- The regenerated PDF/PPTX preserve the whole system, architecture, installation/use guidance, recent Git history, complete file tree, effective-line inventory, and validation evidence; target behavior and tagged historical predecessors are described separately.

NetSpeed-Calculator measurement and safety contract

- Actions are ``full``, ``download``, ``upload``, ``latency``, ``validate``, and ``providers``. ``validate`` checks reachability and ``providers`` lists the catalog; neither runs a throughput transfer.
- Each throughput direction uses parallel TCP flows, discards the configured warmup/slow-start interval, and samples $d(\text{bytes})/dt$ so the excluded ramp cannot contaminate the estimate.
- Per-provider samples are cleaned with Tukey-IQR or MAD rejection, summarized with a trimmed mean, and assigned a small-sample Student-t confidence interval.
- Cross-provider fusion starts with inverse-variance weighting and switches to DerSimonian-Laird random effects when Cochran's Q shows genuine disagreement; I-squared quantifies heterogeneity.
- Bufferbloat is the RTT increase while the link is saturated, graded A+ through F. A fast idle Mbps number does not excuse poor latency under load.
- A zero-byte transfer records and reports its endpoint/network cause instead of masquerading as a measured 0.00 Mbps connection.
- Full runs commonly transfer 100-200 MB and deliberately saturate the link. The agent is Ask-Execs tier D; run once with explicit operator awareness and do not repeat only to seek a prettier result.
- The network/measurement stack uses Python's standard library; existing PyYAML reads ``config.yaml``. JSON evidence lands under ``<app>/Temp/NetSpeedCalculator``, and ``INI_SECTION_NETSPEED_CALCULATOR`` feeds Parametrizer/Forker and Exec Report.

Googler structured search, file discovery, and responsibility boundary

- The visual/pool Googler compiles structured fields into valid Google syntax: operator colons have no following space, exact phrases are double-quoted, alternatives use uppercase OR inside parentheses, and exclusions use ``-term`` without a gap.
- Presets are ``book``, ``book_public``, ``paper``, ``manual``, ``docs``, ``slides``, ``sheets``, and ``directory``. A preset fills only empty fields, so an explicit user value always wins.

- File aliases expand ``ebook``, ``book``, ``docs``, ``slides``, ``sheets``, ``text``, ``code``, and ``data``; multiple file types or sites become grouped OR clauses, while excluded sites become ``-site:`` filters.
- The remaining fields cover exact/author phrases; title, URL, text, and anchor operators; alternatives; AROUND proximity; numeric ranges; before/after dates; related/cache/define/source discovery; and term exclusions.
- For PDF, EPUB, document, slide, sheet, code, or data hunts, ``content_mode: links_only`` is the correct success path: Googler returns URL/title records without trying to extract text from a binary response.
- A typical downstream flow is Googler (``links_only``) -> Parametrizer -> Apirer (authorized download) -> File-Extractor or File-Interpreter -> Summarizer. Crawler remains appropriate when the target is an already-known web page.
- The direct Multi-Turn ``googler`` tool accepts equivalent hand-written operators inside ``query``; the structured fields and presets belong to the visual/pool agent and must not be advertised as direct-tool parameters.
- Googler locates publicly indexed URLs only and does not bypass access controls. Indexing is not permission: copyright, licensing, authorization, downloading, and use remain the operator's responsibility.

Googler plain-HTTP-first and browser-fallback search resilience

- A measured failure drove the redesign: bundled headless Chromium returned zero results even for a plain control query, and the old single DuckDuckGo fallback returned an error page, while the same dork in visible installed Chrome returned real EPUB URLs.
- Tier 0 uses plain ``urllib`` before any browser: DuckDuckGo HTML, Bing, DuckDuckGo Lite, and Mojeek provide server-rendered pages without browser fingerprints or CSS-selector dependence. v1.50.3 unescapes HTML entities, decodes Bing ``ck/a`` Base64URL targets, and filters Mojeek's own promotional links before the first non-empty result set wins.
- If Tier 0 is empty, Tier 1 defaults to visible installed Chrome, falls back to bundled Chromium, and walks seven direct-result browser routes: DuckDuckGo HTML/Lite, Mojeek, Bing, Google, Brave, Startpage. Headless remains opt-in and more refusal-prone.
- Each browser route receives ``attempts_per_engine`` bounded attempts with polite jittered backoff. The log names the route that actually answered instead of implying every result came from Google.
- ``engines`` can pin a browser route such as ``[google]`` and deliberately skips Tier 0. Empty selection enables both documented tiers; tolerant booleans keep wrapped string ``false`` from silently becoming true.
- ``site:`` and ``filetype:`` work broadly, but ``before:``, ``after:``, ``AROUND()``, and numeric-range semantics are Google-specific. A fallback engine may return broader candidates, so exact full-vocabulary work should pin Google and reports must preserve the answering-engine truth.
- The 73-test deterministic suite covers query compilation, config defaults, HTTP-before-browser order, seven-route browser order, retry/fallback stopping, pinned-engine Tier-0 bypass, tolerant booleans, and redirect unwrapping. The optional headed dork-hunt harness stores public/open-source proof under Tlamatini ``Temp``; the v1.50.3 tag records the first paired-Tlamatinis Googler improvement phase.

WAL-safe SQLite backup, staging, and hot-swap

- SQLite WAL mode can hold committed pages in ``db.sqlite3-wal``, so copying only the main file can silently produce an old backup while claiming success.
- ``sqlite_copy.consistent_copy()`` uses SQLite's online backup API to read through WAL, converts the destination to DELETE journal mode, and requires ``PRAGMA quick_check`` before success.
- Backup DB writes that verified self-contained copy to the selected directory. Set DB writes the same safe form into ``DB/ToLoad/db.sqlite3`` without touching Django's open live connection.
- Before Django imports, ``manage.py::_apply_pending_db_swap()`` archives the outgoing main database plus WAL/SHM/journal sidecars under ``DB/Older/<timestamp>``.
- The swap removes stale sidecars beside the destination before promotion, preventing SQLite from replaying pages belonging to the previous database over the selected replacement.
- Database copy truth is fail-safe: unreadable, inconsistent, or unchecked output is failure. The previous live database remains available if promotion cannot finish safely.

External MCP onboarding, deep research, and private-build boundaries

- The External MCP Adder skill's eight-step lifecycle is transport classification, secret-separated configuration, import, Doctor, intentional activation, healthy wait, status/list inspection, and remote call.
- Memory and Sequential Thinking remain inactive shipped defaults; deletion tombstones and persistent per-user state are respected, and at most five catalog servers are active at once.
- Deep Internet Research is append-only prompt 118 (`getting_started`, `sort_rank=100`). It requests Multi-Turn plus Exec Report for a long, link-rich search and may use authorized MCPs/agents without making them hidden requirements.
- Ollama Pro or higher is the documented minimum tier for complete intended cloud-model operation. This is not sponsorship, and plan pricing/limits must be checked with Ollama.
- The explicit private builder merges same-machine contact sources into gitignored `contacts.private.json` using normalized names, alias union, and non-empty-value preservation.
- Public builds ship an empty contacts book; self-modify snapshots contain no contact files; generated dossiers never reproduce contact values, credentials, or live catalog secrets.

Recent implementation assets and inventory impact

- v1.50.4 assets include `test_web_process_stays_lean.py`, the `build.py` frozen-process exclusion, canonical `langchain_core.tools` imports in runtime/tests, and `docs/claude/recent-fixes.md`. The regression suite guards against warning muting, direct ML-stack imports, accidental Torch exclusion from carried Python, and loss of the upstream guarded import contract.
- WAL-safe database assets include `agent/sqlite_copy.py`, the pre-Django `manage.py` swap, DB-menu views, `test_db_backup_restore_wal.py`, `run_db_wal_tests.ps1`, and the headed `test_db_backup_set_visible.py` suite.
- External-MCP onboarding assets include `skills_pkg/adding_external_mcp/SKILL.md` plus its transport, configuration, doctor, and activation references; migration 0194 and `test_deep_research_prompt.py` cover the new starter prompt.
- Private-release evidence includes `build_complete_private_release.py::sync_contacts_private`, the public empty-contact contract, and source-snapshot contact exclusion. Generated docs never reproduce contact values or live External-MCP credentials.
- The carried search/verdict/build assets remain represented by Grepper encoding tests, `agent_verdict.py`, Kubernetes contracts, `Uninstaller.exe` preservation, and the frozen-archive carriage proof.
- Blue-hat assets include the six tracked files under `security/`, build/source-snapshot log exclusions, official ASR and audit-policy GUID contracts, path-safe UAC launchers, the bounded defender watch loop, the expanded visible harness that passed 40/40 non-destructive checks, and fail-open self-update carryover for operator-owned `security_logs/` evidence.
- The inventory includes `image copy.png` as binary diagnostic evidence of the pre-fix startup console; its image contents and machine-specific paths are not reproduced in the dossiers. Line totals count text only and exclude comments, blanks, and Python docstrings according to the documented method.

v1.41.4 External-MCP structured output

- Modern MCP servers may return a short human-readable pointer in `content` while placing the actual result in `structuredContent`; the old parser discarded that machine-readable payload.
- Without the actual data, the model could repeat the same valid tool call until Tlmatini's repetition breaker force-stopped the run, making a successful external server appear to auto-cancel.
- `_format_mcp_tool_result` is now the single formatter used by both `_StdioMcpClient.call_tool` and `_NetworkMcpClientBase.call_tool`, so transport choice no longer changes result fidelity.
- Text blocks and non-text content are retained, while a sole `{"result": ...}` structured envelope is unwrapped before JSON serialization.
- `isError` still returns an explicit error and can now include structured-only error details; non-dict results are stringified safely.
- Structured payloads are capped at 24,000 characters by default with an explicit truncation marker, protecting the model context from unexpectedly huge tool responses.
- Seven tests cover pointer-plus-data, unchanged plain text, envelope unwrapping, text and structured-only errors, payload capping, and non-dict input.

- The fix is released as `v1.41.4` at `cec16594` and is present on `origin/main`.

v1.42.0 STM32er PlatformIO expansion

- Release status: STM32er PlatformIO Phase 1 was published in tagged `v1.42.0` at `c58b01ad`.
- `stm32\_backend=auto` keeps the legacy Template-MCP path for blank/STM32F4 requests, but a board, a non-F4 device, or a PlatformIO-only action routes to the new direct PlatformIO backend.
- Friendly board aliases and device-to-board mappings include the STM32F103 Blue Pill, while raw PlatformIO board ids remain accepted for broader `ststm32` coverage.
- The backend mirrors ESP32er's zero-config bootstrap and shared per-user PlatformIO core, then supports environment, board, project, source, package, build, upload, monitor, QA, and artifact actions.
- A preflight resolves the board/family, validates `platformio.ini`, probes PlatformIO and ST-LINK readiness, and requires hardware only for upload/monitor operations; compile-only actions remain boardless-safe.
- `scaffold\_build\_flash` creates or reuses a project, writes source, builds, and flashes only when ST-LINK is confidently detected; otherwise a successful build is reported with a clear connect-and-flash next step.
- The broad family parser recognizes the full ST line, but PlatformIO-incompatible newest families C0/H5/U0/WBA/N6 are deliberately refused instead of risking an incorrect linker or target.
- The planned CubeCLT/CubeMX backend remains proposal-only for those newest devices, especially STM32N6 signing and external-flash requirements.
- New assets include the all-families proposal and migrations `0177`-`0179`: one-call Blue Pill build/conditional flash, two stepwise camera-verified board walkthroughs, then a deliberate category-grouped no-gap catalog renumber.
- Registry, contracts, wrapped-tool defaults, config, agent code, descriptions, and tests move together; focused coverage pins family/routing safety plus catalog contiguity, prompt-name identity, category ordering, and demo presence.

v1.42.0 stepwise STM32 camera-verification demos

- Migration `0178\_add\_stm32\_stepwise\_blink\_camera\_prompts.py` adds two `firmware\_iot` walkthroughs: STM32F103 Blue Pill over an external ST-LINK V2 and STM32F407G-DISC1 over its embedded ST-LINK/V2.
- Both prompts require Multi-Turn, Exec Report, and Step-by-Step mode, execute exactly one stage per turn, wait for the operator's `READY`, and verify each prerequisite before moving forward.
- The six-stage Blue Pill path covers driver/CLI readiness, four-wire SWD wiring and probe detection, PlatformIO bootstrap, project/source/build, ST-LINK flash, and camera proof of the PC13 LED.
- The five-stage Discovery path uses the board's ST-LINK USB port, then bootstrap, project/source/build, embedded-probe flash, and camera proof of the green PD12 LED.
- Final evidence comes from `chat\_agent\_camcorder`; the prompt may pass the clip to Video-Analyzer or Image-Interpreter and must return a clear PASS or FAIL with the saved file path.
- These are seeded demonstrations and operator procedures, not a claim that hardware verification occurred during dossier generation.

v1.42.0 category-grouped prompt catalog with no gaps

- Released migration `0179\_regroup\_resort\_prompts\_no\_gaps.py` is a one-time deliberate override of the earlier no-renumber convention; it runs after the two new STM32 walkthroughs are appended.
- Every Prompt is sorted by the same category-display rank used by the UI and then by its prior id, so each category becomes one contiguous block from beginner workflows through specialized surfaces and the `other` fallback.
- Because `idPrompt` is the primary key, the migration first parks rows above 1,000,000 and then assigns final ids 1..N, avoiding collisions while rewriting `promptName` to `prompt-<id>`.
- The migration is intentionally one-way: reverse is a no-op because original ids are not stored; the source documents that no runtime foreign key references fixed prompt numbers.
- Future additions still append at max(idPrompt)+1, preserving contiguity until another deletion; the frontend's gap-tolerant fallback remains a defensive compatibility path.

- ``test_prompt_catalog_contiguous.py`` adds four database tests for no gaps, promptName/id agreement, nondecreasing category rank, and presence of both STM32 board demos plus Camcorder evidence.

v1.41.3 categorized and deduplicated prompt catalog

- Migration ``0175_prompt_category_and_dedup.py`` classifies the 106 historical prompt rows into 13 named operator categories, from Getting Started and Files/Search through ACPX, firmware, security, messaging, media, and a fail-safe More bucket.
- Migration ``0176_delete_duplicate_acpx_prompts.py`` physically deletes ids 40-52: 13 banner/Gemini variants that duplicate the seven portable ACPX demos retained at ids 33-39; surviving ids are never renumbered.
- Gaps are now valid. ``/agent/list_prompts/`` returns all visible rows regardless of id continuity, and the offline ``prompt-N`` fallback skips a missing id instead of terminating the catalog at the first gap.
- ``Prompt.category`` and ``Prompt.hidden`` remain schema-level controls, while ``PROMPT_CATEGORY_ORDER`` gives every known category a stable display rank and routes unknown or future values into ``other`` rather than dropping them.
- The modal renders explicit category headers and counts, then restores that grouped basic-to-advanced order whenever the search query clears.
- Live search accepts a prompt number, title words, mode labels, acronym, contiguous text, or fuzzy subsequence; it requires every query token, ranks best-first, highlights matched characters, and exposes Enter-to-open plus Escape/clear behavior.
- Prompt cards retain their One-Shot, Multi-Turn, ACPX, Exec Report, and Step-by-Step mode badges and continue to set the matching toolbar toggles when selected.
- The catalog stays viewport-pinned and bounded in CSS so its header and search bar remain reachable independently of the chat input height, with no JavaScript geometry coupling reintroduced.

v1.41.2 per-user Hard Cancel

- ``agent/cancellation.py`` mints a monotonically increasing run epoch per user and permanently latches the highest cancelled epoch; clearing the legacy setup boolean can no longer resurrect that run.
- Cancellation is isolated per user, so a browser tab cannot kill another user's TeleTlatamini or concurrent browser run; a missing epoch is deliberately fail-open so a dropped payload field cannot poison all future requests.
- ``ask_rag``, both unified-chain payload rebuilds, and ``CapabilityAwareToolAgentExecutor`` carry and check ``run_epoch``, closing the prior gap where model retries or tool loops could continue after Cancel.
- The executor returns a structured cancelled result instead of raising, preserving already-completed tool evidence, Exec Report data, and Create Flow inputs without triggering a fabricated transient-error fallback.
- Self-healing consults the same latch before retries, after watchdog waits, and before tactic announcements, so no new recovery tactic can be emitted once the operator cancels.
- Ask Execs polls the run latch and resolves a blocked Proceed/Deny request as deny; consumer teardown revokes the exact status emitter so a dying run cannot re-arm the UI.
- Frontend ``userCancelledRun`` is mutable per-session state: late tactic frames become strict no-ops until the next submit/reconnect, preventing the Send button from flipping back to Cancel.
- Coverage includes 24 cancellation contract tests, focused Ask-Execs/self-healing tests, and visible browser regression harnesses for long tool chains, model steps, repeated cancels, next-request recovery, and approval-modal cancellation.

v1.41.0 screenshot paste and image drop

- The chat accepts clipboard bitmaps through document-level Ctrl+V handling and image files dropped only onto the main chat column, avoiding conflict with the External-MCP dialog's document-level JSON drop surface.
- ``POST /agent/paste_image/`` validates the request, enforces a 25 MB ceiling, uses Pillow to flatten transparency onto white, re-encodes to JPEG, and writes a collision-safe ``image_<timestamp>.jpg`` under Tlatamini's guarded Temp directory.
- The browser inserts the saved absolute path at the remembered caret, including after focus moves to the page body during Alt+Tab, then renders one removable thumbnail chip per image.

- Removing a chip removes both its thumbnail and its exact path from the message, so an accidental paste can be reversed before submission.
- The path is the integration contract: Image-Interpreter reads local files, and ``prompt.pmt`` teaches Tlamatini to treat a fresh Temp image path as the user's supplied screenshot instead of asking for another attachment.
- ``computeFormMinHeight()`` measures the chips row and a `ResizeObserver` watches it, preventing the new row from pushing the textarea or Send button beyond the viewport.
- Implementation assets include ``chat_image_paste.js``, the paste view/URL, template chip/drop-overlay nodes, ``.chat-img-*`` CSS, layout integration, self-knowledge/prompt guidance, and Temp-policy regression coverage.

v1.40.1 configurable web port

- ``django_port`` moves the web UI and chat WebSocket bind away from a hardcoded 8000: edit the integer in ``config.json``, restart Tlamatini, and no rebuild or source edit is required.
- The motivating failure is Windows ``WinError 10013``: Hyper-V, WSL, or Docker can reserve port 8000 inside a dynamic exclusion range, making a frozen build unable to bind until the port is changed.
- Three stdlib-only helpers run before Django imports: ``_resolve_config_path()`` chooses ``CONFIG_PATH``, the frozen executable's neighbor, or source ``agent/config.json``; ``_resolve_django_port()`` validates ``1..65535``; ``_apply_configured_port()`` injects the result.
- The completion pass calls ``_apply_configured_port(sys.argv)`` once from ``main()``, outside the frozen branch, so frozen double-click, ``.flw`` association, browser auto-open, source ``runserver``, and ``startserver`` all agree.
- Resolution is fail-open to 8000 for missing, unreadable, malformed, non-numeric, or out-of-range values, while an explicit CLI port such as ``runserver 9100`` always wins and is never double-appended.
- The injected source-mode value is a bare port so Django keeps its loopback host; direct Daphne/Uvicorn bypasses ``manage.py``, MCP listeners ``8765`/`50051`` use their own settings, and TeleTlamatini keeps its own base URL.
- The 24-test ``agent/test_django_port_config.py`` suite AST-lifts the pre-Django helpers and pins path resolution, validation, fail-open behavior, CLI precedence, frozen/source wiring, and ``startserver`` forwarding without importing side-effectful ``manage.py``.
- ``freeingport8000.ps1`` is a separate elevated Windows repair helper that resets dynamic TCP/UDP ranges, restarts WinNAT, reports excluded ranges, and performs a loopback bind test; changing ``django_port`` remains the safer normal remedy, and generated docs never reproduce the script's machine-specific log path.

Tlamatini-FlowPills companion discovery

- Tlamatini-FlowPills reads ``HKCU\Software\XAIHT\Tlamatini`` first, especially the exact ``AgentsRoot``, before falling back to Installed Apps, ``.flw`` association data, executable-relative roots, or source/preserved probes.
- The registry contract always rewrites six `REG_SZ` values — ``InstallLocation``, ``AgentsRoot``, ``SourceAgentsRoot``, ``AgentManifestPath``, ``Version``, and ``AgentCatalogVersion`` — using an empty value when something is unknown so stale metadata cannot survive across source and frozen runs.
- ``agent_manifest.py`` discovers only complete templates, excludes ``pools`` and ``__pycache__``, hashes script/config contents, computes a name-set catalog id, and writes atomically only when meaningful data changed.
- Launch publication runs first in ``AgentConfig.ready()`` on a daemon thread with its own idempotency gate, so optional MCP, model, ACPX, or skill import failures cannot suppress companion discovery.
- An agents-preserving uninstall restamps the manifest as ``preserved``, writes ``.tlamatini-preserved-agents.json`` with the manifest SHA-256, and keeps the discovery key pointing to the preserved catalog.
- The contract is HKCU-only, no-admin, fail-open, and read-only with respect to agent templates; the filesystem remains the final validity authority for companion applications.

Unreal Engine 5.8 one-prompt scaffold

- The new Unreal scaffold prompt asks for only project name and destination, locates or obtains ``XaihtUnrealEngineMCP``, and invokes its deterministic ``scaffold_unreal_project.py`` helper.
- The scaffold copies and renames ``MCPGameProject``, sets `EngineAssociation 5.8`, finds an installed UE 5.8 even when it is not registered, bundles UnrealMCP, and generates the Visual Studio 2026 solution.

- UE 5.8 build compatibility is explicit: V7 build settings, `Unreal5\_8` include order, a `Directory.Build.targets` mitigation for the Windows environment-length limit, and a pre-fixed Visual Studio Tools plugin.
- The prompt instructs operators to build the project target rather than the entire solution, then open the editor; UnrealMCP starts its TCP listener at `127.0.0.1:55557` for Unreal.
- Unreal normalizes disk-style `/Content` references to `/Game`, maps the friendly material `slot` input to `slot\_index`, and forwards one command per TCP connection into the live editor.
- Migrations `0173` and `0174`, Unreal code/config comments, README/Book entries, and the current release metadata carry the scaffold workflow across source, catalog, and operator documentation.

v1.39.5 responsiveness and safety hardening

- The `v1.39.5` smoothness wave focuses on bounded waits, concurrency isolation, accurate partial-result reporting, and lossless final answers rather than a new agent count.
- Image-Interpreter now bounds Ollama connect/read gaps; the System-Metrics WebSocket bounds receive time; External MCP warm-connect/supervisor gates recover if thread start fails; and command/ACPX output decoding is UTF-8-safe.
- Nmapper assigns per-host budgets to slow actions, keeps the outer kill budget above them, preserves partial output, uses collision-proof filenames for parallel scans, and labels hard timeouts honestly.
- Multi-Turn folds deferred completion deliverables into every exit path, while orphan-survivor state is keyed by conversation user so simultaneous requests cannot consume or clear each other's evidence.
- `.flw` export redaction covers ordinary secret paths and URI userinfo, and the command parser distinguishes Windows trailing backslashes from escaped inner quotes at assignment boundaries.
- These changes are now committed release behavior; the user's pre-refresh uncommitted configuration values remain private and are not quoted in this dossier.

Nmapper local nmap bridge

- Nmapper is the `v1.39.3` local nmap bridge for authorized pentesting and CTF recon: it is a use-only integration, not a bundled scanner.
- The agent never ships or redistributes nmap; it resolves a user-installed `nmap` from explicit config, PATH, Program Files, or `%LOCALAPPDATA%`, and its `install` action launches the official free installer path.
- The default scan path is an unprivileged TCP connect scan (`-sT`), while raw-packet features such as SYN/OS/UDP are downgraded or refused safely when Npcap or elevated packet capture is unavailable.
- Supported actions include `quick`, `full`, `top\_ports`, `version`, `scripts`, `host\_discovery`, `udp`, `custom`, `validate`, and `install`, always for targets the operator owns or is explicitly authorized to assess.
- Each run emits one atomic `INI\_SECTION\_NMAPPER` block with action, target, scan technique, ports, return code, success state, hosts-up/open-port summaries, Npcap state, XML path/content, normal output, and stage.
- Implementation assets include `agent/agents/nmapper/`, migrations `0170`-`0172`, `test\_nmapper\_agent.py`, `chat\_agent\_nmapper`, `update\_nmapper\_connection`, contracts/Parametrizer fields, ACP connector assets, FlowCreator/FlowHypervisor entries, and handbook/docs updates.

Startup dialog and prompt-catalog polish

- `v1.39.4` restored first-run/startup dialog closeability so a fresh launch can no longer be trapped behind an unclosable overlay.
- Commit `a45fe0e0` followed the public `v1.39.4` tag with Catalog-of-Prompts localization cleanup; that historical polish remains carried by the `v1.50.4` release.
- The prompt catalog path stays centralized through the secure one-call `/agent/list\_prompts/` endpoint ordered by category rank and stable surviving id, while the gap-tolerant probe loop remains only as an offline fallback.
- Frontend mutable-state tests and dialog templates continue to guard the chat/startup/overlay surfaces so future cleanup passes do not reintroduce const-poison or close-button regressions.

v1.38.0 robotic loop closure

- `v1.38.0` is the milestone where the Robotic-Loop-Training story became concrete: Tlamatini demonstrated a closed hardware loop by programming a robotic arm from a blank page and two cameras.
- The loop is intentionally composable rather than one monolith: STM32er writes/builds/flashs firmware, Camcorder records the physical attempt, Video-Analyzer judges the captured motion, and Forker routes the next branch.
- Video-Analyzer keeps the loop conservative: a deterministic OpenCV gate rejects no-motion clips before model spending, then two independent Ollama cloud vision interpreters must agree before `PASS\_OK` is emitted.
- Forker branches on substring-safe `TLM\_VERDICT::<TOKEN>` markers, so `FAIL\_NO\_MOTION`, `FAIL\_WRONG\_MOTION`, `UNCLEAR`, or `ANALYSIS\_ERROR` can never accidentally match the success route.
- The PDF and PPTX now describe that loop as a system capability, not merely a release-note flourish, because it explains how Tlamatini can iteratively improve real hardware with observed evidence.

v1.38.1 frontend-state recovery hotfix

- `v1.38.1` was the same-week frontend-state-recovery hotfix: `package.json` was aligned at the tagged commit `08efa1d2`, while the functional fix landed in `af356c31` after the `85ee4e6c` const-poison incident.
- The core contract is explicit: cross-file runtime globals in `agent\_page\_state.js` and `acp-globals.js` that other modules reassign must remain `let`, because per-file ESLint cannot see those cross-file writes.
- `agent/test\_frontend\_mutable\_state.py` now guards both source files and collected staticfiles so an automated cleanup cannot silently turn chat state, ACP state, tools, agents, skills, history, or busy flags back into `const`.
- The Catalog of Prompts now loads through one secure `GET /agent/list\_prompts/` endpoint ordered by `idPrompt`, eliminating expected-404 console spam and preventing an `idPrompt` gap from hiding later prompts.
- The legacy prompt probe loop remains as an offline fallback, and the same fix also hardened dialogs: Configure-Mcps probe loops exit cleanly, About-video `play()` promises are guarded, and Esc closes About/Update overlays.

Post-v1.36.0 self-healing Multi-Turn reliability

- Every Multi-Turn model step now goes through `agent/self\_healing.py::SelfHealingInvoker`, so model calls are bounded by `unified\_agent\_llm\_step\_timeout\_seconds` and retried with distinct tactics instead of hanging silently.
- Recovery tactics include plain retry, short back-off, trimming oldest messages with `trim\_messages`, and a tool-less summary fallback; the ladder can run up to `unified\_agent\_llm\_step\_max\_tactics` unless the user presses Cancel.
- A status broadcaster registered by `consumers.py` sends live first-person recovery messages to the user's chat while the executor works in a worker thread.
- If recovery is exhausted after agents already ran, `mcp\_agent.py` builds a degraded but truthful answer from real `ToolMessage` results, preserves Exec Report/Create Flow evidence, and prepends `recovery\_preamble(...)` instead of claiming no tools ran.
- Coverage includes `agent/test\_self\_healing.py`, `agent/tests.py`, `Tlamatini/tests\_e2e/test\_self\_healing\_visual.py`, and `Tlamatini/tests\_e2e/test\_create\_flow\_visual.py` for visible browser validation.
- Frontend follow-up: `agent\_page\_ui.js::isSelfHealingStatusMessage()` anchors on leading `Tactic #` or `Tactic` status frames so `appendChatMessage()` keeps controls disabled and the Send button on Cancel while the run is still executing.
- The matcher deliberately avoids substring matching because the final `recovery\_preamble(...)` quotes tactic lines; a loose `includes` match would misclassify the final answer and trap the UI on Cancel forever.

Create Flow and Exec Report gating

- The whole-answer SUCCESS/FAILURE classifier `agent/services/answer\_analyzer.py` was removed on 2026-07-06, so no extra LLM round trip computes `answer\_success`.
- The browser now shows Create Flow when Multi-Turn ran, at least one successful tool call resolves to a registered canvas agent, and the user is not anonymous.
- Successful tool calls are resolved through a punctuation/space/case-insensitive registry key, so display names such as `File Creator`, `File-Creator`, and `filecreator` converge to the live Agents sidebar entry.
- Generated `.flw` downloads keep only successful, resolvable tool-call entries, post a successful-only `tool\_calls\_log` to `/agent/flow\_from\_tool\_calls/`, and drop failed or unregistered executions rather than turning them into broken workflow

nodes.

- If the registry cannot load, the frontend fails open: the button stays available and the backend flow normalizer remains the final validation layer.
- Exec Report remains per-tool evidence, not a whole-answer verdict; the checkbox is disabled/greyed unless Multi-Turn is checked.

Frontend recovery controls and Create Flow name resolution

- ``agent_page_chat.js::appendChatMessage()`` now has a self-healing status branch before the final-answer branch, so status frames render without calling ``enableControlsAfterOperation()``.
- ``disableControlsDuringOperation()`` is re-applied idempotently for each live tactic status line, preserving the user's Cancel button while the worker thread continues.
- ``agent_page_ui.js::isSelfHealingStatusMessage()`` strips leading icons/symbols and then anchors on ``Tactic #`` / ``Tactic``, matching standalone status frames but not the final recovery summary.
- Create Flow validation now uses ``_resolveSuccessfulAgents()``, ``_agentNameKey()``, and ``_buildRegistryKeyMap()`` to normalize display names against the live registry and skip only unresolved successful entries.
- ``eslint.config.mjs`` declares ``isSelfHealingStatusMessage`` as a global, while ``docs/claude/frontend.md``, ``docs/claude/multi-turn.md``, and ``docs/claude/recent-fixes.md`` document the gotcha and the no-substring rule.

Discoverer PDCP key integration

- Discoverer now has an optional ProjectDiscovery Cloud Platform key (``pdcapi_key`` / ``PDCP_API_KEY``) for cvemap/vulnx rate limits and nuclei ``-ai`` or cloud upload features.
- Config -> Access Keys Wizard exposes ``Security Recon (ProjectDiscovery)``, writes the key to ``config.json``, ``data.keys``, and ``agent/agents/discoverer/config.yaml``, and blank fields preserve existing values.
- ``tools._seed_global_agent_defaults`` auto-injects the configured key into every ``chat_agent_discoverer`` run so prompts never paste the credential.
- ``agent_contracts.py`` redacts ``pdcapi_key`` from ``flw`` exports, and ``regen_secrets.py`` scrubs it back to ``PDCP_API_KEY`` before a push-able tree.
- The new ``0169_add_discoverer_cvemap_latest_demo_prompt.py`` migration seeds a passive latest-CVE briefing prompt that uses cvemap/vulnx and reports whether ``pdcapi_used`` was active.

Discoverer vulnx and Go-toolchain Git-deny guard

- ProjectDiscovery retired cvemap's CVE API in August 2025, so Tlmatini keeps the operator-facing ``cvemap`` tool key but installs and runs ProjectDiscovery's successor binary, ``vulnx``.
- ``discoverer.py`` now maps ``cvemap`` to ``github.com/projectdiscovery/cvemap/cmd/vulnx@latest``, resolves the installed binary as ``vulnx``, and builds ``vulnx id <CVE>`` or ``vulnx search --severity ... --product ... --limit ...`` arguments.
- The findings counter now understands vulnx object JSON such as ``{"count": N, "results": [...]}``, so Exec Report and Forker routing see the real result count instead of a misleading one-line object.
- The private Go compiler and ProjectDiscovery tool binaries still install under ``<install_dir>/Go`` / ``<install_dir>/Go/bin-tools``, keeping the runtime self-contained and avoiding any system Go or PATH mutation.
- The ``gitignore`` Go-deny block, tracked ``git_deny_go.py``, and its managed pre-commit hook prevent ``Go/``, ``bin-tools/``, ``go-build/``, ``pkg/mod/``, and downloaded Go archives from entering source control; ignored ``Go/`` content is not counted as project code.
- The committed asset wave also includes ``0169_add_discoverer_cvemap_latest_demo_prompt.py``, ``claude/skills/tlmatini-daily-chat-test/harness/discoverer_1000.py``, and ``Tlmatini/agent/test_discoverer_thousand.py`` for latest-CVE and high-volume Discoverer validation.

v1.36.0 Video-Analyzer release delta

- Release identity: ``v1.50.4`` is the current annotated release, and aligned local/remote HEAD resolves to the same ``64b29725`` commit. The release keeps optional Transformers/Torch out of the frozen web process, migrates runtime tool imports to ``langchain_core.tools``, and adds lean-startup regression guards while carrying v1.50.3 Googler resilience,

NetSpeed-Calculator, WAL-safe SQLite movement, External-MCP onboarding, Deep Internet Research, private contact synchronization, and the earlier safety/platform waves.

- New agent: Video-Analyzer becomes the current media-verdict workflow agent and wrapped ``chat_agent_video_analyzer``, complementing Image-Interpreter with video-specific motion analysis.
- Implementation assets: ``agent/agents/video_analyzer/``, migrations ``0166_add_video_analyzer.py``, ``0167_add_chat_agent_video_analyzer_tool.py``, ``0168_add_video_analyzer_demo_prompt.py``, ``test_video_analyzer_agent.py``, ``chat_agent_registry.py``, ``mcp_agent.py``, and ``services/agent_contracts.py`` all move together.
- Model strategy: ``interpreter_model_1`` defaults to ``qwen3-vl:235b-cloud``, ``interpreter_model_2`` defaults to ``qwen3.5:cloud``, and ``merging_model`` defaults to ``glm-5.2:cloud``, with independent calls merged only after both interpreters report.
- Routing contract: every run emits ``INI_SECTION_VIDEO_ANALYZER`` plus ``TLM_VERDICT::<TOKEN>`` markers such as ``PASS_OK``, ``FAIL_NO_MOTION``, ``FAIL_WRONG_MOTION``, ``UNCLEAR``, and ``ANALYSIS_ERROR`` for Forker and Parametrizer.
- Adjacent UI work: prompt search moved from exact-title hunting to substring, word-start, and fuzzy matching, and generated ``flw`` files now use a serpentine layout to reduce visual congestion.

Video-Analyzer motion-verdict agent

- Video-Analyzer is Tlamatini's video-verdict agent: she receives ``video_pathfilenames`` as a direct file, wildcard, folder-newest rule, or Camcorder pool name and resolves the video before model calls begin.
- The first gate is deterministic and cheap: OpenCV/numpy frame sampling computes a motion score and returns ``FAIL_NO_MOTION`` without spending LLM calls when the recording clearly shows no movement.
- When motion exists, two Ollama cloud vision models run in parallel. One specializes in temporal/action evidence, the other provides an independent holistic judgement, and a merger model produces the final report.
- The final answer is intentionally conservative: PASS requires both interpreters to agree; disagreement or weak evidence becomes ``UNCLEAR``, and wrong movement becomes ``FAIL_WRONG_MOTION`` rather than a false pass.
- Structured output is ``INI_SECTION_VIDEO_ANALYZER`` with ``video_path``, ``verdict``, ``verdict_token``, ``confidence``, ``motion_score``, ``frames_analyzed``, model names, ``status``, and the body report.
- The robotics loop is now explicit: STM32er can flash firmware, Camcorder can record the board, Video-Analyzer can judge the recorded motion, and Forker can branch on the ``TLM_VERDICT::`` token to retry or finish.

Prompt search and generated .flw layout

- Prompt search now behaves like an operator tool instead of a static dropdown: category grouping, numeric/acronym/substring/word-start/subsequence matching, best-first ranking, highlighted hits, and mode badges make the deduplicated catalog navigable.
- The prompt-card rendering keeps One-Shot, Multi-Turn, ACPX, Exec Report, and Step-by-Step families distinguishable while migrations ``0175``-``0176`` remove redundant ACPX variants without renumbering surviving prompt ids.
- Generated ``flw`` workflows now use a serpentine canvas layout with row capacity and alternating direction, preserving the logical Starter -> Agent -> ... -> Ender order without pushing large chains into an unreadable line.
- This matters for documentation because the PDF and deck must describe not only new agents, but also the operator usability improvements that make the larger system actually usable.

v1.33.2 Zavuerer release delta

- Release identity: latest reachable public tag ``v1.33.2``; the generated artifacts now describe the Zavuerer release family plus post-release cleanup while preserving the v1.32.0 quality-and-identity background.
- New agent: Zavuerer becomes the 83rd workflow-agent type and the 60th wrapped chat-agent, adding ``chat_agent_zavuerer`` for Zavu unified messaging across SMS, WhatsApp, Telegram, Email, and Voice.
- Configuration: Config -> Access Keys Wizard now includes ``Unified Messaging (Zavu)`` and persists ``zavu_api_key``, which the wrapped runtime seeds into Zavuerer without exposing the secret in prompts.

- Canvas/runtime support: ``agent_contracts.py``, ``views.py``, ``capability_registry.py``, ``chat_agent_registry.py``, ``tools.py``, frontend ACP JS/CSS, and migrations ``0159``-``0164`` all move together to make Zavuerer usable from both surfaces.
- Follow-up defaults: ``config.json`` now favors ``glm-5.2:cloud`` across the primary chat/model slots, and the latest commits also adjust runtime parsing/middleware/settings surfaces around the release.
- Cost and safety wording: sign-up for Zavu is free, but sends are pay-as-you-go per message; the docs keep the authorized, opted-in recipient boundary explicit for A2P, WhatsApp-window, consent, and GDPR-style rules.

Zavuerer unified-messaging agent

- Zavuerer is Tlamatini's new Zavu unified-messaging agent: one workflow node and one wrapped ``chat_agent_zavuerer`` tool can send SMS, WhatsApp, Telegram, Email, or Voice messages through Zavu's ``/v1/messages`` API.
- The operator configures one ``zavu_api_key`` through Config -> Access Keys Wizard -> Unified Messaging (Zavu), and the runtime seeds that key into Zavuerer automatically so prompts never need to repeat or expose the secret.
- The agent speaks direct HTTP through the Python standard library, has a safe ``health`` action, refuses sends when the key/recipient/body/channel are invalid, and always emits ``INI_SECTION_ZAVUERER`` for Parametrizer/Forker branching.
- Canvas integration is complete: ``agent_contracts.py`` redacts ``zavu_api_key``, ``views.py`` handles Zavuerer connections, frontend CSS/JS gives the node a visible identity, and migrations ``0159``-``0164`` seed the Agent, Tool, demo/catalog prompts, and setup-wizard dedupe.
- Cost and safety boundary: Zavu sign-up is free, but sending is pay-as-you-go per message; Zavuerer must only message authorized, opted-in recipients, with A2P, WhatsApp 24-hour-window, consent, and GDPR-style responsibilities called out explicitly.

Image-Interpreter triple-model vision pipeline

- Image-Interpreter is now a triple-model vision analyst, not a single generic image describer: each image goes through two parallel interpreter calls and one merger pass.
- ``interpreter_model_1`` defaults to ``qwen3.5:cloud`` and is tuned for forensic OCR, mockup/GUI element inventories, percent-based positions/sizes, colors, fonts, and verbatim text.
- ``interpreter_model_2`` defaults to ``gemma4:cloud`` and reads the image holistically: design intent, visual hierarchy, scene meaning, people, and reasoned identity hypotheses.
- ``merging_model`` defaults to ``glm-5.2:cloud``; it waits behind a barrier until both interpretations arrive, then emits one definitive report with union-of-facts, conflict notes, and discrepancy handling.
- All four prompt surfaces (``prompt_user``, ``prompt_interpreter_model_1``, ``prompt_interpreter_model_2``, and ``prompt_merging_model``) receive the image file name as an identity clue, because a file named after a person often depicts that person.
- Fail-safe behavior is explicit: one failed interpreter still lets the merger work from the survivor; a failed merger returns both raw interpretations concatenated instead of losing the analysis.
- The structured output is now ``INI_SECTION_IMAGE_INTERPRETER`` with ``file_path``, ``interpreter_model_1``, ``interpreter_model_2``, ``merging_model``, ``status``, and the merged report body for Parametrizer/Forker routing.
- Config -> Models now exposes all three Image-Interpreter model slots (``image_interpreter_model``, ``image_interpreter_model_2``, ``image_merging_model``), and older preserved configs receive defaults so Save is not blocked by empty new fields.

External MCP universal client

- The ``v1.26.0`` headline feature is the External MCP universal client: Tlamatini can now consume any MCP server declared in ``external_mcps.json`` instead of depending only on bundled MCP integrations.
- Four transports are supported in the current implementation — stdio, streamable HTTP, legacy SSE, and WebSocket — and the active server set is intentionally bounded so operators can expose high-value remote tools without flooding the planner.
- Once connected, remote MCP tools are wrapped into the same Multi-Turn execution surface under ``ext__<server>__<tool>``, so they participate in planning, execution reporting, Ask Execs, and the rest of the operator guardrails instead of becoming a parallel hidden subsystem.

MCP Doctor agent and wrapped tool

- MCP Doctor is the new onboarding and triage specialist added with the External MCP release: she inspects a configured server entry and tells the operator what is wrong before a live connection attempt wastes time.
- The diagnostic checks cover transport shape, runtime command availability on PATH, placeholder or missing secrets, endpoint/source/docs links, and the concrete next step the operator should take to make the server connectable.
- Operators can reach the same behavior from both surfaces that matter: the MCP Doctor workflow agent on the canvas and the wrapped ``chat_agent_mcp_doctor`` tool inside Multi-Turn.

External MCP implementation assets

- The release is backed by real tracked assets rather than markdown-only claims: ``agent/external_mcp_manager.py``, ``agent/external_mcps.json``, the ``agent/agents/mcp_doctor/`` tree, the ``0141`-`0143`` migrations, ``static/agent/js/external_mcps_dialog.js``, and ``static/agent/css/external_mcps_dialog.css`` are the core implementation wave.
- The current test surface proves this is not a shallow UI feature: ``test_external_mcp_universal.py``, ``test_external_mcp_transports.py``, ``test_external_mcp_e2e.py``, ``test_external_mcp_add_flow.py``, and ``test_parametrizer_mcp_doctor.py`` exercise the universal-client path and the onboarding diagnosis path.
- Handbook evidence now exists alongside the code too: the README tutorial, Book sections, capability/planner wiring, and the dialog assets all moved together in the same release wave, with later cleanup removing obsolete draft documentation from the tracked tree.

Blenderer

- Blenderer was introduced in ``v1.20.0`` as the 77th workflow agent and remains the direct bridge to the official Blender MCP add-on, letting Tlamatini operate a live Blender session from either Multi-Turn chat or the visual workflow canvas.
- The bridge talks over a TCP socket (default ``localhost:9876``) and supports both raw ``execute_code`` requests and higher-level scene/object/material/render actions, so operators can mix deterministic verbs with precise Python-driven 3D automation.
- This extends Tlamatini beyond code and firmware orchestration into DCC / 3D-production work: asset inspection, scene mutation, material changes, camera setup, and render-triggering now live inside the same operator surface as the rest of the system.

In-app self-update

- The packaged application now includes an in-app self-update flow exposed from About -> Check for updates, so operators can refresh a frozen install without manually unpacking and replacing the entire release folder.
- The backend checks the latest GitHub release, downloads and stages the package, then hands off the locked-file swap to ``apply_update.ps1``, which performs the replacement after the running executable exits and relaunches the updated app.
- The update path is state-preserving by design: it keeps ``config.json``, user content, and one ``agents_backup`` generation, and it stages the user's database through ``DB/ToLoad/`` plus ``post_update_migrate.flag`` so the next launch restores and migrates that DB instead of wiping it.

Self-modify source snapshot

- Self-modify builds now rely on ``copy_source_assets.py`` to generate ``TlamatiniSourceCode/`` as a fresh rebuild-oriented snapshot of the repository.
- That snapshot includes source, build scripts, docs, skills, and small required binaries while deliberately omitting or redacting heavy media and secrets; ``_REBUILD_INSTRUCTIONS.md`` plus ``_SOURCE_SNAPSHOT_MANIFEST.json`` explain how to restore the missing payloads.
- Because the snapshot is optional, the runtime contract remains strict: Tlamatini must verify that ``TlamatiniSourceCode/`` exists before claiming she can inspect, modify, or rebuild herself.

API-Keys Wizard

- Config now includes an Access Keys Wizard / API-Keys Wizard path so operators can manage provider credentials from the browser instead of editing ``config.json`` directly.

- The backend exposes masked status plus explicit save endpoints, which keeps the operator flow convenient without echoing raw secrets back into the page.
- That feature arrives as a real asset wave, not just a hidden helper: ``agent/access_key_wizard.py``, ``static/agent/js/access_keys_wizard.js``, ``static/agent/css/access_keys_wizard.css``, and the updated ``templates/agent/agent_page.html`` now form a dedicated setup surface.
- This matters operationally because ACPX agents, cloud LLM providers, and adjacent integrations often fail for simple missing-key reasons; the wizard turns that setup into a first-class UI workflow.

Earlier implementation assets retained in the current tree

- The tagged ``v1.41.4`` wave adds the shared ``_format_mcp_tool_result`` path in ``external_mcp_manager.py`` plus seven focused cases in ``test_external_mcp_universal.py`` for machine-readable MCP results.
- The tagged ``v1.42.0`` STM32er/prompt wave adds over one thousand lines to ``stm32er.py``, expands `config/registry/contracts/tools/tests/docs`, and tracks the all-families proposal, migrations ``0177`-`0179``, and ``test_prompt_catalog_contiguous.py``.
- The clearer disclaimer commit for README.md and BookOfTlmatini.md is included in the ``v1.42.0`` ancestry; neither handbook is modified by this generation pass.
- The ``v1.41.0`` image-ingestion wave adds ``chat_image_paste.js``, paste view/URL wiring, chat chip/drop-overlay template nodes, image CSS, layout observation, Temp-policy coverage, and matching README/Book/self-knowledge guidance.
- The ``v1.41.2`` cancellation wave adds ``agent/cancellation.py``, ``test_cancellation.py``, ``test_ask_execs_allowlist.py``, expanded self-healing/frontend tests, and coordinated changes across consumers, executor, RAG, retry, permission, settings, and chat-state surfaces.
- Two browser regression harnesses under ``.claude/skills/tlmatini-daily-chat-test/harness/`` exercise repeated cancels, next-request recovery, model/tool-chain cancellation, Ask-Execs cancellation, and the destructive/human-contacting/network allowlist contract.
- The ``v1.41.3`` prompt-catalog wave adds migrations ``0175`-`0176``, Prompt category/hidden fields, ordered category metadata in ``views.py``, and grouped, gap-tolerant, fuzzy-searchable catalog behavior in ``tools_dialog.js`/`.css``.
- The same prompt wave physically removes 13 duplicate ACPX rows while retaining seven portable originals and stable surviving ids; the primary endpoint and offline fallback both tolerate the resulting gap.
- ``freeingport8000.ps1`` is the new Windows repair asset for resetting dynamic ranges, restarting WinNAT, reporting exclusions, and bind-testing 8000; its machine-specific scratch path is deliberately excluded from generated prose.
- The committed Discoverer PDCP assets include ``access_key_wizard.py`` Security Recon fields, ``tools.py`` default seeding, ``agent_contracts.py`` ``.flw`` redaction, ``regen_secrets.py`` scrubbing, and migration ``0169_add_discoverer_cvemap_latest_demo_prompt.py`` for the latest-CVE prompt.
- Discoverer hardening assets now include ``discoverer.py`` changes for ``cvemap`` -> ``vulnx``, ``.gitignore`` Go-deny patterns, tracked ``git_deny_go.py`` guard/pre-commit installer, ``discoverer_1000.py``, and ``test_discoverer_thousand.py`` validation coverage.
- The project inventory is rebuilt from ``git ls-files`` plus ``git ls-files --others --exclude-standard`` on every run, so any git-unignored local assets are counted while ignored runtime caches such as ``Go/`` remain outside the dossier.
- The newest frontend assets include ``agent_page_chat.js``, ``agent_page_ui.js``, ``eslint.config.mjs``, and the Claude frontend/Multi-Turn/recent-fixes notes that document self-healing status frames and Create Flow name resolution.
- The ``v1.40.1`` port assets span committed ``manage.py`/`config.json``, source/startserver integration, the committed 24-test ``agent/test_django_port_config.py`` suite, version surfaces in ``package.json`/`VERSIONING.md``, and operator contracts across README, Book, self-knowledge, prompt guidance, and ``docs/claude``.
- The newest agent assets are concrete: ``agent/agents/zavuerer/``, migrations ``0159_add_zavuerer.py`` through ``0164_dedup_zavuerer_setup_wizards.py``, ``test_zavuerer_agent.py``, Access Keys Wizard Zavu fields, planner capability hints, wrapped-tool registration, and ACP canvas styling/connection support.
- The latest cleanup/assets span also includes ``GEMINI.md``, ``FirstFinalPlanToSpeedUp.md``, ``docs/claude/recent-fixes.md``, response-parser/runtime/settings/middleware touch-ups, and removal of the stale ``Tlmatini/db.sqlite3.bak-prereseat`` backup from the tracked surface.
- The same wave preserves evidence-oriented tests and build guards such as ``test_private_data_guard.py``, performance/visual checks, About-window authorship tests, and public-release verification rules that distinguish sensitive

PII from valid creator names.

- The same span refreshes shipped visual/media assets: ``TlmatiniAbout.png`` replaces the old ``TlmatiniAbout.jpg``, and ``agent/images/TlmatiniAndKyber.mp4`` is part of the repository asset set described by the dossier.
- The same recent window also retains the earlier self-modify/browser-setup asset wave — ``copy_source_assets.py``, ``agent/access_key_wizard.py``, ``static/agent/js/access_keys_wizard.js``, ``static/agent/css/access_keys_wizard.css``, and the Blender control surface in ``agent/agents/blenderer/``.
- Key operator/runtime files such as ``prompt.pmt``, ``chat_agent_registry.py``, ``tools.py``, ``views.py``, ``urls.py``, ``manage.py``, ``file_extractor.py``, and the File-Creator/File-Extractor templates also changed, so the visible features are backed by concrete implementation assets rather than documentation-only promises.
- Because the dossier already includes the full repository inventory (git-tracked files plus git-unignored working-tree additions) and the full line-count inventory, these named assets serve as the human-readable shortlist of what changed most materially in the latest release wave.

File-Creator hardening

- The ``v1.19.5`` File-Creator hardening pass fixes the wrong-symbol / wrong-escape corruption path that hit backslash-dense Java, JSON, CSS, and regex files during wrapped chat-agent execution.
- Two byte-exact channels now exist: plain ``content`` is re-extracted verbatim from the raw request, and ``content_b64`` can carry source or binary bytes through a parser-immune base64 path when exact escaping matters most.
- For operators, the consequence is straightforward: code generation and document generation can now be described as byte-complete file writes rather than best-effort convenience output.
- This belongs in the dossier because File-Creator is one of Tlmatini's central deterministic execution surfaces and one of the safest alternatives to GUI typing or editor-driving automation.

Self-knowledge and identity contract

- Version ``1.8.0`` gives Tlmatini a first-person self-knowledge map in ``Tlmatini/agent/Tlmatini.md``, so she can answer more accurately about her own architecture, runtime modes, open ports, pages, and internal capability surface.
- That self-reference is injected into all prompt chains through ``prompt.pmt`` and ``agent/rag/config.py``, but it fails open if the file is missing or unreadable and it never overrides a user-loaded project when the request is a generic summary of the provided context.
- The language contract matters too: when a pronoun is used for Tlmatini in the documentation or prompt guidance, she is referred to as ``she`` / ``her``, matching the updated handbook identity rules.

Self-modify builds

- Self-modification is a separate capability axis from frozen-vs-source runtime: only builds created with ``python build.py --self-modify`` bundle ``TlmatiniSourceCode/`` next to the application.
- When that directory is present, she can inspect and modify her own shipped source tree; when it is absent, she must say so plainly and fall back to her injected self-knowledge plus the surrounding docs.
- The build pipeline now announces that choice explicitly, so operators can tell whether a release is self-modify-capable before asking her to work on herself.

Multi-Turn 4096-turn autonomy

- The unified-agent loop now defaults to 4096 iterations instead of 256, giving long autonomous operator runs much more room before they exhaust the turn budget.
- That expansion is about conversational/tool-loop depth, not about blindly firing more tools at once: the planner's selected-tool cap still keeps the tool surface bounded per request.
- Operationally, the bigger ceiling helps long workflows, while duplicate-call guards and the dedicated ``chat_agent_sleeper`` tool remain the antidote to accidental busy-polling loops.

Ask Execs in Multi-Turn

- Introduced in ``v1.10.0`` and still part of the current ``v1.26.0`` surface, ``Ask Execs`` is the Multi-Turn-only safety modifier that makes Tlmatini ask before each state-changing Tool, MCP, wrapped agent, or skill-backed execution instead of running

it immediately.

- The permission dialog is explicit and auditable: it names the Tool or Agent family, the underlying raw tool name, the full parameters, the program or command to be executed, and the shell or execution surface involved.
- Proceed runs that one step and then prompts again at the next state-changing step; Deny halts the entire chain immediately and appends a red `Execution interrupted` banner even when Exec Report itself is off.

Ask Execs runtime path

- Under the hood, `agent/exec\_permission.py` provides `ExecPermissionBroker`, which lets the synchronous worker-thread executor emit a permission request onto the WebSocket event loop and then block on a `threading.Event` until the browser replies.
- The gate sits after deduplication and quota checks, so skipped calls never prompt and denied calls never appear as executed rows; only work that truly ran lands in Exec Report.
- The round-trip is fail-safe: browser disconnect, emit failure, cancel, or broker shutdown all resolve to Deny, so an unconfirmed state-changing action never slips through just because the UI vanished at the wrong time.

Windows attention issuing

- The current Windows attention path is explicit and local: the browser calls `POST /agent/flash\_window/`, and the backend routes that request through `agent/window\_flash.py`.
- That helper can flash the `Tlmatini.exe` console/taskbar window with `FlashWindowEx` and always prints an uppercase attention banner, so the signal survives in `tlmatini.log` even when the browser is minimized.
- Two concrete reasons are wired today: Ask Execs execution approval prompts and Notifier notifications. The path is best-effort and fail-safe, degrading cleanly on non-Windows or windowless launches.

Windows Installed-apps registration

- Introduced in `v1.11.0` and still carried by the current `v1.26.0` release, the frozen install now behaves like a real Windows application: `install.py` writes a per-user HKCU Add/Remove Programs entry so Tlmatini appears in Settings -> Apps -> Installed apps and in the legacy Programs and Features list.
- The entry carries `DisplayName`, `DisplayVersion`, `InstallLocation`, `DisplayIcon`, `UninstallString`, `QuietUninstallString`, `NoModify`, `NoRepair`, and best-effort `EstimatedSize`, all pointing at the bundled `Uninstaller.exe` without requiring administrator rights.
- The matching runtime self-heal in `agent/apps.py` calls `windows\_app\_registration.self\_heal\_for\_frozen()` on every frozen launch, so installs created before this feature existed can appear in Windows' uninstall UI after the next normal app start.

De-Compressor agent

- De-Compressor is the deterministic archive worker for compression and decompression tasks, deciding direction from whichever side exposes a recognized archive extension.
- Supported archive families are `.gz`, `.zip`, `.7z`, `.tar.gz`, and `.gz.tar`; file-to-folder extraction and file-or-directory packing are both documented in the README and Book.
- Password handling is explicit: `passwordless=true` skips it, while `passwordless=false` requires the `DE\_COMPRESSER\_PWD` environment variable and fails fast if the secret is missing.

De-Compressor integration and fallback behavior

- The agent is reachable from both operator surfaces: ACP canvas nodes wire through dedicated connection-update views, and checked Multi-Turn can invoke it through `chat\_agent\_de\_compressor`.
- Format engines are practical rather than magical: stdlib `gzip` and `zipfile` cover core cases, `7z` is preferred for encrypted `7z` or `zip`, and `py7zr` was added to `requirements.txt` as the Python fallback.
- Every run emits an `INI\_SECTION\_DE\_COMPRESSER<<< ... >>>END\_SECTION\_DE\_COMPRESSER` block and still triggers `target\_agents`, so downstream Parametrizer or Raiser logic can branch on `success=true|false` instead of guessing from prose.

Unreal MCP and the Unrealer agent

- Unreal MCP is a UE5 plugin that runs inside the editor and listens on ``127.0.0.1:55557`` for one JSON command per TCP connection; Tlamatini is the client side of that link, not the plugin host.
- The Unrealer workflow agent forwards any command the connected plugin build exposes, up to a 53-command surface across nine categories: actor manipulation (incl. viewport screenshots), Blueprint authoring and node wiring, input mappings, UMG widget building, in-editor Python/console execution, level I/O, asset import, and material authoring. Headless build/cook/test is out of scope (it needs UnrealEditor-Cmd, not the editor socket).
- The same integration is available in both operator surfaces: checked Multi-Turn via ``chat_agent_unrealer``, and ACP canvas flows via the visual Unrealer node plus Parametrizer chaining.

Extended Unreal MCP surface

- Unrealer's documentation now points at the public ``XAIHT/XaihtUnrealEngineMCP`` fork, the Unreal Engine MCP variant developed specifically for Tlamatini.
- That fork exposes the extended 53-command, nine-category surface documented in README and Book: not only the base editor/Blueprint/UMG verbs, but also system, level, asset, material, screenshot, viewport, and in-editor Python paths.
- The practical message for operators is simple: Unrealer forwards the connected plugin's verb surface directly, so Tlamatini's client does not need a new release every time the plugin adds another supported command.

Installing the UE5 plugin and smoke-testing it

- Install the upstream plugin into ``<YourProject>/Plugins/UnrealMCP/``, enable it from ``Edit -> Plugins``, restart UE5, and confirm the Output Log says ``UnrealMCP listening on 127.0.0.1:55557``.
- Tlamatini does not compile or embed the plugin; the Unreal editor must already be running with the listener bound before any Unrealer call can succeed.
- A seeded smoke test ships in the Prompts table: ``Unreal MCP End-to-End Editor Drive`` walks through sanity-check, actor spawn, Blueprint creation/compile, and UMG widget assembly.

Orphan-process cleanup

- Tlamatini now ships a three-tier orphan reaper in ``Tlamatini/agent/orphan_reaper.py`` focused on Windows console-host leftovers such as ``conhost.exe`` and ``openconsole.exe``.
- Tier 1 runs after spawn-capable Multi-Turn tool calls, Tier 2 runs once after the final answer in a background thread, and Tier 3 runs again during application shutdown through the same cleanup path that already tears down pools.
- The candidate set stays narrow on purpose: dead descendants of the current process tree, orphaned console hosts tied to that tree, and pool-linked processes whose ``cmdline`` still points into ``agents/pools/...`` even though tracking records are gone.

Orphan-process prevention and survivor reporting

- Prevention landed alongside cleanup: Windows spawn sites now use ``CREATE_NO_WINDOW | DETACHED_PROCESS | CREATE_NEW_PROCESS_GROUP`` with stdio piped to ``DEVNULL``, so the console host is usually never allocated in the first place.
- The ACPX runtime now kills full process trees instead of only top-level wrappers, and pool-agent scripts gained a conservative ``subprocess.Popen`` guard so forgotten descendants still inherit ``CREATE_NO_WINDOW``.
- If something survives both cleanup tiers, Tlamatini sends a second chat bubble listing each surviving ``name + PID``; the reaper never raises into the user path because a cleanup crash would be worse than the leftovers it tried to remove.

How to use it

- Run from source: create a virtual environment, install requirements, migrate, create a superuser, collect static files, and start Django.
- Open ``/agent/`` for chat. Load a file or directory context before asking codebase-specific questions.

- Keep Multi-Turn unchecked for direct Q&A; enable Multi-Turn for tasks that need tools, wrapped agents, monitoring, or workflow seeding.
- Use ``chat_agent_globber`` to find files by pattern, ``chat_agent_grep`` to locate matching content, and ``chat_agent_editor`` when you need an exact in-place change instead of rewriting a whole file or shelling out to `grep/findstr/sed`.
- To use the External MCP capability, open ``External -> MCPs``, register or import a server into ``external_mcps.json``, choose the transport/runtime fields, and let the dialog connect it before expecting its ``ext__<server>__<tool>`` tools to appear in Multi-Turn.
- When you are onboarding or debugging an external MCP, call ``chat_agent_mcp_doctor`` first or use the MCP Doctor workflow node; it can tell you whether the issue is transport selection, a missing runtime on PATH, placeholder secrets, or a bad endpoint before you spend time on a live connect attempt.
- If you want a guided external-MCP onboarding flow, use the Step-by-Step mode in the External MCP dialog so each required field is introduced progressively instead of dumping the whole connection contract at once.
- For a deterministic MCP setup, invoke the ``adding-external-mcp`` skill and follow `classify -> import -> doctor -> activate -> wait -> status/list -> call`; do not treat a saved catalog row as a connected server.
- Use Config -> Access Keys Wizard when you need to wire or update provider credentials without editing ``config.json`` manually.
- Use About -> Check for updates on packaged installs when you want Tlmatini to fetch and stage the latest release without manually replacing the install folder.
- Tick ``Ask Execs`` when you want human approval before each state-changing Multi-Turn step; it is disabled until Multi-Turn is on, and a single Deny stops the whole chain with an explicit red interruption banner.
- When you are using a packaged install on Windows 10 or Windows 11, uninstall it through Settings -> Apps -> Installed apps or the legacy Programs and Features entry, not by manually deleting the folder.
- If an Ask Execs approval dialog or a Notifier event needs you while the browser is buried, watch for Tlmatini's taskbar-attention flash and the matching uppercase banner in ``tlmatini.log``.
- If you want her to inspect or modify herself, verify that ``TlmatiniSourceCode/`` exists in the current build first; self-modify is optional and absent builds must be treated honestly as read-only about their own code tree.
- For authorized Kali Linux assessments, run MCP-Kali-Server on the Kali box, set ``Config -> URLs -> Kali server (Kali)`` once, and then call ``chat_agent_kalier`` from Multi-Turn with the desired ``action`` and ``target`` without repeating the box URL each turn.
- For local nmap reconnaissance, install nmap yourself or call ``chat_agent_nmapper`` with ``action='install'`` to launch the official free installer; then use ``quick``, ``full``, ``top_ports``, ``version``, ``scripts``, ``host_discovery``, ``udp``, ``custom``, or ``validate`` only against hosts you own or are explicitly authorized to test.
- For Internet measurement, call ``chat_agent_netspeed_calculator`` once with ``latency`` or ``validate`` for low-bandwidth diagnosis, or explicitly approve ``full`` / ``download`` / ``upload`` knowing a full run commonly transfers 100-200 MB; report the confidence interval and provider disagreement, not only one Mbps number.
- For STM32 firmware work, install STM32CubeIDE, leave ``Config -> URLs -> STM32 MCP server script`` blank for zero-config bootstrap, and then call ``chat_agent_stm32er`` from Multi-Turn with one ``action`` at a time such as ``validate``, ``create_project``, ``write_source``, ``build``, ``build_and_flash``, ``serial_session``, or ``live_monitor``.
- For ESP32 firmware work, leave ``Config -> URLs -> pio_executable`` blank for zero-config PlatformIO bootstrap, then call ``chat_agent_esp32er`` from Multi-Turn with actions like ``bootstrap``, ``validate``, ``create_project``, ``write_source``, ``build``, ``upload``, ``build_and_upload``, ``monitor``, or ``monitor_session``.
- For ESPHome smart-home firmware work, leave ``Config -> URLs -> esphome_executable`` blank for zero-config bootstrap, then call ``chat_agent_esphomer`` from Multi-Turn with actions like ``bootstrap``, ``validate``, ``new_config``, ``config``, ``compile``, ``upload``, ``logs``, or the one-shot ``scaffold_compile_upload`` flow.
- For desktop-window control, call ``chat_agent_windower`` from Multi-Turn to focus, tile, resize, list, or close a window by title, or model the same action in ACP with the Windower node.
- For interactive web automation, call ``chat_agent_playwrighter`` from Multi-Turn with a ``steps_json`` script, or author the same step list visually with the Playwrighter node on the canvas.

- For Blender work, enable the official Blender MCP add-on in Blender, make sure its TCP listener is reachable (default `localhost:9876`), then call `chat_agent_blenderer` from Multi-Turn or use the Blenderer node on the canvas.
- For Unreal Engine work, enable the Unreal MCP plugin inside a live UE5 project first, then call `chat_agent_unrealer` from Multi-Turn or use the visual Unreal node on the canvas.
- Archive jobs can now be described directly in Multi-Turn or modeled visually in ACP: De-Compressor infers compress vs decompress from the `input` or `output` extension.
- If a second post-answer warning bubble ever lists surviving `name + PID` entries, treat it as an honest cleanup report and end the listed processes manually from Task Manager if needed.
- Use the `ACPX-Skills` navbar menu when you need to browse, enable/disable, diagnose, or reload the shipped SKILL.md catalog without asking the LLM to be your admin surface.
- Use the DB dropdown when you need a safe database snapshot or want to stage a different `db.sqlite3` for the next start-up without hot-swapping the live SQLite file.
- Open `/agentic_control_panel/` to drag agents, connect them, configure each node, validate, start, pause/resume, stop, and save `.flw` workflows.
- Use `python build.py`, `python build_uninstaller.py`, and `python build_installer.py` only when producing a packaged Windows release.

Agent descriptions and catalog source of truth

- The authoritative human-readable source for workflow-agent descriptions is `agents_descriptions.md` at the repo root, not an embedded JavaScript map or a hard-coded Django list.
- Current validation compares live template directories, `agents_descriptions.md` rows, and the README / Book bestiary counts so the generated dossier stays aligned with the running product.
- The ACP sidebar hover tooltip and the right-click Description dialog both resolve through that markdown file first; `README.md` is only a legacy fallback when the dedicated description file is absent.

Reviewer and Analyzer

- The workflow catalog now includes two new high-value specialists: Reviewer and Analyzer, lifting the canvas inventory to 64 agents and the seed-skill catalog to 23 SKILL.md packages.
- Reviewer is LLM-powered: it resolves a git diff for `repo_path`, reviews it with a senior-engineer prompt, and emits an `INI_SECTION_REVIEWER` block whose first routable field is `verdict = APPROVE | REQUEST_CHANGES | COMMENT`.
- Analyzer is deterministic and scanner-driven: it runs whichever of `bandit`, `semgrep`, `ruff`, `eslint`, `gitleaks`, and `pip-audit` are installed on PATH over `target_path`, then emits an `INI_SECTION_ANALYZER` block with `status` and `total_findings` for downstream routing.
- Both agents always trigger `target_agents`, so a downstream Forker can branch on `{verdict}`, `{status}`, or `{total_findings}` instead of scraping prose.
- They are intentionally canvas-only workflow agents: there is no wrapped `chat_agent_reviewer` or `chat_agent_analyzer`, and therefore no duplicate Exec Report row family for those names.
- The chat-side counterparts live in the ACPX skill catalog instead: `code-review` exposes senior-engineer git-diff review, while `security-audit` exposes the deterministic multi-scanner sweep.

Operator surface counts

- The live operator surface now stands at 88 workflow agents, 108 Multi-Turn tools, 12 ACPX tools, and 29 skills.
- Source inspection confirms the total: 20 core Python tools + 66 wrapped chat-agent tools + 12 ACPX/Skill tools + 10 External-MCP supervisors = 108 built-in Multi-Turn tools; healthy active servers add dynamic `ext__*` remotes separately.
- The count growth over older public badges comes from stacked waves: the deterministic file trio, ESPHomer, MCP Doctor, Zavuerer, Video-Analyzer, Nmapper, NetSpeed-Calculator, and the `adding-external-mcp` skill.
- The workflow-agent and wrapped-tool totals are validated from the live tree even when some handbook badges or older prose lines lag behind the newest release wave, so the dossier stays tied to source truth instead of stale summaries.

- This matters operationally because the planner never binds everything at once: the documented default ``max_selected_tools`` cap stays at 20, so breadth of capability does not mean uncontrolled tool sprawl per turn.

Kalier current role

- Kalier is Tlamatini's current Kali Linux bridge: a direct client for MCP-Kali-Server that lets her drive authorized recon, enumeration, web scanning, and offensive-security workflows from chat or canvas.
- It can issue one capability per run, including ``nmap``, ``gobuster``, ``dirb``, ``nikto``, ``sqlmap``, ``metasploit``, ``hydra``, ``john``, ``wpscan``, ``enum4linux``, arbitrary ``command``, or a safe ``health`` probe of the remote server.
- The agent emits ``INI_SECTION_KALIER`` with ``action``, ``endpoint``, ``subject``, ``return_code``, ``success``, ``timed_out``, and ``server_url``, so downstream Forker or Parametrizer logic can branch on results without scraping prose.
- The practical operator result is simpler prompts: after the Kali box URL is configured once, normal Multi-Turn requests no longer repeat ``server_url`` unless you intentionally override it for a one-off target.
- Two operator surfaces ship in lock-step: the wrapped Multi-Turn tool ``chat_agent_kalier`` now auto-injects the configured ``kali_server_url``, while the visual Kalier canvas node still stores ``server_url`` explicitly in YAML per node.
- Kalier talks straight to the Kali-side Flask API over HTTP using Python-stdlib ``urllib``, so it stays self-contained in the pool subprocess and works the same in source or frozen builds; the embedded-client injection fails open if the config value is blank or unreadable.
- Authorized use only: the intended operator flow is an in-scope lab, CTF, or permitted engagement, often with ``ssh -L 5000:localhost:5000 user@KALI_IP`` tunneling a remote Kali box back to ``http://127.0.0.1:5000``, and the repo now includes ``Tlamatini-Kali-Setup.md`` for the zero-client walkthrough.

STM32er current role

- STM32er is Tlamatini's critical-mission STM32 bridge. The established route talks to the ``STM32 Template Project MCP`` for STM32F407, while released ``v1.42.0`` adds a direct PlatformIO route for supported mainstream STM32 boards without removing that flow.
- Both backends keep zero-config intent: the template route bootstraps its MCP dependencies, and the new route resolves or installs PlatformIO Core in the same shared per-user location used by ESP32er.
- Backend-specific preflight preserves target safety: compile-only work may proceed without attached hardware, but upload, reset, serial, and live operations are refused when the required toolchain, project, board mapping, programmer, or ST-LINK evidence is missing.
- Two operator surfaces ship in lock-step: the wrapped Multi-Turn tool ``chat_agent_stm32er`` takes one ``action`` per call, while the visual STM32er canvas node stores the same fields in YAML and triggers downstream agents on both success and failure.
- The tool surface retains the 23 MCP verbs and locally adds PlatformIO environment, board, project, source, build, flash, monitor, package, QA, artifact, and safe scaffold composites; every run still emits one ``INI_SECTION_STM32ER`` block for routing.
- Config seeding supplies both MCP and PlatformIO defaults, while ``stm32_backend=auto``, ``board``, and ``device`` keep the normal prompt focused on firmware intent. Newest-silicon CubeCLT/N6 handling remains proposal-only and is not advertised as implemented.

ESP32er current role

- ESP32er is Tlamatini's current PlatformIO Core bridge: she can scaffold, author, build, upload, and monitor ESP32-class firmware without relying on an external MCP server or IDE.
- The operator promise is zero-config bootstrap: leave ``pio_executable`` blank and ESP32er downloads or pip-falls-back to PlatformIO Core on first use, validates it, and caches it under a per-user directory so the user installs only the board USB driver plus Tlamatini.
- Before any build-or-upload action, ESP32er runs a serial-aware preflight over ``pio`` resolution, project shape, and connected ports; upload and monitor require a real serial device, while non-espressif32 targets are warned about rather than hard-refused because PlatformIO is intentionally multi-target.
- Two operator surfaces ship in lock-step: the wrapped Multi-Turn tool ``chat_agent_esp32er`` takes one ``action`` per call, while the visual ESP32er canvas node stores the same fields in YAML and triggers downstream agents on both success

and failure.

- The tool surface covers environment/meta (`bootstrap`, `validate`, `system\_info`, `boards`), project lifecycle (`create\_project`, `write\_source`, `read\_source`, `list\_sources`, `clean`), build and flash (`build`, `upload`, `build\_and\_upload`, `list\_artifacts`), serial HIL (`device\_list`, `monitor`, `monitor\_session`), and package / QA paths (`pkg\_install`, `pkg\_list`, `pkg\_update`, `check`, `test`), with every run emitting an `INI\_SECTION\_ESP32ER` block for Forker or Parametrizer routing.
- Config -> URLs now seeds the chat path with `pio\_executable` and `pio\_core\_dir`, so firmware prompts usually describe only the board, project, and task while the wrapped tool auto-injects the PlatformIO runtime plumbing.

ESP32 Template Project reference baseline

- The new `ESP32TemplateProject` repository is the known-good baseline documented in BookOfTlmatini's bonus chapter: a plain PlatformIO project, not a server, meant to prove an ESP32 board and toolchain are healthy before larger firmware work.
- It mirrors ESP32er's grain: `platformio.ini`, `src/`, `include/`, `lib/`, `test/`, a blinking `main.cpp`, serial output at 115200, and GitHub-ready docs/CI so the reference project does not silently rot.
- Operationally, ESP32er can either point at a checkout of that template (`project\_dir`) or scaffold an equivalent from scratch with `action=create\_project`, then carry the directory through build, upload, and monitor steps.

ESPHome current role

- ESPHome is Tlmatini's ESPHome bridge: she can author YAML-based smart-home device configs, validate them, compile firmware, upload over USB or OTA, and observe logs without introducing an extra MCP server or IDE.
- The operator promise is zero-config bootstrap: leave `esphome\_executable` blank and ESPHome installs or resolves ESPHome on first use, so the user installs only the board USB driver plus Tlmatini.
- Before any compile-or-upload action, ESPHome runs a fail-safe preflight over `esphome` resolution, YAML existence, and serial-or-OTA readiness; upload, run, and logs require a real serial board or an OTA host because the first flash is always USB.
- Two operator surfaces ship in lock-step: the wrapped Multi-Turn tool `chat\_agent\_esphomer` takes one `action` per call, while the visual ESPHome canvas node stores the same fields in YAML and triggers downstream agents on both success and failure.
- The tool surface covers environment/meta (`bootstrap`, `validate`, `version`), device-YAML lifecycle (`new\_config`, `write\_config`, `read\_config`, `config`, `clean`), build and flash (`compile`, `upload`, `run`, `list\_artifacts`), bounded observation (`logs`), and the one-shot `scaffold\_compile\_upload` lifecycle.
- Config -> URLs now seeds the chat path with `esphome\_executable`, so smart-home firmware prompts usually describe only the device, board, and task while the wrapped tool auto-injects the ESPHome runtime plumbing.

ESPHome template baseline

- The bundled `ESPHomeTemplateProject` is the known-good ESPHome baseline documented in README and Book: a phone-controllable light with native `api`, `ota`, `wifi`, and a board LED output, shipped as `agent/agents/esphomer/ESPHomeTemplateProject/tlmatini-light.yaml`.
- It matters because ESPHome's source-of-truth is a YAML device file, not a C++ project tree: that sample proves the first real workflow of `new\_config` -> `config` -> `compile` -> `upload` without forcing users to invent a valid starter config from memory.
- Operationally, the sample closes the gap between the new agent and a practical first build a user can validate, compile, flash, and then control from a smart-home hub such as Home Assistant.

Windower on Multi-Turn and canvas

- Windower is the new 66th workflow agent: a deterministic Win32 window manager that finds an application window by title and performs one lifecycle operation on the window itself instead of clicking inside it.
- It supports `focus`, `minimize`, `maximize`, `restore`, `move`, `resize`, `move\_resize`, `close`, `topmost`, `untopmost`, `arrange`, and `list`, with `substring`, `exact`, or `regex` title matching plus `match\_index` for duplicate titles.

- The agent emits ``INI_SECTION_WINDOWER`` with ``action``, ``window_title``, ``matched``, ``match_count``, ``state``, ``left``, ``top``, ``width``, and ``height``, so downstream Forker or Parametrizer logic can branch on presence, state, or geometry.
- Two operator surfaces ship in lock-step: the wrapped Multi-Turn tool ``chat_agent_windower`` accepts free-form key=value requests, while the visual Windower canvas node stores the same operation fields in YAML.
- Windower is the desktop-window sibling of Mouser and Keyboarder: use Windower when the goal is the window as a whole, Mouser for controls inside it, and Keyboarder for text entry into it.
- Because Windower changes real window state, its executions appear in Exec Report and it always triggers ``target_agents`` whether the action succeeds or fails.

Playwrighter current role

- Playwrighter is the new 65th workflow agent in ``v1.5.0``: a deterministic Playwright-powered browser automator for Chromium, Firefox, or WebKit that executes ordered interactive steps instead of static fetches.
- It covers the gap between Crawler and Googler: logins, multi-step forms, wizard clicks, JS-rendered SPA scraping, screenshots after interaction, assertions, downloads, and authenticated end-to-end UI checks.
- The agent emits ``INI_SECTION_PLAYWRIGHTER`` with ``start_url``, ``final_url``, ``status``, ``steps_run``, ``assert_result``, and extracted values so downstream Forker or Parametrizer logic can branch on pass/fail or reuse scraped data.
- Two operator surfaces ship in lock-step: the wrapped Multi-Turn tool ``chat_agent_playwrighter`` takes the whole script as ``steps_json``, while the visual Playwrighter canvas node stores the same declarative step list in YAML.
- Session continuity is built in: ``headless: false`` lets operators watch it drive, and ``storage_state_in`` / ``storage_state_out`` carry login state across runs without forcing a manual browser setup each time.
- Because Playwrighter is state-changing, its executions appear in Exec Report and it always triggers ``target_agents`` whether the run succeeds or fails.

Reviewer precision patch in v1.4.1

- The ``v1.4.1`` Reviewer refinement tightened accuracy rather than adding a new surface: when ``diff_ref`` is empty, the review prompt labels the diff as the uncommitted working tree plus staged area, so the model must not describe those findings as already committed or pushed.
- The same patch teaches the model Tlmatini's managed-secret convention: ``agent/config.json`` and selected ``agent/agents/*/config.yaml`` files can hold live local credentials in a keyed working copy, while ``regen_secrets.py --mode push-able`` scrubs them back to placeholders before commit.
- That guidance is mirrored into the ``code-review`` SKILL.md package too, keeping the chat-surface review behavior and the canvas Reviewer agent aligned on commit-state wording and secret-severity expectations.

Native dialogs and Tkinter removal in v1.4.2

- The current tagged release ``v1.4.2`` removes Tkinter from the unstable runtime-facing dialog path and replaces it with ``Tlmatini/agent/native_dialogs.py``, a native Windows dialog bridge used by browser-triggered pickers.
- This change pairs with the existing DB and operator dialogs: file and folder selection still feels local and GUI-first, but the fragile Tkinter dependency is no longer part of the interactive runtime path that users trigger from chat or ACP surfaces.
- The patch arrived with dedicated tests (``test_native_dialogs.py``) and with follow-up orphan-reaper/runtime adjustments, so the release reads as a stability pass rather than a cosmetic refactor.

ACPX-Skills menu

- The new ``ACPX-Skills`` navbar menu gives operators four direct actions over the skill catalog: Browse Skills, Configure Skills, Diagnostics, and Reload Registry.
- ``Configure Skills`` flips ``Skill.enabled`` exactly the way MCPs and Tools are toggled, so disabled skills disappear from ``list_skills`` and reject ``invoke_skill`` with ``SKILL_DISABLED`` instead of silently half-working.
- The diagnostics view cross-checks skill dependencies against disabled tools, disabled MCPs, missing ACPX agents, and orphan database rows whose SKILL.md disappeared from disk.

Source-mode bootstrap commands

```
python -m venv venv
venv\Scripts\activate
pip install -r requirements.txt
python Tlamatini/manage.py migrate
python Tlamatini/manage.py createsuperuser
python Tlamatini/manage.py collectstatic --noinput
python Tlamatini/manage.py runserver --noreload
```


4. Ollama Setup Without Administrative Rights

- Open a normal PowerShell window, not an elevated one, for the safest no-admin Windows installation path.
- Install into `%LOCALAPPDATA%\Programs\Ollama` with the official PowerShell installer script and then reopen PowerShell so PATH updates are visible.
- Activate Ollama Pro or a higher plan such as Max for Tlamatini's complete intended functionality, then run `ollama signin` so the host is linked before using the shipped `:cloud` defaults. This requirement is not a sponsorship; verify current plan details directly with Ollama.
- Verify the CLI with `ollama --version`, start `ollama serve` if the background service is not already active, and confirm `http://127.0.0.1:11434/api/tags` responds.
- Pull the default repository model tags exactly as written if you want the shipped config and agent templates to work unchanged.
- The Book now clarifies the token rule: a localhost Ollama usually needs no Ollama bearer token in Tlamatini, while a remote Ollama endpoint may require one in `Config -> Access Keys Wizard` or the matching config key.

No-admin Ollama commands and default model pulls

```
$env:OLLAMA_INSTALL_DIR = "$env:LOCALAPPDATA\Programs\Ollama"
irm https://ollama.com/install.ps1 | iex
ollama --version
ollama signin
ollama serve
Invoke-WebRequest http://127.0.0.1:11434/api/tags -UseBasicParsing
ollama pull Nomic-Embed-Text:latest
ollama pull glm-5.2:cloud
ollama pull qwen3.5:cloud
ollama pull gpt-oss:120b-cloud
ollama pull qwen3.5:397b-cloud
ollama pull glm-5.1:cloud
```

5. Runtime, Release, and Operator Diagnostics

Running the application

- Development server: ``python Tlmatini/manage.py runserver`` — the ``--noreload`` flag is now OPTIONAL (plain ``runserver`` boots clean and auto-reloads since the 2026-07-11 ``agent/apps.py`` reloader-aware fix; it used to double-start the MCP helper ports :8765 / :50051 and crash with WinError 10048).
- Preferred async/dev bootstrap: ``python Tlmatini/manage.py startserver``, which starts MCP services before the Django server.
- Production-style ASGI entrypoint: ``daphne -b 127.0.0.1 -p 8000 tlmatini.asgi:application`` — this path bypasses ``manage.py``, so it does not read ``django_port`` and the port must be passed on the command line.
- Current startup also re-applies GPU-performance / Ollama-pinning hooks in the background on supported NVIDIA Windows hosts, so restart-time behavior stays closer to the tuned development baseline.
- That same early startup window is also where a staged ``DB/ToLoad/db.sqlite3`` file is promoted into the live database path, before Django opens SQLite.
- In frozen mode, startup now also self-heals the per-user Windows Installed-apps entry when ``Uninstaller.exe`` is present beside ``Tlmatini.exe``, so old installs can gain a standard uninstall surface without a reinstall.
- Startup now also prints a ``--- [VERSION] Tlmatini ...`` banner, making the running build visible in both the console and ``tlmatini.log`` without an HTTP call.
- Startup cleans pool state, repopulates the agent registry, launches MCP metrics/file-search servers, and then serves HTTP plus WebSocket traffic.

Embedding-memory pre-flight guard

- README and BookOfTlmatini now document an embedding-memory pre-flight guard for GPU hosts before a directory-context load starts its FAISS embedding burst.
- On supported NVIDIA hosts it estimates embedding-model VRAM pressure, and when the projected load is too high it emits a non-blocking warning chat bubble instead of silently letting RAM<->VRAM thrash surprise the operator.
- CPU-only, AMD, and Apple-Silicon hosts stay fail-open: the guard becomes a no-op when the NVIDIA probe does not apply.
- The practical operator response is straightforward: switch to a smaller embedding model, reconnect if needed, or proceed knowingly with the heavier model.

Reconnect and restart safeguards

- Config -> Models and Config -> URLs dialogs now track their pre-edit baseline and can show a reconnect-required dialog when the saved values change what the live chat session should trust.
- The restored-session autoload path now buffers early WebSocket frames so context-loading spinners and disabled-input state are not lost during automatic reconnect/restore flows.
- Startup and restart behavior now also re-apply GPU performance and Ollama keep-alive hooks in the background on supported NVIDIA Windows hosts, improving warm-model readiness without blocking Django boot.
- Browser-driven attention routing is now part of that operator-safety layer too: Ask Execs prompts and Notifier events can raise a taskbar flash plus a log banner without relying on the browser window already being visible.
- Windows process hygiene is now part of that safety story too: detached no-window spawns and the three-tier orphan reaper reduce the chance that Task Manager shows stale Tlmatini-icon console helpers after long runs.
- Ask Execs extends that safety story into execution approval itself: the operator can now stop a destructive chain before the next mutation instead of only auditing it after the fact in Exec Report.

Media and voice family

- The current media family spans capture, playback, and speech: Shoter (screen), Camcorder (camera-in), Recorder (mic-in), AudioPlayer (speakers-out), VideoPlayer (screen-out with audio), Talker (text-to-speech), and Whisperer (speech-to-text).

- Talker remains female-only by design and uses an Ollama neural TTS model with SNAC decoding, while Whisperer records the microphone itself or transcribes a file through faster-whisper locally or cloud Whisper APIs.
- Recent stability work matters here too: Talker now chunks long input by sentence for long-form speech, and media-output defaults were moved into the application `Temp` directory rather than user content folders.

Autonomous command watchdog

- A boot-time autonomous command watchdog now protects the chat against shell wrappers that stay alive while making zero CPU or I/O progress, the classic signature of a mangled prompt waiting forever on stdin.
- It never kills on elapsed time alone: the subtree must outlive the grace window and remain idle for a configured streak, so long builds, downloads, and compiles are preserved while only genuinely wedged interpreters are reaped.
- This watchdog complements rather than replaces the orphan reaper: the watchdog rescues blocked synchronous tool calls before they return, while the orphan reaper still handles post-return survivors and stale console companions.

Prompt catalog and answer readability discipline

- Version `1.3.2` tightened the HTML answer contract with a Prime Directive on visual readability: explicit background and text color, no grey-on-dark body text, and safer table-body defaults.
- The seeded `Prompts` dropdown was also re-sorted into a learner path: context-only Q&A first, then metrics, files search, shell, code generation, vision, specialized single-tool actions, agent control, Unreal, and heavier Multi-Turn/ACPX demos last.
- The `v1.35.0` prompt-search pass then makes that larger catalog easier to operate: prompt cards support substring, word-start, and fuzzy matching, with mode badges that keep one-shot, Multi-Turn, ACPX, Exec Report, and Step-by-Step demos visually distinct.
- Those readability rules remain in force in the `v1.50.4` release documentation set; it carries measured networking, WAL-safe database movement, structured and resilient Googler discovery, guided MCP onboarding, and current counts while retaining encoding-safe search, guarded execution truth, private MCP runtime/defaults, diagram hardening, LaTeXer, the binary guard, PDFer, FlowCreator, prompt standardization, category grouping, and ranked fuzzy search.

Ask Execs and execution approval

- Introduced in `v1.10.0` and still part of the current `v1.26.0` surface, `Ask Execs` is the Multi-Turn-only safety modifier that makes Tlamatini ask before each state-changing Tool, MCP, wrapped agent, or skill-backed execution instead of running it immediately.
- The permission dialog is explicit and auditable: it names the Tool or Agent family, the underlying raw tool name, the full parameters, the program or command to be executed, and the shell or execution surface involved.
- Proceed runs that one step and then prompts again at the next state-changing step; Deny halts the entire chain immediately and appends a red `Execution interrupted` banner even when Exec Report itself is off.
- Under the hood, `agent/exec\_permission.py` provides `ExecPermissionBroker`, which lets the synchronous worker-thread executor emit a permission request onto the WebSocket event loop and then block on a `threading.Event` until the browser replies.
- The gate sits after deduplication and quota checks, so skipped calls never prompt and denied calls never appear as executed rows; only work that truly ran lands in Exec Report.
- The round-trip is fail-safe: browser disconnect, emit failure, cancel, or broker shutdown all resolve to Deny, so an unconfirmed state-changing action never slips through just because the UI vanished at the wrong time.

Windows attention issuing

- The current Windows attention path is explicit and local: the browser calls `POST /agent/flash\_window/`, and the backend routes that request through `agent/window\_flash.py`.
- That helper can flash the `Tlamatini.exe` console/taskbar window with `FlashWindowEx` and always prints an uppercase attention banner, so the signal survives in `tlamatini.log` even when the browser is minimized.
- Two concrete reasons are wired today: Ask Execs execution approval prompts and Notifier notifications. The path is best-effort and fail-safe, degrading cleanly on non-Windows or windowless launches.

Unreal MCP runtime behavior

- Each Unreal run is one command: load `config.yaml`, open a fresh TCP socket, send `{"type": "command", "params": {"params": {}}}`, read until valid JSON arrives, and log one atomic `INI_SECTION_UNREALER<<< ... >>>END_SECTION_UNREALER` block.
- The wrapped-tool path stores chat runs under `agent/agents/pools/_chat_runs/_unrealer_<seq>_<id>/`, while visual flows use normal `unrealer_<n>` pool folders and can chain response fields through Parametrizer mappings.
- Exec Report treats Unreal as its own row family, and troubleshooting stays concrete: connection-refused means the plugin is not listening, while read-timeout usually means UE5's game thread is busy.

Orphan reaper runtime behavior

- Tlmatini now ships a three-tier orphan reaper in `Tlmatini/agent/orphan_reaper.py` focused on Windows console-host leftovers such as `conhost.exe` and `openconsole.exe`.
- Tier 1 runs after spawn-capable Multi-Turn tool calls, Tier 2 runs once after the final answer in a background thread, and Tier 3 runs again during application shutdown through the same cleanup path that already tears down pools.
- The candidate set stays narrow on purpose: dead descendants of the current process tree, orphaned console hosts tied to that tree, and pool-linked processes whose `cmdline` still points into `agents/pools/...` even though tracking records are gone.
- Prevention landed alongside cleanup: Windows spawn sites now use `CREATE_NO_WINDOW | DETACHED_PROCESS | CREATE_NEW_PROCESS_GROUP` with `stdio` piped to `DEVNULL`, so the console host is usually never allocated in the first place.
- The ACPX runtime now kills full process trees instead of only top-level wrappers, and pool-agent scripts gained a conservative `subprocess.Popen` guard so forgotten descendants still inherit `CREATE_NO_WINDOW`.
- If something survives both cleanup tiers, Tlmatini sends a second chat bubble listing each surviving `name + PID`; the reaper never raises into the user path because a cleanup crash would be worse than the leftovers it tried to remove.

Release pipeline

- Release production is a three-step pipeline: `build.py` -> `build_uninstaller.py` -> `build_installer.py`.
- The final distributable is the full versioned release folder `dist/Tlmatini_Release_v<version>/`, not a stray executable copied outside its payload.
- Use `build.py --self-modify` when you intentionally want a release that ships `TlmatiniSourceCode/` so she can inspect or modify herself at runtime.
- Current `build.py` treats `README.md` and `jd-cli/` as required post-build assets and fails hard if those payloads are missing.
- Bundled support scripts cover shortcut creation/removal, `.flw` association, the PowerShell launcher, Windows-specific installer ergonomics, and the per-user Installed-apps registration path.

Windows uninstall registration

- Introduced in `v1.11.0` and still carried by the current `v1.26.0` release, the frozen install now behaves like a real Windows application: `install.py` writes a per-user HKCU Add/Remove Programs entry so Tlmatini appears in Settings -> Apps -> Installed apps and in the legacy Programs and Features list.
- The entry carries `DisplayName`, `DisplayVersion`, `InstallLocation`, `DisplayIcon`, `UninstallString`, `QuietUninstallString`, `NoModify`, `NoRepair`, and best-effort `EstimatedSize`, all pointing at the bundled `Uninstaller.exe` without requiring administrator rights.
- The matching runtime self-heal in `agent/apps.py` calls `windows_app_registration.self_heal_for_frozen()` on every frozen launch, so installs created before this feature existed can appear in Windows' uninstall UI after the next normal app start.

Exec Report

- Exec Report is a Multi-Turn-only transparency layer that appends operation tables for every wrapped agent family, including observational and read-only agents; `_EXEC_REPORT_TOOLS` only refines grouping and style.

- Rows are recorded from the live tool-call stream rather than guessed from the LLM prose, so the report is the operational ground truth.
- Each row receives a deterministic SUCCESS/FAILURE verdict from the agent's structured self-report: completed diagnostics and intact work are green, while degraded, not-done, and agent-error statuses are red under the guarded five-class vocabulary.
- When Ask Execs is enabled, Exec Report and the red denial banner complement each other: already-executed steps still render as tables, while the denied step stays out of the tables and is surfaced only through the interruption banner.

ACPX and skills

- ACPX lets Tlmatini spawn external coding-agent CLIs such as Codex, Claude Code, Cursor, Gemini, Qwen, and others as managed child processes.
- It pairs those agents with markdown-driven `SKILL.md` packages, validated I/O contracts, permission gating, and append-only audit logs.
- Transport-aware drain rules and bounded event bodies reduce latency while protecting the LLM context budget during external-agent relays.
- The operator-facing references are `README.md` and `ACPX.md`, while the implementation lives under `agent/acpx/`, `agent/skills/`, and `agent/skills\_pkg/`.

Application log

- The built-in `tlmatini.log` file captures both stdout and stderr through a tee stream initialized in `manage.py` before Django starts.
- In source mode the log sits next to `manage.py`; in frozen mode it lives next to the executable.
- Immediate flush behavior makes the log the primary forensic artifact for startup problems, warnings, tracebacks, and runtime diagnostics.

6. Agent Catalog and Runtime Model

Tlmatini currently exposes 88 workflow-agent templates.

Category	Representative agents
Control	starter, ender, stopper, cleaner, barrier, flowbacker
Execution and files	executer, pythonxer, pser, file_creator, file_extractor, file_interpreter, de_compressor, playwrighter, windower, unrealer, kalier, stm32er, esp32er, esphomer, arduiner, mover, deleter
DevOps and infra	gitter, dockerer, kubernetes, jenkinser, ssher, scper
Data and APIs	sqler, mongoxer, apirer, crawler, googler
Monitoring and routing	monitor_log, monitor_netstat, flowhypervisor, forker, asker, counter, and, or
Communication	notifier, emailer, recmailer, telegrammer, teletlmatini, whatsapper
Security and media	kyber_keygen, kyber_cipher, kyber_decipher, image_interpreter, video_analyzer, shoter, camcorder, recorder, audioplayer, videoplayer, j_decompiler
Workflow intelligence	flowcreator, gatewayer, gateway_relayer, node_manager, parametrizer, prompter, summarizer, acpxer

All workflow agents follow a common deployment pattern: template directory, YAML configuration, session-scoped pool copy, PID/status/log files, target/source wiring, and optional reanimation state.

Agent catalog validation

- The authoritative human-readable source for workflow-agent descriptions is `agents\_descriptions.md` at the repo root, not an embedded JavaScript map or a hard-coded Django list.
- Current validation compares live template directories, `agents\_descriptions.md` rows, and the README / Book bestiary counts so the generated dossier stays aligned with the running product.
- The ACP sidebar hover tooltip and the right-click Description dialog both resolve through that markdown file first; `README.md` is only a legacy fallback when the dedicated description file is absent.

User jurisdiction over plain-Python agents

- Every agent in `Tlmatini/agent/agents/` is intentionally plain Python so the user can read, audit, edit, restrict, or disable its operating code. This transparency is a user-control mechanism, not a warranty that an agent is secure or suitable for a particular environment.
- Agents have no independent authority or jurisdiction. The user alone decides whether, where, how, and with which permissions an agent runs; enabling, configuring, modifying, chaining, or executing it places that execution under the user's control and jurisdiction.
- The user is responsible for code/config review, least-privilege secrets and credentials, authorized files and targets, browsers, shells, APIs, external MCPs, machines, hardware, downstream systems, supervision, and compliance with applicable law, policy, license, contract, and authorization.
- By running an agent, the user accepts responsibility for its actions and consequences. To the fullest extent permitted by applicable law, security breaches, data exposure or loss, unauthorized actions, credential leaks, unsafe automation, violations, compromise, device damage, financial loss, or other harm arising from use are the responsibility of the user who runs it.
- Tlmatini's orchestration, documentation, examples, and guardrails do not authorize third-party access and cannot replace the user's security review, permission controls, monitoring, or legal compliance.

How agent runtimes are shaped

- Every workflow agent follows the same operational skeleton: template directory, `config.yaml`, a session-scoped pool copy, PID/status/log files, and explicit source/target wiring.
- Chat-wrapped tool calls launch isolated runtime copies under `agent/agents/pools/\_chat\_runs\_`, while ACP uses named pool folders such as `starter\_1` or `unrealer\_1`.

- Specialized agents now stretch the platform in different directions: Globber/Grepper/Editor cover deterministic file discovery, regex search, and surgical in-place edits; Video-Analyzer closes hardware-in-the-loop video verdicts; MCP Doctor performs safe external-MCP onboarding diagnosis; ACPXer drives external coding-agent CLIs; Kalier drives a remote or tunneled Kali Linux tool server; Nmapper drives local use-only nmap scans for authorized targets; STM32er drives a zero-config STM32 firmware MCP bridge; ESP32er drives PlatformIO directly; ESPHomer drives ESPHome directly for YAML-authored smart-home devices; Blenderer drives a live Blender editor over the official MCP add-on socket; Unrealr drives a live UE5 editor; TeleTlmatini bridges full Tlmatini conversations into Telegram; Telegrammer uses official Telegram surfaces; Whatsapper defaults to Meta's official business Cloud API but can explicitly use an unofficial personal-account Web route; and Instant Messaging Doctor diagnoses the official messaging credentials and policy without silently switching providers.

MCP Doctor spotlight

- MCP Doctor is the new onboarding and triage specialist added with the External MCP release: she inspects a configured server entry and tells the operator what is wrong before a live connection attempt wastes time.
- The diagnostic checks cover transport shape, runtime command availability on PATH, placeholder or missing secrets, endpoint/source/docs links, and the concrete next step the operator should take to make the server connectable.
- Operators can reach the same behavior from both surfaces that matter: the MCP Doctor workflow agent on the canvas and the wrapped ``chat_agent_mcp_doctor`` tool inside Multi-Turn.

Blenderer spotlight

- Blenderer was introduced in ``v1.20.0`` as the 77th workflow agent and remains the direct bridge to the official Blender MCP add-on, letting Tlmatini operate a live Blender session from either Multi-Turn chat or the visual workflow canvas.
- The bridge talks over a TCP socket (default ``localhost:9876``) and supports both raw ``execute_code`` requests and higher-level scene/object/material/render actions, so operators can mix deterministic verbs with precise Python-driven 3D automation.
- This extends Tlmatini beyond code and firmware orchestration into DCC / 3D-production work: asset inspection, scene mutation, material changes, camera setup, and render-triggering now live inside the same operator surface as the rest of the system.

Self-update spotlight

- The packaged application now includes an in-app self-update flow exposed from About -> Check for updates, so operators can refresh a frozen install without manually unpacking and replacing the entire release folder.
- The backend checks the latest GitHub release, downloads and stages the package, then hands off the locked-file swap to ``apply_update.ps1``, which performs the replacement after the running executable exits and relaunches the updated app.
- The update path is state-preserving by design: it keeps ``config.json``, user content, and one ``agents_backup`` generation, and it stages the user's database through ``DB/ToLoad/`` plus ``post_update_migrate.flag`` so the next launch restores and migrates that DB instead of wiping it.

Reviewer and Analyzer spotlight

- The workflow catalog now includes two new high-value specialists: Reviewer and Analyzer, lifting the canvas inventory to 64 agents and the seed-skill catalog to 23 SKILL.md packages.
- Reviewer is LLM-powered: it resolves a git diff for ``repo_path``, reviews it with a senior-engineer prompt, and emits an ``INI_SECTION_REVIEWER`` block whose first routable field is ``verdict = APPROVE | REQUEST_CHANGES | COMMENT``.
- Analyzer is deterministic and scanner-driven: it runs whichever of ``bandit``, ``semgrep``, ``ruff``, ``eslint``, ``gitleaks``, and ``pip-audit`` are installed on PATH over ``target_path``, then emits an ``INI_SECTION_ANALYZER`` block with ``status`` and ``total_findings`` for downstream routing.
- Both agents always trigger ``target_agents``, so a downstream Forker can branch on ``{verdict}``, ``{status}``, or ``{total_findings}`` instead of scraping prose.
- They are intentionally canvas-only workflow agents: there is no wrapped ``chat_agent_reviewer`` or ``chat_agent_analyzer``, and therefore no duplicate Exec Report row family for those names.

- The chat-side counterparts live in the ACPX skill catalog instead: ``code-review`` exposes senior-engineer git-diff review, while ``security-audit`` exposes the deterministic multi-scanner sweep.

Operator surface counts

- The live operator surface now stands at 88 workflow agents, 108 Multi-Turn tools, 12 ACPX tools, and 29 skills.
- Source inspection confirms the total: 20 core Python tools + 66 wrapped chat-agent tools + 12 ACPX/Skill tools + 10 External-MCP supervisors = 108 built-in Multi-Turn tools; healthy active servers add dynamic ``ext__*`` remotes separately.
- The count growth over older public badges comes from stacked waves: the deterministic file trio, ESPHomer, MCP Doctor, Zavuerer, Video-Analyzer, Nmapper, NetSpeed-Calculator, and the ``adding-external-mcp`` skill.
- The workflow-agent and wrapped-tool totals are validated from the live tree even when some handbook badges or older prose lines lag behind the newest release wave, so the dossier stays tied to source truth instead of stale summaries.
- This matters operationally because the planner never binds everything at once: the documented default ``max_selected_tools`` cap stays at 20, so breadth of capability does not mean uncontrolled tool sprawl per turn.

Kalier spotlight

- Kalier is Tlamatini's current Kali Linux bridge: a direct client for MCP-Kali-Server that lets her drive authorized recon, enumeration, web scanning, and offensive-security workflows from chat or canvas.
- It can issue one capability per run, including ``nmap``, ``gobuster``, ``dirb``, ``nikto``, ``sqlmap``, ``metasploit``, ``hydra``, ``john``, ``wpscan``, ``enum4linux``, arbitrary ``command``, or a safe ``health`` probe of the remote server.
- The agent emits ``INI_SECTION_KALIER`` with ``action``, ``endpoint``, ``subject``, ``return_code``, ``success``, ``timed_out``, and ``server_url``, so downstream Forker or Parametrizer logic can branch on results without scraping prose.
- The practical operator result is simpler prompts: after the Kali box URL is configured once, normal Multi-Turn requests no longer repeat ``server_url`` unless you intentionally override it for a one-off target.
- Two operator surfaces ship in lock-step: the wrapped Multi-Turn tool ``chat_agent_kalier`` now auto-injects the configured ``kali_server_url``, while the visual Kalier canvas node still stores ``server_url`` explicitly in YAML per node.
- Kalier talks straight to the Kali-side Flask API over HTTP using Python-stdlib ``urllib``, so it stays self-contained in the pool subprocess and works the same in source or frozen builds; the embedded-client injection fails open if the config value is blank or unreadable.
- Authorized use only: the intended operator flow is an in-scope lab, CTF, or permitted engagement, often with ``ssh -L 5000:localhost:5000 user@KALI_IP`` tunneling a remote Kali box back to ``http://127.0.0.1:5000``, and the repo now includes ``Tlamatini-Kali-Setup.md`` for the zero-client walkthrough.

STM32er spotlight

- STM32er is Tlamatini's critical-mission STM32 bridge. The established route talks to the ``STM32 Template Project MCP`` for STM32F407, while released ``v1.42.0`` adds a direct PlatformIO route for supported mainstream STM32 boards without removing that flow.
- Both backends keep zero-config intent: the template route bootstraps its MCP dependencies, and the new route resolves or installs PlatformIO Core in the same shared per-user location used by ESP32er.
- Backend-specific preflight preserves target safety: compile-only work may proceed without attached hardware, but upload, reset, serial, and live operations are refused when the required toolchain, project, board mapping, programmer, or ST-LINK evidence is missing.
- Two operator surfaces ship in lock-step: the wrapped Multi-Turn tool ``chat_agent_stm32er`` takes one ``action`` per call, while the visual STM32er canvas node stores the same fields in YAML and triggers downstream agents on both success and failure.
- The tool surface retains the 23 MCP verbs and locally adds PlatformIO environment, board, project, source, build, flash, monitor, package, QA, artifact, and safe scaffold composites; every run still emits one ``INI_SECTION_STM32ER`` block for routing.
- Config seeding supplies both MCP and PlatformIO defaults, while ``stm32_backend=auto``, ``board``, and ``device`` keep the normal prompt focused on firmware intent. Newest-silicon CubeCLT/N6 handling remains proposal-only and is not advertised as implemented.

Windower spotlight

- Windower is the new 66th workflow agent: a deterministic Win32 window manager that finds an application window by title and performs one lifecycle operation on the window itself instead of clicking inside it.
- It supports ``focus``, ``minimize``, ``maximize``, ``restore``, ``move``, ``resize``, ``move_resize``, ``close``, ``topmost``, ``untopmost``, ``arrange``, and ``list``, with ``substring``, ``exact``, or ``regex`` title matching plus ``match_index`` for duplicate titles.
- The agent emits ``INI_SECTION_WINDOWER`` with ``action``, ``window_title``, ``matched``, ``match_count``, ``state``, ``left``, ``top``, ``width``, and ``height``, so downstream Forker or Parametrizer logic can branch on presence, state, or geometry.
- Two operator surfaces ship in lock-step: the wrapped Multi-Turn tool ``chat_agent_windower`` accepts free-form key=value requests, while the visual Windower canvas node stores the same operation fields in YAML.
- Windower is the desktop-window sibling of Mouser and Keyboarder: use Windower when the goal is the window as a whole, Mouser for controls inside it, and Keyboarder for text entry into it.
- Because Windower changes real window state, its executions appear in Exec Report and it always triggers ``target_agents`` whether the action succeeds or fails.

Playwrighter spotlight

- Playwrighter is the new 65th workflow agent in ``v1.5.0``: a deterministic Playwright-powered browser automator for Chromium, Firefox, or WebKit that executes ordered interactive steps instead of static fetches.
- It covers the gap between Crawler and Googler: logins, multi-step forms, wizard clicks, JS-rendered SPA scraping, screenshots after interaction, assertions, downloads, and authenticated end-to-end UI checks.
- The agent emits ``INI_SECTION_PLAYWRIGHTER`` with ``start_url``, ``final_url``, ``status``, ``steps_run``, ``assert_result``, and extracted values so downstream Forker or Parametrizer logic can branch on pass/fail or reuse scraped data.
- Two operator surfaces ship in lock-step: the wrapped Multi-Turn tool ``chat_agent_playwrighter`` takes the whole script as ``steps_json``, while the visual Playwrighter canvas node stores the same declarative step list in YAML.
- Session continuity is built in: ``headless: false`` lets operators watch it drive, and ``storage_state_in`` / ``storage_state_out`` carry login state across runs without forcing a manual browser setup each time.
- Because Playwrighter is state-changing, its executions appear in Exec Report and it always triggers ``target_agents`` whether the run succeeds or fails.

Reviewer precision spotlight

- The ``v1.4.1`` Reviewer refinement tightened accuracy rather than adding a new surface: when ``diff_ref`` is empty, the review prompt labels the diff as the uncommitted working tree plus staged area, so the model must not describe those findings as already committed or pushed.
- The same patch teaches the model Tlmatini's managed-secret convention: ``agent/config.json`` and selected ``agent/agents/*/config.yaml`` files can hold live local credentials in a keyed working copy, while ``regen_secrets.py --mode push-able`` scrubs them back to placeholders before commit.
- That guidance is mirrored into the ``code-review`` SKILL.md package too, keeping the chat-surface review behavior and the canvas Reviewer agent aligned on commit-state wording and secret-severity expectations.

Native-dialog spotlight

- The current tagged release ``v1.4.2`` removes Tkinter from the unstable runtime-facing dialog path and replaces it with ``Tlmatini/agent/native_dialogs.py``, a native Windows dialog bridge used by browser-triggered pickers.
- This change pairs with the existing DB and operator dialogs: file and folder selection still feels local and GUI-first, but the fragile Tkinter dependency is no longer part of the interactive runtime path that users trigger from chat or ACP surfaces.
- The patch arrived with dedicated tests (``test_native_dialogs.py``) and with follow-up orphan-reaper/runtime adjustments, so the release reads as a stability pass rather than a cosmetic refactor.

Unrealer spotlight

- Unreal MCP is a UE5 plugin that runs inside the editor and listens on ``127.0.0.1:55557`` for one JSON command per TCP connection; Tlmatini is the client side of that link, not the plugin host.

- The Unreal workflow agent forwards any command the connected plugin build exposes, up to a 53-command surface across nine categories: actor manipulation (incl. viewport screenshots), Blueprint authoring and node wiring, input mappings, UMG widget building, in-editor Python/console execution, level I/O, asset import, and material authoring. Headless build/cook/test is out of scope (it needs UnrealEditor-Cmd, not the editor socket).
- The same integration is available in both operator surfaces: checked Multi-Turn via ``chat_agent_unrealer``, and ACP canvas flows via the visual Unreal node plus Parametrizer chaining.
- Each Unreal run is one command: load ``config.yaml``, open a fresh TCP socket, send ``{"type": "command", "params": { "params" }}`, read until valid JSON arrives, and log one atomic ``INI_SECTION_UNREALER<<< ... >>>END_SECTION_UNREALER`` block.
- The wrapped-tool path stores chat runs under ``agent/agents/pools/_chat_runs/_unrealer_<seq>_<id>/``, while visual flows use normal ``unrealer_<n>`` pool folders and can chain response fields through Parametrizer mappings.
- Exec Report treats Unreal as its own row family, and troubleshooting stays concrete: connection-refused means the plugin is not listening, while read-timeout usually means UE5's game thread is busy.

De-Compressor spotlight

- De-Compressor is the deterministic archive worker for compression and decompression tasks, deciding direction from whichever side exposes a recognized archive extension.
- Supported archive families are ``.gz``, ``.zip``, ``.7z``, ``.tar.gz``, and ``.gz.tar``; file-to-folder extraction and file-or-directory packing are both documented in the README and Book.
- Password handling is explicit: ``passwordless=true`` skips it, while ``passwordless=false`` requires the ``DE_COMPRESSER_PWD`` environment variable and fails fast if the secret is missing.
- The agent is reachable from both operator surfaces: ACP canvas nodes wire through dedicated connection-update views, and checked Multi-Turn can invoke it through ``chat_agent_de_compressor``.
- Format engines are practical rather than magical: `stdlib`gzip`` and ``zipfile`` cover core cases, ``.7z`` is preferred for encrypted ``.7z`` or ``.zip``, and ``py7zr`` was added to ``requirements.txt`` as the Python fallback.
- Every run emits an ``INI_SECTION_DE_COMPRESSER<<< ... >>>END_SECTION_DE_COMPRESSER`` block and still triggers ``target_agents``, so downstream Parametrizer or Raiser logic can branch on ``success=true|false`` instead of guessing from prose.

Orphan-reaper spotlight

- Tlmatini now ships a three-tier orphan reaper in ``Tlmatini/agent/orphan_reaper.py`` focused on Windows console-host leftovers such as ``conhost.exe`` and ``openconsole.exe``.
- Tier 1 runs after spawn-capable Multi-Turn tool calls, Tier 2 runs once after the final answer in a background thread, and Tier 3 runs again during application shutdown through the same cleanup path that already tears down pools.
- The candidate set stays narrow on purpose: dead descendants of the current process tree, orphaned console hosts tied to that tree, and pool-linked processes whose ``cmdline`` still points into ``agents/pools/...`` even though tracking records are gone.

7. Repository Facts and Git Changes

Metric	Value
Repository inventory files	1030
Tracked files in git	1030
Git-unignored working-tree additions	0
Workflow agents	88
Multi-Turn tools	108
Wrapped chat-agent tools	66
Skills	29
agents_descriptions.md rows	88
Django migrations	197
Frontend JavaScript modules	37
Frontend CSS files	11
HTML templates	4
Python requirements	80
Binary/asset inventory files skipped from line count	50
Resolved version	1.50.4
Version source	git

Latest commits

Date	Commit	Subject
2026-08-29	64b29725	Trying to fix the starting runtime error at installed Tlamatini, by angelahack1
2026-08-28	e0450327	Googler improvement phase 1 under paired Tlamatinis staging, by Tlamatini's-AutoBot.
2026-08-28	a329e6dd	Updating visual documentation, bby angelahack1
2026-08-27	7abc751b	Tlamatini/Tlamatini-Spanish piring, by Tlamatini's-AutoBot.
2026-08-26	fc6a533e	Fixing Glitches found on Tlamatini (english) by Tlamatini-Spanish's Claude, by angelahack1
2026-08-25	cf14c6ac	Bumping visual documentation to v1.50.0, and sweep robust/enhancement of security Talatini Blue-Hat asistant, by Tlamatini's-AutoBot.
2026-08-25	d161098e	Bumping everything to v1.50.0, by Tlamatini's-AutoBot.
2026-08-25	834eaa16	Tlamatini has completelly implemented her security harnessing mechanics into her, by angelahack1
2026-08-24	ae6fec4c	Tlamatini implements her security harnessing mechanics into her, by angelahack1
2026-08-23	6b0054a1	Bumped version to 1.49.1, by angelahack1

Changes since the last committed PDF/PPTX refresh

Last committed visual-dossier refresh: 64b29725 on 2026-08-29 — Trying to fix the starting runtime error at installed Tlamatini, by angelahack1

- Since the last committed PDF/PPTX refresh, Git shows focused platform evolution across autonomy, operator ergonomics, runtime self-knowledge, and documentation fidelity.

Git changes from the last 3 days

- The current annotated release and aligned local/remote HEAD both resolve to `v1.50.4` at `64b29725`. Runtime versions remain Git/build-derived through `agent/version.py`, while generated inventories derive agent, tool, skill, asset, migration, and effective-line totals from live source.

- The release root-fixes installed-runtime startup noise and latency: frozen Django builds exclude optional `transformers` so its guarded token-counter fallback cannot import the unused Torch stack, while carried Python keeps Torch for Talker. Runtime and tests now import tools from `langchain\_core.tools`, and source-derived guards prohibit warning muting, accidental ML imports, or an unsafe upstream contract change.
- The tagged `v1.26.0` release now includes ESPHomer as a fourth firmware lane, bridging Tlamatini to ESPHome so she can author YAML device configs, validate, compile, upload, and observe smart-home firmware from chat or canvas.
- The latest dossier pass resolves the product at annotated release `v1.50.4` (`64b29725`), confirms aligned local/remote HEAD at the same commit, and combines README.md and BookOfTlamatini.md with source/Git truth while retaining complete installation, Ollama, architecture, usage, tree, line inventory, and responsibility context.
- Documentation itself changed during the recent window, so the regenerated dossier is part of the tracked operator surface rather than an external afterthought.

3-day commit appendix 1 of 1

Date	Commit	Subject
2026-08-29	64b29725	Trying to fix the starting runtime error at installed Tlamatini, by angelahack1
2026-08-28	e0450327	Googler improvement phase 1 under paired Tlamatinis staging, by Tlamatini's-AutoBot.
2026-08-28	a329e6dd	Updating visual documentation, bby angelahack1
2026-08-27	7abc751b	Tlamatini/Tlamatini-Spanish piring, by Tlamatini's-AutoBot.
2026-08-26	fc6a533e	Fixing Glitches found on Tlamatini (english) by Tlamatini-Spanish's Claude, by angelahack1

8. Effective Line Inventory by Language

Methodology: git-tracked text files plus git-unignored working-tree additions. Blank lines and comment-only lines are excluded. Python counts also remove module, class, and function docstrings detected through AST parsing.

Language	Files	Effective lines	Total lines	Share
Python	597	162,114	237,104	71.7%
Markdown	178	25,238	33,411	11.2%
JavaScript	37	18,112	23,672	8.0%
CSS	11	6,570	8,700	2.9%
Other text	20	4,742	5,560	2.1%
YAML	93	2,138	5,607	0.9%
PowerShell	10	1,692	2,318	0.7%
Prompt template	2	1,173	1,301	0.5%
Text	7	1,142	1,454	0.5%
HTML	4	1,123	1,169	0.5%
Tlmatini Flow	4	837	837	0.4%
JSON	10	608	608	0.3%
JavaScript module	2	457	562	0.2%
Batch	4	264	380	0.1%
Protocol Buffers	1	20	33	0.0%

Total effective lines: 226,230

9. Largest Effective Source Files

Path	Language	Effective	Total
Tlmatini/agent/views.py	Python	8,660	12,657
Tlmatini/agent/tests.py	Python	5,700	7,452
Tlmatini/agent/doc_generation/complete_project_docs.py	Python	3,993	4,437
Tlmatini/agent/tools.py	Python	3,214	4,858
Tlmatini/agent/agents/latexer/latexer.py	Python	3,151	4,593
BookOfTlmatini.md	Markdown	2,728	3,887
Tlmatini/agent/agents/flowcreator/agentic_skill.md	Markdown	2,378	2,620
Tlmatini/agent/static/agent/css/agentic_control_panel.css	CSS	2,084	2,905
Tlmatini/agent/external_mcp_manager.py	Python	2,066	2,604
Tlmatini/agent/agents/stm32er/stm32er.py	Python	1,983	2,694
Tlmatini/agent/chat_agent_registry.py	Python	1,967	2,018
Tlmatini/agent/static/agent/css/agent_page.css	CSS	1,878	2,426
Tlmatini/agent/static/agent/js/agent_page_chat.js	JavaScript	1,775	2,446
Tlmatini/agent/mcp_agent.py	Python	1,655	2,758
Tlmatini/agent/static/agent/js/acp-agent-connectors.js	JavaScript	1,577	1,755
Tlmatini/agent/static/agent/js/agent_page_init.js	JavaScript	1,468	1,747
docs/claude/recent-fixes.md	Markdown	1,458	2,029
Tlmatini/agent/consumers.py	Python	1,407	1,879
Tlmatini/agent/static/agent/js/acp-canvas-core.js	JavaScript	1,400	1,722
Tlmatini/agent/agents/netspeed_calculator/netspeed_calculator.py	Python	1,399	1,872
Tlmatini/agent/test_stm32er_agent.py	Python	1,238	1,772
build.py	Python	1,219	1,986
Tlmatini/agent/agents/crawler/crawler.py	Python	1,102	1,570
Tlmatini/agent/test_latexer_suite.py	Python	1,068	1,645
Tlmatini/agent/agents/arduiner/arduiner.py	Python	1,062	1,487

10. Complete Repository File Tree (Repository Appendix)

Tree appendix 1 of 17

```
Tlamatini/
|-- .gitignore
|-- .mcp.json
|-- 10000xRedesignOfUpdatingMechanicsOnTlamatini.md
|-- _acpx_pipeline_demo_report.md
|-- ACPX.md
|-- agents_descriptions.md
|-- apply_update.ps1
|-- audit_dependencies.py
|-- backup_db.py
|-- BookOfTlamatini.md
|-- build.py
|-- build_all.cmd
|-- build_complete_private_release.py
|-- build_complete_public_release.py
|-- build_installer.py
|-- build_uninstaller.py
|-- check_private_data.py
|-- Claude-Desktop-KALI-MCP-Session.md
|-- CLAUDE.md
|-- copy_source_assets.py
|-- CreateShortcut.json
|-- CreateShortcut.ps1
|-- DesignOfIncludingMemoryMCPS.txt
|-- Discoverier-new-agent.md
|-- eslint.config.mjs
|-- example_of_prompt_to_make_de-compressor_agent.txt
|-- FirstFinalPlanToSpeedUp.md
|-- freeingport8000.ps1
|-- GEMINI.md
|-- git_deny_go.py
|-- image_copy.png
|-- image.png
|-- install.py
|-- KIMI.md
|-- LICENSE
|-- MCPMemoriesFlowCreation.flw
|-- MessagingConnectorAssistant_Design.md
|-- OllamaPricing.png
|-- OOB_shift_reaper-and-NAMU-Design.pdf
|-- package.json
|-- PIVOT_CHANGES.md
|-- pnpm-lock.yaml
|-- preserved_user_state.json
|-- README.md
|-- regen_secrets.py
|-- register_flw.ps1
|-- RemoveShortcut.ps1
|-- requirements.txt
|-- surgical_improving_speed_of_Tlamatini_by_a_factor_of_3X.md
|-- test_author_banner.py
|-- test_check_private_data.py
|-- test_perf_3x_visual.py
|-- test_private_data_guard.py
|-- Tlamatini-Kali-Setup.md
|-- Tlamatini.ico
|-- Tlamatini.jpg
|-- Tlamatini.ps1
|-- tlamatini_acpx.py
|-- tlamatini_app_summary.pdf
|-- Tlamatini_eXtended_Artificial_Intelligence_Humanly_Tempered.pptx
|-- TLAMATINI_MCP.md
|-- tlamatini_mcp_server.py
|-- TlamatiniJudgementDay.md
|-- uncommit-keys.bat
|-- uninstall.py
|-- unregister_flw.ps1
|-- VERSIONING.md
|-- versioning.py
|-- .claude/
|   |-- settings.json
|   |-- hooks/
|   |   |-- announce_skills.py
|   |   |-- test_announce_skills.py
|   |-- memory/
|       |-- feedback_agent_naming_conventions.md
```

Tree appendix 2 of 17

```
-- feedback_cont_overbuild_exec_safety.md
-- feedback_hard_real_scenario_tests.md
-- feedback_main_branch_only.md
-- feedback_package_json_version_bump.md
-- feedback_run_tlamatini_agents_visible.md
-- feedback_state_constraints_upfront.md
-- feedback_track_changes_pivot_file.md
-- feedback_update_agent_docs.md
-- feedback_user_owns_git.md
-- MEMORY.md
-- project_acpx_oneshot_prompt.md
-- project_acpx_skills_menu.md
-- project_acpx_toggle_skills.md
-- project_acpxer_added.md
-- project_agent_table_wiped_on_boot.md
-- project_arduino_agent.md
-- project_ask_execs_feature.md
-- project_audioplayer_agent.md
-- project_build_concurrency_guard.md
-- project_build_tests_and_installer_enterkey.md
-- project_camcorder_agent.md
-- project_carried_python_for_agents.md
-- project_conjunction_parser_fix.md
-- project_daily_chat_test_skill.md
-- project_desktop_ui_lifecycle.md
-- project_director_virtuoso_demo_prompts.md
-- project_doc_refresh_2026_05_06.md
-- project_doc_refresh_2026_05_08.md
-- project_doc_refresh_2026_05_09.md
-- project_eight_fixes_2026_05_07.md
-- project_emailer_recmailoner_oneshot.md
-- project_embedding_memory_guard.md
-- project_esp32er_agent.md
-- project_execute_command_bounded_fix.md
-- project_execute_file_foreground_fix.md
-- project_external_exec_safety_layer.md
-- project_flow_compiler_dialog_wins.md
-- project_ghost_distinfo_dependency_audit.md
-- project_kalier_agent.md
-- project_keyboarder_wrapped_2026_05_07.md
-- project_latexer_agent.md
-- project_living_canvas_dropped.md
-- project_mouser_wrapped_2026_05_07.md
-- project_native_picker_tcltk_fix.md
-- project_native_toast.md
-- project_netspeed_calculator_agent.md
-- project_numpy_pyinstaller.md
-- project_ollama_source_build_breaks_embeddings.md
-- project_pdfer_agent.md
-- project_planner_followup.md
-- project_playwrighter_agent.md
-- project_playwrighter_hold_open.md
-- project_prompt_catalog_mode_badges.md
-- project_pythonxer_forkbomb_fix.md
-- project_pythonxer_strict_ruff_gate.md
-- project_quote_apostrophe_fix_2026_05_07.md
-- project_reaper_console_window_fix.md
-- project_recorder_agent.md
-- project_reviewer_analyzer_agents.md
-- project_reviewer_analyzer_demo_prompts.md
-- project_reviewer_committed_secrets_falsepos.md
-- project_secret_leak_recovery.md
-- project_stm32er_agent.md
-- project_stm32er_bootstrap_preflight.md
-- project_stm32er_demo_prompts.md
-- project_stm32er_docs_libs_parametrizer.md
-- project_stm32er_hil_serial_proof_fix.md
-- project_stm32er_tests.md
-- project_summarizer_oneshot_mode.md
-- project_taskbar_flash_attention.md
-- project_teletlamatini_acpx.md
-- project_temp_templates_policy.md
-- project_unity_mcp_declined.md
-- project_unrealer_expanded_surface.md
-- project_versioning_2026_05_15.md
-- project_videooplayer_agent.md
```

Tree appendix 3 of 17

```
| | | |-- project_windower_agent.md
| | | |-- user_profile.md
| | |-- skills/
| | | |-- tlamatini-agent-creation/
| | | | |-- SKILL.md
| | | |-- tlamatini-agent-naming/
| | | | |-- SKILL.md
| | | |-- tlamatini-daily-chat-test/
| | | | |-- .gitignore
| | | | |-- SKILL.md
| | | | |-- harness/
| | | | | |-- acp_backend_banner_test.py
| | | | | |-- acp_backend_banner_test.py.antes_shoter
| | | | | |-- acp_dialog_full_sweep.py
| | | | | |-- acp_dialog_theme_visible.py
| | | | | |-- ask_execs_regression.py
| | | | | |-- ask_execs_regression.py.antes_shoter
| | | | | |-- bulk_toggle_behaviour.py
| | | | | |-- bulk_toggle_visible.py
| | | | | |-- cancel_regression.py
| | | | | |-- cancel_regression.py.antes_shoter
| | | | | |-- config.py
| | | | | |-- cyber_watchdog_test.py
| | | | | |-- dialog_policy_visible.py
| | | | | |-- dialog_theme_visible.py
| | | | | |-- discoverer_1000.py
| | | | | |-- discoverer_1000.py.antes_shoter
| | | | | |-- flowcreator_wizard_e2e.py
| | | | | |-- googler_dork_hunt.py
| | | | | |-- latexer_openmp_e2e.py
| | | | | |-- latexer_stepbystep_5.py
| | | | | |-- mcp_playwright_suite.py
| | | | | |-- playwright_run.py
| | | | | |-- qualify.py
| | | | | |-- questions.py
| | | | | |-- README.md
| | | | | |-- requirements.txt
| | | | | |-- run_test.py
| | | | | |-- shoter_shot.py
| | | | | |-- step_by_step_catalog.py
| | | | | |-- step_by_step_catalog.py.antes_shoter
| | | | | |-- talk_test.py
| | | | | |-- wrapped_questions.py
| | | |-- tlamatini-self-modify-inclusion/
| | | | |-- SKILL.md
| | | | |-- scripts/
| | | | | |-- sweep_self_modify.py
| | | |-- tlamatini-self-update-inclusion/
| | | | |-- SKILL.md
| | | | |-- scripts/
| | | | | |-- sweep_self_update.py
|-- .codex/
| |-- skills/
| | |-- full-project-pdf-dossier/
| | | |-- SKILL.md
| | |-- overlap-safe-pptx-dossier/
| | | |-- SKILL.md
|-- .gemini/
| |-- skills/
| | |-- tlamatini-agent-creation/
| | | |-- SKILL.md
| | |-- tlamatini-agent-naming/
| | | |-- SKILL.md
| | |-- tlamatini-daily-chat-test/
| | | |-- .gitignore
| | | |-- SKILL.md
| | | |-- harness/
| | | | |-- acp_backend_banner_test.py
| | | | |-- acp_backend_banner_test.py.antes_shoter
| | | | |-- acp_dialog_full_sweep.py
| | | | |-- acp_dialog_theme_visible.py
| | | | |-- ask_execs_regression.py
| | | | |-- ask_execs_regression.py.antes_shoter
| | | | |-- bulk_toggle_behaviour.py
| | | | |-- bulk_toggle_visible.py
| | | | |-- cancel_regression.py
```

Tree appendix 4 of 17

```
|
|
|   |-- cancel_regression.py.antes_shoter
|   |-- config.py
|   |-- cyber_watchdog_test.py
|   |-- dialog_policy_visible.py
|   |-- dialog_theme_visible.py
|   |-- discoverer_1000.py
|   |-- discoverer_1000.py.antes_shoter
|   |-- flowcreator_wizard_e2e.py
|   |-- googler_dork_hunt.py
|   |-- latexer_openmp_e2e.py
|   |-- latexer_stepbystep_5.py
|   |-- mcp_playwright_suite.py
|   |-- playwrighter_run.py
|   |-- qualify.py
|   |-- questions.py
|   |-- README.md
|   |-- requirements.txt
|   |-- run_test.py
|   |-- shooter_shot.py
|   |-- step_by_step_catalog.py
|   |-- step_by_step_catalog.py.antes_shoter
|   |-- talk_test.py
|   |-- wrapped_questions.py
|   |-- tlamatini-self-modify-inclusion/
|   |   |-- SKILL.md
|   |   |-- scripts/
|   |   |   |-- sweep_self_modify.py
|   |-- tlamatini-self-update-inclusion/
|   |   |-- SKILL.md
|   |   |-- scripts/
|   |   |   |-- sweep_self_update.py
|
|-- .github/
|   |-- workflows/
|   |   |-- name-guard.yml
|
|-- .scanning/
|   |-- finding-policy.json
|
|-- AuxTests/
|   |-- mypdf2.py
|
|-- demo_flows/
|   |-- demo1_globber_to_parametrizer_to_zavuerer.flw
|   |-- demo2_apirer_to_parametrizer_to_zavuerer.flw
|   |-- demo3_zavuerer_health_to_parametrizer_to_filecreator.flw
|
|-- docs/
|   |-- companion-app-discovery.md
|   |-- external_mcp_bulletproof_architecture.md
|   |-- stm32er_all_families_proposal.md
|   |-- claude/
|   |   |-- acpx.md
|   |   |-- agents.md
|   |   |-- architecture.md
|   |   |-- exec-report.md
|   |   |-- frontend.md
|   |   |-- gotchas.md
|   |   |-- INDEX.md
|   |   |-- mcp-tools.md
|   |   |-- multi-turn.md
|   |   |-- recent-fixes.md
|
|-- pyinstaller_hooks/
|   |-- hook-numpy.py
|   |-- hook-torch.py
|
|-- scripts/
|   |-- check_js_parse.mjs
|
|-- security/
|   |-- automated_tests_of_security_assets.py
|   |-- enable_tlamatini_v2.bat
|   |-- README.md
|   |-- run_defender.bat
|   |-- tlamatini_defender.ps1
|   |-- tlamatini_whitelist_v2.ps1
|
|-- Tests/
|   |-- test_about_window_name_visible.py
|   |-- test_perf_3x_visual.py
|
|-- Tlamatini/
|   |-- cat_art.py
|   |-- hoy
|   |-- manage.py
```


Tree appendix 5 of 17

```
|-- .agents/
|   |-- workflows/
|   |   |-- create_new_agent.md
|   |-- .mcps/
|   |   |-- create_new_mcp.md
|   |-- .skills/
|   |   |-- create_new_skill.md
|   |-- agent/
|   |   |-- __init__.py
|   |   |-- access_key_wizard.py
|   |   |-- admin.py
|   |   |-- agent_manifest.py
|   |   |-- agent_verdict.py
|   |   |-- apps.py
|   |   |-- cancellation.py
|   |   |-- capability_registry.py
|   |   |-- chain_files_search_lcel.py
|   |   |-- chain_system_lcel.py
|   |   |-- chat_agent_registry.py
|   |   |-- chat_agent_runtime.py
|   |   |-- chat_history_loader.py
|   |   |-- command_togen_pb2.txt
|   |   |-- command_watchdog.py
|   |   |-- config.json
|   |   |-- config_loader.py
|   |   |-- constants.py
|   |   |-- consumers.py
|   |   |-- contacts.py
|   |   |-- embedding_memory_guard.py
|   |   |-- exec_permission.py
|   |   |-- external_mcp_defaults.py
|   |   |-- external_mcp_manager.py
|   |   |-- external_mcps.json
|   |   |-- filesearch.proto
|   |   |-- filesearch_pb2.py
|   |   |-- filesearch_pb2_grpc.py
|   |   |-- global_execution_planner.py
|   |   |-- global_state.py
|   |   |-- gpu_perf.py
|   |   |-- inet_determiner.py
|   |   |-- llm_timing.py
|   |   |-- local_toolcall_parser.py
|   |   |-- log_identity.py
|   |   |-- mcp_agent.py
|   |   |-- mcp_files_search_client.py
|   |   |-- mcp_files_search_server.py
|   |   |-- mcp_system_client.py
|   |   |-- mcp_system_server.py
|   |   |-- models.py
|   |   |-- native_dialogs.py
|   |   |-- orphan_reaper.py
|   |   |-- path_guard.py
|   |   |-- prompt.pmt
|   |   |-- rag_enhancements.py
|   |   |-- routing.py
|   |   |-- run_db_wal_tests.ps1
|   |   |-- runtime_provisioner.py
|   |   |-- self_healing.py
|   |   |-- self_update.py
|   |   |-- sqlite_copy.py
|   |   |-- test_access_key_wizard.py
|   |   |-- test_agent_display_names.py
|   |   |-- test_agent_manifest.py
|   |   |-- test_agent_verdict.py
|   |   |-- test_agents_see_hidden_dirs.py
|   |   |-- test_arduino_agent.py
|   |   |-- test_ask_execs_allowlist.py
|   |   |-- test_audioplayer_agent.py
|   |   |-- test_binary_guard.py
|   |   |-- test_blender_agent.py
|   |   |-- test_build_pip_quiet.py
|   |   |-- test_build_scripts.py
|   |   |-- test_camcorder_agent.py
|   |   |-- test_cancellation.py
|   |   |-- test_chain_readiness.py
|   |   |-- test_chat_bridge_bots.py
```

Tree appendix 6 of 17

```
| |-- test_chat_history_window.py
| |-- test_checkbox_bulk_toggle.py
| |-- test_command_watchdog.py
| |-- test_contacts.py
| |-- test_crawler_agent.py
| |-- test_createsuperuser_wizard.py
| |-- test_db_backup_restore_wal.py
| |-- test_db_backup_safety.py
| |-- test_de_compressor.py
| |-- test_deep_research_prompt.py
| |-- test_deleter_safety.py
| |-- test_dialog_dismissal_policy.py
| |-- test_dialog_theme.py
| |-- test_discoverer_agent.py
| |-- test_discoverer_thousand.py
| |-- test_django_port_config.py
| |-- test_editor_agent.py
| |-- test_embedding_memory_guard.py
| |-- test_esp32er_agent.py
| |-- test_esphomer_agent.py
| |-- test_exec_report_verdict.py
| |-- test_execute_command_bounded.py
| |-- test_external_mcp_add_flow.py
| |-- test_external_mcp_e2e.py
| |-- test_external_mcp_transports.py
| |-- test_external_mcp_universal.py
| |-- test_file_extractor_reader.py
| |-- test_flow_contracts.py
| |-- test_frontend_mutable_state.py
| |-- test_globber_agent.py
| |-- test_googler_agent.py
| |-- test_googler_dorks.py
| |-- test_grepper_agent.py
| |-- test_grepper_encodings.py
| |-- test_image_interpreter_agent.py
| |-- test_instant_messaging_doctor.py
| |-- test_j_decompiler_agent.py
| |-- test_js_gates.py
| |-- test_kalier_agent.py
| |-- test_latexer_agent.py
| |-- test_latexer_repair_ladder.py
| |-- test_latexer_suite.py
| |-- test_latexer_verbatim_channel.py
| |-- test_log_identity.py
| |-- test_native_dialogs.py
| |-- test_netspeed_calculator_agent.py
| |-- test_nmapper_agent.py
| |-- test_no_audio_in_tests.py
| |-- test_orphan_reaper.py
| |-- test_parametrizer_mcp_doctor.py
| |-- test_password_quoting.py
| |-- test_pdfer_agent.py
| |-- test_playwrighter_agent.py
| |-- test_preserved_user_state.py
| |-- test_prompt_catalog_contiguous.py
| |-- test_recorder_agent.py
| |-- test_runtime_provisioner.py
| |-- test_security_assets_carriage.py
| |-- test_self_healing.py
| |-- test_self_knowledge_is_current.py
| |-- test_self_modify_gate.py
| |-- test_self_update.py
| |-- test_shoter_takes_screenshots.py
| |-- test_sqlite_wal_mode.py
| |-- test_status_vocabulary.py
| |-- test_step_by_step_mode.py
| |-- test_stm32er_agent.py
| |-- test_talker_agent.py
| |-- test_telegrammer_identity.py
| |-- test_temp_dir_policy.py
| |-- test_tool_failure_recovery.py
| |-- test_unrealer_agent.py
| |-- test_version_guard.py
| |-- test_video_analyzer_agent.py
| |-- test_videoplayer_agent.py
| |-- test_watchdog_foreground_exemption.py
```

Tree appendix 7 of 17

```
-- test_web_process_stays_lean.py
-- test_whatsapp_identity.py
-- test_whisperer_agent.py
-- test_windower_agent.py
-- test_windows_app_registration.py
-- test_zavuerer_agent.py
-- tests.py
-- tests_perf_3x.py
-- Tlamatini.md
-- tools.py
-- urls.py
-- version.py
-- views.py
-- web_search_llm.py
-- window_flash.py
-- windows_app_registration.py
-- acpx/
|  -- __init__.py
|  -- agent_registry.py
|  -- config.py
|  -- permissions.py
|  -- runtime.py
|  -- service.py
|  -- session_store.py
|  -- tests.py
|  -- tools.py
|  -- windows_spawn.py
-- agents/
|  -- acpxer/
|  |  -- acpxer.py
|  |  -- config.yaml
|  -- analyzer/
|  |  -- analyzer.py
|  |  -- config.yaml
|  -- and/
|  |  -- and.py
|  |  -- config.yaml
|  -- apirer/
|  |  -- apirer.py
|  |  -- config.yaml
|  -- arduiner/
|  |  -- arduiner.py
|  |  -- config.yaml
|  |  -- ArduinoTemplateProject/
|  |  |  -- ArduinoTemplateProject.ino
|  |  |  -- README.md
|  |  |  -- sketch.yaml
|  |  |  -- src/
|  |  |  |  -- Heartbeat.cpp
|  |  |  |  -- Heartbeat.h
|  -- asker/
|  |  -- asker.py
|  |  -- config.yaml
|  -- audioplayer/
|  |  -- audioplayer.py
|  |  -- config.yaml
|  -- barrier/
|  |  -- barrier.py
|  |  -- config.yaml
|  |  -- test_barrier.py
|  -- blenderer/
|  |  -- blenderer.py
|  |  -- config.yaml
|  -- camcorder/
|  |  -- camcorder.py
|  |  -- config.yaml
|  -- cleaner/
|  |  -- __init__.py
|  |  -- cleaner.py
|  |  -- config.yaml
|  -- counter/
|  |  -- config.yaml
|  |  -- counter.py
|  -- crawler/
|  |  -- config.yaml
|  |  -- crawler.py
```

Tree appendix 8 of 17

```
-- croner/
| |-- config.yaml
| |-- croner.py
-- de_compressor/
| |-- config.yaml
| |-- de_compressor.py
-- deleter/
| |-- config.yaml
| |-- deleter.py
-- discoverer/
| |-- config.yaml
| |-- discoverer.py
-- dockerer/
| |-- config.yaml
| |-- dockerer.py
-- editor/
| |-- config.yaml
| |-- editor.py
-- emailer/
| |-- config.yaml
| |-- emailer.py
-- ender/
| |-- config.yaml
| |-- ender.py
-- esp32er/
| |-- config.yaml
| |-- esp32er.py
-- esphomer/
| |-- config.yaml
| |-- esphomer.py
| |-- ESPHomeTemplateProject/
| | |-- README.md
| | |-- tlamatini-light.yaml
-- executor/
| |-- config.yaml
| |-- executor.py
-- file_creator/
| |-- config.yaml
| |-- file_creator.py
-- file_extractor/
| |-- config.yaml
| |-- file_extractor.py
-- file_interpreter/
| |-- config.yaml
| |-- file_interpreter.py
-- flowbacker/
| |-- config.yaml
| |-- flowbacker.py
-- flowcreator/
| |-- agentic_skill.md
| |-- config.yaml
| |-- flowcreator.py
| |-- result_to_flw.py
-- flowhypervisor/
| |-- config.yaml
| |-- flowhypervisor.py
| |-- hypervisor_alert.wav
| |-- monitoring-prompt.pmt
-- forker/
| |-- config.yaml
| |-- forker.py
-- gateway_relayer/
| |-- config.yaml
| |-- gateway_relayer.md
| |-- gateway_relayer.py
-- gatewayer/
| |-- config.yaml
| |-- gatewayer.md
| |-- gatewayer.py
| |-- gatewayer_explanation.md
-- gitter/
| |-- config.yaml
| |-- gitter.py
-- globber/
| |-- config.yaml
| |-- globber.py
```

Tree appendix 9 of 17

```

-- googler/
|   |-- config.yaml
|   |-- googler.py
-- grepper/
|   |-- config.yaml
|   |-- grepper.py
-- image_interpreter/
|   |-- config.yaml
|   |-- image_interpreter.py
-- instant_messaging_doctor/
|   |-- config.yaml
|   |-- instant_messaging_doctor.py
-- j_decompiler/
|   |-- config.yaml
|   |-- j_decompiler.py
-- jenkinser/
|   |-- config.yaml
|   |-- jenkinser.py
-- kalier/
|   |-- config.yaml
|   |-- kalier.py
-- keyboarder/
|   |-- config.yaml
|   |-- keyboarder.py
-- kubernetes/
|   |-- config.yaml
|   |-- kubernetes.py
-- kyber_cipher/
|   |-- config.yaml
|   |-- kyber_cipher.py
-- kyber_decipher/
|   |-- config.yaml
|   |-- kyber_decipher.py
-- kyber_keygen/
|   |-- config.yaml
|   |-- kyber_keygen.py
-- latexer/
|   |-- config.yaml
|   |-- latexer.py
-- mcp_doctor/
|   |-- config.yaml
|   |-- mcp_doctor.py
-- mongoxer/
|   |-- config.yaml
|   |-- mongoxer.py
-- monitor_log/
|   |-- config.yaml
|   |-- monitor_log.py
-- monitor_netstat/
|   |-- config.yaml
|   |-- monitor_netstat.py
-- mouser/
|   |-- config.yaml
|   |-- mouser.py
-- mover/
|   |-- config.yaml
|   |-- mover.py
-- netspeed_calculator/
|   |-- config.yaml
|   |-- netspeed_calculator.py
-- nmapper/
|   |-- config.yaml
|   |-- nmapper.py
-- node_manager/
|   |-- config.yaml
|   |-- node_manager.md
|   |-- node_manager.py
|   |-- nodes_example.json
|   |-- nodes_example.yaml
-- notifier/
|   |-- config.yaml
|   |-- notifier.py
-- or/
|   |-- config.yaml
|   |-- or.py
-- parametrizer/

```

Tree appendix 10 of 17

```

|-- config.yaml
|-- parametrizer.py
-- pdfer/
| |-- config.yaml
| |-- pdfer.py
-- playwrighter/
| |-- config.yaml
| |-- playwrighter.py
-- prompter/
| |-- config.yaml
| |-- prompter.py
-- pser/
| |-- config.yaml
| |-- pser.py
-- pythonxer/
| |-- config.yaml
| |-- pythonxer.py
-- raiser/
| |-- config.yaml
| |-- raiser.py
-- recmailer/
| |-- config.yaml
| |-- recmailer.py
-- recorder/
| |-- config.yaml
| |-- recorder.py
-- reviewer/
| |-- config.yaml
| |-- reviewer.py
-- scper/
| |-- config.yaml
| |-- scper.py
-- shoter/
| |-- config.yaml
| |-- shoter.py
-- sleeper/
| |-- config.yaml
| |-- sleeper.py
-- sqler/
| |-- config.yaml
| |-- sqler.py
-- ssher/
| |-- config.yaml
| |-- ssher.py
-- starter/
| |-- config.yaml
| |-- starter.py
-- stm32er/
| |-- config.yaml
| |-- stm32er.py
-- stopper/
| |-- config.yaml
| |-- stopper.py
-- summarizer/
| |-- config.yaml
| |-- summarizer.py
-- talker/
| |-- config.yaml
| |-- talker.py
-- telegrammer/
| |-- config.yaml
| |-- HOW_TO_GET_YOUR_TELEGRAM_ASSETS.md
| |-- telegrammer.py
| |-- guide_assets/
| | |-- telegram_01_botfather_search.jpg
| | |-- telegram_02_newbot_token.jpg
| | |-- telegram_03_start_bot_getupdates.jpg
| | |-- telegram_04_tlamatini_contacts.jpg
-- teletlamatini/
| |-- config.yaml
| |-- teletlamatini.py
-- unrealer/
| |-- config.yaml
| |-- unrealer.py
-- video_analyzer/
| |-- config.yaml

```


Tree appendix 11 of 17

```
| | | `-- video_analyzer.py
| | | -- videoplayer/
| | | | -- config.yaml
| | | | `-- videoplayer.py
| | | -- whatsapp/
| | | | -- config.yaml
| | | | -- HOW_TO_GET_YOUR_WHATSAPP_ASSETS.md
| | | | -- whatsapp.py
| | | | `-- guide_assets/
| | | | | -- whatsapp_01_meta_create_app.jpg
| | | | | -- whatsapp_02_api_setup_keys.jpg
| | | | | -- whatsapp_03_test_recipient_send.jpg
| | | | | -- whatsapp_04_system_user_token.jpg
| | | | | `-- whatsapp_05_tlamatini_contacts.jpg
| | | -- whisperer/
| | | | -- config.yaml
| | | | `-- whisperer.py
| | | -- windower/
| | | | -- config.yaml
| | | | `-- windower.py
| | | `-- zavuerer/
| | | | -- config.yaml
| | | | `-- zavuerer.py
| | -- doc_generation/
| | | -- complete_project_docs.py
| | | -- markdown_to_pdf.py
| | | -- refresh_project_docs.py
| | | `-- test_output.pdf
| -- images/
| | -- ACPXKeysConfigureWizard.jpg
| | -- ConfigureModels.jpg
| | -- FlowPill.jpg
| | -- HiIamTlamatini.png
| | -- LabInEnglish.mp4
| | -- LabInSpanish.mp4
| | -- MenuConfig.jpg
| | -- mockup.jpg
| | -- Modify_the_last_video_keepi.mp4
| | -- RealisticTlamatini.png
| | -- ShouldersUoTlamatini.png
| | -- Tlamatini AI Agentic Advisor Video.mp4
| | -- TlamatiniAndKyber.mp4
| | -- TlamatiniClosedMouthClosedEyes.jpg
| | -- TlamatiniClosedMouthOpenedEyes.jpg
| | -- TlamatiniDrawings.png
| | -- TlamatiniOpenedMouthClosedEyes.jpg
| | -- TlamattiniOpenedMouthOpenedEyes.jpg
| | -- TlammattiniLetsMakeSomeMagic.mp4
| | -- TorsoTlamatini.png
| | -- versions.png
| | `-- XAIHT-Tlamatini.mp4
| -- imaging/
| | -- converter.py
| | -- image_interpreter.py
| | `-- screenshot.py
| -- management/
| | -- __init__.py
| | `-- commands/
| | | -- acpx_lint.py
| | | `-- startserver.py
| -- migrations/
| | -- 0001_initial.py
| | -- 0002_populate_db.py
| | -- 0003_add_cleaner.py
| | -- 0004_add_deleter.py
| | -- 0005_add_executer.py
| | -- 0006_add_notifier.py
| | -- 0007_add_stopper.py
| | -- 0008_add_recmailer.py
| | -- 0009_add_whatsapp.py
| | -- 0010_add_pythoner.py
| | -- 0011_add_asker.py
| | -- 0012_repopulate_all_agents.py
| | -- 0013_add_forker.py
| | -- 0014_repopulate_all_agents.py
| | -- 0015_add_shoter.py
```

Tree appendix 12 of 17

```
-- 0016_repopulate_all_agents.py
-- 0017_add_ssh.py
-- 0018_repopulate_all_agents.py
-- 0019_add_scper.py
-- 0020_repopulate_all_agents.py
-- 0021_add_telegramrx.py
-- 0022_repopulate_all_agents.py
-- 0023_add_mongoxer.py
-- 0024_repopulate_all_agents.py
-- 0025_add_telegramer.py
-- 0026_repopulate_all_agents.py
-- 0027_add_sqler.py
-- 0028_repopulate_all_agents.py
-- 0029_add_prompiter.py
-- 0030_repopulate_all_agents.py
-- 0031_add_flowcreator.py
-- 0032_repopulate_all_agents.py
-- 0033_add_gitter.py
-- 0034_add_dockerer.py
-- 0035_add_pser.py
-- 0036_add_kuberneter.py
-- 0037_add_apirer.py
-- 0038_add_jenkinser.py
-- 0039_add_crawler.py
-- 0040_add_summarizer.py
-- 0041_add_flowhypervisor.py
-- 0042_add_mouser.py
-- 0043_agentmessage_conversation_user.py
-- 0044_add_counter.py
-- 0045_add_file_interpreter.py
-- 0046_add_image_interpreter.py
-- 0047_add_gatewayer.py
-- 0048_add_gateway_relayer.py
-- 0049_add_node_manager.py
-- 0050_add_file_creator.py
-- 0051_add_file_extractor.py
-- 0052_add_kyber_keygen.py
-- 0053_add_kyber_cipher.py
-- 0054_add_kyber_decipher.py
-- 0055_fix_kyber_cipher_names.py
-- 0056_add_parametrizer.py
-- 0057_add_flowbacker.py
-- 0058_add_barrier.py
-- 0059_add_j_decompiler.py
-- 0060_add_agent_parametrizer_tool.py
-- 0061_add_agent_starter_tool.py
-- 0062_sync_agent_control_tools_and_prompts.py
-- 0063_add_agent_parametrizer_prompt.py
-- 0064_add_chat_agent_run_model.py
-- 0065_add_chat_wrapped_agent_tools.py
-- 0066_add_keyboard.py
-- 0067_add_multi_turn_demo_prompts.py
-- 0068_add_googler_tool.py
-- 0069_add_googler_agent.py
-- 0070_add_teletlamatini.py
-- 0071_acpx_skills.py
-- 0072_add_acpx_demo_prompts.py
-- 0073_acpx_demo_gemini_uplift.py
-- 0074_simplify_demo_prompts.py
-- 0075_add_acpx_tool_surface.py
-- 0076_add_acpxer.py
-- 0077_add_whatstlamatini.py
-- 0078_add_chat_agent_keyboarder_tool.py
-- 0079_add_chat_agent_mouser_tool.py
-- 0080_add_chat_agent_sleeper_tool.py
-- 0081_add_window_present_and_run_wait_tools.py
-- 0082_add_chat_agent_j_decompiler_tool.py
-- 0083_add_de_compressor.py
-- 0084_add_chat_agent_de_compressor_tool.py
-- 0085_add_unrealer.py
-- 0086_add_chat_agent_unrealer_tool.py
-- 0087_add_unrealer_demo_prompt.py
-- 0088_add_reviewer.py
-- 0089_add_analyzer.py
-- 0090_add_reviewer_analyzer_demo_prompts.py
-- 0091_add_playwrighter.py
```

Tree appendix 13 of 17

```
-- 0092_add_chat_agent_playwrighter_tool.py
-- 0093_add_windower.py
-- 0094_add_chat_agent_windower_tool.py
-- 0095_add_windower_playwrighter_demo_prompts.py
-- 0096_add_director_virtuoso_demo_prompts.py
-- 0097_add_kalier.py
-- 0098_add_chat_agent_kalier_tool.py
-- 0099_add_kalier_demo_prompts.py
-- 0100_add_unrealer_extended_demo_prompts.py
-- 0101_add_stm32er.py
-- 0102_add_chat_agent_stm32er_tool.py
-- 0103_add_stm32er_demo_prompts.py
-- 0104_fix_stm32er_hil_serial_proof.py
-- 0105_add_esp32er.py
-- 0106_add_chat_agent_esp32er_tool.py
-- 0107_add_esp32er_demo_prompts.py
-- 0108_add_flow_making_demo_prompt.py
-- 0109_add_arduiner.py
-- 0110_add_chat_agent_arduiner_tool.py
-- 0111_add_arduiner_demo_prompts.py
-- 0112_add_camcorder.py
-- 0113_add_chat_agent_camcorder_tool.py
-- 0114_add_recorder.py
-- 0115_add_chat_agent_recorder_tool.py
-- 0116_add_audioplayer.py
-- 0117_add_chat_agent_audioplayer_tool.py
-- 0118_add_videoplayer.py
-- 0119_add_chat_agent_videoplayer_tool.py
-- 0120_add_talker.py
-- 0121_add_chat_agent_talker_tool.py
-- 0122_add_talker_demo_prompt.py
-- 0123_add_whisperer.py
-- 0124_add_chat_agent_whisperer_tool.py
-- 0125_add_whisperer_demo_prompt.py
-- 0126_add_blenderer.py
-- 0127_add_chat_agent_blenderer_tool.py
-- 0128_add_blenderer_demo_prompts.py
-- 0129_add_editor.py
-- 0130_add_chat_agent_editor_tool.py
-- 0131_add_editor_demo_prompts.py
-- 0132_add_grepper.py
-- 0133_add_chat_agent_grepper_tool.py
-- 0134_add_grepper_demo_prompts.py
-- 0135_add_globber.py
-- 0136_add_chat_agent_globber_tool.py
-- 0137_add_globber_demo_prompts.py
-- 0138_add_esphomer.py
-- 0139_add_chat_agent_esphomer_tool.py
-- 0140_add_esphomer_demo_prompts.py
-- 0141_add_mcp_doctor.py
-- 0142_add_chat_agent_mcp_doctor_tool.py
-- 0143_add_mcp_doctor_demo_prompt.py
-- 0144_insert_java17_maven_demo_prompt_at_5.py
-- 0145_insert_createsuperuser_wizard_prompt_at_1.py
-- 0146_update_createsuperuser_wizard_continuation.py
-- 0147_add_unreal_game_demo_prompts.py
-- 0148_add_discoverer_demo_prompts.py
-- 0149_add_discoverer.py
-- 0150_add_chat_agent_discoverer_tool.py
-- 0151_retire_old_messaging_add_telegrammer.py
-- 0152_add_instant_messaging_doctor.py
-- 0153_add_chat_agent_instant_messaging_doctor_tool.py
-- 0154_add_instant_messaging_doctor_demo_prompt.py
-- 0155_add_contact_scaffold_demo_prompt.py
-- 0156_add_telegrammer_identity_demo_prompts.py
-- 0157_add_whatsapp_identity_demo_prompt.py
-- 0158_redesign_messaging_demo_prompts.py
-- 0159_add_zavuerer.py
-- 0160_add_chat_agent_zavuerer_tool.py
-- 0161_add_zavuerer_demo_prompts.py
-- 0162_add_zavuerer_catalog_prompts.py
-- 0163_add_zavuerer_get_key_wizard_prompt.py
-- 0164_dedup_zavuerer_setup_wizards.py
-- 0165_add_image_interpreter_triple_model_demo_prompt.py
-- 0166_add_video_analyzer.py
-- 0167_add_chat_agent_video_analyzer_tool.py
```

Tree appendix 14 of 17

```
-- 0168_add_video_analyzer_demo_prompt.py
-- 0169_add_discoverer_cvemap_latest_demo_prompt.py
-- 0170_add_nmapper.py
-- 0171_add_chat_agent_nmapper_tool.py
-- 0172_add_nmapper_demo_prompts.py
-- 0173_add_unreal_scaffold_demo_prompt.py
-- 0174_unreal_scaffold_build_project_tip.py
-- 0175_prompt_category_and_dedup.py
-- 0176_delete_duplicate_acpx_prompts.py
-- 0177_add_stm32er_platformio_demo_prompt.py
-- 0178_add_stm32_stepwise_blink_camera_prompts.py
-- 0179_regroup_resort_prompts_no_gaps.py
-- 0180_add_kalier_setup_wizard_prompt.py
-- 0181_prompt_sort_rank.py
-- 0182_add_step_by_step_section_openers.py
-- 0183_standardize_security_recon_prompts.py
-- 0184_standardize_prompt_params_batch2.py
-- 0185_standardize_prompt_params_batch3.py
-- 0186_add_chat_agent_flowcreator.py
-- 0187_add_flowcreator_end_to_end_wizard_prompt.py
-- 0188_add_pdfer.py
-- 0189_add_chat_agent_pdfer_tool.py
-- 0190_add_pdfer_demo_prompts.py
-- 0191_add_latexer.py
-- 0192_add_chat_agent_latexer_tool.py
-- 0193_add_latexer_demo_prompts.py
-- 0194_add_deep_research_demo_prompt.py
-- 0195_add_netspeed_calculator.py
-- 0196_add_chat_agent_netspeed_calculator_tool.py
-- 0197_add_netspeed_calculator_demo_prompt.py
-- __init__.py
-- monitors/
--   -- monitor_sql.py
-- opus_client/
--   -- claude_opus_client.py
--   -- examples.py
--   -- README.md
-- rag/
--   -- __init__.py
--   -- binary_guard.py
--   -- config.py
--   -- factory.py
--   -- interaction.py
--   -- interface.py
--   -- loaders.py
--   -- prompts.py
--   -- retrieval.py
--   -- splitters.py
--   -- utils.py
--   -- chains/
--     -- base.py
--     -- basic.py
--     -- history_aware.py
--     -- unified.py
-- services/
--   -- __init__.py
--   -- agent_contracts.py
--   -- agent_paths.py
--   -- filesystem.py
--   -- flow_compiler.py
--   -- flow_spec.py
--   -- response_parser.py
-- skills/
--   -- __init__.py
--   -- frontmatter.py
--   -- harness.py
--   -- io_contract.py
--   -- registry.py
-- skills_pkg/
--   -- meta/
--     -- lint.py
--     -- schema.json
--   -- acp_router/
--     -- SKILL.md
--   -- adding_external_mcp/
--     -- SKILL.md
```

Tree appendix 15 of 17

```

|-- references/
|   |-- external_mcp_catalog_format.md
|   |-- llm_reflection_research.md
|   |-- transport_guide.md
|   |-- troubleshooting.md
|-- code_review/
|   |-- SKILL.md
|-- create_new_agent/
|   |-- SKILL.md
|-- create_new_mcp/
|   |-- SKILL.md
|-- flow_making/
|   |-- SKILL.md
|   |-- references/
|   |   |-- flw_schema.md
|   |-- scripts/
|   |   |-- make_flow.py
|   |   |-- result_to_flw.py
|-- github/
|   |-- SKILL.md
|-- gmail/
|   |-- SKILL.md
|-- hello_world/
|   |-- SKILL.md
|-- jira/
|   |-- SKILL.md
|-- kali_pentest/
|   |-- SKILL.md
|-- notion/
|   |-- SKILL.md
|-- roblox_studio/
|   |-- SKILL.md
|-- security_audit/
|   |-- SKILL.md
|-- setup_new_acpx_key/
|   |-- SKILL.md
|-- skill_creator/
|   |-- SKILL.md
|   |-- scripts/
|   |   |-- quick_validate.py
|-- slack/
|   |-- SKILL.md
|-- summarize/
|   |-- SKILL.md
|-- tlamatini_allowed_hosts_tighten/
|   |-- SKILL.md
|-- tlamatini_csrf_exempt_audit/
|   |-- SKILL.md
|-- tlamatini_exec_report_row_adder/
|   |-- SKILL.md
|-- tlamatini_flow_from_objective/
|   |-- SKILL.md
|-- tlamatini_flw_doctor/
|   |-- SKILL.md
|-- tlamatini_new_acp_agent/
|   |-- SKILL.md
|-- tlamatini_planner_trace_replay/
|   |-- SKILL.md
|-- tlamatini_static_version_bumper/
|   |-- SKILL.md
|-- todoist/
|   |-- SKILL.md
|-- trello/
|   |-- SKILL.md
|-- weather/
|   |-- SKILL.md
-- static/
|   |-- agent/
|   |   |-- css/
|   |   |   |-- access_keys_wizard.css
|   |   |   |-- agent_page.css
|   |   |   |-- agentic_control_panel.css
|   |   |   |-- avatar.css
|   |   |   |-- contacts_dialog.css
|   |   |   |-- dialog_theme.css
|   |   |   |-- external_mcps_dialog.css

```

Tree appendix 16 of 17

```

|-- login.css
|-- skills_dialog.css
|-- tools_dialog.css
`-- welcome.css
-- img/
|-- spinner.svg
|-- Tlamatini.ico
`-- avatar/
|-- ec_mc.jpg
|-- ec_mo.jpg
|-- eo_mc.jpg
|-- eo_mo.jpg
-- js/
|-- access_keys_wizard.js
|-- acp-agent-connectors.js
|-- acp-canvas-core.js
|-- acp-canvas-undo.js
|-- acp-connection-status.js
|-- acp-control-buttons.js
|-- acp-file-io.js
|-- acp-flow-snapshot.js
|-- acp-globals.js
|-- acp-layout.js
|-- acp-parametrizer-dialog.js
|-- acp-running-state.js
|-- acp-session.js
|-- acp-undo-manager.js
|-- acp-validate.js
|-- agent_page_canvas.js
|-- agent_page_chat.js
|-- agent_page_context.js
|-- agent_page_dialogs.js
|-- agent_page_init.js
|-- agent_page_layout.js
|-- agent_page_state.js
|-- agent_page_ui.js
|-- agentic_control_panel.js
|-- avatar.js
|-- canvas_item_dialog.js
|-- chat_image_paste.js
|-- chat_page_runtime_poller.js
|-- checkbox_bulk_toggle.js
|-- contacts_dialog.js
|-- contextual_menus.js
|-- dialog_policy.js
|-- external_mcps_dialog.js
|-- release_notes_renderer.js
|-- shared-runtime-dialogs.js
|-- skills_dialog.js
|-- tools_dialog.js
-- sounds/
|-- hypervisor_alert.wav
|-- notification.wav
-- video/
|-- XAIHT-Tlamatini.mp4
-- templates/
|-- agent/
|-- agent_page.html
|-- agentic_control_panel.html
|-- login.html
|-- welcome.html
-- test_fixtures/
|-- talker_orpheus_tokens.txt
-- TlamatiniSourceCode/
|-- README.md
-- DB/
|-- Older/
|-- README.md
-- ToLoad/
|-- README.md
-- jd-cli/
|-- jd-cli.bat
|-- jd-cli.jar
-- tests_e2e/
|-- oob_child_helper.py
|-- README.md

```

Tree appendix 17 of 17

```
| |-- test_create_flow_visual.py
| |-- test_db_backup_set_visible.py
| |-- test_oob_browser_visible.py
| |-- test_oob_namu_unit.py
| |-- test_prompts_catalog_visual.py
| |-- test_self_healing_visual.py
| |-- test_voice_visual.py
| |-- Tlamatini-Overnight-100.py
| |-- Tlamatini-Whatsapper-Daily-Tests.py
|-- tlamatini/
|   |-- __init__.py
|   |-- asgi.py
|   |-- context_processors.py
|   |-- logging_filters.py
|   |-- middleware.py
|   |-- settings.py
|   |-- urls.py
|   |-- wsgi.py
```