

TLAMATINI

Complete Project Dossier: what the system does, how it works, how to use it, complete tracked file tree, and effective line inventory



Measure	Value
Generated	May 11, 2026 10:56 PM UTC-0600
Current HEAD	fb1b390 - Updating documentation respect config plane, and some others light improvements, by angelahack1
Tracked files	428
Workflow agents	60
Total effective lines	89,121
Total physical text lines	120,783

1. What Tlamatini Is

- Tlamatini is a local-first AI developer assistant built with Django, Django Channels, LangChain, LangGraph, FAISS/BM25 retrieval, and a large in-repository agent application.
- It combines a browser chat surface, a Retrieval-Augmented Generation stack, a Multi-Turn tool executor, MCP-backed context providers, wrapped chat-agent runtimes, and a visual Agentic Control Panel for workflow design.
- The platform is designed for development operations: codebase analysis, file and directory context, command execution, Python execution, screenshots, web/search helpers, notifications, DevOps tools, local model operation, and Windows packaging.

What the system does

- Answers codebase questions with loaded file or directory context.
- Uses hybrid retrieval to extract metadata, split content, rank source chunks, and respect context budgets.
- Runs checked Multi-Turn requests through request-scoped planning, capability selection, tool calls, observations, monitoring, and final synthesis.
- Launches wrapped copies of selected workflow agents in isolated runtime folders without mutating templates.
- Lets users design, validate, save, pause, resume, and stop visual workflows through the Agentic Control Panel.
- Turns successful Multi-Turn tool executions into starter `.flw` workflows that can be inspected and validated in ACP.
- Packages the project into a distributable Windows release with installer and uninstaller tooling.

How it works

- Browser UI sends chat and workflow requests through Django views and Channels WebSockets.
- RAG chains load selected file/directory context, retrieve relevant chunks, and build answer prompts.
- When Multi-Turn is enabled, the global planner selects context and tool stages before the executor binds only the relevant tools.
- Tool calls execute in the backend, append observations, and may create wrapped runtime copies under `agent/agents/pools/_chat_runs_/`.
- ACP flows deploy session-scoped pool instances, wire config values, validate NxN graph rules, and execute through Starter-driven flow semantics.
- Build scripts collect static assets, bundle Django/Python resources, add agent templates, and assemble `pkg.zip`, `Uninstaller.exe`, and `dist/Tlamatini_Release/`.

2. Architecture Layers

Layer	Role
Browser interfaces	Chat page plus Agentic Control Panel templates and JavaScript modules.
Django/Channels	Authentication, views, WebSockets, session state, message persistence, and ASGI startup.
RAG and context	Metadata extraction, text splitting, FAISS/BM25 retrieval, context budgeting, and fallback behavior.
Multi-Turn engine	Capability registry, global execution planner, explicit tool loop, answer parsing, and answer-success classification.
Tools and agents	Core tools, MCP context providers, wrapped chat-agent launchers, and 57 visual workflow agent templates.
Packaging	PyInstaller build scripts, shortcut registration, `.flw` association, installer, uninstaller, and release folder assembly.

Design principles

- Evidence-first answers: Tlamatini grounds responses in selected project context and hybrid retrieval rather than freeform model memory.
- Explicit orchestration: checked Multi-Turn uses a visible tool loop, capability scoring, and staged planning instead of a single opaque call.
- Runtime isolation: wrapped chat-agent copies run in session-scoped folders so template agents remain pristine while live runs stay inspectable.
- Operator truth over vibes: Exec Report tables, tlamatini.log, skill audits, and ACPX transcripts make the system auditable after execution.

3. Installation, Configuration, and Everyday Use

Installation essentials

- Python 3.12.10 is the strongly recommended source-mode version in the README, and the codebase has been tested most deeply there.
- Source installs require a clone, virtual environment, dependency install from `requirements.txt`, migrations, a superuser, static collection, and then the web server.
- You can run either the checked-in cloud/back-end defaults from `Tlamatini/agent/config.json` or a local Ollama-backed configuration with matching model names.
- Packaged Windows installs create a default `user / changeme` account; manual source installs use your own `createsuperuser` account instead.

Configuration essentials

- Source mode resolves `Tlamatini/agent/config.json`; frozen builds resolve `config.json` next to the executable; `CONFIG\_PATH` overrides both.
- Core keys include `embedding-model`, `chained-model`, `ollama\_base\_url`, `ollama\_token`, `enable\_unified\_agent`, `unified\_agent\_model`, and `unified\_agent\_max\_iterations`.
- Multi-Turn is toggled from the chat toolbar, but it depends on the unified-agent configuration and the selected model/base-url pairing being valid.
- Image interpretation can run through Claude-backed cloud paths or Qwen/Ollama-backed local paths, and remote Ollama can be protected with a bearer token.

How to use it

- Run from source: create a virtual environment, install requirements, migrate, create a superuser, collect static files, and start Django.
- Open `/agent/` for chat. Load a file or directory context before asking codebase-specific questions.
- Keep Multi-Turn unchecked for direct Q&A; enable Multi-Turn for tasks that need tools, wrapped agents, monitoring, or workflow seeding.
- Open `/agentic\_control\_panel/` to drag agents, connect them, configure each node, validate, start, pause/resume, stop, and save `.flw` workflows.
- Use `python build.py`, `python build\_uninstaller.py`, and `python build\_installer.py` only when producing a packaged Windows release.

Source-mode bootstrap commands

```
python -m venv venv
venv\Scripts\activate
pip install -r requirements.txt
python Tlamatini/manage.py migrate
python Tlamatini/manage.py createsuperuser
python Tlamatini/manage.py collectstatic --noinput
python Tlamatini/manage.py runserver --noreload
```

4. Ollama Setup Without Administrative Rights

- Open a normal PowerShell window, not an elevated one, for the safest no-admin Windows installation path.
- Install into `%LOCALAPPDATA%\Programs\Ollama` with the official PowerShell installer script and then reopen PowerShell so PATH updates are visible.
- Verify the CLI with `ollama --version`, start `ollama serve` if the background service is not already active, and confirm `http://127.0.0.1:11434/api/tags` responds.
- Pull the default repository model tags exactly as written if you want the shipped config and agent templates to work unchanged.

No-admin Ollama commands and default model pulls

```
$env:OLLAMA_INSTALL_DIR = "$env:LOCALAPPDATA\Programs\ollama"
irm https://ollama.com/install.ps1 | iex
ollama --version
ollama serve
Invoke-WebRequest http://127.0.0.1:11434/api/tags -UseBasicParsing
ollama pull qwen3-embedding:8b
ollama pull glm-5:cloud
ollama pull qwen3.5:cloud
ollama pull gpt-oss:120b-cloud
ollama pull qwen3.5:397b-cloud
ollama pull llama3.2-vision:11b
```

5. Runtime, Release, and Operator Diagnostics

Running the application

- Development server: ``python Tlamatini/manage.py runserver --noreload``.
- Preferred async/dev bootstrap: ``python Tlamatini/manage.py startserver``, which starts MCP services before the Django server.
- Production-style ASGI entrypoint: ``daphne -b 127.0.0.1 -p 8000 tlamatini.asgi:application``.
- Startup cleans pool state, repopulates the agent registry, launches MCP metrics/file-search servers, and then serves HTTP plus WebSocket traffic.

Release pipeline

- Release production is a three-step pipeline: ``build.py`` -> ``build_uninstaller.py`` -> ``build_installer.py``.
- The final distributable is the full ``dist/Tlamatini_Release/`` folder, not a stray executable copied outside its payload.
- Current ``build.py`` treats ``README.md`` and ``jd-cli/`` as required post-build assets and fails hard if those payloads are missing.
- Bundled support scripts cover shortcut creation/removal, ``.flw`` association, the PowerShell launcher, and Windows-specific installer ergonomics.

Exec Report

- Exec Report is a Multi-Turn-only transparency layer that appends one operation table per state-changing agent family to the final answer.
- Rows are recorded from the live tool-call stream rather than guessed from the LLM prose, so the report is the operational ground truth.
- Each row receives a SUCCESS/FAILURE verdict from raw tool returns, making long installs, deployments, and remediations inspectable after the fact.

ACPX and skills

- ACPX lets Tlamatini spawn external coding-agent CLIs such as Codex, Claude Code, Cursor, Gemini, Qwen, and others as managed child processes.
- It pairs those agents with markdown-driven ``SKILL.md`` packages, validated I/O contracts, permission gating, and append-only audit logs.
- Transport-aware drain rules and bounded event bodies reduce latency while protecting the LLM context budget during external-agent relays.
- The operator-facing references are ``README.md`` and ``ACPX.md``, while the implementation lives under ``agent/acpx/``, ``agent/skills/``, and ``agent/skills_pkg/``.

Application log

- The built-in ``tlamatini.log`` file captures both stdout and stderr through a tee stream initialized in ``manage.py`` before Django starts.
- In source mode the log sits next to ``manage.py``; in frozen mode it lives next to the executable.
- Immediate flush behavior makes the log the primary forensic artifact for startup problems, warnings, tracebacks, and runtime diagnostics.

6. Agent Catalog and Runtime Model

Tlmatini currently exposes 60 workflow-agent templates.

Category	Representative agents
Control	starter, ender, stopper, cleaner, barrier, flowbacker
Execution and files	executer, pythonxer, pser, file_creator, file_extractor, file_interpreter, mover, deleter
DevOps and infra	gitter, dockerer, kubernetes, jenkinser, ssher, scper
Data and APIs	sqler, mongoxer, apirer, crawler, googler
Monitoring and routing	monitor_log, monitor_netstat, flowhypervisor, forker, asker, counter, and, or
Communication	notifier, emailer, recmailer, telegramer, telegramrx, whatsapper
Security and media	kyber_keygen, kyber_cipher, kyber_decipher, image_interpreter, shoter, j_decompiler
Workflow intelligence	flowcreator, gatewayer, gateway_relayer, node_manager, parametrizer, prompter, summarizer

All workflow agents follow a common deployment pattern: template directory, YAML configuration, session-scoped pool copy, PID/status/log files, target/source wiring, and optional reanimation state.

7. Repository Facts and Git Changes

Metric	Value
Tracked files in git	428
Workflow agents	60
Django migrations	81
Frontend JavaScript modules	27
Frontend CSS files	5
HTML templates	4
Python requirements	62
Binary/asset tracked files skipped from line count	14

Latest commits

Date	Commit	Subject
2026-05-11	fb1b390	Updating documentation respect config plane, and some others light improvements, by angelahack1
2026-05-11	484b8ec	Fixing initial loading status lock on initial context-load stage, by angelahack1
2026-05-11	ac747e3	Implement configuration on GUI!!, by Tlamatini's-AutoBot.
2026-05-11	b286cd6	Improving dialog layout/size of "Configure MCPs", by Tlamatini's-AutoBot.
2026-05-11	1e62faa	Improving window vertical bar in agent_page, by Tlamatini's-AutoBot.
2026-05-09	79d0410	Update video links in README.md
2026-05-09	04502c3	Dialog edits always win modification to agentic canvas, by angelahack1
2026-05-09	2d27fa0	Fixing placeholders, by angelahack1
2026-05-09	c1088bb	Fixing quoting mechanics in Recmailer and Emailer agents, by angelahack1
2026-05-09	8c2e5a6	Improving dinamic welcome user-facing strings in TeleTlamatini agent, by angelahack1

Git changes from the last 2 days

- Documentation itself changed during the last 2 days, so the regenerated dossier is part of the tracked operator surface rather than an external afterthought.

2-day commit appendix 1 of 1

Date	Commit	Subject
2026-05-11	fb1b390	Updating documentation respect config plane, and some others light improvements, by angelahack1
2026-05-11	484b8ec	Fixing initial loading status lock on initial context-load stage, by angelahack1
2026-05-11	ac747e3	Implement configuration on GUI!!, by Tlamatini's-AutoBot.
2026-05-11	b286cd6	Improving dialog layout/size of "Configure MCPs", by Tlamatini's-AutoBot.
2026-05-11	1e62faa	Improving window vertical bar in agent_page, by Tlamatini's-AutoBot.

8. Effective Line Inventory by Language

Methodology: tracked text files only. Blank lines and comment-only lines are excluded. Python counts also remove module, class, and function docstrings detected through AST parsing.

Language	Files	Effective lines	Total lines	Share
Python	246	60,054	83,283	67.4%
JavaScript	27	11,619	14,729	13.0%
Markdown	47	10,318	13,132	11.6%
CSS	5	2,934	3,668	3.3%
YAML	63	911	2,061	1.0%
Other text	3	780	957	0.9%
HTML	4	723	741	0.8%
PowerShell	5	506	752	0.6%
Prompt template	2	403	477	0.5%
JSON	5	381	381	0.4%
JavaScript module	1	344	411	0.4%
Text	4	115	134	0.1%
Protocol Buffers	1	20	33	0.0%
Batch	1	13	24	0.0%

Total effective lines: 89,121

9. Largest Effective Source Files

Path	Language	Effective	Total
Tlmatini/agent/views.py	Python	6,402	9,201
Tlmatini/agent/tests.py	Python	3,886	4,963
Tlmatini/agent/tools.py	Python	2,201	3,094
Tlmatini/agent/agents/flowcreator/agentic_skill.md	Markdown	1,778	1,981
Tlmatini/agent/static/agent/css/agentic_control_panel.css	CSS	1,631	2,140
BookOfTlmatini.md	Markdown	1,474	2,042
Tlmatini/agent/doc_generation/complete_project_docs.py	Python	1,281	1,460
Tlmatini/agent/static/agent/js/acp-canvas-core.js	JavaScript	1,256	1,566
Tlmatini/agent/consumers.py	Python	1,096	1,318
Tlmatini/agent/static/agent/js/acp-agent-connectors.js	JavaScript	1,073	1,211
Tlmatini/agent/static/agent/css/agent_page.css	CSS	1,050	1,237
Tlmatini/agent/agents/whatstlmatini/whatstlmatini.py	Python	1,044	1,300
Tlmatini/agent/static/agent/js/acp-control-buttons.js	JavaScript	1,036	1,344
Tlmatini/agent/acpx/tests.py	Python	1,035	1,299
Tlmatini/agent/static/agent/js/agent_page_chat.js	JavaScript	955	1,322
KIMI.md	Markdown	915	1,088
Tlmatini/agent/static/agent/js/canvas_item_dialog.js	JavaScript	898	1,165
Tlmatini/agent/agents/teletlmatini/teletlmatini.py	Python	888	1,147
Tlmatini/agent/agents/crawler/crawler.py	Python	881	1,261
Tlmatini/agent/static/agent/js/agent_page_init.js	JavaScript	867	999
Tlmatini/agent/static/agent/js/acp-canvas-undo.js	JavaScript	805	916
Tlmatini/agent/acpx/runtime.py	Python	798	1,087
Tlmatini/agent/agents/parametrizer/parametrizer.py	Python	794	1,118
Tlmatini/agent/agents/file_interpreter/file_interpreter.py	Python	749	969
Tlmatini/agent/agents/node_manager/node_manager.py	Python	719	950

10. Complete Tracked File Tree (Repository Appendix)

Tree appendix 1 of 8

```
Tlamatini/
|-- .gitignore
|-- _acpx_pipeline_demo_report.md
|-- ACPX.md
|-- agents_descriptions.md
|-- BookOfTlamatini.md
|-- build.py
|-- build_installer.py
|-- build_uninstaller.py
|-- CLAUDE.md
|-- CreateShortcut.json
|-- CreateShortcut.ps1
|-- eslint.config.mjs
|-- install.py
|-- KIMI.md
|-- LICENSE
|-- package.json
|-- prompt_example_2_create_agent.txt
|-- README.md
|-- regen_secrets.py
|-- register_flw.ps1
|-- RemoveShortcut.ps1
|-- requirements.txt
|-- Tlamatini.ico
|-- Tlamatini.jpg
|-- Tlamatini.ps1
|-- tlamatini_app_summary.pdf
|-- Tlamatini_extended_Artificial_Intelligence_Humanly_Tempered.pptx
|-- uninstall.py
|-- unregister_flw.ps1
|-- .codex/
|   |-- skills/
|   |   |-- full-project-pdf-dossier/
|   |   |   |-- SKILL.md
|   |   |-- overlap-safe-pptx-dossier/
|   |   |   |-- SKILL.md
|   |-- .github/
|   |   |-- workflows/
|   |   |   |-- name-guard.yml
|   |-- docs/
|   |   |-- claude/
|   |   |   |-- acpx.md
|   |   |   |-- agents.md
|   |   |   |-- architecture.md
|   |   |   |-- exec-report.md
|   |   |   |-- frontend.md
|   |   |   |-- gotchas.md
|   |   |   |-- INDEX.md
|   |   |   |-- mcp-tools.md
|   |   |   |-- multi-turn.md
|   |-- pyinstaller_hooks/
|   |   |-- hook-numpy.py
|   |-- Tlamatini/
|   |   |-- cat_art.py
|   |   |-- manage.py
|   |   |-- .agents/
|   |   |   |-- workflows/
|   |   |   |   |-- create_new_agent.md
|   |   |-- .mcps/
|   |   |   |-- create_new_mcp.md
|   |   |-- agent/
|   |   |   |-- __init__.py
|   |   |   |-- admin.py
|   |   |   |-- apps.py
|   |   |   |-- capability_registry.py
|   |   |   |-- chain_files_search_lcel.py
|   |   |   |-- chain_system_lcel.py
|   |   |   |-- chat_agent_registry.py
|   |   |   |-- chat_agent_runtime.py
|   |   |   |-- chat_history_loader.py
|   |   |   |-- command_togen_pb2.txt
|   |   |   |-- config.json
|   |   |   |-- config_loader.py
|   |   |   |-- constants.py
|   |   |   |-- consumers.py
|   |   |   |-- filesearch.proto
```

Tree appendix 2 of 8

```
-- filesearch_pb2.py
-- filesearch_pb2_grpc.py
-- global_execution_planner.py
-- global_state.py
-- inet_determiner.py
-- mcp_agent.py
-- mcp_files_search_client.py
-- mcp_files_search_server.py
-- mcp_system_client.py
-- mcp_system_server.py
-- models.py
-- path_guard.py
-- prompt.pmt
-- rag_enhancements.py
-- routing.py
-- test_flow_contracts.py
-- test_password_quoting.py
-- tests.py
-- tools.py
-- urls.py
-- views.py
-- web_search_llm.py
-- acpx/
|  -- __init__.py
|  -- agent_registry.py
|  -- config.py
|  -- permissions.py
|  -- runtime.py
|  -- service.py
|  -- session_store.py
|  -- tests.py
|  -- tools.py
|  -- windows_spawn.py
-- agents/
|  -- acpxer/
|  |  -- acpxer.py
|  |  -- config.yaml
|  -- and/
|  |  -- and.py
|  |  -- config.yaml
|  -- apirer/
|  |  -- apirer.py
|  |  -- config.yaml
|  -- asker/
|  |  -- asker.py
|  |  -- config.yaml
|  -- barrier/
|  |  -- barrier.py
|  |  -- config.yaml
|  |  -- test_barrier.py
|  -- cleaner/
|  |  -- __init__.py
|  |  -- cleaner.py
|  |  -- config.yaml
|  -- counter/
|  |  -- config.yaml
|  |  -- counter.py
|  -- crawler/
|  |  -- config.yaml
|  |  -- crawler.py
|  -- croner/
|  |  -- config.yaml
|  |  -- croner.py
|  -- deleter/
|  |  -- config.yaml
|  |  -- deleter.py
|  -- dockerer/
|  |  -- config.yaml
|  |  -- dockerer.py
|  -- emailer/
|  |  -- config.yaml
|  |  -- emailer.py
|  -- ender/
|  |  -- config.yaml
|  |  -- ender.py
|  -- executer/
```

Tree appendix 3 of 8

```
-- config.yaml
-- executor.py
-- file_creator/
|   |-- config.yaml
|   |-- file_creator.py
-- file_extractor/
|   |-- config.yaml
|   |-- file_extractor.py
-- file_interpreter/
|   |-- config.yaml
|   |-- file_interpreter.py
-- flowbacker/
|   |-- config.yaml
|   |-- flowbacker.py
-- flowcreator/
|   |-- agentic_skill.md
|   |-- config.yaml
|   |-- flowcreator.py
-- flowhypervisor/
|   |-- config.yaml
|   |-- flowhypervisor.py
|   |-- hypervisor_alert.wav
|   |-- monitoring-prompt.pmt
-- forker/
|   |-- config.yaml
|   |-- forker.py
-- gateway_relayer/
|   |-- config.yaml
|   |-- gateway_relayer.md
|   |-- gateway_relayer.py
-- gatewayer/
|   |-- config.yaml
|   |-- gatewayer.md
|   |-- gatewayer.py
|   |-- gatewayer_explanation.md
-- gitter/
|   |-- config.yaml
|   |-- gitter.py
-- googler/
|   |-- config.yaml
|   |-- googler.py
-- image_interpreter/
|   |-- config.yaml
|   |-- image_interpreter.py
-- j_decompiler/
|   |-- config.yaml
|   |-- j_decompiler.py
-- jenkinser/
|   |-- config.yaml
|   |-- jenkinser.py
-- keyboarder/
|   |-- config.yaml
|   |-- keyboarder.py
-- kubernetes/
|   |-- config.yaml
|   |-- kubernetes.py
-- kyber_cipher/
|   |-- config.yaml
|   |-- kyber_cipher.py
-- kyber_decipher/
|   |-- config.yaml
|   |-- kyber_decipher.py
-- kyber_keygen/
|   |-- config.yaml
|   |-- kyber_keygen.py
-- mongoxer/
|   |-- config.yaml
|   |-- mongoxer.py
-- monitor_log/
|   |-- config.yaml
|   |-- monitor_log.py
-- monitor_netstat/
|   |-- config.yaml
|   |-- monitor_netstat.py
-- mouser/
|   |-- config.yaml
```

Tree appendix 4 of 8

```

|-- mouser.py
|-- mover/
|   |-- config.yaml
|   |-- mover.py
|-- node_manager/
|   |-- config.yaml
|   |-- node_manager.md
|   |-- node_manager.py
|   |-- nodes_example.json
|   |-- nodes_example.yaml
|-- notifier/
|   |-- config.yaml
|   |-- notifier.py
|-- or/
|   |-- config.yaml
|   |-- or.py
|-- parametrizer/
|   |-- config.yaml
|   |-- parametrizer.py
|-- prompter/
|   |-- config.yaml
|   |-- prompter.py
|-- psfer/
|   |-- config.yaml
|   |-- psfer.py
|-- pythonxer/
|   |-- config.yaml
|   |-- pythonxer.py
|-- raiser/
|   |-- config.yaml
|   |-- raiser.py
|-- recmailer/
|   |-- config.yaml
|   |-- recmailer.py
|-- scper/
|   |-- config.yaml
|   |-- scper.py
|-- shoter/
|   |-- config.yaml
|   |-- shoter.py
|-- sleeper/
|   |-- config.yaml
|   |-- sleeper.py
|-- sqler/
|   |-- config.yaml
|   |-- sqler.py
|-- ssher/
|   |-- config.yaml
|   |-- ssher.py
|-- starter/
|   |-- config.yaml
|   |-- starter.py
|-- stopper/
|   |-- config.yaml
|   |-- stopper.py
|-- summarizer/
|   |-- config.yaml
|   |-- summarizer.py
|-- telegramer/
|   |-- config.yaml
|   |-- telegramer.py
|-- telegramrx/
|   |-- config.yaml
|   |-- telegramrx.py
|-- teletlamatini/
|   |-- config.yaml
|   |-- teletlamatini.py
|-- whatsappper/
|   |-- config.yaml
|   |-- whatsappper.py
|-- whatstlamatini/
|   |-- config.yaml
|   |-- whatstlamatini.py
|-- doc_generation/
|   |-- complete_project_docs.py
|   |-- markdown_to_pdf.py

```

Tree appendix 5 of 8

```
-- refresh_project_docs.py
-- test_output.pdf
-- images/
|-- mockup.jpg
|-- TlamatiniAbout.jpg
|-- XAIHT-Tlamatini.mp4
-- imaging/
|-- converter.py
|-- image_interpreter.py
|-- screenshot.py
-- management/
|-- __init__.py
|-- commands/
|   |-- acpx_lint.py
|   |-- startserver.py
-- migrations/
|-- 0001_initial.py
|-- 0002_populate_db.py
|-- 0003_add_cleaner.py
|-- 0004_add_deleter.py
|-- 0005_add_executer.py
|-- 0006_add_notifier.py
|-- 0007_add_stopper.py
|-- 0008_add_recmailer.py
|-- 0009_add_whatstapper.py
|-- 0010_add_pythonxer.py
|-- 0011_add_asker.py
|-- 0012_repopulate_all_agents.py
|-- 0013_add_forker.py
|-- 0014_repopulate_all_agents.py
|-- 0015_add_shoter.py
|-- 0016_repopulate_all_agents.py
|-- 0017_add_ssher.py
|-- 0018_repopulate_all_agents.py
|-- 0019_add_scper.py
|-- 0020_repopulate_all_agents.py
|-- 0021_add_telegramrx.py
|-- 0022_repopulate_all_agents.py
|-- 0023_add_mongoxer.py
|-- 0024_repopulate_all_agents.py
|-- 0025_add_telegramer.py
|-- 0026_repopulate_all_agents.py
|-- 0027_add_sqler.py
|-- 0028_repopulate_all_agents.py
|-- 0029_add_prompter.py
|-- 0030_repopulate_all_agents.py
|-- 0031_add_flowcreator.py
|-- 0032_repopulate_all_agents.py
|-- 0033_add_gitter.py
|-- 0034_add_dockerer.py
|-- 0035_add_pser.py
|-- 0036_add_kubernereter.py
|-- 0037_add_apirer.py
|-- 0038_add_jenkinser.py
|-- 0039_add_crawler.py
|-- 0040_add_summarizer.py
|-- 0041_add_flowhypervisor.py
|-- 0042_add_mouser.py
|-- 0043_agentmessage_conversation_user.py
|-- 0044_add_counter.py
|-- 0045_add_file_interpreter.py
|-- 0046_add_image_interpreter.py
|-- 0047_add_gatewayer.py
|-- 0048_add_gateway_relayer.py
|-- 0049_add_node_manager.py
|-- 0050_add_file_creator.py
|-- 0051_add_file_extractor.py
|-- 0052_add_kyber_keygen.py
|-- 0053_add_kyber_cipher.py
|-- 0054_add_kyber_decipher.py
|-- 0055_fix_kyber_cipher_names.py
|-- 0056_add_parametrizer.py
|-- 0057_add_flowbacker.py
|-- 0058_add_barrier.py
|-- 0059_add_j_decompiler.py
|-- 0060_add_agent_parametrizer_tool.py
```

Tree appendix 6 of 8

```
-- 0061_add_agent_starter_tool.py
-- 0062_sync_agent_control_tools_and_prompts.py
-- 0063_add_agent_parametrizer_prompt.py
-- 0064_add_chat_agent_run_model.py
-- 0065_add_chat_wrapped_agent_tools.py
-- 0066_add_keyboarder.py
-- 0067_add_multi_turn_demo_prompts.py
-- 0068_add_googler_tool.py
-- 0069_add_googler_agent.py
-- 0070_add_teletlamatini.py
-- 0071_acpx_skills.py
-- 0072_add_acpx_demo_prompts.py
-- 0073_acpx_demo_gemini_uplift.py
-- 0074_simplify_demo_prompts.py
-- 0075_add_acpx_tool_surface.py
-- 0076_add_acpxer.py
-- 0077_add_whatstlamatini.py
-- 0078_add_chat_agent_keyboarder_tool.py
-- 0079_add_chat_agent_mouser_tool.py
-- 0080_add_chat_agent_sleeper_tool.py
-- 0081_add_window_present_and_run_wait_tools.py
-- __init__.py
-- monitors/
--   -- monitor_sql.py
-- opus_client/
--   -- claude_opus_client.py
--   -- examples.py
--   -- README.md
-- rag/
--   -- __init__.py
--   -- config.py
--   -- factory.py
--   -- interaction.py
--   -- interface.py
--   -- loaders.py
--   -- prompts.py
--   -- retrieval.py
--   -- splitters.py
--   -- utils.py
--   -- chains/
--     -- base.py
--     -- basic.py
--     -- history_aware.py
--     -- unified.py
-- services/
--   -- __init__.py
--   -- agent_contracts.py
--   -- agent_paths.py
--   -- answer_analyzer.py
--   -- filesystem.py
--   -- flow_compiler.py
--   -- flow_spec.py
--   -- response_parser.py
-- skills/
--   -- __init__.py
--   -- frontmatter.py
--   -- harness.py
--   -- io_contract.py
--   -- registry.py
-- skills_pkg/
--   -- _meta/
--     -- lint.py
--     -- schema.json
--   -- acp_router/
--     -- SKILL.md
--   -- github/
--     -- SKILL.md
--   -- gmail/
--     -- SKILL.md
--   -- hello_world/
--     -- SKILL.md
--   -- jira/
--     -- SKILL.md
--   -- notion/
--     -- SKILL.md
--   -- setup_new_acpx_key/
```


Tree appendix 7 of 8

```
| | | | | `-- SKILL.md
| | | | | -- skill_creator/
| | | | | | -- SKILL.md
| | | | | | -- scripts/
| | | | | | | -- quick_validate.py
| | | | | -- slack/
| | | | | | -- SKILL.md
| | | | | -- summarize/
| | | | | | -- SKILL.md
| | | | | -- tlamatini_allowed_hosts_tighten/
| | | | | | -- SKILL.md
| | | | | -- tlamatini_csrf_exempt_audit/
| | | | | | -- SKILL.md
| | | | | -- tlamatini_exec_report_row_adder/
| | | | | | -- SKILL.md
| | | | | -- tlamatini_flow_from_objective/
| | | | | | -- SKILL.md
| | | | | -- tlamatini_flw_doctor/
| | | | | | -- SKILL.md
| | | | | -- tlamatini_new_acp_agent/
| | | | | | -- SKILL.md
| | | | | -- tlamatini_planner_trace_replay/
| | | | | | -- SKILL.md
| | | | | -- tlamatini_static_version_bumper/
| | | | | | -- SKILL.md
| | | | | -- todoist/
| | | | | | -- SKILL.md
| | | | | -- trello/
| | | | | | -- SKILL.md
| | | | | -- weather/
| | | | | | -- SKILL.md
| | | | -- static/
| | | | | -- agent/
| | | | | | -- css/
| | | | | | | -- agent_page.css
| | | | | | | -- agentic_control_panel.css
| | | | | | | -- login.css
| | | | | | | -- tools_dialog.css
| | | | | | | -- welcome.css
| | | | | | -- img/
| | | | | | | -- spinner.svg
| | | | | | | -- Tlamatini.ico
| | | | | | -- js/
| | | | | | | -- acp-agent-connectors.js
| | | | | | | -- acp-canvas-core.js
| | | | | | | -- acp-canvas-undo.js
| | | | | | | -- acp-control-buttons.js
| | | | | | | -- acp-file-io.js
| | | | | | | -- acp-flow-snapshot.js
| | | | | | | -- acp-globals.js
| | | | | | | -- acp-layout.js
| | | | | | | -- acp-parametrizer-dialog.js
| | | | | | | -- acp-running-state.js
| | | | | | | -- acp-session.js
| | | | | | | -- acp-undo-manager.js
| | | | | | | -- acp-validate.js
| | | | | | | -- agent_page_canvas.js
| | | | | | | -- agent_page_chat.js
| | | | | | | -- agent_page_context.js
| | | | | | | -- agent_page_dialogs.js
| | | | | | | -- agent_page_init.js
| | | | | | | -- agent_page_layout.js
| | | | | | | -- agent_page_state.js
| | | | | | | -- agent_page_ui.js
| | | | | | | -- agentic_control_panel.js
| | | | | | | -- canvas_item_dialog.js
| | | | | | | -- chat_page_runtime_poller.js
| | | | | | | -- contextual_menus.js
| | | | | | | -- shared-runtime-dialogs.js
| | | | | | | -- tools_dialog.js
| | | | | | -- sounds/
| | | | | | | -- hypervisor_alert.wav
| | | | | | | -- notification.wav
| | | | | | -- video/
| | | | | | | -- XAIHT-Tlamatini.mp4
| | | | -- telegram/
```

Tree appendix 8 of 8

```
| | |-- AztecTlamatini.txt
| | |-- config.yaml
| | |-- telegram_receiver.py
| | |-- templates/
| | |-- agent/
| | |   |-- agent_page.html
| | |   |-- agentic_control_panel.html
| | |   |-- login.html
| | |   |-- welcome.html
|-- jd-cli/
| |-- jd-cli.bat
| |-- jd-cli.jar
|-- tlamatini/
| |-- __init__.py
| |-- asgi.py
| |-- context_processors.py
| |-- logging_filters.py
| |-- middleware.py
| |-- settings.py
| |-- urls.py
| |-- wsgi.py
```