

TLAMATINI

Complete Project Dossier: what the system does, how it works, how to use Tlamatini, complete repository file tree, and effective line inventory



Measure	Value
Generated	July 09, 2026 12:21 PM UTC-0600
Current HEAD	08efa1d2 - chore(release): bump package.json version to 1.38.1 for the v1.38.1 hotfix tag
Resolved version	1.38.1 (git)
Repository inventory files	816
Tracked files	816
Git-unignored working-tree additions	0
Workflow agents	84
Multi-Turn tools	93
Skills	27
Total effective lines	170,639
Total physical text lines	239,861

1. What Tlamatini Is

- Tlamatini is a self-hosted AI developer assistant (cloud LLMs by default; the app and RAG run locally) built with Django, Django Channels, LangChain, LangGraph, FAISS/BM25 retrieval, and a large in-repository agent application.
- She combines a browser chat surface, a Retrieval-Augmented Generation stack, a Multi-Turn tool executor, MCP-backed context providers, wrapped chat-agent runtimes, and a visual Agentic Control Panel for workflow design.
- She is designed for development operations: codebase analysis, file and directory context, deterministic file discovery/search/editing, command execution, Python execution, screenshots, web/search helpers, notifications and attention routing, DevOps tools, local model operation, Windows packaging and uninstall registration, first-person self-knowledge about her own runtime, and embedded-firmware control for STM32F4, ESP32-class, Arduino-class, and ESPHome smart-home boards.

Agent-directory disclaimer: user jurisdiction and responsibility

- The workflow agents in ``Tlamatini/agent/agents/`` are plain-Python programs on purpose: they are readable, editable, auditable operating code under the user's control.
- When a user enables, configures, modifies, chains, or runs those agents, the actions of those agents fall under that user's jurisdiction. The prompts, config files, secrets, credentials, files, folders, network targets, browsers, shells, APIs, external MCP servers, hardware devices, and downstream systems they touch are selected and authorized by the user.
- Tlamatini provides orchestration, documentation, and guardrails, but she cannot guarantee that every user-edited agent, workflow, external service, credential scope, target machine, or local environment is safe.
- Any security breach, data exposure, unauthorized action, credential leak, unsafe automation, policy violation, device damage, or other harm caused by running agents or agent workflows is the responsibility of the user who runs them.
- Operators should audit agents before use, restrict credentials and permissions, and operate them only on systems where they have explicit authorization.

What the system does

- Answers codebase questions with loaded file or directory context.
- Uses hybrid retrieval to extract metadata, split content, rank source chunks, and respect context budgets.
- Can discover files by glob pattern, search their contents by regex, and make surgical in-place replacements through the Globber, Grepper, and Editor agent/tool trio.
- Can connect to external MCP servers declared in ``external_mcps.json``, expose their remote tools to Multi-Turn under the ``ext__<server>__<tool>`` naming convention, and supervise those connections through `status / reconnect / doctor / import / list / call` helpers.
- Gives operators GUI-first database maintenance through the new DB dropdown for backup and staged database replacement.
- Lets operators manage provider secrets from the browser through the Config -> Access Keys Wizard instead of hand-editing ``config.json``.
- Can drive Blender through the Blenderer agent, using the official Blender MCP add-on socket to inspect scenes, mutate objects and materials, run raw code, and automate renders from chat or the workflow canvas.
- Can pause before every state-changing Multi-Turn execution and ask the operator to approve or deny that exact step through the Ask Execs checkbox.
- Can raise a Windows attention signal when the browser needs the operator: Ask Execs prompts and Notifier events can flash Tlamatini's own taskbar presence and leave an uppercase banner in ``tlamatini.log``.
- Registers packaged installs in Windows ``Installed apps`` / ``Programs and Features`` with a real uninstall entry, so the release behaves like a normal installed application instead of only a shortcut bundle.
- Can update packaged installs in place through About -> Check for updates: she checks the latest GitHub release, stages the download, swaps locked files externally, and preserves operator state such as ``config.json``, the database, and content.
- Hardens generated files: File-Creator's bulk-write path now preserves long content byte-complete even when it contains heavy quoting or semicolon-rich source text.

- Warns GPU-host operators before a directory-context load is likely to saturate VRAM and degrade embedding throughput.
- Exposes a coherent versioning surface across builds, runtime UI, logs, and an open health-check endpoint.
- Carries a first-person self-knowledge map so she can answer more accurately about her own architecture, ports, runtime modes, pages, and capabilities.
- Can command Kali Linux offensive-security tooling through MCP-Kali-Server for authorized recon, enumeration, web scanning, and assessment workflows.
- Can diagnose an external MCP before the first live connection through the MCP Doctor agent and wrapped ``chat_agent_mcp_doctor`` tool, checking transport, runtime requirements, PATH availability, placeholder secrets, and the next operator step.
- Can scaffold, author, build, flash, reset, and observe STM32F4 firmware through STM32er and the STM32 Template Project MCP, with a fail-safe preflight before any hardware mutation.
- Can scaffold, author, build, upload, and monitor ESP32-class firmware through ESP32er and PlatformIO Core, with zero-config bootstrap and a serial-aware preflight before hardware mutation.
- Can author YAML-based smart-home firmware through ESPHomer and ESPHome, including zero-config bootstrap, device-config generation, validation, compile, USB/OTA upload, and bounded log observation for ESP32 / ESP8266 / RP2040 / BK72xx devices.
- Can play media on the operator's machine: an audio file to the speakers through AudioPlayer (soundfile + sounddevice — volume in percent and a time-played budget that truncates a longer file or loops a shorter one), or a video file with audio on a chosen display through VideoPlayer (ffpyplayer, whose wheel bundles ffmpeg + SDL, plus an OpenCV window — display, volume, the same truncate/loop time budget, window size, and fullscreen); both are observational/output and ship on the canvas and as wrapped chat tools.
- Can SPEAK and LISTEN: Talker (text-to-speech) renders input_text to a 24 kHz WAV through an Ollama neural TTS model (default Orpheus-3b-FT) and is female-voice-only by design, while Whisperer (speech-to-text) records the microphone itself or transcribes a file via faster-whisper locally (NVIDIA-GPU auto-detect with an always-present CPU fallback) or a cloud Whisper API; both light a zero-latency console REC indicator driven by the live audio stream and are observational/output, on the canvas and as wrapped chat tools.
- Can manage real desktop windows by title: focus them, tile them, resize them, list them, and close them deterministically through Win32 calls.
- Can drive a real Playwright browser through scripted interactive steps for logins, forms, assertions, downloads, extraction, and end-to-end UI checks.
- Can drive a live Unreal Engine 5 editor through the Unreal MCP plugin, from either Multi-Turn chat or the visual workflow canvas.
- Actively reaps orphaned Windows console-host and pool-child processes so long Multi-Turn or ACPX sessions do not leave misleading Tlamatini-icon ghosts in Task Manager.
- Can autonomously kill only genuinely hung shell-wrapper subtrees through a boot-time command watchdog that measures CPU and I/O progress instead of guessing from elapsed time.
- Runs checked Multi-Turn requests through request-scoped planning, capability selection, tool calls, observations, monitoring, and final synthesis.
- Can optionally inspect and modify her own bundled source tree in self-modify builds after verifying that ``TlamatiniSourceCode/`` is actually present.
- Launches wrapped copies of selected workflow agents in isolated runtime folders without mutating templates.
- Lets users design, validate, save, pause, resume, and stop visual workflows through the Agentic Control Panel.
- Turns successful Multi-Turn tool executions into starter ``flw`` workflows that can be inspected and validated in ACP.
- Packages the project into a distributable Windows release with installer and uninstaller tooling.

How it works

- Browser UI sends chat and workflow requests through Django views and Channels WebSockets.
- RAG chains load selected file/directory context, retrieve relevant chunks, and build answer prompts.

- DB-menu actions validate directories or SQLite files in the browser, then call Django views that either copy the live database out or stage a replacement into `DB/ToLoad/db.sqlite3`.
- Config -> Access Keys Wizard reads masked provider-key status from the backend and persists only the edited secrets, keeping the browser flow honest without dumping live values back to the page.
- The file-navigation and file-edit trio sits above raw shell execution: Globber enumerates matching files, Grepper scans content with regex while pruning noisy/binary trees, and Editor performs byte-exact in-place replacements without rewriting an entire file.
- External MCP connectivity is catalog-driven: `external\_mcps.json` stores Claude-style `mcpServers` entries, `external\_mcp\_manager.py` negotiates stdio / streamable-HTTP / SSE / WebSocket transports, and wrapped remote tools are surfaced into the planner as `ext\_\_<server>\_\_<tool>` only after the connection is healthy.
- The MCP Doctor path is intentionally safer than a live connect: it reads the configured server entry, validates transport shape, runtime commands, PATH/toolchain presence, placeholder secrets, and docs/source URLs, then returns an onboarding diagnosis without consuming the server's real tool surface.
- Blenderer opens the official Blender MCP add-on TCP socket (default `localhost:9876`), sends one action payload or raw code-execution request, and returns the structured result through the same wrapped-tool / canvas contract used by the rest of the agent catalog.
- When Ask Execs is enabled, the synchronous Multi-Turn executor stops before each state-changing tool call, emits an `exec\_permission\_request`, and waits on `ExecPermissionBroker` until the browser sends Proceed or Deny.
- When the browser surfaces an Ask Execs prompt or a Notifier event, JavaScript can POST to `/agent/flash\_window/`; the backend then best-effort flashes the `Tlmatini.exe` console/taskbar window through `window\_flash.py` and prints an uppercase attention banner for the log.
- Installer-time registration writes a per-user HKCU Add/Remove Programs entry pointing at `Uninstaller.exe`, and frozen startup re-checks that entry through `windows\_app\_registration.self\_heal\_for\_frozen()` so older installs retroactively appear in Windows' uninstall surfaces.
- In-app self-update uses Django views plus `self\_update.py` to check GitHub releases, download and stage the selected package, then hand off the locked-file swap to the external `apply\_update.ps1` helper before relaunch.
- Frozen-build hardening now verifies media dependencies during packaging too: `build.py` embeds numpy and OpenCV in both shipped Python runtimes and refuses to produce a release if those imports are missing.
- Before a heavy directory embedding run on supported NVIDIA hosts, a fail-open pre-flight guard can estimate VRAM pressure and surface a non-blocking warning in chat.
- Version resolution now flows through git tags, a runtime resolver module, generated build artefacts, and an open `/agent/version/` endpoint.
- A first-person self-knowledge file (`Tlmatini.md`) is injected into prompt construction for all chains, but loaded user context still outranks that self-reference when the request is a generic summary of the provided project.
- When Multi-Turn is enabled, the global planner selects context and tool stages before the executor binds only the relevant tools, including wrapped deterministic agents such as De-Compressor.
- Optional self-modify builds bundle `TlmatiniSourceCode/`; `copy\_source\_assets.py` generates that snapshot with rebuild instructions and redacted secrets, and prompt rules require her to verify that directory exists before claiming she can inspect or change her own code.
- The Kalier path talks directly to the MCP-Kali-Server Flask API over HTTP with Python-stdlib `urllib`, auto-seeding the default box from `kali\_server\_url` in Config -> URLs before any one-off per-call override is applied, and captures one atomic `INI\_SECTION\_KALIER` block per run.
- The STM32er path spawns the STM32 Template Project MCP stdio server, performs the MCP initialize handshake, runs exactly one requested tool or composite action, and emits one atomic `INI\_SECTION\_STM32ER` block with the result, project directory, and stage metadata.
- Before any flash-capable STM32er action, a critical-mission preflight validates the arm-none-eabi toolchain, STM32CubeIDE, programmer path, ST-LINK presence, and STM32F-family match; compile-only steps can run boardless, but unsafe hardware mutations are refused fail-safe.
- The ESP32er path resolves or bootstraps PlatformIO Core, invokes `pio` subcommands directly with Python-stdlib process control, validates project and serial-port readiness, and emits one atomic `INI\_SECTION\_ESP32ER` block with stage, project, port, and stdout/stderr payloads.

- The ESPHomer path resolves or bootstraps the `esphome` CLI, can generate a minimal valid YAML device config headlessly, validates either a serial board or OTA host before upload/log actions, and emits one atomic `INI\_SECTION\_ESPHOMER` block with action, config path, stage, and captured CLI output.
- The Windower path uses Win32 APIs plus the cross-process `AttachThreadInput` focus-transfer dance to locate windows by title and apply one lifecycle action while still returning structured geometry/state fields.
- The Playwrighter path loads a declarative step list, drives Playwright against Chromium/Firefox/WebKit, and emits one atomic `INI\_SECTION\_PLAYWRIGHTER` block with status, assertions, extracted values, and the final URL.
- The Unreal path opens a TCP socket to the Unreal MCP plugin, sends one `{"type": command, "params": {...}}` payload, captures the JSON reply, and emits one `INI\_SECTION\_UNREALER` block for downstream logic.
- A boot-time command watchdog samples CPU time and I/O bytes across shell-interpreter subtrees and reaps only the ones that stay idle past the grace-and-streak window, protecting healthy long-running commands while rescuing wedged prompt waits.
- After spawn-capable tool calls and again after the final answer, the orphan reaper can sweep dead descendants, orphaned `conhost.exe` companions, and stale pool-linked processes without ever raising into the chat path.
- Tool calls execute in the backend, append observations, and may create wrapped runtime copies under `agent/agents/pools/\_chat\_runs\_`.
- On the next full start-up, `manage.py` can swap a staged database into place before Django imports, while archiving the previous live database under `DB/Older/<timestamp>`.
- ACP flows deploy session-scoped pool instances, wire config values, validate NxN graph rules, and execute through Starter-driven flow semantics.
- Build scripts collect static assets, bundle Django/Python resources, add agent templates, and assemble `pkg.zip`, `Uninstaller.exe`, and `dist/Tlmatini\_Release/`; `build.py --self-modify` additionally injects the generated source snapshot for self-rebuildable releases.

2. Architecture Layers

Layer	Role
Browser interfaces	Chat page plus Agentic Control Panel templates and JavaScript modules.
Django/Channels	Authentication, views, WebSockets, session state, message persistence, and ASGI startup.
RAG and context	Metadata extraction, text splitting, FAISS/BM25 retrieval, context budgeting, and fallback behavior.
Multi-Turn engine	Capability registry, global execution planner, explicit tool loop, answer parsing, and answer-success classification.
Tools and agents	Core tools, MCP context providers, wrapped chat-agent launchers, and the current visual workflow agent templates.
Packaging	PyInstaller build scripts, shortcut registration, `.flw` association, installer, uninstaller, and release folder assembly.

Design principles

- Evidence-first answers: Tlamatini grounds responses in selected project context and hybrid retrieval rather than freeform model memory.
- Explicit orchestration: checked Multi-Turn uses a visible tool loop, capability scoring, and staged planning instead of a single opaque call.
- Operational reversibility: risky changes such as database replacement are staged, archived, and delayed to the only safe window instead of hot-swapped mid-session.
- Fail-open diagnostics: GPU pressure probes and session-restore safeguards warn early without breaking CPU-only or degraded environments.
- Runtime isolation: wrapped chat-agent copies run in session-scoped folders so template agents remain pristine while live runs stay inspectable.
- Self-knowledge with scope discipline: she can talk accurately about herself without letting self-reference override a user-loaded project context.
- Operator truth over vibes: Exec Report tables, tlamatini.log, skill audits, and ACPX transcripts make the system auditable after execution.

3. Installation, Configuration, and Everyday Use

Start here - the easiest path

- BookOfTlmatini now leads with a five-step onboarding path because the easiest way to succeed with Tlmatini is to treat setup as one guided sequence instead of reading the whole handbook first.
- Recommended path for most operators: install the packaged release from GitHub Releases, launch the Start-menu shortcut, and let the bundled Python 3.12.10 plus dependencies carry the runtime without asking the user to install Python manually.
- Developer path stays available: clone the repo, create a virtual environment, install `requirements.txt`, run migrations, and start Django with `python Tlmatini/manage.py runserver --noreload`.
- After the app opens, the first in-app surfaces that matter are `Config -> Models`, `Config -> URLs`, and `Config -> Access Keys Wizard`; those now form the real beginner path, not manual JSON editing.
- For ordinary question-answering keep Multi-Turn off; turn it on only when you want Tlmatini to execute tools, wrapped agents, or remote MCP capabilities instead of answering directly.

Installation essentials

- The easiest path for most users is the packaged installer from GitHub Releases: no manual Python install is required because the release already carries Python 3.12.10 and the project dependencies.
- Source mode remains the developer path: clone the repo, create a virtual environment, install `requirements.txt`, run migrations, create a superuser, collect static files, and then launch Django.
- Packaged Windows installs open the browser at `http://127.0.0.1:8000/` and create the default `user / changeme` login; manual source installs use your own `createsuperuser` account instead.
- When a newer packaged release exists, the intended upgrade path is in-app: `About -> Check for updates`, not manual folder replacement.
- You can run either the checked-in cloud/back-end defaults from `Tlmatini/agent/config.json` or a local/remote Ollama-backed configuration with matching model names.

First configuration screens

- Three new onboarding screenshots now anchor the first-run path: `Tlmatini/agent/images/MenuConfig.jpg`, `ConfigureModels.jpg`, and `ACPXKeysConfigureWizard.jpg`.
- `Config -> Models` is the place where operators map embedding, chat, vision, and auxiliary model names to what Ollama actually exposes on the host machine.
- `Config -> Access Keys Wizard` now carries an especially important rule: a localhost Ollama usually needs no Ollama token, while a remote Ollama endpoint may require one.
- Saved model, URL, or credential changes can invalidate the assumptions of the current session, so reconnecting after major Config edits is now part of the honest operator guidance.

Configuration essentials

- Source mode resolves `Tlmatini/agent/config.json`; frozen builds resolve `config.json` next to the executable; `CONFIG\_PATH` overrides both.
- Core keys include `embedding-model`, `chained-model`, `ollama\_base\_url`, `ollama\_token`, `enable\_unified\_agent`, `unified\_agent\_model`, and `unified\_agent\_max\_iterations`.
- The checked-in default model baseline moved again in the recent Git window: the shared config now favors `glm-5.2:cloud`, so source or frozen installs that keep the shipped config should be documented as cloud-first unless the operator intentionally swaps models.
- URL configuration now also includes `kali\_server\_url`, the STM32er bootstrap fields `stm32\_mcp\_server\_script`, `stm32\_mcp\_python`, `stm32\_template\_dir`, `stm32\_ide\_root`, `stm32\_mcp\_repo\_url`, and `stm32\_mcp\_install\_dir`, plus ESP32er's `pio\_executable` and `pio\_core\_dir`, all edited from `Config -> URLs` and inherited automatically by the chat-side wrapped tools.

- Credential configuration is no longer hand-edit-only: Config -> Access Keys Wizard provides a browser-side path for ACPX, provider secrets, unified messaging, and Security Recon (ProjectDiscovery) keys such as ``pdcg_api_key`` while preserving masked status in the UI.
- The chat-side Config -> Models and Config -> URLs dialogs are now first-class configuration surfaces, and they can explicitly ask the operator to reconnect when saved values change live-session assumptions.
- The separate DB dropdown is not a config editor: it is a maintenance surface for copying the live SQLite database out or staging a replacement for the next full start-up.
- Multi-Turn is toggled from the chat toolbar, but it depends on the unified-agent configuration and the selected model/base-url pairing being valid; the current default iteration ceiling is 4096, and Ask Execs only becomes available when Multi-Turn itself is on.
- Image-Interpreter now uses three model slots from Config -> Models: ``image_interpreter_model`` for the first forensic interpreter, ``image_interpreter_model_2`` for the second holistic interpreter, and ``image_merging_model`` for the final report merger.

DB menu and database swap-in

- The new DB dropdown gives operators two GUI-first maintenance paths: ``Backup database`` copies the live SQLite file out, and ``Set DB`` stages a chosen ``db.sqlite3`` for the next full start-up.
- Both dialogs are live-validated in the browser and now expose Browse buttons that open native host-side pickers for folders or ``db.sqlite3`` files.
- Backup is read-only and uses the currently live database path; Set DB never hot-swaps the file mid-session because Django already holds SQLite open.
- Set DB writes the selected file to ``DB/ToLoad/db.sqlite3``; the real swap happens only at the top of ``manage.py`` before Django imports anything.
- When that swap runs, the previous live database is moved into ``DB/Older/<timestamp>/db.sqlite3``, creating a built-in rollback trail instead of overwriting history.
- Reconnect is not enough for this path: the operator must fully restart Tlmatini so the pre-Django swap window opens again.
- If the staged file is bad or locked, startup fails open: Tlmatini logs the error and continues with the previous live database.

Versioning system

- Tlmatini now follows Semantic Versioning 2.0.0 with git tags as the single source of truth: you tag, then you build, instead of hand-editing version strings across files.
- The build path resolves a version once and propagates it into generated runtime metadata, Win32 VERSIONINFO resources, and the release-folder naming convention.
- On untagged commits the resolver falls back honestly to a git-derived development version instead of failing the build or lying about the release state.

Version surfaces

- Operators can now see the running version in the About dialog, the startup banner, the open ``GET /agent/version/`` health-check endpoint, and Windows file properties on the built executables.
- Packaged installs also project the same release identity into Windows' Installed-apps metadata through the ARP ``DisplayVersion`` field, so the uninstall surface and the binaries agree on the version being removed.
- The runtime resolver lives in ``Tlmatini/agent/version.py``, while the build-oriented coordination logic lives in the repo-root ``versioning.py`` and the longer policy notes live in ``VERSIONING.md``.
- Build overrides are supported in a predictable order: CLI ``--version``, then ``TLMATINI_VERSION``, then git describe, then the sentinel ``0.0.0+unknown``.

Current release focus in 1.38.1

- The repository currently resolves to the `v1.38.1` release line (HEAD is the tagged hotfix commit `08efa1d2`), with README.md, BookOfTlmatini.md, Git history, source inspection, and generated inventory tables confirming the workflow-agent, Multi-Turn-tool, skill, asset, and effective-line totals.
- `v1.36.0` is the Video-Analyzer release: the new `video\_analyzer` workflow agent and wrapped `chat\_agent\_video\_analyzer` tool read recorded videos, check for motion, ask two vision models for independent evidence, merge their reports, and emit explicit routeable verdict tokens.
- `v1.35.0` improves prompt discovery: the Tools dialog prompt cards now search by substring, word-start, and fuzzy matches and show mode badges so operators can navigate the larger seeded prompt catalog without memorizing exact names.
- The post-tag flow-layout commit improves generated `.flw` layout: chat-created workflows now use a serpentine/boustrophedon grid so long Starter -> Agent -> ... -> Ender chains stay readable on the canvas instead of drifting off-screen.
- The newest committed reliability wave adds `agent/self\_healing.py`: Multi-Turn model steps are watchdog-bounded, retry through distinct tactics, broadcast recovery status, and preserve completed agent work in degraded answers instead of discarding evidence.
- Create Flow now follows concrete tool evidence rather than the removed whole-answer classifier: the button appears when Multi-Turn produced at least one successful agent call, and generated `.flw` downloads keep only successful executions.
- The live frontend follow-up keeps the browser honest during self-healing: `agent\_page\_chat.js` recognizes live tactic-status frames and re-asserts the busy/Cancel state until the real final answer arrives.
- Create Flow resolution now tolerates display-name drift: successful calls are normalized against the live Agents sidebar, resolvable successes are kept, and unresolved successful entries are skipped instead of disabling the whole button.
- The newest committed Discoverer wave adds PDCP key wiring: `PDCP\_API\_KEY` can be managed from Config -> Access Keys Wizard -> Security Recon (ProjectDiscovery), auto-injected into `chat\_agent\_discoverer`, redacted from `.flw`, and scrubbed by `regen\_secrets.py`.
- Discoverer's CVE lane now treats the legacy `cvemap` tool key as ProjectDiscovery `vulnx`: the old cvemap API was retired in August 2025, so Tlmatini installs/runs the `vulnx` binary, supports `search`/`id`, and counts object-style JSON findings correctly.
- The private Go toolchain remains self-contained under `/Go`, but `.gitignore` and `git\_deny\_go.py` now make Go compiler/cache/tool binaries invisible to Git and block accidental commits with a pre-commit guard.
- `v1.34.x` adds the triple-model Image-Interpreter release and the matching Config -> Models dialog work: three visible model fields now correspond to interpreter 1, interpreter 2, and image merger instead of hiding a multi-model agent behind one old vision-model slot.
- `v1.33.x` remains the Zavuerer release family: the Zavu unified-messaging workflow agent adds SMS, WhatsApp, Telegram, Email, and Voice delivery through one configured API key, with setup-wizard dedupe and cloud-default cleanup carried forward.
- README.md and BookOfTlmatini.md continue to present the MIT-licensed project, the Agent-directory responsibility disclaimer, the easy-start installation path, Ollama setup guidance, and the full operator story instead of a narrow changelog summary.
- The resulting PDF/PPTX refresh treats `v1.38.1` — the robotic-arm looping milestone `v1.38.0` plus the frontend-state-recovery hotfix — as the current product snapshot while preserving the historical context for self-update, media agents, deterministic file tools, firmware agents, External MCPs, ACPX skills, Zavuerer, and Image-Interpreter.

v1.38.0 robotic loop closure

- `v1.38.0` is the milestone where the Robotic-Loop-Training story became concrete: Tlmatini demonstrated a closed hardware loop by programming a robotic arm from a blank page and two cameras.
- The loop is intentionally composable rather than one monolith: STM32er writes/builds/flashes firmware, Camcorder records the physical attempt, Video-Analyzer judges the captured motion, and Forker routes the next branch.
- Video-Analyzer keeps the loop conservative: a deterministic OpenCV gate rejects no-motion clips before model spending, then two independent Ollama cloud vision interpreters must agree before `PASS\_OK` is emitted.

- Forker branches on substring-safe ``TLM_VERDICT::<TOKEN>`` markers, so ``FAIL_NO_MOTION``, ``FAIL_WRONG_MOTION``, ``UNCLEAR``, or ``ANALYSIS_ERROR`` can never accidentally match the success route.
- The PDF and PPTX now describe that loop as a system capability, not merely a release-note flourish, because it explains how Tlmatini can iteratively improve real hardware with observed evidence.

v1.38.1 frontend-state recovery hotfix

- ``v1.38.1`` is the same-week frontend-state-recovery hotfix: `package.json` is aligned at the tagged HEAD ``08efa1d2``, while the functional fix landed in ``af356c31`` after the ``85ee4e6c`` const-poison incident.
- The core contract is explicit: cross-file runtime globals in ``agent_page_state.js`` and ``acp-globals.js`` that other modules reassign must remain ``let``, because per-file ESLint cannot see those cross-file writes.
- ``agent/test_frontend_mutable_state.py`` now guards both source files and collected staticfiles so an automated cleanup cannot silently turn chat state, ACP state, tools, agents, skills, history, or busy flags back into ``const``.
- The Catalog of Prompts now loads through one secure ``GET /agent/list_prompts/`` endpoint ordered by ``idPrompt``, eliminating expected-404 console spam and preventing an ``idPrompt`` gap from hiding later prompts.
- The legacy prompt probe loop remains as an offline fallback, and the same fix also hardened dialogs: Configure-Mcps probe loops exit cleanly, About-video ``play()`` promises are guarded, and Esc closes About/Update overlays.

Post-v1.36.0 self-healing Multi-Turn reliability

- Every Multi-Turn model step now goes through ``agent/self_healing.py::SelfHealingInvoker``, so model calls are bounded by ``unified_agent_llm_step_timeout_seconds`` and retried with distinct tactics instead of hanging silently.
- Recovery tactics include plain retry, short back-off, trimming oldest messages with ``trim_messages``, and a tool-less summary fallback; the ladder can run up to ``unified_agent_llm_step_max_tactics`` unless the user presses Cancel.
- A status broadcaster registered by ``consumers.py`` sends live first-person recovery messages to the user's chat while the executor works in a worker thread.
- If recovery is exhausted after agents already ran, ``mcp_agent.py`` builds a degraded but truthful answer from real ``ToolMessage`` results, preserves Exec Report/Create Flow evidence, and prepends ``recovery_preamble(...)`` instead of claiming no tools ran.
- Coverage includes ``agent/test_self_healing.py``, ``agent/tests.py``, ``Tlmatini/tests_e2e/test_self_healing_visual.py``, and ``Tlmatini/tests_e2e/test_create_flow_visual.py`` for visible browser validation.
- Frontend follow-up: ``agent_page_ui.js::isSelfHealingStatusMessage()`` anchors on leading ``Tactic #`` or ``Tactic `` status frames so ``appendChatMessage()`` keeps controls disabled and the Send button on Cancel while the run is still executing.
- The matcher deliberately avoids substring matching because the final ``recovery_preamble(...)`` quotes tactic lines; a loose ``includes`` match would misclassify the final answer and trap the UI on Cancel forever.

Create Flow and Exec Report gating

- The whole-answer SUCCESS/FAILURE classifier ``agent/services/answer_analyzer.py`` was removed on 2026-07-06, so no extra LLM round trip computes ``answer_success``.
- The browser now shows Create Flow when Multi-Turn ran, at least one successful tool call resolves to a registered canvas agent, and the user is not anonymous.
- Successful tool calls are resolved through a punctuation/space/case-insensitive registry key, so display names such as ``File Creator``, ``File-Creator``, and ``filecreator`` converge to the live Agents sidebar entry.
- Generated ``flw`` downloads keep only successful, resolvable tool-call entries, post a successful-only ``tool_calls_log`` to ``/agent/flow_from_tool_calls/``, and drop failed or unregistered executions rather than turning them into broken workflow nodes.
- If the registry cannot load, the frontend fails open: the button stays available and the backend flow normalizer remains the final validation layer.
- Exec Report remains per-tool evidence, not a whole-answer verdict; the checkbox is disabled/greyed unless Multi-Turn is checked.

Frontend recovery controls and Create Flow name resolution

- ``agent_page_chat.js::appendChatMessage()`` now has a self-healing status branch before the final-answer branch, so status frames render without calling ``enableControlsAfterOperation()``.
- ``disableControlsDuringOperation()`` is re-applied idempotently for each live tactic status line, preserving the user's Cancel button while the worker thread continues.
- ``agent_page_ui.js::isSelfHealingStatusMessage()`` strips leading icons/symbols and then anchors on ``Tactic #`` / ``Tactic``, matching standalone status frames but not the final recovery summary.
- Create Flow validation now uses ``_resolveSuccessfulAgents()``, ``_agentNameKey()``, and ``_buildRegistryKeyMap()`` to normalize display names against the live registry and skip only unresolved successful entries.
- ``eslint.config.mjs`` declares ``isSelfHealingStatusMessage`` as a global, while ``docs/claude/frontend.md``, ``docs/claude/multi-turn.md``, and ``docs/claude/recent-fixes.md`` document the gotcha and the no-substring rule.

Discoverer PDCP key integration

- Discoverer now has an optional ProjectDiscovery Cloud Platform key (``pdcpi_key`` / ``PDCP_API_KEY``) for cvemap/vulnx rate limits and nuclei ``-ai`` or cloud upload features.
- Config -> Access Keys Wizard exposes ``Security Recon (ProjectDiscovery)``, writes the key to ``config.json``, ``data.keys``, and ``agent/agents/discoverer/config.yaml``, and blank fields preserve existing values.
- ``tools._seed_global_agent_defaults`` auto-injects the configured key into every ``chat_agent_discoverer`` run so prompts never paste the credential.
- ``agent_contracts.py`` redacts ``pdcpi_key`` from ``.flw`` exports, and ``regen_secrets.py`` scrubs it back to ``PDCP_API_KEY`` before a push-able tree.
- The new ``0169_add_discoverer_cvemap_latest_demo_prompt.py`` migration seeds a passive latest-CVE briefing prompt that uses cvemap/vulnx and reports whether ``pdcpi_used`` was active.

Discoverer vulnx and Go-toolchain Git-deny guard

- ProjectDiscovery retired cvemap's CVE API in August 2025, so Tlmatini keeps the operator-facing ``cvemap`` tool key but installs and runs ProjectDiscovery's successor binary, ``vulnx``.
- ``discoverer.py`` now maps ``cvemap`` to ``github.com/projectdiscovery/cvemap/cmd/vulnx@latest``, resolves the installed binary as ``vulnx``, and builds ``vulnx id <CVE>`` or ``vulnx search --severity ... --product ... --limit ...`` arguments.
- The findings counter now understands vulnx object JSON such as ``{"count": N, "results": [...]}``, so Exec Report and Forker routing see the real result count instead of a misleading one-line object.
- The private Go compiler and ProjectDiscovery tool binaries still install under ``<install_dir>/Go`` / ``<install_dir>/Go/bin-tools``, keeping the runtime self-contained and avoiding any system Go or PATH mutation.
- The ``.gitignore`` Go-deny block, tracked ``git_deny_go.py``, and its managed pre-commit hook prevent ``Go/``, ``bin-tools/``, ``go-build/``, ``pkg/mod/``, and downloaded Go archives from entering source control; ignored ``Go/`` content is not counted as project code.
- The committed asset wave also includes ``0169_add_discoverer_cvemap_latest_demo_prompt.py``, ``.claude/skills/tlmatini-daily-chat-test/harness/discoverer_1000.py``, and ``Tlmatini/agent/test_discoverer_thousand.py`` for latest-CVE and high-volume Discoverer validation.

v1.36.0 Video-Analyzer release delta

- Release identity: latest reachable public tag ``v1.38.1``; the live HEAD is the tagged hotfix commit itself (frontend state recovery + the one-call ``/agent/list_prompts/`` prompt catalog).
- New agent: Video-Analyzer becomes the current media-verdict workflow agent and wrapped ``chat_agent_video_analyzer``, complementing Image-Interpreter with video-specific motion analysis.
- Implementation assets: ``agent/agents/video_analyzer/``, migrations ``0166_add_video_analyzer.py``, ``0167_add_chat_agent_video_analyzer_tool.py``, ``0168_add_video_analyzer_demo_prompt.py``, ``test_video_analyzer_agent.py``, ``chat_agent_registry.py``, ``mcp_agent.py``, and ``services/agent_contracts.py`` all move together.

- Model strategy: ``interpreter_model_1`` defaults to ``qwen3-vl:235b-cloud``, ``interpreter_model_2`` defaults to ``qwen3.5:cloud``, and ``merging_model`` defaults to ``glm-5.2:cloud``, with independent calls merged only after both interpreters report.
- Routing contract: every run emits ``INI_SECTION_VIDEO_ANALYZER`` plus ``TLM_VERDICT::<TOKEN>`` markers such as ``PASS_OK``, ``FAIL_NO_MOTION``, ``FAIL_WRONG_MOTION``, ``UNCLEAR``, and ``ANALYSIS_ERROR`` for Forker and Parametrizer.
- Adjacent UI work: prompt search moved from exact-title hunting to substring, word-start, and fuzzy matching, and generated ``flw`` files now use a serpentine layout to reduce visual congestion.

Video-Analyzer motion-verdict agent

- Video-Analyzer is Tlamatini's video-verdict agent: she receives ``video_pathfilenames`` as a direct file, wildcard, folder-newest rule, or Camcorder pool name and resolves the video before model calls begin.
- The first gate is deterministic and cheap: OpenCV/numpy frame sampling computes a motion score and returns ``FAIL_NO_MOTION`` without spending LLM calls when the recording clearly shows no movement.
- When motion exists, two Ollama cloud vision models run in parallel. One specializes in temporal/action evidence, the other provides an independent holistic judgement, and a merger model produces the final report.
- The final answer is intentionally conservative: PASS requires both interpreters to agree; disagreement or weak evidence becomes ``UNCLEAR``, and wrong movement becomes ``FAIL_WRONG_MOTION`` rather than a false pass.
- Structured output is ``INI_SECTION_VIDEO_ANALYZER`` with ``video_path``, ``verdict``, ``verdict_token``, ``confidence``, ``motion_score``, ``frames_analyzed``, model names, ``status``, and the body report.
- The robotics loop is now explicit: STM32er can flash firmware, Camcorder can record the board, Video-Analyzer can judge the recorded motion, and Forker can branch on the ``TLM_VERDICT::`` token to retry or finish.

Prompt search and generated .flw layout

- Prompt search now behaves like an operator tool instead of a static dropdown: substring matches, word-start matches, fuzzy scoring, and mode badges make the full seeded prompt catalog navigable.
- The prompt-card rendering work was validated against the seeded catalog so one-shot, Multi-Turn, ACPX, Exec Report, and Step-by-Step prompt families remain distinguishable while searching.
- Generated ``flw`` workflows now use a serpentine canvas layout with row capacity and alternating direction, preserving the logical Starter -> Agent -> ... -> Ender order without pushing large chains into an unreadable line.
- This matters for documentation because the PDF and deck must describe not only new agents, but also the operator usability improvements that make the larger system actually usable.

v1.33.2 Zavuerer release delta

- Release identity: latest reachable public tag ``v1.33.2``; the generated artifacts now describe the Zavuerer release family plus post-release cleanup while preserving the v1.32.0 quality-and-identity background.
- New agent: Zavuerer becomes the 83rd workflow-agent type and the 60th wrapped chat-agent, adding ``chat_agent_zavuerer`` for Zavu unified messaging across SMS, WhatsApp, Telegram, Email, and Voice.
- Configuration: Config -> Access Keys Wizard now includes ``Unified Messaging (Zavu)`` and persists ``zavu_api_key``, which the wrapped runtime seeds into Zavuerer without exposing the secret in prompts.
- Canvas/runtime support: ``agent_contracts.py``, ``views.py``, ``capability_registry.py``, ``chat_agent_registry.py``, ``tools.py``, frontend ACP JS/CSS, and migrations ``0159``-``0164`` all move together to make Zavuerer usable from both surfaces.
- Follow-up defaults: ``config.json`` now favors ``glm-5.2:cloud`` across the primary chat/model slots, and the latest commits also adjust runtime parsing/middleware/settings surfaces around the release.
- Cost and safety wording: sign-up for Zavu is free, but sends are pay-as-you-go per message; the docs keep the authorized, opted-in recipient boundary explicit for A2P, WhatsApp-window, consent, and GDPR-style rules.

Zavuerer unified-messaging agent

- Zavuerer is Tlamatini's new Zavu unified-messaging agent: one workflow node and one wrapped ``chat_agent_zavuerer`` tool can send SMS, WhatsApp, Telegram, Email, or Voice messages through Zavu's ``/v1/messages`` API.

- The operator configures one `zavu\_api\_key` through Config -> Access Keys Wizard -> Unified Messaging (Zavu), and the runtime seeds that key into Zavuerer automatically so prompts never need to repeat or expose the secret.
- The agent speaks direct HTTP through the Python standard library, has a safe `health` action, refuses sends when the key/recipient/body/channel are invalid, and always emits `INI\_SECTION\_ZAVUERER` for Parametrizer/Forker branching.
- Canvas integration is complete: `agent\_contracts.py` redacts `zavu\_api\_key`, `views.py` handles Zavuerer connections, frontend CSS/JS gives the node a visible identity, and migrations `0159`-`0164` seed the Agent, Tool, demo/catalog prompts, and setup-wizard dedupe.
- Cost and safety boundary: Zavu sign-up is free, but sending is pay-as-you-go per message; Zavuerer must only message authorized, opted-in recipients, with A2P, WhatsApp 24-hour-window, consent, and GDPR-style responsibilities called out explicitly.

Image-Interpreter triple-model vision pipeline

- Image-Interpreter is now a triple-model vision analyst, not a single generic image describer: each image goes through two parallel interpreter calls and one merger pass.
- `interpreter\_model\_1` defaults to `qwen3.5:cloud` and is tuned for forensic OCR, mockup/GUI element inventories, percent-based positions/sizes, colors, fonts, and verbatim text.
- `interpreter\_model\_2` defaults to `gemma4:cloud` and reads the image holistically: design intent, visual hierarchy, scene meaning, people, and reasoned identity hypotheses.
- `merging\_model` defaults to `glm-5.2:cloud`; it waits behind a barrier until both interpretations arrive, then emits one definitive report with union-of-facts, conflict notes, and discrepancy handling.
- All four prompt surfaces (`prompt\_user`, `prompt\_interpreter\_model\_1`, `prompt\_interpreter\_model\_2`, and `prompt\_merging\_model`) receive the image file name as an identity clue, because a file named after a person often depicts that person.
- Fail-safe behavior is explicit: one failed interpreter still lets the merger work from the survivor; a failed merger returns both raw interpretations concatenated instead of losing the analysis.
- The structured output is now `INI\_SECTION\_IMAGE\_INTERPRETER` with `file\_path`, `interpreter\_model\_1`, `interpreter\_model\_2`, `merging\_model`, `status`, and the merged report body for Parametrizer/Forker routing.
- Config -> Models now exposes all three Image-Interpreter model slots (`image\_interpreter\_model`, `image\_interpreter\_model\_2`, `image\_merging\_model`), and older preserved configs receive defaults so Save is not blocked by empty new fields.

External MCP universal client

- The `v1.26.0` headline feature is the External MCP universal client: Tlamatini can now consume any MCP server declared in `external\_mcps.json` instead of depending only on bundled MCP integrations.
- Four transports are supported in the current implementation — stdio, streamable HTTP, legacy SSE, and WebSocket — and the active server set is intentionally bounded so operators can expose high-value remote tools without flooding the planner.
- Once connected, remote MCP tools are wrapped into the same Multi-Turn execution surface under `ext\_\_<server>\_\_<tool>`, so they participate in planning, execution reporting, Ask Execs, and the rest of the operator guardrails instead of becoming a parallel hidden subsystem.

MCP Doctor agent and wrapped tool

- MCP Doctor is the new onboarding and triage specialist added with the External MCP release: she inspects a configured server entry and tells the operator what is wrong before a live connection attempt wastes time.
- The diagnostic checks cover transport shape, runtime command availability on PATH, placeholder or missing secrets, endpoint/source/docs links, and the concrete next step the operator should take to make the server connectable.
- Operators can reach the same behavior from both surfaces that matter: the MCP Doctor workflow agent on the canvas and the wrapped `chat\_agent\_mcp\_doctor` tool inside Multi-Turn.

External MCP implementation assets

- The release is backed by real tracked assets rather than markdown-only claims: ``agent/external_mcp_manager.py``, ``agent/external_mcps.json``, the ``agent/agents/mcp_doctor/`` tree, the ``0141`-`0143`` migrations, ``static/agent/js/external_mcps_dialog.js``, and ``static/agent/css/external_mcps_dialog.css`` are the core implementation wave.
- The current test surface proves this is not a shallow UI feature: ``test_external_mcp_universal.py``, ``test_external_mcp_transports.py``, ``test_external_mcp_e2e.py``, ``test_external_mcp_add_flow.py``, and ``test_parametrizer_mcp_doctor.py`` exercise the universal-client path and the onboarding diagnosis path.
- Handbook evidence now exists alongside the code too: the README tutorial, Book sections, capability/planner wiring, and the dialog assets all moved together in the same release wave, with later cleanup removing obsolete draft documentation from the tracked tree.

Blenderer

- Blenderer was introduced in ``v1.20.0`` as the 77th workflow agent and remains the direct bridge to the official Blender MCP add-on, letting Tlamatini operate a live Blender session from either Multi-Turn chat or the visual workflow canvas.
- The bridge talks over a TCP socket (default ``localhost:9876``) and supports both raw ``execute_code`` requests and higher-level scene/object/material/render actions, so operators can mix deterministic verbs with precise Python-driven 3D automation.
- This extends Tlamatini beyond code and firmware orchestration into DCC / 3D-production work: asset inspection, scene mutation, material changes, camera setup, and render-triggering now live inside the same operator surface as the rest of the system.

In-app self-update

- The packaged application now includes an in-app self-update flow exposed from About -> Check for updates, so operators can refresh a frozen install without manually unpacking and replacing the entire release folder.
- The backend checks the latest GitHub release, downloads and stages the package, then hands off the locked-file swap to ``apply_update.ps1``, which performs the replacement after the running executable exits and relaunches the updated app.
- The update path is state-preserving by design: it keeps ``config.json``, user content, and one ``agents_backup`` generation, and it stages the user's database through ``DB/ToLoad/`` plus ``post_update_migrate.flag`` so the next launch restores and migrates that DB instead of wiping it.

Self-modify source snapshot

- Self-modify builds now rely on ``copy_source_assets.py`` to generate ``TlamatiniSourceCode/`` as a fresh rebuild-oriented snapshot of the repository.
- That snapshot includes source, build scripts, docs, skills, and small required binaries while deliberately omitting or redacting heavy media and secrets; ``_REBUILD_INSTRUCTIONS.md`` plus ``_SOURCE_SNAPSHOT_MANIFEST.json`` explain how to restore the missing payloads.
- Because the snapshot is optional, the runtime contract remains strict: Tlamatini must verify that ``TlamatiniSourceCode/`` exists before claiming she can inspect, modify, or rebuild herself.

API-Keys Wizard

- Config now includes an Access Keys Wizard / API-Keys Wizard path so operators can manage provider credentials from the browser instead of editing ``config.json`` directly.
- The backend exposes masked status plus explicit save endpoints, which keeps the operator flow convenient without echoing raw secrets back into the page.
- That feature arrives as a real asset wave, not just a hidden helper: ``agent/access_key_wizard.py``, ``static/agent/js/access_keys_wizard.js``, ``static/agent/css/access_keys_wizard.css``, and the updated ``templates/agent/agent_page.html`` now form a dedicated setup surface.
- This matters operationally because ACPX agents, cloud LLM providers, and adjacent integrations often fail for simple missing-key reasons; the wizard turns that setup into a first-class UI workflow.

New assets in the current release wave

- Recent assets worth calling out explicitly now span several release waves: onboarding screenshots ``agent/images/MenuConfig.jpg``, ``agent/images/ConfigureModels.jpg``, and ``agent/images/ACPXKeysConfigureWizard.jpg``; the External MCP + MCP Doctor implementation files; data-preserving updater files; numpy/OpenCV build checks; deterministic file-agent directories; and the ESPHomer smart-home firmware tree.
- The ``v1.36.0`` wave added concrete video-verdict assets: ``agent/agents/video_analyzer/``, migrations ``0166`-`0168``, ``test_video_analyzer_agent.py``, ``chat_agent_video_analyzer`` registry wiring, Video-Analyzer service contracts, and a seeded robotic-loop demo prompt.
- The adjacent ``v1.35.0``-through-``v1.38.1`` work updates prompt-card search/rendering assets (now fed by the one-call ``/agent/list_prompts/`` endpoint), ``flw`` generation layout code, and the restored-mutable frontend state, so the latest operator improvements are visible in JavaScript/CSS and canvas workflow output, not only markdown.
- The newest committed reliability assets include ``agent/self_healing.py``, ``agent/test_self_healing.py``, ``Tlmatini/tests_e2e/test_self_healing_visual.py``, ``Tlmatini/tests_e2e/test_create_flow_visual.py``, and coordinated changes in ``mcp_agent.py``, ``consumers.py``, ``response_parser.py``, and the chat frontend.
- The committed Discoverer PDCP assets include ``access_key_wizard.py`` Security Recon fields, ``tools.py`` default seeding, ``agent_contracts.py`` ``flw`` redaction, ``regen_secrets.py`` scrubbing, and migration ``0169_add_discoverer_cvemap_latest_demo_prompt.py`` for the latest-CVE prompt.
- Discoverer hardening assets now include ``discoverer.py`` changes for ``cvemap`` -> ``vulnx``, ``gitignore`` Go-deny patterns, tracked ``git_deny_go.py`` guard/pre-commit installer, ``discoverer_1000.py``, and ``test_discoverer_thousand.py`` validation coverage.
- The project inventory is rebuilt from ``git ls-files`` plus ``git ls-files --others --exclude-standard`` on every run, so any git-unignored local assets are counted while ignored runtime caches such as ``Go/`` remain outside the dossier.
- The newest frontend assets include ``agent_page_chat.js``, ``agent_page_ui.js``, ``eslint.config.mjs``, and the Claude frontend/Multi-Turn/recent-fixes notes that document self-healing status frames and Create Flow name resolution.
- The earlier ``v1.33.2`` wave adds or updates concrete assets too: ``agent/agents/zavuerer/``, migrations ``0159`-`0164``, Zavu Access Keys Wizard fields, planner hints, wrapped-tool registration, and the latest messaging-agent config defaults.
- The newest agent assets are concrete: ``agent/agents/zavuerer/``, migrations ``0159_add_zavuerer.py`` through ``0164_dedup_zavuerer_setup_wizards.py``, ``test_zavuerer_agent.py``, Access Keys Wizard Zavu fields, planner capability hints, wrapped-tool registration, and ACP canvas styling/connection support.
- The latest cleanup/assets span also includes ``GEMINI.md``, ``FirstFinalPlanToSpeedUp.md``, ``docs/claude/recent-fixes.md``, ``response-parser/runtime/settings/middleware`` touch-ups, and removal of the stale ``Tlmatini/db.sqlite3.bak-prereseat`` backup from the tracked surface.
- The same wave preserves evidence-oriented tests and build guards such as ``test_private_data_guard.py``, performance/visual checks, About-window authorship tests, and public-release verification rules that distinguish sensitive PII from valid creator names.
- The same span refreshes shipped visual/media assets: ``TlmatiniAbout.png`` replaces the old ``TlmatiniAbout.jpg``, and ``agent/images/TlmatiniAndKyber.mp4`` is part of the repository asset set described by the dossier.
- The same recent window also retains the earlier self-modify/browser-setup asset wave — ``copy_source_assets.py``, ``agent/access_key_wizard.py``, ``static/agent/js/access_keys_wizard.js``, ``static/agent/css/access_keys_wizard.css``, and the Blender control surface in ``agent/agents/blenderer/``.
- Key operator/runtime files such as ``prompt.pmt``, ``chat_agent_registry.py``, ``tools.py``, ``views.py``, ``urls.py``, ``manage.py``, ``file_extractor.py``, and the File-Creator/File-Extractor templates also changed, so the visible features are backed by concrete implementation assets rather than documentation-only promises.
- Because the dossier already includes the full repository inventory (git-tracked files plus git-unignored working-tree additions) and the full line-count inventory, these named assets serve as the human-readable shortlist of what changed most materially in the latest release wave.

File-Creator hardening

- The ``v1.19.5`` File-Creator hardening pass fixes the wrong-symbol / wrong-escape corruption path that hit backslash-dense Java, JSON, CSS, and regex files during wrapped chat-agent execution.
- Two byte-exact channels now exist: plain ``content`` is re-extracted verbatim from the raw request, and ``content_b64`` can carry source or binary bytes through a parser-immune base64 path when exact escaping matters most.

- For operators, the consequence is straightforward: code generation and document generation can now be described as byte-complete file writes rather than best-effort convenience output.
- This belongs in the dossier because File-Creator is one of Tlmatini's central deterministic execution surfaces and one of the safest alternatives to GUI typing or editor-driving automation.

Self-knowledge and identity contract

- Version `1.8.0` gives Tlmatini a first-person self-knowledge map in `Tlmatini/agent/Tlmatini.md`, so she can answer more accurately about her own architecture, runtime modes, open ports, pages, and internal capability surface.
- That self-reference is injected into all prompt chains through `prompt.pmt` and `agent/rag/config.py`, but it fails open if the file is missing or unreadable and it never overrides a user-loaded project when the request is a generic summary of the provided context.
- The language contract matters too: when a pronoun is used for Tlmatini in the documentation or prompt guidance, she is referred to as `she` / `her`, matching the updated handbook identity rules.

Self-modify builds

- Self-modification is a separate capability axis from frozen-vs-source runtime: only builds created with `python build.py --self-modify` bundle `TlmatiniSourceCode/` next to the application.
- When that directory is present, she can inspect and modify her own shipped source tree; when it is absent, she must say so plainly and fall back to her injected self-knowledge plus the surrounding docs.
- The build pipeline now announces that choice explicitly, so operators can tell whether a release is self-modify-capable before asking her to work on herself.

Multi-Turn 4096-turn autonomy

- The unified-agent loop now defaults to 4096 iterations instead of 256, giving long autonomous operator runs much more room before they exhaust the turn budget.
- That expansion is about conversational/tool-loop depth, not about blindly firing more tools at once: the planner's selected-tool cap still keeps the tool surface bounded per request.
- Operationally, the bigger ceiling helps long workflows, while duplicate-call guards and the dedicated `chat\_agent\_sleeper` tool remain the antidote to accidental busy-polling loops.

Ask Execs in Multi-Turn

- Introduced in `v1.10.0` and still part of the current `v1.26.0` surface, `Ask Execs` is the Multi-Turn-only safety modifier that makes Tlmatini ask before each state-changing Tool, MCP, wrapped agent, or skill-backed execution instead of running it immediately.
- The permission dialog is explicit and auditable: it names the Tool or Agent family, the underlying raw tool name, the full parameters, the program or command to be executed, and the shell or execution surface involved.
- Proceed runs that one step and then prompts again at the next state-changing step; Deny halts the entire chain immediately and appends a red `Execution interrupted` banner even when Exec Report itself is off.

Ask Execs runtime path

- Under the hood, `agent/exec\_permission.py` provides `ExecPermissionBroker`, which lets the synchronous worker-thread executor emit a permission request onto the WebSocket event loop and then block on a `threading.Event` until the browser replies.
- The gate sits after deduplication and quota checks, so skipped calls never prompt and denied calls never appear as executed rows; only work that truly ran lands in Exec Report.
- The round-trip is fail-safe: browser disconnect, emit failure, cancel, or broker shutdown all resolve to Deny, so an unconfirmed state-changing action never slips through just because the UI vanished at the wrong time.

Windows attention issuing

- The current Windows attention path is explicit and local: the browser calls `POST /agent/flash\_window/`, and the backend routes that request through `agent/window\_flash.py`.

- That helper can flash the `Tlmatini.exe` console/taskbar window with `FlashWindowEx` and always prints an uppercase attention banner, so the signal survives in `tlmatini.log` even when the browser is minimized.
- Two concrete reasons are wired today: Ask Execs execution approval prompts and Notifier notifications. The path is best-effort and fail-safe, degrading cleanly on non-Windows or windowless launches.

Windows Installed-apps registration

- Introduced in `v1.11.0` and still carried by the current `v1.26.0` release, the frozen install now behaves like a real Windows application: `install.py` writes a per-user HKCU Add/Remove Programs entry so Tlmatini appears in Settings -> Apps -> Installed apps and in the legacy Programs and Features list.
- The entry carries `DisplayName`, `DisplayVersion`, `InstallLocation`, `DisplayIcon`, `UninstallString`, `QuietUninstallString`, `NoModify`, `NoRepair`, and best-effort `EstimatedSize`, all pointing at the bundled `Uninstaller.exe` without requiring administrator rights.
- The matching runtime self-heal in `agent/apps.py` calls `windows\_app\_registration.self\_heal\_for\_frozen()` on every frozen launch, so installs created before this feature existed can appear in Windows' uninstall UI after the next normal app start.

De-Compressor agent

- De-Compressor is the deterministic archive worker for compression and decompression tasks, deciding direction from whichever side exposes a recognized archive extension.
- Supported archive families are `.gz`, `.zip`, `.7z`, `.tar.gz`, and `.gz.tar`; file-to-folder extraction and file-or-directory packing are both documented in the README and Book.
- Password handling is explicit: `passwordless=true` skips it, while `passwordless=false` requires the `DE\_COMPRESSER\_PWD` environment variable and fails fast if the secret is missing.

De-Compressor integration and fallback behavior

- The agent is reachable from both operator surfaces: ACP canvas nodes wire through dedicated connection-update views, and checked Multi-Turn can invoke it through `chat\_agent\_de\_compressor`.
- Format engines are practical rather than magical: stdlib `gzip` and `zipfile` cover core cases, `7z` is preferred for encrypted `7z` or `zip`, and `py7zr` was added to `requirements.txt` as the Python fallback.
- Every run emits an `INI\_SECTION\_DE\_COMPRESSER<<< ... >>>END\_SECTION\_DE\_COMPRESSER` block and still triggers `target\_agents`, so downstream Parametrizer or Raiser logic can branch on `success=true|false` instead of guessing from prose.

Unreal MCP and the Unreal agent

- Unreal MCP is a UE5 plugin that runs inside the editor and listens on `127.0.0.1:55557` for one JSON command per TCP connection; Tlmatini is the client side of that link, not the plugin host.
- The Unreal workflow agent forwards any command the connected plugin build exposes, up to a 53-command surface across nine categories: actor manipulation (incl. viewport screenshots), Blueprint authoring and node wiring, input mappings, UMG widget building, in-editor Python/console execution, level I/O, asset import, and material authoring. Headless build/cook/test is out of scope (it needs UnrealEditor-Cmd, not the editor socket).
- The same integration is available in both operator surfaces: checked Multi-Turn via `chat\_agent\_unreal`, and ACP canvas flows via the visual Unreal node plus Parametrizer chaining.

Extended Unreal MCP surface

- Unreal's documentation now points at the public `XAIHT/XaihtUnrealEngineMCP` fork, the Unreal Engine MCP variant developed specifically for Tlmatini.
- That fork exposes the extended 53-command, nine-category surface documented in README and Book: not only the base editor/Blueprint/UMG verbs, but also system, level, asset, material, screenshot, viewport, and in-editor Python paths.
- The practical message for operators is simple: Unreal forwards the connected plugin's verb surface directly, so Tlmatini's client does not need a new release every time the plugin adds another supported command.

Installing the UE5 plugin and smoke-testing it

- Install the upstream plugin into ``<YourProject>/Plugins/UnrealMCP/``, enable it from `Edit -> Plugins`, restart UE5, and confirm the Output Log says `UnrealMCP listening on 127.0.0.1:55557`.
- Tlamatini does not compile or embed the plugin; the Unreal editor must already be running with the listener bound before any Unreal call can succeed.
- A seeded smoke test ships in the Prompts table: `Unreal MCP End-to-End Editor Drive` walks through sanity-check, actor spawn, Blueprint creation/compile, and UMG widget assembly.

Orphan-process cleanup

- Tlamatini now ships a three-tier orphan reaper in `Tlamatini/agent/orphan\_reaper.py` focused on Windows console-host leftovers such as `conhost.exe` and `openconsole.exe`.
- Tier 1 runs after spawn-capable Multi-Turn tool calls, Tier 2 runs once after the final answer in a background thread, and Tier 3 runs again during application shutdown through the same cleanup path that already tears down pools.
- The candidate set stays narrow on purpose: dead descendants of the current process tree, orphaned console hosts tied to that tree, and pool-linked processes whose `cmdline` still points into `agents/pools/...` even though tracking records are gone.

Orphan-process prevention and survivor reporting

- Prevention landed alongside cleanup: Windows spawn sites now use `CREATE\_NO\_WINDOW | DETACHED\_PROCESS | CREATE\_NEW\_PROCESS\_GROUP` with stdio piped to `DEVNULL`, so the console host is usually never allocated in the first place.
- The ACPX runtime now kills full process trees instead of only top-level wrappers, and pool-agent scripts gained a conservative `subprocess.Popen` guard so forgotten descendants still inherit `CREATE\_NO\_WINDOW`.
- If something survives both cleanup tiers, Tlamatini sends a second chat bubble listing each surviving `name + PID`; the reaper never raises into the user path because a cleanup crash would be worse than the leftovers it tried to remove.

How to use it

- Run from source: create a virtual environment, install requirements, migrate, create a superuser, collect static files, and start Django.
- Open `/agent/` for chat. Load a file or directory context before asking codebase-specific questions.
- Keep Multi-Turn unchecked for direct Q&A; enable Multi-Turn for tasks that need tools, wrapped agents, monitoring, or workflow seeding.
- Use `chat\_agent\_globber` to find files by pattern, `chat\_agent\_grepper` to locate matching content, and `chat\_agent\_editor` when you need an exact in-place change instead of rewriting a whole file or shelling out to grep/findstr/sed.
- To use the External MCP capability, open `External -> MCPs`, register or import a server into `external\_mcps.json`, choose the transport/runtime fields, and let the dialog connect it before expecting its `ext\_\_<server>\_\_<tool>` tools to appear in Multi-Turn.
- When you are onboarding or debugging an external MCP, call `chat\_agent\_mcp\_doctor` first or use the MCP Doctor workflow node; it can tell you whether the issue is transport selection, a missing runtime on PATH, placeholder secrets, or a bad endpoint before you spend time on a live connect attempt.
- If you want a guided external-MCP onboarding flow, use the Step-by-Step mode in the External MCP dialog so each required field is introduced progressively instead of dumping the whole connection contract at once.
- Use Config -> Access Keys Wizard when you need to wire or update provider credentials without editing `config.json` manually.
- Use About -> Check for updates on packaged installs when you want Tlamatini to fetch and stage the latest release without manually replacing the install folder.
- Tick `Ask Execs` when you want human approval before each state-changing Multi-Turn step; it is disabled until Multi-Turn is on, and a single Deny stops the whole chain with an explicit red interruption banner.

- When you are using a packaged install on Windows 10 or Windows 11, uninstall it through Settings -> Apps -> Installed apps or the legacy Programs and Features entry, not by manually deleting the folder.
- If an Ask Execs approval dialog or a Notifier event needs you while the browser is buried, watch for Tlmatini's taskbar-attention flash and the matching uppercase banner in `tlmatini.log`.
- If you want her to inspect or modify herself, verify that `TlmatiniSourceCode/` exists in the current build first; self-modify is optional and absent builds must be treated honestly as read-only about their own code tree.
- For authorized Kali Linux assessments, run MCP-Kali-Server on the Kali box, set `Config -> URLs -> Kali server (Kali)` once, and then call `chat\_agent\_kalier` from Multi-Turn with the desired `action` and `target` without repeating the box URL each turn.
- For STM32 firmware work, install STM32CubeIDE, leave `Config -> URLs -> STM32 MCP server script` blank for zero-config bootstrap, and then call `chat\_agent\_stm32er` from Multi-Turn with one `action` at a time such as `validate`, `create\_project`, `write\_source`, `build`, `build\_and\_flash`, `serial\_session`, or `live\_monitor`.
- For ESP32 firmware work, leave `Config -> URLs -> pio\_executable` blank for zero-config PlatformIO bootstrap, then call `chat\_agent\_esp32er` from Multi-Turn with actions like `bootstrap`, `validate`, `create\_project`, `write\_source`, `build`, `upload`, `build\_and\_upload`, `monitor`, or `monitor\_session`.
- For ESPHome smart-home firmware work, leave `Config -> URLs -> esphome\_executable` blank for zero-config bootstrap, then call `chat\_agent\_esphomer` from Multi-Turn with actions like `bootstrap`, `validate`, `new\_config`, `config`, `compile`, `upload`, `logs`, or the one-shot `scaffold\_compile\_upload` flow.
- For desktop-window control, call `chat\_agent\_windower` from Multi-Turn to focus, tile, resize, list, or close a window by title, or model the same action in ACP with the Windower node.
- For interactive web automation, call `chat\_agent\_playwrighter` from Multi-Turn with a `steps\_json` script, or author the same step list visually with the Playwrighter node on the canvas.
- For Blender work, enable the official Blender MCP add-on in Blender, make sure its TCP listener is reachable (default `localhost:9876`), then call `chat\_agent\_blenderer` from Multi-Turn or use the Blenderer node on the canvas.
- For Unreal Engine work, enable the Unreal MCP plugin inside a live UE5 project first, then call `chat\_agent\_unrealer` from Multi-Turn or use the visual Unrealer node on the canvas.
- Archive jobs can now be described directly in Multi-Turn or modeled visually in ACP: De-Compressor infers compress vs decompress from the `input` or `output` extension.
- If a second post-answer warning bubble ever lists surviving `name + PID` entries, treat it as an honest cleanup report and end the listed processes manually from Task Manager if needed.
- Use the `ACPX-Skills` navbar menu when you need to browse, enable/disable, diagnose, or reload the shipped SKILL.md catalog without asking the LLM to be your admin surface.
- Use the DB dropdown when you need a safe database snapshot or want to stage a different `db.sqlite3` for the next start-up without hot-swapping the live SQLite file.
- Open `/agentic\_control\_panel/` to drag agents, connect them, configure each node, validate, start, pause/resume, stop, and save `.flw` workflows.
- Use `python build.py`, `python build\_uninstaller.py`, and `python build\_installer.py` only when producing a packaged Windows release.

Agent descriptions and catalog source of truth

- The authoritative human-readable source for workflow-agent descriptions is `agents\_descriptions.md` at the repo root, not an embedded JavaScript map or a hard-coded Django list.
- Current validation compares live template directories, `agents\_descriptions.md` rows, and the README / Book bestiary counts so the generated dossier stays aligned with the running product.
- The ACP sidebar hover tooltip and the right-click Description dialog both resolve through that markdown file first; `README.md` is only a legacy fallback when the dedicated description file is absent.

Reviewer and Analyzer

- The workflow catalog now includes two new high-value specialists: Reviewer and Analyzer, lifting the canvas inventory to 64 agents and the seed-skill catalog to 23 SKILL.md packages.

- Reviewer is LLM-powered: it resolves a git diff for ``repo_path``, reviews it with a senior-engineer prompt, and emits an ``INI_SECTION_REVIEWER`` block whose first routable field is ``verdict = APPROVE | REQUEST_CHANGES | COMMENT``.
- Analyzer is deterministic and scanner-driven: it runs whichever of ``bandit``, ``semgrep``, ``ruff``, ``eslint``, ``gitleaks``, and ``pip-audit`` are installed on PATH over ``target_path``, then emits an ``INI_SECTION_ANALYZER`` block with ``status`` and ``total_findings`` for downstream routing.
- Both agents always trigger ``target_agents``, so a downstream Forker can branch on ``{verdict}``, ``{status}``, or ``{total_findings}`` instead of scraping prose.
- They are intentionally canvas-only workflow agents: there is no wrapped ``chat_agent_reviewer`` or ``chat_agent_analyzer``, and therefore no duplicate Exec Report row family for those names.
- The chat-side counterparts live in the ACPX skill catalog instead: ``code-review`` exposes senior-engineer git-diff review, while ``security-audit`` exposes the deterministic multi-scanner sweep.

Operator surface counts

- The live operator surface now stands at 84 workflow agents, 93 Multi-Turn tools, 12 ACPX tools, and 27 skills.
- Source inspection confirms the total: 61 distinct wrapped chat-agent tools bound from ``chat_agent_registry.py``, which combines with 20 core Python tools and 12 ACPX/Skill tools for 93 Multi-Turn tools overall.
- The count growth over older public badges now comes from several stacked waves together: the deterministic file-navigation/file-edit trio (Globber, Grepper, Editor), the ESPHomer smart-home firmware lane, MCP Doctor for External MCP onboarding, Zavuerer unified messaging, and Video-Analyzer for robotic video verdicts.
- The workflow-agent and wrapped-tool totals are validated from the live tree even when some handbook badges or older prose lines lag behind the newest release wave, so the dossier stays tied to source truth instead of stale summaries.
- This matters operationally because the planner never binds everything at once: the documented default ``max_selected_tools`` cap stays at 20, so breadth of capability does not mean uncontrolled tool sprawl per turn.

Kalier current role

- Kalier is Tlamatini's current Kali Linux bridge: a direct client for MCP-Kali-Server that lets her drive authorized recon, enumeration, web scanning, and offensive-security workflows from chat or canvas.
- It can issue one capability per run, including ``nmap``, ``gobuster``, ``dirb``, ``nikto``, ``sqlmap``, ``metasploit``, ``hydra``, ``john``, ``wpscan``, ``enum4linux``, arbitrary ``command``, or a safe ``health`` probe of the remote server.
- The agent emits ``INI_SECTION_KALIER`` with ``action``, ``endpoint``, ``subject``, ``return_code``, ``success``, ``timed_out``, and ``server_url``, so downstream Forker or Parametrizer logic can branch on results without scraping prose.
- The practical operator result is simpler prompts: after the Kali box URL is configured once, normal Multi-Turn requests no longer repeat ``server_url`` unless you intentionally override it for a one-off target.
- Two operator surfaces ship in lock-step: the wrapped Multi-Turn tool ``chat_agent_kalier`` now auto-injects the configured ``kali_server_url``, while the visual Kalier canvas node still stores ``server_url`` explicitly in YAML per node.
- Kalier talks straight to the Kali-side Flask API over HTTP using Python-stdlib ``urllib``, so it stays self-contained in the pool subprocess and works the same in source or frozen builds; the embedded-client injection fails open if the config value is blank or unreadable.
- Authorized use only: the intended operator flow is an in-scope lab, CTF, or permitted engagement, often with ``ssh -L 5000:localhost:5000 user@KALI_IP`` tunneling a remote Kali box back to ``http://127.0.0.1:5000``, and the repo now includes ``Tlamatini-Kali-Setup.md`` for the zero-client walkthrough.

STM32er current role

- STM32er is Tlamatini's current STM32 bridge: she talks to the ``STM32 Template Project MCP`` so she can scaffold, author, build, flash, reset, and observe STM32F4 firmware without driving STM32CubeIDE manually.
- The operator promise is zero-config bootstrap: leave ``server_script`` blank and STM32er downloads or zip-falls-back to the MCP server on first use, installs ``mcp`` and ``pyserial`` if needed, validates, and caches the result so the user only installs STM32CubeIDE plus Tlamatini.

- Before any compile-or-hardware action, STM32er runs a critical-mission fail-safe preflight over the arm-none-eabi toolchain, STM32CubeIDE, programmer path, ST-LINK probe, and target family; compile-only steps can run boardless, but flash, erase, reset, serial, and SWD/live-memory operations are refused when the environment or device is wrong.
- Two operator surfaces ship in lock-step: the wrapped Multi-Turn tool ``chat_agent_stm32er`` takes one ``action`` per call, while the visual STM32er canvas node stores the same fields in YAML and triggers downstream agents on both success and failure.
- The tool surface includes the full project lifecycle plus hardware-in-the-loop composites: ``validate``, ``bootstrap``, ``create_project``, ``write_source``, ``build``, ``build_and_flash``, ``serial_session``, ``live_monitor``, and the rest of the 23 MCP verbs, with every run emitting an ``INI_SECTION_STM32ER`` block for Forker or Parametrizer routing.
- Config -> URLs now seeds the chat path with ``stm32_mcp_server_script``, ``stm32_mcp_python``, ``stm32_template_dir``, ``stm32_ide_root``, ``stm32_mcp_repo_url``, and ``stm32_mcp_install_dir``, so firmware prompts normally describe only the task and target board instead of the plumbing.

ESP32er current role

- ESP32er is Tlamatini's current PlatformIO Core bridge: she can scaffold, author, build, upload, and monitor ESP32-class firmware without relying on an external MCP server or IDE.
- The operator promise is zero-config bootstrap: leave ``pio_executable`` blank and ESP32er downloads or pip-falls-back to PlatformIO Core on first use, validates it, and caches it under a per-user directory so the user installs only the board USB driver plus Tlamatini.
- Before any build-or-upload action, ESP32er runs a serial-aware preflight over ``pio`` resolution, project shape, and connected ports; upload and monitor require a real serial device, while non-esp8266 targets are warned about rather than hard-refused because PlatformIO is intentionally multi-target.
- Two operator surfaces ship in lock-step: the wrapped Multi-Turn tool ``chat_agent_esp32er`` takes one ``action`` per call, while the visual ESP32er canvas node stores the same fields in YAML and triggers downstream agents on both success and failure.
- The tool surface covers environment/meta (``bootstrap``, ``validate``, ``system_info``, ``boards``), project lifecycle (``create_project``, ``write_source``, ``read_source``, ``list_sources``, ``clean``), build and flash (``build``, ``upload``, ``build_and_upload``, ``list_artifacts``), serial HIL (``device_list``, ``monitor``, ``monitor_session``), and package / QA paths (``pkg_install``, ``pkg_list``, ``pkg_update``, ``check``, ``test``), with every run emitting an ``INI_SECTION_ESP32ER`` block for Forker or Parametrizer routing.
- Config -> URLs now seeds the chat path with ``pio_executable`` and ``pio_core_dir``, so firmware prompts usually describe only the board, project, and task while the wrapped tool auto-injects the PlatformIO runtime plumbing.

ESP32 Template Project reference baseline

- The new ``ESP32TemplateProject`` repository is the known-good baseline documented in BookOfTlamatini's bonus chapter: a plain PlatformIO project, not a server, meant to prove an ESP32 board and toolchain are healthy before larger firmware work.
- It mirrors ESP32er's grain: ``platformio.ini``, ``src/``, ``include/``, ``lib/``, ``test/``, a blinking ``main.cpp``, serial output at 115200, and GitHub-ready docs/CI so the reference project does not silently rot.
- Operationally, ESP32er can either point at a checkout of that template (``project_dir``) or scaffold an equivalent from scratch with ``action=create_project``, then carry the directory through build, upload, and monitor steps.

ESPHome current role

- ESPHome is Tlamatini's ESPHome bridge: she can author YAML-based smart-home device configs, validate them, compile firmware, upload over USB or OTA, and observe logs without introducing an extra MCP server or IDE.
- The operator promise is zero-config bootstrap: leave ``esphome_executable`` blank and ESPHome installs or resolves ESPHome on first use, so the user installs only the board USB driver plus Tlamatini.
- Before any compile-or-upload action, ESPHome runs a fail-safe preflight over ``esphome`` resolution, YAML existence, and serial-or-OTA readiness; upload, run, and logs require a real serial board or an OTA host because the first flash is always USB.
- Two operator surfaces ship in lock-step: the wrapped Multi-Turn tool ``chat_agent_esphome`` takes one ``action`` per call, while the visual ESPHome canvas node stores the same fields in YAML and triggers downstream agents on both

success and failure.

- The tool surface covers environment/meta (`bootstrap`, `validate`, `version`), device-YAML lifecycle (`new\_config`, `write\_config`, `read\_config`, `config`, `clean`), build and flash (`compile`, `upload`, `run`, `list\_artifacts`), bounded observation (`logs`), and the one-shot `scaffold\_compile\_upload` lifecycle.
- Config -> URLs now seeds the chat path with `esphome\_executable`, so smart-home firmware prompts usually describe only the device, board, and task while the wrapped tool auto-injects the ESPHome runtime plumbing.

ESPHome template baseline

- The bundled `ESPHomeTemplateProject` is the known-good ESPHome baseline documented in README and Book: a phone-controllable light with native `api`, `ota`, `wifi`, and a board LED output, shipped as `agent/agents/esphomer/ESPHomeTemplateProject/tlmatini-light.yaml`.
- It matters because ESPHomer's source-of-truth is a YAML device file, not a C++ project tree: that sample proves the first real workflow of `new\_config` -> `config` -> `compile` -> `upload` without forcing users to invent a valid starter config from memory.
- Operationally, the sample closes the gap between the new agent and a practical first build a user can validate, compile, flash, and then control from a smart-home hub such as Home Assistant.

Windower on Multi-Turn and canvas

- Windower is the new 66th workflow agent: a deterministic Win32 window manager that finds an application window by title and performs one lifecycle operation on the window itself instead of clicking inside it.
- It supports `focus`, `minimize`, `maximize`, `restore`, `move`, `resize`, `move\_resize`, `close`, `topmost`, `untopmost`, `arrange`, and `list`, with `substring`, `exact`, or `regex` title matching plus `match\_index` for duplicate titles.
- The agent emits `INI\_SECTION\_WINDOWER` with `action`, `window\_title`, `matched`, `match\_count`, `state`, `left`, `top`, `width`, and `height`, so downstream Forker or Parametrizer logic can branch on presence, state, or geometry.
- Two operator surfaces ship in lock-step: the wrapped Multi-Turn tool `chat\_agent\_windower` accepts free-form key=value requests, while the visual Windower canvas node stores the same operation fields in YAML.
- Windower is the desktop-window sibling of Mouser and Keyboarder: use Windower when the goal is the window as a whole, Mouser for controls inside it, and Keyboarder for text entry into it.
- Because Windower changes real window state, its executions appear in Exec Report and it always triggers `target\_agents` whether the action succeeds or fails.

Playwrighter current role

- Playwrighter is the new 65th workflow agent in `v1.5.0`: a deterministic Playwright-powered browser automator for Chromium, Firefox, or WebKit that executes ordered interactive steps instead of static fetches.
- It covers the gap between Crawler and Googler: logins, multi-step forms, wizard clicks, JS-rendered SPA scraping, screenshots after interaction, assertions, downloads, and authenticated end-to-end UI checks.
- The agent emits `INI\_SECTION\_PLAYWRIGHTER` with `start\_url`, `final\_url`, `status`, `steps\_run`, `assert\_result`, and extracted values so downstream Forker or Parametrizer logic can branch on pass/fail or reuse scraped data.
- Two operator surfaces ship in lock-step: the wrapped Multi-Turn tool `chat\_agent\_playwrighter` takes the whole script as `steps\_json`, while the visual Playwrighter canvas node stores the same declarative step list in YAML.
- Session continuity is built in: `headless: false` lets operators watch it drive, and `storage\_state\_in` / `storage\_state\_out` carry login state across runs without forcing a manual browser setup each time.
- Because Playwrighter is state-changing, its executions appear in Exec Report and it always triggers `target\_agents` whether the run succeeds or fails.

Reviewer precision patch in v1.4.1

- The `v1.4.1` Reviewer refinement tightened accuracy rather than adding a new surface: when `diff\_ref` is empty, the review prompt labels the diff as the uncommitted working tree plus staged area, so the model must not describe those findings as already committed or pushed.

- The same patch teaches the model Tlamatini's managed-secret convention: ``agent/config.json`` and selected ``agent/agents/*/config.yaml`` files can hold live local credentials in a keyed working copy, while ``regen_secrets.py --mode push-able`` scrubs them back to placeholders before commit.
- That guidance is mirrored into the ``code-review`` SKILL.md package too, keeping the chat-surface review behavior and the canvas Reviewer agent aligned on commit-state wording and secret-severity expectations.

Native dialogs and Tkinter removal in v1.4.2

- The current tagged release ``v1.4.2`` removes Tkinter from the unstable runtime-facing dialog path and replaces it with ``Tlamatini/agent/native_dialogs.py``, a native Windows dialog bridge used by browser-triggered pickers.
- This change pairs with the existing DB and operator dialogs: file and folder selection still feels local and GUI-first, but the fragile Tkinter dependency is no longer part of the interactive runtime path that users trigger from chat or ACP surfaces.
- The patch arrived with dedicated tests (``test_native_dialogs.py``) and with follow-up orphan-reaper/runtime adjustments, so the release reads as a stability pass rather than a cosmetic refactor.

ACPX-Skills menu

- The new ``ACPX-Skills`` navbar menu gives operators four direct actions over the skill catalog: Browse Skills, Configure Skills, Diagnostics, and Reload Registry.
- ``Configure Skills`` flips ``Skill.enabled`` exactly the way MCPs and Tools are toggled, so disabled skills disappear from ``list_skills`` and reject ``invoke_skill`` with ``SKILL_DISABLED`` instead of silently half-working.
- The diagnostics view cross-checks skill dependencies against disabled tools, disabled MCPs, missing ACPX agents, and orphan database rows whose SKILL.md disappeared from disk.

Source-mode bootstrap commands

```
python -m venv venv
venv\Scripts\activate
pip install -r requirements.txt
python Tlamatini/manage.py migrate
python Tlamatini/manage.py createsuperuser
python Tlamatini/manage.py collectstatic --noinput
python Tlamatini/manage.py runserver --noreload
```

4. Ollama Setup Without Administrative Rights

- Open a normal PowerShell window, not an elevated one, for the safest no-admin Windows installation path.
- Install into `%LOCALAPPDATA%\Programs\Ollama` with the official PowerShell installer script and then reopen PowerShell so PATH updates are visible.
- If you plan to use the default `:cloud` models from the shipped config, sign in with `ollama signin` so the host is linked to your Ollama account before you test the app.
- Verify the CLI with `ollama --version`, start `ollama serve` if the background service is not already active, and confirm `http://127.0.0.1:11434/api/tags` responds.
- Pull the default repository model tags exactly as written if you want the shipped config and agent templates to work unchanged.
- The Book now clarifies the token rule: a localhost Ollama usually needs no Ollama bearer token in Tlmatini, while a remote Ollama endpoint may require one in `Config -> Access Keys Wizard` or the matching config key.

No-admin Ollama commands and default model pulls

```
$env:OLLAMA_INSTALL_DIR = "$env:LOCALAPPDATA\Programs\Ollama"
irm https://ollama.com/install.ps1 | iex
ollama --version
ollama signin
ollama serve
Invoke-WebRequest http://127.0.0.1:11434/api/tags -UseBasicParsing
ollama pull Nomic-Embed-Text:latest
ollama pull glm-5.2:cloud
ollama pull qwen3.5:cloud
ollama pull gpt-oss:120b-cloud
ollama pull qwen3.5:397b-cloud
ollama pull glm-5.1:cloud
```

5. Runtime, Release, and Operator Diagnostics

Running the application

- Development server: ``python Tlamatini/manage.py runserver --noreload``.
- Preferred async/dev bootstrap: ``python Tlamatini/manage.py startserver``, which starts MCP services before the Django server.
- Production-style ASGI endpoint: ``daphne -b 127.0.0.1 -p 8000 tlamatini.asgi:application``.
- Current startup also re-applies GPU-performance / Ollama-pinning hooks in the background on supported NVIDIA Windows hosts, so restart-time behavior stays closer to the tuned development baseline.
- That same early startup window is also where a staged ``DB/ToLoad/db.sqlite3`` file is promoted into the live database path, before Django opens SQLite.
- In frozen mode, startup now also self-heals the per-user Windows Installed-apps entry when ``Uninstaller.exe`` is present beside ``Tlamatini.exe``, so old installs can gain a standard uninstall surface without a reinstall.
- Startup now also prints a ``--- [VERSION] Tlamatini ...`` banner, making the running build visible in both the console and ``tlamatini.log`` without an HTTP call.
- Startup cleans pool state, repopulates the agent registry, launches MCP metrics/file-search servers, and then serves HTTP plus WebSocket traffic.

Embedding-memory pre-flight guard

- README and BookOfTlamatini now document an embedding-memory pre-flight guard for GPU hosts before a directory-context load starts its FAISS embedding burst.
- On supported NVIDIA hosts it estimates embedding-model VRAM pressure, and when the projected load is too high it emits a non-blocking warning chat bubble instead of silently letting RAM<->VRAM thrash surprise the operator.
- CPU-only, AMD, and Apple-Silicon hosts stay fail-open: the guard becomes a no-op when the NVIDIA probe does not apply.
- The practical operator response is straightforward: switch to a smaller embedding model, reconnect if needed, or proceed knowingly with the heavier model.

Reconnect and restart safeguards

- Config -> Models and Config -> URLs dialogs now track their pre-edit baseline and can show a reconnect-required dialog when the saved values change what the live chat session should trust.
- The restored-session autoload path now buffers early WebSocket frames so context-loading spinners and disabled-input state are not lost during automatic reconnect/restore flows.
- Startup and restart behavior now also re-apply GPU performance and Ollama keep-alive hooks in the background on supported NVIDIA Windows hosts, improving warm-model readiness without blocking Django boot.
- Browser-driven attention routing is now part of that operator-safety layer too: Ask Execs prompts and Notifier events can raise a taskbar flash plus a log banner without relying on the browser window already being visible.
- Windows process hygiene is now part of that safety story too: detached no-window spawns and the three-tier orphan reaper reduce the chance that Task Manager shows stale Tlamatini-icon console helpers after long runs.
- Ask Execs extends that safety story into execution approval itself: the operator can now stop a destructive chain before the next mutation instead of only auditing it after the fact in Exec Report.

Media and voice family

- The current media family spans capture, playback, and speech: Shoter (screen), Camcorder (camera-in), Recorder (mic-in), AudioPlayer (speakers-out), VideoPlayer (screen-out with audio), Talker (text-to-speech), and Whisperer (speech-to-text).
- Talker remains female-only by design and uses an Ollama neural TTS model with SNAC decoding, while Whisperer records the microphone itself or transcribes a file through faster-whisper locally or cloud Whisper APIs.

- Recent stability work matters here too: Talker now chunks long input by sentence for long-form speech, and media-output defaults were moved into the application ``Temp`` directory rather than user content folders.

Autonomous command watchdog

- A boot-time autonomous command watchdog now protects the chat against shell wrappers that stay alive while making zero CPU or I/O progress, the classic signature of a mangled prompt waiting forever on stdin.
- It never kills on elapsed time alone: the subtree must outlive the grace window and remain idle for a configured streak, so long builds, downloads, and compiles are preserved while only genuinely wedged interpreters are reaped.
- This watchdog complements rather than replaces the orphan reaper: the watchdog rescues blocked synchronous tool calls before they return, while the orphan reaper still handles post-return survivors and stale console companions.

Prompt catalog and answer readability discipline

- Version ``1.3.2`` tightened the HTML answer contract with a Prime Directive on visual readability: explicit background and text color, no grey-on-dark body text, and safer table-body defaults.
- The seeded ``Prompts`` dropdown was also re-sorted into a learner path: context-only Q&A first, then metrics, files search, shell, code generation, vision, specialized single-tool actions, agent control, Unrealer, and heavier Multi-Turn/ACPX demos last.
- The ``v1.35.0`` prompt-search pass then makes that larger catalog easier to operate: prompt cards support substring, word-start, and fuzzy matching, with mode badges that keep one-shot, Multi-Turn, ACPX, Exec Report, and Step-by-Step demos visually distinct.
- Those readability rules remain in force in the current documentation set, and the current ``v1.38.1`` release state keeps runtime surfaces, self-knowledge wording, firmware/External-MCP demos, ACPX skills, Zavuerer messaging, Video-Analyzer, Robotic-Loop-Training, generated ``flw`` layout, and operator handbook aligned.

Ask Execs and execution approval

- Introduced in ``v1.10.0`` and still part of the current ``v1.26.0`` surface, ``Ask Execs`` is the Multi-Turn-only safety modifier that makes Tlamatini ask before each state-changing Tool, MCP, wrapped agent, or skill-backed execution instead of running it immediately.
- The permission dialog is explicit and auditable: it names the Tool or Agent family, the underlying raw tool name, the full parameters, the program or command to be executed, and the shell or execution surface involved.
- Proceed runs that one step and then prompts again at the next state-changing step; Deny halts the entire chain immediately and appends a red ``Execution interrupted`` banner even when Exec Report itself is off.
- Under the hood, ``agent/exec_permission.py`` provides ``ExecPermissionBroker``, which lets the synchronous worker-thread executor emit a permission request onto the WebSocket event loop and then block on a ``threading.Event`` until the browser replies.
- The gate sits after deduplication and quota checks, so skipped calls never prompt and denied calls never appear as executed rows; only work that truly ran lands in Exec Report.
- The round-trip is fail-safe: browser disconnect, emit failure, cancel, or broker shutdown all resolve to Deny, so an unconfirmed state-changing action never slips through just because the UI vanished at the wrong time.

Windows attention issuing

- The current Windows attention path is explicit and local: the browser calls ``POST /agent/flash_window/``, and the backend routes that request through ``agent/window_flash.py``.
- That helper can flash the ``Tlamatini.exe`` console/taskbar window with ``FlashWindowEx`` and always prints an uppercase attention banner, so the signal survives in ``tlamatini.log`` even when the browser is minimized.
- Two concrete reasons are wired today: Ask Execs execution approval prompts and Notifier notifications. The path is best-effort and fail-safe, degrading cleanly on non-Windows or windowless launches.

Unreal MCP runtime behavior

- Each Unrealer run is one command: load ``config.yaml``, open a fresh TCP socket, send ``{"type": "command", "params": "params"}``, read until valid JSON arrives, and log one atomic ``INI_SECTION_UNREALER<<< ...``

>>>END_SECTION_UNREALER` block.

- The wrapped-tool path stores chat runs under `agent/agents/pools/\_chat\_runs/\_unrealer\_<seq>\_<id>/`, while visual flows use normal `unrealer\_<n>` pool folders and can chain response fields through Parametrizer mappings.
- Exec Report treats Unreal as its own row family, and troubleshooting stays concrete: connection-refused means the plugin is not listening, while read-timeout usually means UE5's game thread is busy.

Orphan reaper runtime behavior

- Tlmatini now ships a three-tier orphan reaper in `Tlmatini/agent/orphan\_reaper.py` focused on Windows console-host leftovers such as `conhost.exe` and `openconsole.exe`.
- Tier 1 runs after spawn-capable Multi-Turn tool calls, Tier 2 runs once after the final answer in a background thread, and Tier 3 runs again during application shutdown through the same cleanup path that already tears down pools.
- The candidate set stays narrow on purpose: dead descendants of the current process tree, orphaned console hosts tied to that tree, and pool-linked processes whose `cmdline` still points into `agents/pools/...` even though tracking records are gone.
- Prevention landed alongside cleanup: Windows spawn sites now use `CREATE\_NO\_WINDOW | DETACHED\_PROCESS | CREATE\_NEW\_PROCESS\_GROUP` with stdio piped to `DEVNULL`, so the console host is usually never allocated in the first place.
- The ACPX runtime now kills full process trees instead of only top-level wrappers, and pool-agent scripts gained a conservative `subprocess.Popen` guard so forgotten descendants still inherit `CREATE\_NO\_WINDOW`.
- If something survives both cleanup tiers, Tlmatini sends a second chat bubble listing each surviving `name + PID`; the reaper never raises into the user path because a cleanup crash would be worse than the leftovers it tried to remove.

Release pipeline

- Release production is a three-step pipeline: `build.py` -> `build\_uninstaller.py` -> `build\_installer.py`.
- The final distributable is the full versioned release folder `dist/Tlmatini\_Release\_v<version>/`, not a stray executable copied outside its payload.
- Use `build.py --self-modify` when you intentionally want a release that ships `TlmatiniSourceCode/` so she can inspect or modify herself at runtime.
- Current `build.py` treats `README.md` and `jd-cli/` as required post-build assets and fails hard if those payloads are missing.
- Bundled support scripts cover shortcut creation/removal, `.flw` association, the PowerShell launcher, Windows-specific installer ergonomics, and the per-user Installed-apps registration path.

Windows uninstall registration

- Introduced in `v1.11.0` and still carried by the current `v1.26.0` release, the frozen install now behaves like a real Windows application: `install.py` writes a per-user HKCU Add/Remove Programs entry so Tlmatini appears in Settings -> Apps -> Installed apps and in the legacy Programs and Features list.
- The entry carries `DisplayName`, `DisplayVersion`, `InstallLocation`, `DisplayIcon`, `UninstallString`, `QuietUninstallString`, `NoModify`, `NoRepair`, and best-effort `EstimatedSize`, all pointing at the bundled `Uninstaller.exe` without requiring administrator rights.
- The matching runtime self-heal in `agent/apps.py` calls `windows\_app\_registration.self\_heal\_for\_frozen()` on every frozen launch, so installs created before this feature existed can appear in Windows' uninstall UI after the next normal app start.

Exec Report

- Exec Report is a Multi-Turn-only transparency layer that appends one operation table per state-changing agent family to the final answer.
- Rows are recorded from the live tool-call stream rather than guessed from the LLM prose, so the report is the operational ground truth.

- Each row receives a SUCCESS/FAILURE verdict from raw tool returns, making long installs, deployments, and remediations inspectable after the fact.
- When Ask Execs is enabled, Exec Report and the red denial banner complement each other: already-executed steps still render as tables, while the denied step stays out of the tables and is surfaced only through the interruption banner.

ACPX and skills

- ACPX lets Tlamatini spawn external coding-agent CLIs such as Codex, Claude Code, Cursor, Gemini, Qwen, and others as managed child processes.
- It pairs those agents with markdown-driven ``SKILL.md`` packages, validated I/O contracts, permission gating, and append-only audit logs.
- Transport-aware drain rules and bounded event bodies reduce latency while protecting the LLM context budget during external-agent relays.
- The operator-facing references are ``README.md`` and ``ACPX.md``, while the implementation lives under ``agent/acpx/``, ``agent/skills/``, and ``agent/skills_pkg/``.

Application log

- The built-in ``tlamatini.log`` file captures both stdout and stderr through a tee stream initialized in ``manage.py`` before Django starts.
- In source mode the log sits next to ``manage.py``; in frozen mode it lives next to the executable.
- Immediate flush behavior makes the log the primary forensic artifact for startup problems, warnings, tracebacks, and runtime diagnostics.

6. Agent Catalog and Runtime Model

Tlmatini currently exposes 84 workflow-agent templates.

Category	Representative agents
Control	starter, ender, stopper, cleaner, barrier, flowbacker
Execution and files	executer, pythonxer, pser, file_creator, file_extractor, file_interpreter, de_compressor, playwrighter, windower, unrealer, kalier, stm32er, esp32er, esphomer, arduiner, mover, deleter
DevOps and infra	gitter, dockerer, kubernetes, jenkinser, ssher, scper
Data and APIs	sqler, mongoxer, apirer, crawler, googler
Monitoring and routing	monitor_log, monitor_netstat, flowhypervisor, forker, asker, counter, and, or
Communication	notifier, emailer, recmailer, telegrammer, teletlmatini, whatsappper
Security and media	kyber_keygen, kyber_cipher, kyber_decipher, image_interpreter, video_analyzer, shoter, camcorder, recorder, audioplayer, videoplayer, j_decompiler
Workflow intelligence	flowcreator, gatewayer, gateway_relayer, node_manager, parametrizer, prompter, summarizer, acpxer

All workflow agents follow a common deployment pattern: template directory, YAML configuration, session-scoped pool copy, PID/status/log files, target/source wiring, and optional reanimation state.

Agent catalog validation

- The authoritative human-readable source for workflow-agent descriptions is `agents\_descriptions.md` at the repo root, not an embedded JavaScript map or a hard-coded Django list.
- Current validation compares live template directories, `agents\_descriptions.md` rows, and the README / Book bestiary counts so the generated dossier stays aligned with the running product.
- The ACP sidebar hover tooltip and the right-click Description dialog both resolve through that markdown file first; `README.md` is only a legacy fallback when the dedicated description file is absent.

User jurisdiction over plain-Python agents

- The workflow agents in `Tlmatini/agent/agents/` are plain-Python programs on purpose: they are readable, editable, auditable operating code under the user's control.
- When a user enables, configures, modifies, chains, or runs those agents, the actions of those agents fall under that user's jurisdiction. The prompts, config files, secrets, credentials, files, folders, network targets, browsers, shells, APIs, external MCP servers, hardware devices, and downstream systems they touch are selected and authorized by the user.
- Tlmatini provides orchestration, documentation, and guardrails, but she cannot guarantee that every user-edited agent, workflow, external service, credential scope, target machine, or local environment is safe.
- Any security breach, data exposure, unauthorized action, credential leak, unsafe automation, policy violation, device damage, or other harm caused by running agents or agent workflows is the responsibility of the user who runs them.
- Operators should audit agents before use, restrict credentials and permissions, and operate them only on systems where they have explicit authorization.

How agent runtimes are shaped

- Every workflow agent follows the same operational skeleton: template directory, `config.yaml`, a session-scoped pool copy, PID/status/log files, and explicit source/target wiring.
- Chat-wrapped tool calls launch isolated runtime copies under `agent/agents/pools/\_chat\_runs\_/\_`, while ACP uses named pool folders such as `starter\_1` or `unrealer\_1`.
- Specialized agents now stretch the platform in different directions: Globber/Grepper/Editor cover deterministic file discovery, regex search, and surgical in-place edits; Video-Analyzer closes hardware-in-the-loop video verdicts; MCP Doctor performs safe external-MCP onboarding diagnosis; ACPXer drives external coding-agent CLIs; Kalier drives a remote or tunneled Kali Linux tool server; STM32er drives a zero-config STM32 firmware MCP bridge; ESP32er drives PlatformIO directly; ESPHomer drives ESPHome directly for YAML-authored smart-home devices; Blenderer drives a

live Blender editor over the official MCP add-on socket; Unrealr drives a live UE5 editor; TeleTlamatini bridges full Tlamatini conversations into Telegram; and Telegrammer / Whapper send and receive messages over the official Telegram Bot API and Meta WhatsApp Cloud API.

MCP Doctor spotlight

- MCP Doctor is the new onboarding and triage specialist added with the External MCP release: she inspects a configured server entry and tells the operator what is wrong before a live connection attempt wastes time.
- The diagnostic checks cover transport shape, runtime command availability on PATH, placeholder or missing secrets, endpoint/source/docs links, and the concrete next step the operator should take to make the server connectable.
- Operators can reach the same behavior from both surfaces that matter: the MCP Doctor workflow agent on the canvas and the wrapped ``chat_agent_mcp_doctor`` tool inside Multi-Turn.

Blenderer spotlight

- Blenderer was introduced in ``v1.20.0`` as the 77th workflow agent and remains the direct bridge to the official Blender MCP add-on, letting Tlamatini operate a live Blender session from either Multi-Turn chat or the visual workflow canvas.
- The bridge talks over a TCP socket (default ``localhost:9876``) and supports both raw ``execute_code`` requests and higher-level scene/object/material/render actions, so operators can mix deterministic verbs with precise Python-driven 3D automation.
- This extends Tlamatini beyond code and firmware orchestration into DCC / 3D-production work: asset inspection, scene mutation, material changes, camera setup, and render-triggering now live inside the same operator surface as the rest of the system.

Self-update spotlight

- The packaged application now includes an in-app self-update flow exposed from About -> Check for updates, so operators can refresh a frozen install without manually unpacking and replacing the entire release folder.
- The backend checks the latest GitHub release, downloads and stages the package, then hands off the locked-file swap to ``apply_update.ps1``, which performs the replacement after the running executable exits and relaunches the updated app.
- The update path is state-preserving by design: it keeps ``config.json``, user content, and one ``agents_backup`` generation, and it stages the user's database through ``DB/ToLoad/`` plus ``post_update_migrate.flag`` so the next launch restores and migrates that DB instead of wiping it.

Reviewer and Analyzer spotlight

- The workflow catalog now includes two new high-value specialists: Reviewer and Analyzer, lifting the canvas inventory to 64 agents and the seed-skill catalog to 23 SKILL.md packages.
- Reviewer is LLM-powered: it resolves a git diff for ``repo_path``, reviews it with a senior-engineer prompt, and emits an ``INI_SECTION_REVIEWER`` block whose first routable field is ``verdict = APPROVE | REQUEST_CHANGES | COMMENT``.
- Analyzer is deterministic and scanner-driven: it runs whichever of ``bandit``, ``semgrep``, ``ruff``, ``eslint``, ``gitleaks``, and ``pip-audit`` are installed on PATH over ``target_path``, then emits an ``INI_SECTION_ANALYZER`` block with ``status`` and ``total_findings`` for downstream routing.
- Both agents always trigger ``target_agents``, so a downstream Forker can branch on ``{verdict}``, ``{status}``, or ``{total_findings}`` instead of scraping prose.
- They are intentionally canvas-only workflow agents: there is no wrapped ``chat_agent_reviewer`` or ``chat_agent_analyzer``, and therefore no duplicate Exec Report row family for those names.
- The chat-side counterparts live in the ACPX skill catalog instead: ``code-review`` exposes senior-engineer git-diff review, while ``security-audit`` exposes the deterministic multi-scanner sweep.

Operator surface counts

- The live operator surface now stands at 84 workflow agents, 93 Multi-Turn tools, 12 ACPX tools, and 27 skills.
- Source inspection confirms the total: 61 distinct wrapped chat-agent tools bound from ``chat_agent_registry.py``, which combines with 20 core Python tools and 12 ACPX/Skill tools for 93 Multi-Turn tools overall.

- The count growth over older public badges now comes from several stacked waves together: the deterministic file-navigation/file-edit trio (Globber, Grepper, Editor), the ESPHomer smart-home firmware lane, MCP Doctor for External MCP onboarding, Zavuerer unified messaging, and Video-Analyzer for robotic video verdicts.
- The workflow-agent and wrapped-tool totals are validated from the live tree even when some handbook badges or older prose lines lag behind the newest release wave, so the dossier stays tied to source truth instead of stale summaries.
- This matters operationally because the planner never binds everything at once: the documented default ``max_selected_tools`` cap stays at 20, so breadth of capability does not mean uncontrolled tool sprawl per turn.

Kalier spotlight

- Kalier is Tlamatini's current Kali Linux bridge: a direct client for MCP-Kali-Server that lets her drive authorized recon, enumeration, web scanning, and offensive-security workflows from chat or canvas.
- It can issue one capability per run, including ``nmap``, ``gobuster``, ``dirb``, ``nikto``, ``sqlmap``, ``metasploit``, ``hydra``, ``john``, ``wpscan``, ``enum4linux``, arbitrary ``command``, or a safe ``health`` probe of the remote server.
- The agent emits ``INI_SECTION_KALIER`` with ``action``, ``endpoint``, ``subject``, ``return_code``, ``success``, ``timed_out``, and ``server_url``, so downstream Forker or Parametrizer logic can branch on results without scraping prose.
- The practical operator result is simpler prompts: after the Kali box URL is configured once, normal Multi-Turn requests no longer repeat ``server_url`` unless you intentionally override it for a one-off target.
- Two operator surfaces ship in lock-step: the wrapped Multi-Turn tool ``chat_agent_kalier`` now auto-injects the configured ``kali_server_url``, while the visual Kalier canvas node still stores ``server_url`` explicitly in YAML per node.
- Kalier talks straight to the Kali-side Flask API over HTTP using Python-stdlib ``urllib``, so it stays self-contained in the pool subprocess and works the same in source or frozen builds; the embedded-client injection fails open if the config value is blank or unreadable.
- Authorized use only: the intended operator flow is an in-scope lab, CTF, or permitted engagement, often with ``ssh -L 5000:localhost:5000 user@KALI_IP`` tunneling a remote Kali box back to ``http://127.0.0.1:5000``, and the repo now includes ``Tlamatini-Kali-Setup.md`` for the zero-client walkthrough.

STM32er spotlight

- STM32er is Tlamatini's current STM32 bridge: she talks to the ``STM32 Template Project MCP`` so she can scaffold, author, build, flash, reset, and observe STM32F4 firmware without driving STM32CubeIDE manually.
- The operator promise is zero-config bootstrap: leave ``server_script`` blank and STM32er downloads or zip-falls-back to the MCP server on first use, installs ``mcp`` and ``pyserial`` if needed, validates, and caches the result so the user only installs STM32CubeIDE plus Tlamatini.
- Before any compile-or-hardware action, STM32er runs a critical-mission fail-safe preflight over the arm-none-eabi toolchain, STM32CubeIDE, programmer path, ST-LINK probe, and target family; compile-only steps can run boardless, but flash, erase, reset, serial, and SWD/live-memory operations are refused when the environment or device is wrong.
- Two operator surfaces ship in lock-step: the wrapped Multi-Turn tool ``chat_agent_stm32er`` takes one ``action`` per call, while the visual STM32er canvas node stores the same fields in YAML and triggers downstream agents on both success and failure.
- The tool surface includes the full project lifecycle plus hardware-in-the-loop composites: ``validate``, ``bootstrap``, ``create_project``, ``write_source``, ``build``, ``build_and_flash``, ``serial_session``, ``live_monitor``, and the rest of the 23 MCP verbs, with every run emitting an ``INI_SECTION_STM32ER`` block for Forker or Parametrizer routing.
- Config -> URLs now seeds the chat path with ``stm32_mcp_server_script``, ``stm32_mcp_python``, ``stm32_template_dir``, ``stm32_ide_root``, ``stm32_mcp_repo_url``, and ``stm32_mcp_install_dir``, so firmware prompts normally describe only the task and target board instead of the plumbing.

Windower spotlight

- Windower is the new 66th workflow agent: a deterministic Win32 window manager that finds an application window by title and performs one lifecycle operation on the window itself instead of clicking inside it.
- It supports ``focus``, ``minimize``, ``maximize``, ``restore``, ``move``, ``resize``, ``move_resize``, ``close``, ``topmost``, ``untopmost``, ``arrange``, and ``list``, with ``substring``, ``exact``, or ``regex`` title matching plus ``match_index`` for duplicate titles.

- The agent emits `INI_SECTION_WINDOWER`` with ``action``, ``window_title``, ``matched``, ``match_count``, ``state``, ``left``, ``top``, ``width``, and ``height``, so downstream Forker or Parametrizer logic can branch on presence, state, or geometry.
- Two operator surfaces ship in lock-step: the wrapped Multi-Turn tool ``chat_agent_windower`` accepts free-form key=value requests, while the visual Windower canvas node stores the same operation fields in YAML.
- Windower is the desktop-window sibling of Mouser and Keyboarder: use Windower when the goal is the window as a whole, Mouser for controls inside it, and Keyboarder for text entry into it.
- Because Windower changes real window state, its executions appear in Exec Report and it always triggers ``target_agents`` whether the action succeeds or fails.

Playwrighter spotlight

- Playwrighter is the new 65th workflow agent in ``v1.5.0``: a deterministic Playwright-powered browser automator for Chromium, Firefox, or WebKit that executes ordered interactive steps instead of static fetches.
- It covers the gap between Crawler and Googler: logins, multi-step forms, wizard clicks, JS-rendered SPA scraping, screenshots after interaction, assertions, downloads, and authenticated end-to-end UI checks.
- The agent emits `INI_SECTION_PLAYWRIGHTER`` with ``start_url``, ``final_url``, ``status``, ``steps_run``, ``assert_result``, and extracted values so downstream Forker or Parametrizer logic can branch on pass/fail or reuse scraped data.
- Two operator surfaces ship in lock-step: the wrapped Multi-Turn tool ``chat_agent_playwrighter`` takes the whole script as ``steps_json``, while the visual Playwrighter canvas node stores the same declarative step list in YAML.
- Session continuity is built in: ``headless: false`` lets operators watch it drive, and ``storage_state_in`` / ``storage_state_out`` carry login state across runs without forcing a manual browser setup each time.
- Because Playwrighter is state-changing, its executions appear in Exec Report and it always triggers ``target_agents`` whether the run succeeds or fails.

Reviewer precision spotlight

- The ``v1.4.1`` Reviewer refinement tightened accuracy rather than adding a new surface: when ``diff_ref`` is empty, the review prompt labels the diff as the uncommitted working tree plus staged area, so the model must not describe those findings as already committed or pushed.
- The same patch teaches the model Tlmatini's managed-secret convention: ``agent/config.json`` and selected ``agent/agents/*/config.yaml`` files can hold live local credentials in a keyed working copy, while ``regen_secrets.py --mode push-able`` scrubs them back to placeholders before commit.
- That guidance is mirrored into the ``code-review`` SKILL.md package too, keeping the chat-surface review behavior and the canvas Reviewer agent aligned on commit-state wording and secret-severity expectations.

Native-dialog spotlight

- The current tagged release ``v1.4.2`` removes Tkinter from the unstable runtime-facing dialog path and replaces it with ``Tlmatini/agent/native_dialogs.py``, a native Windows dialog bridge used by browser-triggered pickers.
- This change pairs with the existing DB and operator dialogs: file and folder selection still feels local and GUI-first, but the fragile Tkinter dependency is no longer part of the interactive runtime path that users trigger from chat or ACP surfaces.
- The patch arrived with dedicated tests (``test_native_dialogs.py``) and with follow-up orphan-reaper/runtime adjustments, so the release reads as a stability pass rather than a cosmetic refactor.

Unrealer spotlight

- Unreal MCP is a UE5 plugin that runs inside the editor and listens on ``127.0.0.1:55557`` for one JSON command per TCP connection; Tlmatini is the client side of that link, not the plugin host.
- The Unrealer workflow agent forwards any command the connected plugin build exposes, up to a 53-command surface across nine categories: actor manipulation (incl. viewport screenshots), Blueprint authoring and node wiring, input mappings, UMG widget building, in-editor Python/console execution, level I/O, asset import, and material authoring. Headless build/cook/test is out of scope (it needs UnrealEditor-Cmd, not the editor socket).
- The same integration is available in both operator surfaces: checked Multi-Turn via ``chat_agent_unrealer``, and ACP canvas flows via the visual Unrealer node plus Parametrizer chaining.

- Each Unreal engine run is one command: load ``config.yaml``, open a fresh TCP socket, send ``{"type": "command", "params": {"params": {}}`, read until valid JSON arrives, and log one atomic ``INI_SECTION_UNREALER<<< ... >>>END_SECTION_UNREALER`` block.
- The wrapped-tool path stores chat runs under ``agent/agents/pools/_chat_runs/_unrealer_<seq>_<id>``, while visual flows use normal ``unrealer_<n>`` pool folders and can chain response fields through Parametrizer mappings.
- Exec Report treats Unreal engine as its own row family, and troubleshooting stays concrete: connection-refused means the plugin is not listening, while read-timeout usually means UE5's game thread is busy.

De-Compressor spotlight

- De-Compressor is the deterministic archive worker for compression and decompression tasks, deciding direction from whichever side exposes a recognized archive extension.
- Supported archive families are ``gz``, ``zip``, ``7z``, ``tar.gz``, and ``gz.tar``; file-to-folder extraction and file-or-directory packing are both documented in the README and Book.
- Password handling is explicit: ``passwordless=true`` skips it, while ``passwordless=false`` requires the ``DE_COMPRESSER_PWD`` environment variable and fails fast if the secret is missing.
- The agent is reachable from both operator surfaces: ACP canvas nodes wire through dedicated connection-update views, and checked Multi-Turn can invoke it through ``chat_agent_de_compressor``.
- Format engines are practical rather than magical: ``gzip`` and ``zipfile`` cover core cases, ``7z`` is preferred for encrypted ``7z`` or ``zip``, and ``py7zr`` was added to ``requirements.txt`` as the Python fallback.
- Every run emits an ``INI_SECTION_DE_COMPRESSER<<< ... >>>END_SECTION_DE_COMPRESSER`` block and still triggers ``target_agents``, so downstream Parametrizer or Raiser logic can branch on ``success=true|false`` instead of guessing from prose.

Orphan-reaper spotlight

- Tlmatini now ships a three-tier orphan reaper in ``Tlmatini/agent/orphan_reaper.py`` focused on Windows console-host leftovers such as ``conhost.exe`` and ``openconsole.exe``.
- Tier 1 runs after spawn-capable Multi-Turn tool calls, Tier 2 runs once after the final answer in a background thread, and Tier 3 runs again during application shutdown through the same cleanup path that already tears down pools.
- The candidate set stays narrow on purpose: dead descendants of the current process tree, orphaned console hosts tied to that tree, and pool-linked processes whose ``cmdline`` still points into ``agents/pools/...`` even though tracking records are gone.

7. Repository Facts and Git Changes

Metric	Value
Repository inventory files	816
Tracked files in git	816
Git-unignored working-tree additions	0
Workflow agents	84
Multi-Turn tools	93
Wrapped chat-agent tools	61
Skills	27
agents_descriptions.md rows	85
Django migrations	169
Frontend JavaScript modules	31
Frontend CSS files	9
HTML templates	4
Python requirements	79
Binary/asset inventory files skipped from line count	35
Resolved version	1.38.1
Version source	git

Latest commits

Date	Commit	Subject
2026-07-09	08efa1d2	chore(release): bump package.json version to 1.38.1 for the v1.38.1 hotfix tag
2026-07-09	af356c31	fix(frontend): restore mutable JS globals after the const-poison incident; add /list_prompts/ catalog endpoint + regression tests
2026-07-08	bb1fa2f8	Uppdate self-modify and self-update assets according to the latest changes, by Tlamatini's-AutoBot.
2026-07-08	85ee4e6c	Improving general performance and some personal developer data of angelahack1, by Tlamatini's-AutoBot.
2026-07-08	099e1300	Restore Angela Lopez Mendoza + @angelahack1 across the repo; keep them permanent in every build; make contacts private-complete / public-empty
2026-07-07	74bf4a0e	Making Tlamatini a real looping asistant, this time she demonstrated to program a robotic arm from a wihte page and two cameras, we are in another era, the future is now the past, thanks Tlamatini, by angelahack1
2026-07-07	43aa9921	Improving the PDCP Key retrieval and setting, som markdnown documentations in charge of Codex, Kimi, Claude, etby Tlamatini's-AutoBot. Improving the PDCP Key retrieval and setting, and update of some markdown documentations in charge of Codex, Kimi, Claude, etc., by Tlamatini's-AutoBot.
2026-07-06	35c8d257	Deep improvement in tactics retrying behaviour and reporting the failures in Tlamatini, by Tlamatini's-AutoBot.
2026-07-05	abeb1c84	Updating visual documentation, by angelahack1
2026-07-05	5fc27583	Improving .flw generation layout, by angelahack1

Changes since the last committed PDF/PPTX refresh

Last committed visual-dossier refresh: 74bf4a0e on 2026-07-07 — Making Tlamatini a real looping asistant, this time she demonstrated to program a robotic arm from a wihte page and two cameras, we are in another era, the future is now the past, thanks Tlamatini, by angelahack1

- Since the last committed PDF/PPTX refresh, the repository advanced through `v1.35.0`, `v1.36.0`, `v1.38.0`, and `v1.38.1`: Video-Analyzer became the headline tagged agent release, the Robotic-Loop-Training circle was proven live on a robotic arm, generated flow files are more readable, model-step failures are recovered more truthfully, and the const-poison hotfix restored the frontend while adding the one-call prompt catalog.

- The current visual-doc delta covers ``agent/agents/video_analyzer/``, migrations ``0166`-`0168``, ``test_video_analyzer_agent.py``, ``chat_agent_video_analyzer``, prompt-card search improvements, serpentine ``flw`` layout, ``agent/self_healing.py``, Create Flow gate cleanup, and the carried v1.33.x/v1.34.x model and messaging context.
- The live workspace now includes the untagged ESPHomer wave: a new ESPHome firmware agent, wrapped ``chat_agent_esphomer`` tool, sample YAML project, migrations, tests, and handbook chapters that extend Tlamatini into smart-home device provisioning.
- The same refresh window also delivered the in-app self-update path: ``self_update.py``, new update endpoints, staged release downloads, and the external ``apply_update.ps1`` swap helper that preserves operator state during upgrade.
- The self-knowledge and optional self-modification surface has matured into the current baseline: she can describe her runtime honestly and, when ``TlamatiniSourceCode/`` is present, inspect the bundled rebuildable source tree that explains how she works.

Visual-dossier change appendix 1 of 1

Date	Commit	Subject
2026-07-09	08efa1d2	chore(release): bump package.json version to 1.38.1 for the v1.38.1 hotfix tag
2026-07-09	af356c31	fix(frontend): restore mutable JS globals after the const-poison incident; add <code>/list_prompts/</code> catalog endpoint + regression tests
2026-07-08	bb1fa2f8	Update self-modify and self-update assets according to the latest changes, by Tlamatini's-AutoBot.
2026-07-08	85ee4e6c	Improving general performance and some personal developer data of angelahack1, by Tlamatini's-AutoBot.
2026-07-08	099e1300	Restore Angela Lopez Mendoza + <code>@angelahack1</code> across the repo; keep them permanent in every build; make contacts private-complete / public-empty

Git changes from the last 3 days

- The live Git window now lands on ``v1.38.1`` — the robotic-arm looping milestone ``v1.38.0`` plus the same-week frontend-state-recovery hotfix: README.md, BookOfTlamatini.md, Git history, and source inventory tables confirm the current workflow-agent, Multi-Turn-tool, skill, asset, and effective-line totals.
- The current release wave is broader than a badge bump: ``v1.36.0`` added Video-Analyzer, ``v1.38.0`` proved the Robotic-Loop-Training circle live on a robotic arm (programmed from a blank page and two cameras) on top of the self-healing model-step invoker and the cleaner Create Flow gate, and ``v1.38.1`` recovered the frontend from the const-poison incident while adding the one-call ``/agent/list_prompts/`` prompt catalog.
- The newest committed reliability wave adds ``agent/self_healing.py``: every Multi-Turn model step now runs under a watchdog, switches recovery tactics on transient failures, broadcasts live recovery status, and preserves already-executed agent work instead of discarding it.
- The newest committed Discoverer wave strengthens ProjectDiscovery operation: PDCP key setup is documented and auto-injected, legacy ``cvemap`` CVE searches now run through ``vulnx``, and Go-toolchain source-control guardrails keep the private compiler/cache out of the repository.
- The tagged ``v1.26.0`` release now includes ESPHomer as a fourth firmware lane, bridging Tlamatini to ESPHome so she can author YAML device configs, validate, compile, upload, and observe smart-home firmware from chat or canvas.
- The in-app self-update path itself is now mature across the current Git window: packaged installs can check GitHub releases, stage a download, hand the locked-file replacement to ``apply_update.ps1``, and preserve both operator state and one ``agents_backup`` generation.
- The latest documentation pass aligns the handbook and source with the ``v1.38.1`` release line — the ``v1.38.0`` robotic-arm looping milestone plus the frontend-state-recovery hotfix — so this dossier now carries the current reliability story, media-verdict agent story, prompt-search UX, live line-count inventory, and Agent-directory responsibility boundary instead of stale v1.33.x prose.
- Self-awareness is now part of the steady baseline rather than a one-off milestone: Tlamatini carries a first-person self-knowledge map and, in self-modify builds, can inspect the bundled source snapshot that describes how she actually works.
- Release-identity work also remains relevant: the SemVer policy, git-tag sourcing, runtime version surfaces, and build-time embedding across the Windows artefacts now define how Tlamatini reports her version.

- Documentation itself changed during the recent window, so the regenerated dossier is part of the tracked operator surface rather than an external afterthought.

3-day commit appendix 1 of 1

Date	Commit	Subject
2026-07-09	08efa1d2	chore(release): bump package.json version to 1.38.1 for the v1.38.1 hotfix tag
2026-07-09	af356c31	fix(frontend): restore mutable JS globals after the const-poison incident; add /list_prompts/ catalog endpoint + regression tests
2026-07-08	bb1fa2f8	Update self-modify and self-update assets according to the latest changes, by Tlamatini's-AutoBot.
2026-07-08	85ee4e6c	Improving general performance and some personal developer data of angelahack1, by Tlamatini's-AutoBot.
2026-07-08	099e1300	Restore Angela Lopez Mendoza + @angelahack1 across the repo; keep them permanent in every build; make contacts private-complete / public-empty
2026-07-07	74bf4a0e	Making Tlamatini a real looping assistant, this time she demonstrated to program a robotic arm from a white page and two cameras, we are in another era, the future is now the past, thanks Tlamatini, by angelahack1
2026-07-07	43aa9921	Improving the PDCP Key retrieval and setting, some markdown documentations in charge of Codex, Kimi, Claude, et by Tlamatini's-AutoBot. Improving the PDCP Key retrieval and setting, and update of some markdown documentations in charge of Codex, Kimi, Claude, etc., by Tlamatini's-AutoBot.
2026-07-06	35c8d257	Deep improvement in tactics retrying behaviour and reporting the failures in Tlamatini, by Tlamatini's-AutoBot.

8. Effective Line Inventory by Language

Methodology: tracked text files only. Blank lines and comment-only lines are excluded. Python counts also remove module, class, and function docstrings detected through AST parsing.

Language	Files	Effective lines	Total lines	Share
Python	459	122,182	175,215	71.6%
Markdown	157	20,327	27,027	11.9%
JavaScript	31	16,058	20,431	9.4%
CSS	9	5,657	7,155	3.3%
YAML	89	1,957	4,888	1.1%
HTML	4	1,055	1,073	0.6%
Prompt template	2	1,014	1,133	0.6%
PowerShell	6	672	987	0.4%
JSON	8	544	544	0.3%
Other text	8	506	606	0.3%
JavaScript module	1	417	498	0.2%
Text	5	215	242	0.1%
Protocol Buffers	1	20	33	0.0%
Batch	1	15	29	0.0%

Total effective lines: 170,639

9. Largest Effective Source Files

Path	Language	Effective	Total
Tlmatini/agent/views.py	Python	8,259	12,020
Tlmatini/agent/tests.py	Python	5,510	7,166
Tlmatini/agent/doc_generation/complete_project_docs.py	Python	3,278	3,657
Tlmatini/agent/tools.py	Python	3,056	4,446
BookOfTlmatini.md	Markdown	2,488	3,520
Tlmatini/agent/agents/flowcreator/agentic_skill.md	Markdown	2,264	2,502
Tlmatini/agent/static/agent/css/agentic_control_panel.css	CSS	2,031	2,711
Tlmatini/agent/external_mcp_manager.py	Python	1,841	2,252
Tlmatini/agent/chat_agent_registry.py	Python	1,671	1,708
Tlmatini/agent/static/agent/js/agent_page_chat.js	JavaScript	1,639	2,273
Tlmatini/agent/static/agent/css/agent_page.css	CSS	1,608	2,001
Tlmatini/agent/static/agent/js/acp-agent-connectors.js	JavaScript	1,505	1,679
Tlmatini/agent/static/agent/js/agent_page_init.js	JavaScript	1,462	1,728
Tlmatini/agent/static/agent/js/acp-canvas-core.js	JavaScript	1,381	1,703
Tlmatini/agent/consumers.py	Python	1,338	1,711
Tlmatini/agent/mcp_agent.py	Python	1,327	2,101
Tlmatini/agent/agents/stm32er/stm32er.py	Python	1,212	1,693
Tlmatini/agent/test_stm32er_agent.py	Python	1,200	1,716
Tlmatini/agent/agents/crawler/crawler.py	Python	1,102	1,570
KIMI.md	Markdown	1,100	1,338
Tlmatini/agent/agents/arduiner/arduiner.py	Python	1,062	1,487
Tlmatini/agent/acpx/tests.py	Python	1,035	1,308
Tlmatini/agent/static/agent/js/acp-control-buttons.js	JavaScript	1,035	1,356
Tlmatini/agent/static/agent/js/agent_page_dialogs.js	JavaScript	1,025	1,263
Tlmatini/agent/static/agent/js/acp-canvas-undo.js	JavaScript	1,009	1,132

10. Complete Repository File Tree (Repository Appendix)

Tree appendix 1 of 14

```
Tlamatini/
|-- .gitignore
|-- .mcp.json
|-- _acpx_pipeline_demo_report.md
|-- ACPX.md
|-- agents_descriptions.md
|-- apply_update.ps1
|-- BookOfTlamatini.md
|-- build.py
|-- build_all.cmd
|-- build_complete_private_release.py
|-- build_complete_public_release.py
|-- build_installer.py
|-- build_uninstaller.py
|-- check_private_data.py
|-- Claude-Desktop-KALI-MCP-Session.md
|-- CLAUDE.md
|-- copy_source_assets.py
|-- CreateShortcut.json
|-- CreateShortcut.ps1
|-- Discoverier-new-agent.md
|-- eslint.config.mjs
|-- example_of_prompt_to_make_de-compressor_agent.txt
|-- FirstFinalPlanToSpeedUp.md
|-- GEMINI.md
|-- git_deny_go.py
|-- install.py
|-- KIMI.md
|-- LICENSE
|-- MessagingConnectorAssistant_Design.md
|-- OllamaPricing.png
|-- package.json
|-- PIVOT_CHANGES.md
|-- pnpm-lock.yaml
|-- README.md
|-- regen_secrets.py
|-- register_flw.ps1
|-- RemoveShortcut.ps1
|-- requirements.txt
|-- surgical_improving_speed_of_Tlamatini_by_a_factor_of_3X.md
|-- test_author_banner.py
|-- test_check_private_data.py
|-- test_perf_3x_visual.py
|-- test_private_data_guard.py
|-- Tlamatini-Kali-Setup.md
|-- Tlamatini.ico
|-- Tlamatini.jpg
|-- Tlamatini.ps1
|-- tlamatini_acpx.py
|-- tlamatini_app_summary.pdf
|-- Tlamatini_extended_Artificial_Intelligence_Humanly_Tempered.pptx
|-- TLAMATINI_MCP.md
|-- tlamatini_mcp_server.py
|-- Tlamatini_NIGHTLY_PERFORMANCE_REPORT.md
|-- TlamatiniJudgementDay.md
|-- uninstall.py
|-- unregister_flw.ps1
|-- VERSIONING.md
|-- versioning.py
|-- .claude/
|   |-- settings.json
|   |-- hooks/
|   |   |-- announce_skills.py
|   |   |-- test_announce_skills.py
|   |-- memory/
|   |   |-- feedback_agent_naming_conventions.md
|   |   |-- feedback_dont_overbuild_exec_safety.md
|   |   |-- feedback_hard_real_scenario_tests.md
|   |   |-- feedback_main_branch_only.md
|   |   |-- feedback_package_json_version_bump.md
|   |   |-- feedback_run_tlamatini_agents_visible.md
|   |   |-- feedback_state_constraints_upfront.md
|   |   |-- feedback_track_changes_pivot_file.md
|   |   |-- feedback_update_agent_docs.md
|   |   |-- feedback_user_owns_git.md
|   |-- MEMORY.md
```


Tree appendix 2 of 14

```
-- project_acpx_oneshot_prompt.md
-- project_acpx_skills_menu.md
-- project_acpx_toggle_skills.md
-- project_acpxer_added.md
-- project_arduiner_agent.md
-- project_ask_execs_feature.md
-- project_audioplayer_agent.md
-- project_build_currency_guard.md
-- project_build_tests_and_installer_enterkey.md
-- project_camcorder_agent.md
-- project_carried_python_for_agents.md
-- project_conjunction_parser_fix.md
-- project_daily_chat_test_skill.md
-- project_desktop_ui_lifecycle.md
-- project_director_virtuoso_demo_prompts.md
-- project_doc_refresh_2026_05_06.md
-- project_doc_refresh_2026_05_08.md
-- project_doc_refresh_2026_05_09.md
-- project_eight_fixes_2026_05_07.md
-- project_emailer_recmailer_oneshot.md
-- project_embedding_memory_guard.md
-- project_esp32er_agent.md
-- project_execute_command_bounded_fix.md
-- project_execute_file_foreground_fix.md
-- project_external_exec_safety_layer.md
-- project_flow_compiler_dialog_wins.md
-- project_kalier_agent.md
-- project_keyboard_wrapped_2026_05_07.md
-- project_living_canvas_dropped.md
-- project_mouser_wrapped_2026_05_07.md
-- project_native_picker_tcltk_fix.md
-- project_native_toast.md
-- project_numpy_pyinstaller.md
-- project_ollama_source_build_breaks_embeddings.md
-- project_planner_followup.md
-- project_playwrighter_agent.md
-- project_playwrighter_hold_open.md
-- project_prompt_catalog_mode_badges.md
-- project_pythonxer_forkbomb_fix.md
-- project_pythonxer_strict_ruff_gate.md
-- project_quote_apostrophe_fix_2026_05_07.md
-- project_reaper_console_window_fix.md
-- project_recorder_agent.md
-- project_reviewer_analyzer_agents.md
-- project_reviewer_analyzer_demo_prompts.md
-- project_reviewer_committed_secrets_falsepos.md
-- project_secret_leak_recovery.md
-- project_stm32er_agent.md
-- project_stm32er_bootstrap_preflight.md
-- project_stm32er_demo_prompts.md
-- project_stm32er_docs_libs_parametrizer.md
-- project_stm32er_hil_serial_proof_fix.md
-- project_stm32er_tests.md
-- project_summarizer_oneshot_mode.md
-- project_taskbar_flash_attention.md
-- project_teletlatamini_acpx.md
-- project_temp_templates_policy.md
-- project_unity_mcp_declined.md
-- project_unrealer_expanded_surface.md
-- project_versioning_2026_05_15.md
-- project_videoplayer_agent.md
-- project_windower_agent.md
-- user_profile.md
-- skills/
|-- tlatamini-agent-creation/
|   |-- SKILL.md
|-- tlatamini-agent-naming/
|   |-- SKILL.md
|-- tlatamini-daily-chat-test/
|   |-- .gitignore
|   |-- SKILL.md
|   |-- harness/
|       |-- config.py
|       |-- cyber_watchdog_test.py
|       |-- discoverer_1000.py
|       |-- mcp_playwright_suite.py
```

Tree appendix 3 of 14

```
|
|
|   |-- qualify.py
|   |-- questions.py
|   |-- README.md
|   |-- requirements.txt
|   |-- run_test.py
|   |-- talk_test.py
|   |-- wrapped_questions.py
|-- tlamatini-self-modify-inclusion/
|   |-- SKILL.md
|   |-- scripts/
|       |-- sweep_self_modify.py
|-- tlamatini-self-update-inclusion/
|   |-- SKILL.md
|   |-- scripts/
|       |-- sweep_self_update.py
|-- .codex/
|   |-- skills/
|       |-- full-project-pdf-dossier/
|           |-- SKILL.md
|       |-- overlap-safe-pptx-dossier/
|           |-- SKILL.md
|-- .github/
|   |-- workflows/
|       |-- name-guard.yml
|-- .scanning/
|   |-- finding-policy.json
|-- AuxTests/
|   |-- mypdf2.py
|-- demo_flows/
|   |-- demo1_globber_to_parametrizer_to_zavuerer.flw
|   |-- demo2_apirer_to_parametrizer_to_zavuerer.flw
|   |-- demo3_zavuerer_health_to_parametrizer_to_filecreator.flw
|-- docs/
|   |-- claude/
|       |-- acpx.md
|       |-- agents.md
|       |-- architecture.md
|       |-- exec-report.md
|       |-- frontend.md
|       |-- gotchas.md
|       |-- INDEX.md
|       |-- mcp-tools.md
|       |-- multi-turn.md
|       |-- recent-fixes.md
|-- pyinstaller_hooks/
|   |-- hook-numpy.py
|   |-- hook-torch.py
|-- Tests/
|   |-- test_about_window_name_visible.py
|   |-- test_perf_3x_visual.py
|-- Tlamatini/
|   |-- cat_art.py
|   |-- manage.py
|   |-- .agents/
|       |-- workflows/
|           |-- create_new_agent.md
|   |-- .mcps/
|       |-- create_new_mcp.md
|   |-- .skills/
|       |-- create_new_skill.md
|   |-- agent/
|       |-- __init__.py
|       |-- access_key_wizard.py
|       |-- admin.py
|       |-- apps.py
|       |-- capability_registry.py
|       |-- chain_files_search_lcel.py
|       |-- chain_system_lcel.py
|       |-- chat_agent_registry.py
|       |-- chat_agent_runtime.py
|       |-- chat_history_loader.py
|       |-- command_togen_pb2.txt
|       |-- command_watchdog.py
|       |-- config.json
|       |-- config_loader.py
|       |-- constants.py
```

Tree appendix 4 of 14

```
| |-- consumers.py
| |-- contacts.py
| |-- embedding_memory_guard.py
| |-- exec_permission.py
| |-- external_mcp_manager.py
| |-- filesearch.proto
| |-- filesearch_pb2.py
| |-- filesearch_pb2_grpc.py
| |-- global_execution_planner.py
| |-- global_state.py
| |-- gpu_perf.py
| |-- inet_determiner.py
| |-- llm_timing.py
| |-- mcp_agent.py
| |-- mcp_files_search_client.py
| |-- mcp_files_search_server.py
| |-- mcp_system_client.py
| |-- mcp_system_server.py
| |-- models.py
| |-- native_dialogs.py
| |-- orphan_reaper.py
| |-- path_guard.py
| |-- prompt.pmt
| |-- rag_enhancements.py
| |-- routing.py
| |-- self_healing.py
| |-- self_update.py
| |-- test_access_key_wizard.py
| |-- test_arduino_agent.py
| |-- test_audioplayer_agent.py
| |-- test_blender_agent.py
| |-- test_build_scripts.py
| |-- test_camcorder_agent.py
| |-- test_chat_bridge_bots.py
| |-- test_chat_history_window.py
| |-- test_command_watchdog.py
| |-- test_contacts.py
| |-- test_crawler_agent.py
| |-- test_createsuperuser_wizard.py
| |-- test_de_compressor.py
| |-- test_discoverer_agent.py
| |-- test_discoverer_thousand.py
| |-- test_editor_agent.py
| |-- test_embedding_memory_guard.py
| |-- test_esp32er_agent.py
| |-- test_esphome_agent.py
| |-- test_execute_command_bounded.py
| |-- test_external_mcp_add_flow.py
| |-- test_external_mcp_e2e.py
| |-- test_external_mcp_transports.py
| |-- test_external_mcp_universal.py
| |-- test_file_extractor_reader.py
| |-- test_flow_contracts.py
| |-- test_frontend_mutable_state.py
| |-- test_globber_agent.py
| |-- test_googler_agent.py
| |-- test_greppler_agent.py
| |-- test_image_interpreter_agent.py
| |-- test_instant_messaging_doctor.py
| |-- test_j_decompiler_agent.py
| |-- test_kalier_agent.py
| |-- test_native_dialogs.py
| |-- test_orphan_reaper.py
| |-- test_parametrizer_mcp_doctor.py
| |-- test_password_quoting.py
| |-- test_playwrighter_agent.py
| |-- test_recorder_agent.py
| |-- test_self_healing.py
| |-- test_self_update.py
| |-- test_step_by_step_mode.py
| |-- test_stm32er_agent.py
| |-- test_talker_agent.py
| |-- test_telegrammer_identity.py
| |-- test_temp_dir_policy.py
| |-- test_unrealer_agent.py
| |-- test_video_analyzer_agent.py
```

Tree appendix 5 of 14

```
-- test_videooplayer_agent.py
-- test_watchdog_foreground_exemption.py
-- test_whatsapp_identity.py
-- test_whisperer_agent.py
-- test_windower_agent.py
-- test_windows_app_registration.py
-- test_zavuerer_agent.py
-- tests.py
-- tests_perf_3x.py
-- Tlamatini.md
-- tools.py
-- urls.py
-- version.py
-- views.py
-- web_search_llm.py
-- window_flash.py
-- windows_app_registration.py
-- acpx/
|  -- __init__.py
|  -- agent_registry.py
|  -- config.py
|  -- permissions.py
|  -- runtime.py
|  -- service.py
|  -- session_store.py
|  -- tests.py
|  -- tools.py
|  -- windows_spawn.py
-- agents/
|  -- acpxer/
|  |  -- acpxer.py
|  |  -- config.yaml
|  -- analyzer/
|  |  -- analyzer.py
|  |  -- config.yaml
|  -- and/
|  |  -- and.py
|  |  -- config.yaml
|  -- apirer/
|  |  -- apirer.py
|  |  -- config.yaml
|  -- arduiner/
|  |  -- arduiner.py
|  |  -- config.yaml
|  |  -- ArduinoTemplateProject/
|  |  |  -- ArduinoTemplateProject.ino
|  |  |  -- README.md
|  |  |  -- sketch.yaml
|  |  |  -- src/
|  |  |  |  -- Heartbeat.cpp
|  |  |  |  -- Heartbeat.h
|  -- asker/
|  |  -- asker.py
|  |  -- config.yaml
|  -- audioplayer/
|  |  -- audioplayer.py
|  |  -- config.yaml
|  -- barrier/
|  |  -- barrier.py
|  |  -- config.yaml
|  |  -- test_barrier.py
|  -- blenderer/
|  |  -- blenderer.py
|  |  -- config.yaml
|  -- camcorder/
|  |  -- camcorder.py
|  |  -- config.yaml
|  -- cleaner/
|  |  -- __init__.py
|  |  -- cleaner.py
|  |  -- config.yaml
|  -- counter/
|  |  -- config.yaml
|  |  -- counter.py
|  -- crawler/
|  |  -- config.yaml
```

Tree appendix 6 of 14

```
| | | `-- crawler.py
| | | -- croner/
| | | | -- config.yaml
| | | | `-- croner.py
| | | -- de_compressor/
| | | | -- config.yaml
| | | | `-- de_compressor.py
| | | -- deleter/
| | | | -- config.yaml
| | | | `-- deleter.py
| | | -- discoverer/
| | | | -- config.yaml
| | | | `-- discoverer.py
| | | -- dockerer/
| | | | -- config.yaml
| | | | `-- dockerer.py
| | | -- editor/
| | | | -- config.yaml
| | | | `-- editor.py
| | | -- emailer/
| | | | -- config.yaml
| | | | `-- emailer.py
| | | -- ender/
| | | | -- config.yaml
| | | | `-- ender.py
| | | -- esp32er/
| | | | -- config.yaml
| | | | `-- esp32er.py
| | | -- esphomer/
| | | | -- config.yaml
| | | | -- esphomer.py
| | | | `-- ESPHomeTemplateProject/
| | | | | -- README.md
| | | | | `-- tlamatini-light.yaml
| | | -- executer/
| | | | -- config.yaml
| | | | `-- executer.py
| | | -- file_creator/
| | | | -- config.yaml
| | | | `-- file_creator.py
| | | -- file_extractor/
| | | | -- config.yaml
| | | | `-- file_extractor.py
| | | -- file_interpreter/
| | | | -- config.yaml
| | | | `-- file_interpreter.py
| | | -- flowbacker/
| | | | -- config.yaml
| | | | `-- flowbacker.py
| | | -- flowcreator/
| | | | -- agentic_skill.md
| | | | -- config.yaml
| | | | `-- flowcreator.py
| | | -- flowhypervisor/
| | | | -- config.yaml
| | | | -- flowhypervisor.py
| | | | -- hypervisor_alert.wav
| | | | `-- monitoring-prompt.pmt
| | | -- forker/
| | | | -- config.yaml
| | | | `-- forker.py
| | | -- gateway_relayer/
| | | | -- config.yaml
| | | | -- gateway_relayer.md
| | | | `-- gateway_relayer.py
| | | -- gatewayer/
| | | | -- config.yaml
| | | | -- gatewayer.md
| | | | -- gatewayer.py
| | | | `-- gatewayer_explanation.md
| | | -- gitter/
| | | | -- config.yaml
| | | | `-- gitter.py
| | | -- globber/
| | | | -- config.yaml
| | | | `-- globber.py
```

Tree appendix 7 of 14

```
-- googler/
|-- config.yaml
|-- googler.py
-- grepper/
|-- config.yaml
|-- grepper.py
-- image_interpreter/
|-- config.yaml
|-- image_interpreter.py
-- instant_messaging_doctor/
|-- config.yaml
|-- instant_messaging_doctor.py
-- j_decompiler/
|-- config.yaml
|-- j_decompiler.py
-- jenkinser/
|-- config.yaml
|-- jenkinser.py
-- kalier/
|-- config.yaml
|-- kalier.py
-- keyboarder/
|-- config.yaml
|-- keyboarder.py
-- kubernetes/
|-- config.yaml
|-- kubernetes.py
-- kyber_cipher/
|-- config.yaml
|-- kyber_cipher.py
-- kyber_decipher/
|-- config.yaml
|-- kyber_decipher.py
-- kyber_keygen/
|-- config.yaml
|-- kyber_keygen.py
-- mcp_doctor/
|-- config.yaml
|-- mcp_doctor.py
-- mongoxer/
|-- config.yaml
|-- mongoxer.py
-- monitor_log/
|-- config.yaml
|-- monitor_log.py
-- monitor_netstat/
|-- config.yaml
|-- monitor_netstat.py
-- mouser/
|-- config.yaml
|-- mouser.py
-- mover/
|-- config.yaml
|-- mover.py
-- node_manager/
|-- config.yaml
|-- node_manager.md
|-- node_manager.py
|-- nodes_example.json
|-- nodes_example.yaml
-- notifier/
|-- config.yaml
|-- notifier.py
-- or/
|-- config.yaml
|-- or.py
-- parametrizer/
|-- config.yaml
|-- parametrizer.py
-- playwrighter/
|-- config.yaml
|-- playwrighter.py
-- prompter/
|-- config.yaml
|-- prompter.py
-- pser/
```

Tree appendix 8 of 14

```

|-- config.yaml
|-- pser.py
-- pythonxer/
|-- config.yaml
|-- pythonxer.py
-- raiser/
|-- config.yaml
|-- raiser.py
-- recmailer/
|-- config.yaml
|-- recmailer.py
-- recorder/
|-- config.yaml
|-- recorder.py
-- reviewer/
|-- config.yaml
|-- reviewer.py
-- scper/
|-- config.yaml
|-- scper.py
-- shoter/
|-- config.yaml
|-- shoter.py
-- sleeper/
|-- config.yaml
|-- sleeper.py
-- sqler/
|-- config.yaml
|-- sqler.py
-- ssher/
|-- config.yaml
|-- ssher.py
-- starter/
|-- config.yaml
|-- starter.py
-- stm32er/
|-- config.yaml
|-- stm32er.py
-- stopper/
|-- config.yaml
|-- stopper.py
-- summarizer/
|-- config.yaml
|-- summarizer.py
-- talker/
|-- config.yaml
|-- talker.py
-- telegrammer/
|-- config.yaml
|-- HOW_TO_GET_YOUR_TELEGRAM_ASSETS.md
|-- telegrammer.py
|-- guide_assets/
|-- telegram_01_botfather_search.jpg
|-- telegram_02_newbot_token.jpg
|-- telegram_03_start_bot_getupdates.jpg
|-- telegram_04_tlamatini_contacts.jpg
-- teletlamatini/
|-- config.yaml
|-- teletlamatini.py
-- unrealer/
|-- config.yaml
|-- unrealer.py
-- video_analyzer/
|-- config.yaml
|-- video_analyzer.py
-- videoplayer/
|-- config.yaml
|-- videoplayer.py
-- whatsapper/
|-- config.yaml
|-- HOW_TO_GET_YOUR_WHATSAPP_ASSETS.md
|-- whatsapper.py
|-- guide_assets/
|-- whatsapp_01_meta_create_app.jpg
|-- whatsapp_02_api_setup_keys.jpg
|-- whatsapp_03_test_recipient_send.jpg

```


Tree appendix 9 of 14

```
-- whatsapp_04_system_user_token.jpg
-- whatsapp_05_tlamatini_contacts.jpg
-- whisperer/
|   |-- config.yaml
|   |-- whisperer.py
-- windower/
|   |-- config.yaml
|   |-- windower.py
-- zavuerer/
|   |-- config.yaml
|   |-- zavuerer.py
-- doc_generation/
|-- complete_project_docs.py
|-- markdown_to_pdf.py
|-- refresh_project_docs.py
|-- test_output.pdf
-- images/
|-- HiIamTlamatini.png
|-- mockup.jpg
|-- Modify_the_last_video_keepi.mp4
|-- RealisticTlamatini.png
|-- ShouldersUoTlamatini.png
|-- Tlamatini AI Agentic Advisor Video.mp4
|-- TlamatiniAndKyber.mp4
|-- TlamatiniDrawings.png
|-- TlammatiniLetsMakeSomeMagic.mp4
|-- TorsoTlamatini.png
|-- XAIHT-Tlamatini.mp4
-- imaging/
|-- converter.py
|-- image_interpreter.py
|-- screenshot.py
-- management/
|-- __init__.py
|-- commands/
|   |-- acpx_lint.py
|   |-- startserver.py
-- migrations/
|-- 0001_initial.py
|-- 0002_populate_db.py
|-- 0003_add_cleaner.py
|-- 0004_add_deleter.py
|-- 0005_add_executer.py
|-- 0006_add_notifier.py
|-- 0007_add_stopper.py
|-- 0008_add_recmailer.py
|-- 0009_add_whatsapper.py
|-- 0010_add_pythonxer.py
|-- 0011_add_asker.py
|-- 0012_repopulate_all_agents.py
|-- 0013_add_forker.py
|-- 0014_repopulate_all_agents.py
|-- 0015_add_shoter.py
|-- 0016_repopulate_all_agents.py
|-- 0017_add_ssher.py
|-- 0018_repopulate_all_agents.py
|-- 0019_add_scper.py
|-- 0020_repopulate_all_agents.py
|-- 0021_add_telegramrx.py
|-- 0022_repopulate_all_agents.py
|-- 0023_add_mongoxer.py
|-- 0024_repopulate_all_agents.py
|-- 0025_add_telegramer.py
|-- 0026_repopulate_all_agents.py
|-- 0027_add_sqler.py
|-- 0028_repopulate_all_agents.py
|-- 0029_add_prompter.py
|-- 0030_repopulate_all_agents.py
|-- 0031_add_flowcreator.py
|-- 0032_repopulate_all_agents.py
|-- 0033_add_gitter.py
|-- 0034_add_dockerer.py
|-- 0035_add_pser.py
|-- 0036_add_kubernetex.py
|-- 0037_add_apirer.py
|-- 0038_add_jenkinser.py
```

Tree appendix 10 of 14

```
-- 0039_add_crawler.py
-- 0040_add_summarizer.py
-- 0041_add_flowhypervisor.py
-- 0042_add_mouser.py
-- 0043_agentmessage_conversation_user.py
-- 0044_add_counter.py
-- 0045_add_file_interpreter.py
-- 0046_add_image_interpreter.py
-- 0047_add_gatewayer.py
-- 0048_add_gateway_relayer.py
-- 0049_add_node_manager.py
-- 0050_add_file_creator.py
-- 0051_add_file_extractor.py
-- 0052_add_kyber_keygen.py
-- 0053_add_kyber_cipher.py
-- 0054_add_kyber_decipher.py
-- 0055_fix_kyber_cipher_names.py
-- 0056_add_parametrizer.py
-- 0057_add_flowbacker.py
-- 0058_add_barrier.py
-- 0059_add_j_decompiler.py
-- 0060_add_agent_parametrizer_tool.py
-- 0061_add_agent_starter_tool.py
-- 0062_sync_agent_control_tools_and_prompts.py
-- 0063_add_agent_parametrizer_prompt.py
-- 0064_add_chat_agent_run_model.py
-- 0065_add_chat_wrapped_agent_tools.py
-- 0066_add_keyboarder.py
-- 0067_add_multi_turn_demo_prompts.py
-- 0068_add_googler_tool.py
-- 0069_add_googler_agent.py
-- 0070_add_teletlamatini.py
-- 0071_acpx_skills.py
-- 0072_add_acpx_demo_prompts.py
-- 0073_acpx_demo_gemini_uplift.py
-- 0074_simplify_demo_prompts.py
-- 0075_add_acpx_tool_surface.py
-- 0076_add_acpxer.py
-- 0077_add_whatstlamatini.py
-- 0078_add_chat_agent_keyboarder_tool.py
-- 0079_add_chat_agent_mouser_tool.py
-- 0080_add_chat_agent_sleeper_tool.py
-- 0081_add_window_present_and_run_wait_tools.py
-- 0082_add_chat_agent_j_decompiler_tool.py
-- 0083_add_de_compressor.py
-- 0084_add_chat_agent_de_compressor_tool.py
-- 0085_add_unrealer.py
-- 0086_add_chat_agent_unrealer_tool.py
-- 0087_add_unrealer_demo_prompt.py
-- 0088_add_reviewer.py
-- 0089_add_analyzer.py
-- 0090_add_reviewer_analyzer_demo_prompts.py
-- 0091_add_playwrighter.py
-- 0092_add_chat_agent_playwrighter_tool.py
-- 0093_add_windower.py
-- 0094_add_chat_agent_windower_tool.py
-- 0095_add_windower_playwrighter_demo_prompts.py
-- 0096_add_director_virtuoso_demo_prompts.py
-- 0097_add_kalier.py
-- 0098_add_chat_agent_kalier_tool.py
-- 0099_add_kalier_demo_prompts.py
-- 0100_add_unrealer_extended_demo_prompts.py
-- 0101_add_stm32er.py
-- 0102_add_chat_agent_stm32er_tool.py
-- 0103_add_stm32er_demo_prompts.py
-- 0104_fix_stm32er_hil_serial_proof.py
-- 0105_add_esp32er.py
-- 0106_add_chat_agent_esp32er_tool.py
-- 0107_add_esp32er_demo_prompts.py
-- 0108_add_flow_making_demo_prompt.py
-- 0109_add_arduiner.py
-- 0110_add_chat_agent_arduiner_tool.py
-- 0111_add_arduiner_demo_prompts.py
-- 0112_add_camcorder.py
-- 0113_add_chat_agent_camcorder_tool.py
-- 0114_add_recorder.py
```

Tree appendix 11 of 14

```
-- 0115_add_chat_agent_recorder_tool.py
-- 0116_add_audioplayer.py
-- 0117_add_chat_agent_audioplayer_tool.py
-- 0118_add_videoplayer.py
-- 0119_add_chat_agent_videoplayer_tool.py
-- 0120_add_talker.py
-- 0121_add_chat_agent_talker_tool.py
-- 0122_add_talker_demo_prompt.py
-- 0123_add_whisperer.py
-- 0124_add_chat_agent_whisperer_tool.py
-- 0125_add_whisperer_demo_prompt.py
-- 0126_add_blenderer.py
-- 0127_add_chat_agent_blenderer_tool.py
-- 0128_add_blenderer_demo_prompts.py
-- 0129_add_editor.py
-- 0130_add_chat_agent_editor_tool.py
-- 0131_add_editor_demo_prompts.py
-- 0132_add_grepper.py
-- 0133_add_chat_agent_grepper_tool.py
-- 0134_add_grepper_demo_prompts.py
-- 0135_add_globber.py
-- 0136_add_chat_agent_globber_tool.py
-- 0137_add_globber_demo_prompts.py
-- 0138_add_esphomer.py
-- 0139_add_chat_agent_esphomer_tool.py
-- 0140_add_esphomer_demo_prompts.py
-- 0141_add_mcp_doctor.py
-- 0142_add_chat_agent_mcp_doctor_tool.py
-- 0143_add_mcp_doctor_demo_prompt.py
-- 0144_insert_java17_maven_demo_prompt_at_5.py
-- 0145_insert_createsuperuser_wizard_prompt_at_1.py
-- 0146_update_createsuperuser_wizard_continuation.py
-- 0147_add_unreal_game_demo_prompts.py
-- 0148_add_discoverer_demo_prompts.py
-- 0149_add_discoverer.py
-- 0150_add_chat_agent_discoverer_tool.py
-- 0151_retire_old_messaging_add_telegrammer.py
-- 0152_add_instant_messaging_doctor.py
-- 0153_add_chat_agent_instant_messaging_doctor_tool.py
-- 0154_add_instant_messaging_doctor_demo_prompt.py
-- 0155_add_contact_scaffold_demo_prompt.py
-- 0156_add_telegrammer_identity_demo_prompts.py
-- 0157_add_whatsapp_identity_demo_prompt.py
-- 0158_redesign_messaging_demo_prompts.py
-- 0159_add_zavuerer.py
-- 0160_add_chat_agent_zavuerer_tool.py
-- 0161_add_zavuerer_demo_prompts.py
-- 0162_add_zavuerer_catalog_prompts.py
-- 0163_add_zavuerer_get_key_wizard_prompt.py
-- 0164_dedup_zavuerer_setup_wizards.py
-- 0165_add_image_interpreter_triple_model_demo_prompt.py
-- 0166_add_video_analyzer.py
-- 0167_add_chat_agent_video_analyzer_tool.py
-- 0168_add_video_analyzer_demo_prompt.py
-- 0169_add_discoverer_cvemap_latest_demo_prompt.py
-- __init__.py
-- monitors/
--   -- monitor.sql.py
-- opus_client/
--   -- claude_opus_client.py
--   -- examples.py
--   -- README.md
-- rag/
--   -- __init__.py
--   -- config.py
--   -- factory.py
--   -- interaction.py
--   -- interface.py
--   -- loaders.py
--   -- prompts.py
--   -- retrieval.py
--   -- splitters.py
--   -- utils.py
--   -- chains/
--     -- base.py
--     -- basic.py
```

Tree appendix 12 of 14

```
-- history_aware.py
-- unified.py
-- services/
--   __init__.py
--   agent_contracts.py
--   agent_paths.py
--   filesystem.py
--   flow_compiler.py
--   flow_spec.py
--   response_parser.py
-- skills/
--   __init__.py
--   frontmatter.py
--   harness.py
--   io_contract.py
--   registry.py
-- skills_pkg/
--   _meta/
--     |__ lint.py
--     |__ schema.json
--   acp_router/
--     |__ SKILL.md
--   code_review/
--     |__ SKILL.md
--   create_new_agent/
--     |__ SKILL.md
--   create_new_mcp/
--     |__ SKILL.md
--   flow_making/
--     |__ SKILL.md
--     |__ references/
--     |   |__ flw_schema.md
--     |__ scripts/
--       |__ make_flow.py
--       |__ result_to_flw.py
--   github/
--     |__ SKILL.md
--   gmail/
--     |__ SKILL.md
--   hello_world/
--     |__ SKILL.md
--   jira/
--     |__ SKILL.md
--   kali_pentest/
--     |__ SKILL.md
--   notion/
--     |__ SKILL.md
--   security_audit/
--     |__ SKILL.md
--   setup_new_acpx_key/
--     |__ SKILL.md
--   skill_creator/
--     |__ SKILL.md
--     |__ scripts/
--       |__ quick_validate.py
--   slack/
--     |__ SKILL.md
--   summarize/
--     |__ SKILL.md
--   tlamatini_allowed_hosts_tighten/
--     |__ SKILL.md
--   tlamatini_csrf_exempt_audit/
--     |__ SKILL.md
--   tlamatini_exec_report_row_adder/
--     |__ SKILL.md
--   tlamatini_flow_from_objective/
--     |__ SKILL.md
--   tlamatini_flw_doctor/
--     |__ SKILL.md
--   tlamatini_new_acp_agent/
--     |__ SKILL.md
--   tlamatini_planner_trace_replay/
--     |__ SKILL.md
--   tlamatini_static_version_bumper/
--     |__ SKILL.md
--   todoist/
```

Tree appendix 13 of 14

```

|-- SKILL.md
|-- trello/
|-- SKILL.md
|-- weather/
|-- SKILL.md
-- static/
  |-- agent/
    |-- css/
      |-- access_keys_wizard.css
      |-- agent_page.css
      |-- agentic_control_panel.css
      |-- contacts_dialog.css
      |-- external_mcps_dialog.css
      |-- login.css
      |-- skills_dialog.css
      |-- tools_dialog.css
      |-- welcome.css
    |-- img/
      |-- spinner.svg
      |-- Tlamatini.ico
    |-- js/
      |-- access_keys_wizard.js
      |-- acp-agent-connectors.js
      |-- acp-canvas-core.js
      |-- acp-canvas-undo.js
      |-- acp-control-buttons.js
      |-- acp-file-io.js
      |-- acp-flow-snapshot.js
      |-- acp-globals.js
      |-- acp-layout.js
      |-- acp-parametrizer-dialog.js
      |-- acp-running-state.js
      |-- acp-session.js
      |-- acp-undo-manager.js
      |-- acp-validate.js
      |-- agent_page_canvas.js
      |-- agent_page_chat.js
      |-- agent_page_context.js
      |-- agent_page_dialogs.js
      |-- agent_page_init.js
      |-- agent_page_layout.js
      |-- agent_page_state.js
      |-- agent_page_ui.js
      |-- agentic_control_panel.js
      |-- canvas_item_dialog.js
      |-- chat_page_runtime_poller.js
      |-- contacts_dialog.js
      |-- contextual_menus.js
      |-- external_mcps_dialog.js
      |-- shared-runtime-dialogs.js
      |-- skills_dialog.js
      |-- tools_dialog.js
    |-- sounds/
      |-- hypervisor_alert.wav
      |-- notification.wav
    |-- video/
      |-- XAIHT-Tlamatini.mp4
  -- templates/
    |-- agent/
      |-- agent_page.html
      |-- agentic_control_panel.html
      |-- login.html
      |-- welcome.html
  -- test_fixtures/
    |-- talker_orpheus_tokens.txt
  -- TlamatiniSourceCode/
    |-- README.md
-- DB/
  |-- Older/
    |-- README.md
  |-- ToLoad/
    |-- README.md
-- jd-cli/
  |-- jd-cli.bat
  |-- jd-cli.jar
-- tests_e2e/

```

Tree appendix 14 of 14

```
| |-- README.md
| |-- test_create_flow_visual.py
| |-- test_self_healing_visual.py
|-- tlamatini/
| |-- __init__.py
| |-- asgi.py
| |-- context_processors.py
| |-- logging_filters.py
| |-- middleware.py
| |-- settings.py
| |-- urls.py
| |-- wsgi.py
```