

Part 1: Equivalence Classes

deviceType

Class	Valid/Invalid	Inputs
DC1	Valid	Mobile
DC2	Valid	Console
DC3	Invalid	any other value or empty input, e.g. Handheld , PC , ``

vramMB

Class	Valid/Invalid	Inputs
VC1	Invalid	vramMB <= 2047
VC2	Valid	deviceType = Mobile with 2048 <= vramMB <= 4096
VC3	Valid	deviceType = Mobile with 4097 <= vramMB <= 16384
VC4	Valid	deviceType = Console with 2048 <= vramMB <= 8192
VC5	Valid	deviceType = Console with 8193 <= vramMB <= 16384
VC6	Invalid	vramMB >= 16385

Part 2: Representative Test Cases

Test Case	deviceType	vramMB	Expected Result
TC1	Mobile	1000	unsupported
TC2	Mobile	3000	performance
TC3	Mobile	6000	quality
TC4	Console	5000	performance
TC5	Console	12000	quality
TC6	Console	24000	unsupported
TC7	Handheld	6000	unsupported

Part 3: Boundary Values

Mobile Minimum Engine Baseline

Tested with deviceType = Mobile:

Test Case	vramMB	Expected Result
TC10	2047	unsupported
TC11	2048	performance
TC12	2049	performance