

IINSTANCEBASE INTERFACE

The `IInstanceBase` interface is used as the base class for instances in the SDK. For "world" type plugins, instances instead derive from `IWorldInstanceBase`, which itself derives from `IInstanceBase`.

`IInstanceBase` cannot be directly constructed; it should only be used as a base class.

Properties

`this._sdkType`

Reference to the associated SDK type class.

`this._inst`

Reference to the `IObjectInstance` interface, or `IWorldInstance` interface for "world" type plugins, representing this instance in the editor. This allows access to Construct's built-in features for instances.

Methods

`Release()`

Optional override for when an instance is released.

`OnCreate()`

Optional override for when an instance is created in the editor.

`OnPropertyChanged(id, value)`

Optional override for when a property with the given ID is changed. The value the property was changed to is also passed.

LoadC2Property(name, valueString)

Optional override to use custom logic for importing properties from a Construct 2 project referencing a Construct 2 version of this plugin.

GetProject()

Return the [IProject](#) representing the instance's associated project.

GetObjectType()

Convenience method to return the [IObjectType](#) interface representing Construct's object type class.

GetInstance()

Return the [IObjectInstance](#) corresponding to this instance.

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 23 Jan, 2018 at 13:38