

IEVENTBLOCK INTERFACE

The `IEventBlock` interface represents an event block in the event sheet. Event blocks are the most important kind of event, and consist of a number of conditions, actions to run when the conditions are met, and optionally further sub-events. It derives from `IEventParentRow`.

Creating an event block

The following code sample demonstrates the calls necessary to add an *On start of layout* event to the associated event sheet for a given `ILayoutView`. This is useful with the Custom Importer API, since the `AddDragDropFileImportHandler` callback provides the `ILayoutView` that content was dropped in to.

```

1 // Note: this code is assumed to be in an async function
2 // First get the associated event sheet for the layout view
3 const eventSheet = layoutView.GetLayout().GetEventSheet();
4 if (eventSheet) // note the layout may not have an event sheet
5 {
6     // Get the IOBJECTType for the System plugin
7     const systemType = eventSheet.GetProject().GetSystemType();
8
9     // Create an empty event block at the root level of the event sheet
10    const eventBlock = await eventSheet.GetRoot().AddEventBlock();
11
12    // Add an 'On start of layout' condition
13    eventBlock.AddCondition(systemType, null, "on-start-of-layout");
14
15    // Example code for adding a 'Set position' action
16    //eventBlock.AddAction(iObjectType, null, "set-position", [100, 200]);
17 }

```

Finding condition and action IDs

Some developer methods are available to explore the list of condition and action IDs that can be used to create events with. See [Finding addon IDs](#) for

more information.

Methods

`AddCondition(iObjectClass, reserved, cndId, params)`

`AddAction(iObjectClass, reserved, actId, params)`

Add a condition or action to this event block. These methods are very similar so they are documented together. *iObjectClass* must be an *IObjectClass* (i.e. an *IObjectType* or *IFamily*) to create the condition and action for. The next parameter is reserved for future use; you must pass `null`. *cndId* or *actId* must be a string specifying the condition or action to create; for example the System *On start of layout* condition ID is `"on-start-of-layout"`. If the condition or action uses any parameters, then *params* must be an array with enough elements for every parameter. Each parameter can be a string, number, boolean or *IObjectType*. Expression parameters use a string, which can be any valid expression (including calculations like `"1+1"` for number parameters); if you pass a number, it will be converted to a string. *IObjectClass* can also be passed for object parameters.

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 22 Oct, 2025 at 15:42