

ILAYOUTVIEW INTERFACE

The `ILayoutView` interface provides access to a Layout View from the SDK. Note that this interface represents the editor view; the `ILayout` interface provides the interface to the actual layout in the project model.

Methods

`GetProject()`

Return the `IProject` representing the project associated with this Layout View.

`GetLayout()`

Return an `ILayout` representing the layout in the project model that this Layout View is showing.

`GetActiveLayer()`

Return an `ILayer` representing the current active layer selected in this Layout View.

`GetZoomFactor()`

Return the current zoom factor of the Layout View. For example 1 represents 100% zoom, 0.5 represents 50% zoom, etc.

`LayoutToClientDeviceX(x)`

`LayoutToClientDeviceY(y)`

Convert from layout co-ordinates to device pixel co-ordinates in the layout view canvas. This is useful for rendering at device pixel sizes after calling `SetDeviceTransform()`.

SetDeviceTransform(iRenderer)

Set the given [IWebGLRenderer](#) to a device pixel co-ordinate transform. This means co-ordinates used for rendering are based on device pixel co-ordinates relative to the layout view canvas, rather than layout co-ordinates.

SetDefaultTransform(iRenderer)

Set the given [IWebGLRenderer](#) to a layout co-ordinate transform. This is the default and should be restored after using

`SetDeviceTransform()`.

Refresh()

Schedules the layout view to be redrawn at the next animation frame. Avoid unnecessarily refreshing the layout view, such as refreshing on a timer, since this can waste battery life.

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 8 Jan, 2018 at 16:08