

SET PLAYER AVATAR

Overview

Sets a players avatar, overwriting the existing one if the player already has an avatar set. Supported avatar file types are `Gif`, `Jpeg`, `Png`, `WebP`, `SVG`. The minimum avatar size is `32x32` pixels and the maximum avatar size is `2048x2048` pixels. The maximum file size of uploaded avatars depends on your CGS plan - please refer to your [CGS account](#) to find this value.

If a player is [restricted](#) from setting an avatar with the `Upload Avatar` restriction,, an error will be returned unless a game API key is used to authenticate the request.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
1 | https://auth.construct.net/setavatar.json
```

Authenticating The Request

This end point can be called by [signed in](#) players, or with [secret key](#) authentication.

Session Key Authentication

`sessionKey` `string` **Required**

The [session key](#) of the player you're making the request against.

Secret Key Authentication

secret string **Required**

Your games **secret API key**.

playerID **guid** **Required**

The player ID you wish to make this request against.

Request Parameters

gameID **guid** **Required**

The ID of the game you are making this request against. You can find the ID of your game in your **Construct Game Services (CGS) account**.

avatar string **Sometimes required**

The base64 encoded avatar picture being set for this player. You must specify this, **avatarURL** or **avatarData**.

avatarURL url (string) **Sometimes required**

The absolute URL of the avatar being set for this player. You must specify this, **avatar** or **avatarData**.

File Data

This request additionally supports the posting of files. These files should be sent as **multipart/form-data**, with the corresponding keys.

avatarData multipart/form-data **Sometimes required**

The data of the avatar image being set for this player. You must specify this, **avatar** or **avatarURL**.

Success Response

Successful responses always return a **HTTP 200** status code.

```
1 {
2   "success": true,
3   "avatars": [
4     { ... },
5     { ... }
6   ],
7 }
```

```
7 | "formattingCulture": "en-us"  
8 | }
```

Response Properties

success `bool`

If the request was successful or not.

avatars `Array<Picture>`

A list of `picture objects` representing the player's new avatar. Each picture object is the same avatar, but provided in different sizes. Sizes available are based on widths, and the widths `16, 32, 64, 96, 128, 256` will be shown here along with the original avatar size if it doesn't match a width in this list. Some sizes may not show if the width is less than the original avatar width.

formattingCulture `string`

If some return values are `culture specific`, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
1 | {  
2 |   "success": false,  
3 |   "errorMessage": "The image provided is not valid Base64 data.",  
4 |   "helpURL": "https://www.construct.net/en/game-services/manuals/game-se  
5 |   "shouldRetry": false  
6 | }
```

Response Properties

success `bool`

If the request was successful or not.

errorMessage `string`

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 5 Dec, 2025 at 11:57