

LINK LOGIN PROVIDER

Overview

If a player is signed in, you can link another **login provider** to this player which gives them more ways to **sign-in** to their account. Only one account per provider is permitted for player accounts - for example you can't tie multiple Steam accounts to the same player account.

The provider `UsernamePassword` is not supported for link requests. Use the **set username password** end point instead to set a new username/password or update the users username/password.

When you request a link, the parameter `redirectToURL` will be returned. Make the player visit this URL (for example in a new popup window). Then, with the `pollToken` parameter you can periodically call the **link poll** end point. Once the user completes the sign in process from `redirectToURL`, this end point will tell you that the link request completed successfully, expired or requires further action.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
1 | https://auth.construct.net/link.json
```

Authenticating The Request

This end point is for **signed in** players only.

`sessionKey` string **Required**

The [session key](#) of the player you're making the request against.

Request Parameters

gameID [guid](#) [Required](#)

The ID of the game you are making this request against. You can find the ID of your game in your [Construct Game Services \(CGS\) account](#).

provider [string](#) [Required](#)

The [login provider](#) you wish to link (case insensitive) to this players account. Must be one of [Apple](#), [BattleNet](#), [Discord](#), [Facebook](#), [Github](#), [Google](#), [ItchIO](#), [Microsoft](#), [Patreon](#), [Reddit](#), [Steam](#), [X](#), [Yandex](#). For [UsernamePassword](#), use the [Set Username and Password](#) end point. For [Email](#) use the [Set Email Address](#) end point.

Success Response

Successful responses always return a [HTTP 200](#) status code.

```
1 {  
2   "success": true,  
3   "pollToken": "1e713c44-e4fb-49a3-8005-d0905b2e000f",  
4   "redirectToURL": "https://...",  
5   "formattingCulture": "en-us"  
6 }
```

Response Properties

success [bool](#)

If the request was successfull or not.

pollToken [guid](#)

A polling token to get the status of the user action. For [sign in requests](#) use this poll token on the [sign in poll](#) end point. For [link requests](#) use this poll token on the [link poll](#) end point.

redirectToURL [url \(string\)](#)

The URL to the external third party login provider to complete the sign-in or link request. This property will be null for the Email sign in method as

no redirect is required.

formattingCulture string

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return **HTTP 4xx** status codes.

```
1 {  
2   "success": false,  
3   "errorMessage": "You already have Discord as a sign-in method.",  
4   "helpURL": "https://www.construct.net/en/game-services/manuals/game-se  
5   "shouldRetry": false  
6 }
```

Response Properties

success bool

If the request was successfull or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 14 Apr, 2026 at 05:31