

DELETE PLAYER

Overview

Deleting a player removes them from your game completely, and deletes all associated data from all other Construct Game Services in your game such as leaderboard scores, cloud saves etc. Deletion is completely irreversible.

It's important to ensure that you give players the option to delete themselves for privacy reasons.

Once deleted, requests for this specific player ID will immediately start failing due to the player being deleted, however you may notice other data in Construct Game Services for this player may take a short period of time to be deleted. The length of time to fully delete the player and their data will depend on how much they have interacted with other game services and how busy the CGS servers currently are. It is safe to assume all their data will be fully deleted within 24 hours.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
1 | https://auth.construct.net/deleteplayer.json
```

Authenticating The Request

This end point can be called by **signed in** players, or with **secret key** authentication.

Session Key Authentication

sessionKey string **Required**

The **session key** of the player you're making the request against.

Secret Key Authentication

secret string **Required**

Your games **secret API key**.

playerID guid **Required**

The player ID you wish to make this request against.

Request Parameters

gameID guid **Required**

The ID of the game you are making this request against. You can find the ID of your game in your **Construct Game Services (CGS) account**.

Success Response

Successful responses always return a **HTTP 200** status code.

```
1 {  
2   "success": true,  
3   "formattingCulture": "en-us"  
4 }
```

Response Properties

success bool

If the request was successful or not.

formattingCulture string

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return HTTP 4xx status codes.

```
1 {  
2   "success": false,  
3   "errorMessage": "Your request failed due to...",  
4   "helpURL": "https://www.construct.net/en/game-services/manuals/game-ser  
5   "shouldRetry": false  
6 }
```

Response Properties

success bool

If the request was successful or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.

You are here:

Search this manual:

Community Help

Contact Us

This manual entry was last updated on 5 Dec, 2025 at 11:57