

GET A PLAYER

Overview

This end point allows you to retrieve a **player object** based on the players player name or players ID. As the only way to query this end point is with a secret key, this should only be called by back end services.

As a player, this request is never needed as the relevant player objects are returned in responses when interacting with the other services and end points.

Request URL

All parameters in the request must be sent as a **post** HTTP request. Make all requests to the following URL:

```
1 | https://auth.construct.net/getplayer.json
```

Authenticating The Request

This end point is for **secret key** authenticated requests only. Signed in players cannot call this end point.

secret string **Required**

Your games **secret API key**.

Request Parameters

gameID **guid** **Required**

The ID of the game you are making this request against. You can find the ID of your game in your [Construct Game Services \(CGS\) account](#).

playerID guid Sometimes required

The ID of the player you are querying. You must specify this or **playerName**.

playerName string Sometimes required

The name of the player you are querying. Player names are case insensitive. You must specify this or **playerID**.

Success Response

Successful responses always return a `HTTP 200` status code.

```
1 | {  
2 |   "success": true,  
3 |   "player": { ... },  
4 |   "formattingCulture": "en-us"  
5 | }
```

Response Properties

success bool

If the request was successful or not.

player Player

The player returned from the query.

formattingCulture string

If some return values are [culture specific](#), this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{  
  "success": false,  
  "errorMessage": "Your request failed due to...",  
}
```

```
4 | "helpURL": "https://www.construct.net/en/game-services/manuals/gar
5 | "shouldRetry": false
6 | }
```

Response Properties

success bool

If the request was successfull or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 5 Dec, 2025 at 11:57