

LIST PLAYERS

Overview

This end point allows you to retrieve **expanded player objects** for your game. As the only way to query this end point is with a secret key, this should only be called by back end services.

You can specify a list of player ID's to specify explicitly, otherwise all the players in your game will be returned.

Request URL

All parameters in the request must be sent as a `post` HTTP request. Make all requests to the following URL:

```
1 | https://auth.construct.net/listplayers.json
```

Authenticating The Request

This end point is for **secret key** authenticated requests only. Signed in players cannot call this end point.

secret string **Required**

Your games **secret API key**.

Request Parameters

gameID guid **Required**

The ID of the game you are making this request against. You can find the ID of your game in your **Construct Game Services (CGS)**

account.

order string

How you wish the players returned in this query to be ordered. Can be one of **None**, **AZ**, **ZA**, **Newest**, **Oldest** or **MostRecentlyActive**. The default value if not specified is **Newest**.

playerIDs string

A comma separated list of player ID's you explicitly wish to fetch. This list cannot contain more than **300** player ID's.

perPage int32

How many players you wish to return on each page of results. Cannot be less than **1** or more than **200**. Default value is **50**.

page int32

The page of results you are requesting. The first page is always **1**. If this value is not specified the first page will be returned.

culture string **Optional**

Optionally specify a **supported culture code** for rendering various properties. If not specified, the culture code from your games default language will be used.

Success Response

Successful responses always return a **HTTP 200** status code.

```
1 {  
2   "success": true,  
3   "pagination": { ... },  
4   "players": [  
5     { ... },  
6     { ... }  
7   ],  
8   "formattingCulture": "en-us"  
9 }
```

Response Properties

success `bool`

If the request was successful or not.

pagination `Pagination`

If there are more players returned than can be shown in one page of results, the pagination object can help you browse through the other pages of results.

players `Array<ExpandedPlayer>`

The players returned on this page of results for the query.

formattingCulture `string`

If some return values are `culture specific`, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
1  {
2    "success": false,
3    "errorMessage": "Your request failed due to...",
4    "helpURL": "https://www.construct.net/en/game-services/manuals/ga
5    "shouldRetry": false
6  }
```

Response Properties

success `bool`

If the request was successful or not.

errorMessage `string`

An error message with more detailed information on why the request failed.

helpURL `url (string)`

A link to documentation which should provide help with the error.

shouldRetry **bool**

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 4 Mar, 2026 at 15:24