

SET PLAYER RESTRICTIONS

Overview

Restrict a specific player from performing certain actions in your game/application. The following restrictions with their corresponding ID's are:

0 = Upload Avatar

Prevents the player from uploading an avatar image.

1 = Change Player Name

Prevents the player from being able to change their name.

101 = Cloud Save to Buckets

Prevents the player from cloud saving to game buckets.

102 = Cloud Save to Buckets

Prevents the player from cloud saving to their player account.

200 = Rate

Prevents the player from being able to rate objects.

If an error is returned, the players restrictions will not of been updated.

Request URL

All parameters in the request must be sent as a `POST` HTTP request.
Make all requests to the following URL:

Authenticating The Request

This end point can only be called with **secret key** authentication and specifying which player ID you're making the request against.

Secret Key Authentication

secret string **Required**

Your games **secret API key**.

playerID guid **Required**

The player ID you wish to make this request against.

Request Parameters

gameID guid **Required**

The ID of the game you are making this request against. You can find the ID of your game in your **Construct Game Services (CGS) account**.

restrictedActions string **Sometimes required**

A CSV list of actions to restrict. Values in this list can be the string value of the restricted action for example **Upload Avatar** (case insensitive), or the ID of the restricted action, for example **0**. Don't send this parameter or send an empty string to indicate you wish to remove all existing restrictions currently on this player.

Success Response

Successful responses always return a **HTTP 200** status code.

```
1 {  
2   "success": true,  
3   "formattingCulture": "en-us"  
4 }
```

Response Properties

success bool

If the request was successful or not.

formattingCulture string

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return **HTTP 4xx** status codes.

```
1 {  
2   "success": false,  
3   "errorMessage": "The restriction with the ID 1337 doesn't exist.",  
4   "helpURL": "https://www.construct.net/en/game-services/manuals/game-s  
5   "shouldRetry": false  
6 }
```

Response Properties

success bool

If the request was successful or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 26 Feb, 2026 at 15:19