

END A PLAYER SESSION

Overview

Ends a player session. Calling this end point invalidates the session key, requiring the player to sign in again in the future to create a new session.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
1 | https://auth.construct.net/endsession.json
```

Authenticating The Request

This end point is for **signed in** players only.

sessionKey string **Required**

The **session key** of the player you're making the request against.

Request Parameters

gameID guid **Required**

The ID of the game you are making this request against. You can find the ID of your game in your **Construct Game Services (CGS) account**.

Success Response

Successful responses always return a `HTTP 200` status code.

```
1 | {  
2 |   "success": true,  
3 |   "formattingCulture": "en-us"  
4 | }
```

Response Properties

success `bool`

If the request was successful or not.

formattingCulture `string`

If some return values are `culture specific`, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
1 | {  
2 |   "success": false,  
3 |   "errorMessage": "Your request failed due to...",  
4 |   "helpURL": "https://www.construct.net/en/game-services/manuals",  
5 |   "shouldRetry": false  
6 | }
```

Response Properties

success `bool`

If the request was successful or not.

errorMessage `string`

An error message with more detailed information on why the request failed.

helpURL `url (string)`

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 5 Dec, 2025 at 11:57