

CREATE A CHANNEL

Overview

This end point allows you to create a [broadcast channel](#). Once you've created a channel, you can then start to [create messages](#).

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
1 | https://broadcasts.construct.net/createchannel.json
```

Authenticating The Request

This end point is for [secret key](#) authenticated requests only. Signed in players cannot call this end point.

secret string **Required**

Your games [secret API key](#).

Request Parameters

gameID guid **Required**

The ID of the game you are making this request against. You can find the ID of your game in your [Construct Game Services \(CGS\) account](#).

name string **Required**

The name of the channel you want to create. Must be at least **1** character long and no more than **64** characters long. Channel names do not need to be unique.

description string

A description of the channel. Cannot exceed more than **256** characters long.

language string

The language ISO this channels name and description are written in. Must be one of **AR**, **BG**, **CS**, **DA**, **DE**, **EL**, **EN**, **ES**, **ET**, **FI**, **FR**, **HE**, **HU**, **ID**, **IT**, **JA**, **KO**, **LT**, **LV**, **NB**, **NL**, **PL**, **PT**, **RO**, **RU**, **SK**, **SL**, **SV**, **TH**, **TR**, **UK**, **VI**, **ZH**. Defaults to your games language if not specified.

allowRatings bool **Required**

If players can rate messages published in this channel or not.

requestedLanguage Language **Optional**

Optionally specify a **language** for returning translatable properties into this language. If not specified, your games default language will be used.

culture string **Optional**

Optionally specify a **supported culture code** for rendering various properties. If not specified, the **requestedLanguage** default culture code will be used.

Success Response

Successful responses always return a **HTTP 200** status code.

```
1 | {  
2 |   "success": true,  
3 |   "channel": { ... },  
4 |   "formattingCulture": "en-us"  
5 | }
```

Response Properties

success `bool`

If the request was successful or not.

channel `BroadcastChannel`

The channel object returned from the request.

formattingCulture `string`

If some return values are `culture specific`, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
1 {  
2   "success": false,  
3   "errorMessage": "You've reached the maximum allowed channels for this  
4   "helpURL": "https://www.construct.net/en/game-services/manuals/game-  
5   "shouldRetry": false  
6 }
```

Response Properties

success `bool`

If the request was successful or not.

errorMessage `string`

An error message with more detailed information on why the request failed.

helpURL `url (string)`

A link to documentation which should provide help with the error.

shouldRetry `bool`

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 20 Mar, 2026 at 10:06