

GET CHANNEL

Overview

This end point allows you to retrieve a single channel by it's ID.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
1 | https://broadcasts.construct.net/getchannel.json
```

Authenticating The Request

No authentication is required for calling this end point, however if the request is being made by a signed in player it is recommended to pass in a `sessionKey` parameter as the request response will return additional information useful to the player.

sessionKey string **Optional**

The **session key** of the player who is currently signed in and making this request.

Request Parameters

gameID guid **Required**

The ID of the game you are making this request against. You can find the ID of your game in your **Construct Game Services (CGS) account**.

channelID guid **Required**

The ID of the channel you want to retrieve.

requestedLanguage Language **Optional**

Optionally specify a **language** for returning translatable properties into this language. If not specified, your games default language will be used.

culture string **Optional**

Optionally specify a **supported culture code** for rendering various properties. If not specified, the **requestedLanguage** default culture code will be used.

Success Response

Successful responses always return a **HTTP 200** status code.

```
1 {  
2   "success": true,  
3   "channel": { ... },  
4   "formattingCulture": "en-us"  
5 }
```

Response Properties

success bool

If the request was successfull or not.

channel BroadcastChannel

The channel object returned from the request.

formattingCulture string

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return **HTTP 4xx** status codes.

```
1 | {
2 |   "success": false,
3 |   "errorMessage": "Your request failed due to...",
4 |   "helpURL": "https://www.construct.net/en/game-services/manuals/game
5 |   "shouldRetry": false
6 | }
```

Response Properties

success bool

If the request was successful or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 5 Dec, 2025 at 11:57