

CREATE A MESSAGE

Overview

This end point allows you to create a new **message** in a **channel**.

Request URL

All parameters in the request must be sent as a `POST` HTTP request.
Make all requests to the following URL:

```
1 | https://broadcasts.construct.net/createmessage.json
```

Authenticating The Request

This end point is for **secret key** authenticated requests only. Signed in players cannot call this end point.

secret string **Required**

Your games **secret API key**.

Request Parameters

gameID guid **Required**

The ID of the game you are making this request against. You can find the ID of your game in your **Construct Game Services (CGS) account**.

channelID guid **Required**

The ID of the channel you are publishing this message to.

title string

A title for this message. If specified, the maximum length of the title can be found in your plan settings.

text string **Required**

The text of this message. Can be in any text format, for example HTML, BBCode or just plain text.

language string

Provide this parameter to update the language that the name and description of this channel are written in. Permitted values are **AR**, **BG**, **CS**, **DA**, **DE**, **EL**, **EN**, **ES**, **ET**, **FI**, **FR**, **HE**, **HU**, **ID**, **IT**, **JA**, **KO**, **LT**, **LV**, **NB**, **NL**, **PL**, **PT**, **RO**, **RU**, **SK**, **SL**, **SV**, **TH**, **TR**, **UK**, **VI**, **ZH**. If not specified, your **channels language** will be used.

requestedLanguage Language **Optional**

Optionally specify a **language** for returning translatable properties into this language. If not specified, your games default language will be used.

culture string **Optional**

Optionally specify a **supported culture code** for rendering various properties. If not specified, the **requestedLanguage** default culture code will be used.

Success Response

Successful responses always return a **HTTP 200** status code.

```
1 {  
2   "success": true,  
3   "message": { ... },  
4   "formattingCulture": "en-us"  
5 }
```

Response Properties

success bool

If the request was successfull or not.

message **BroadcastMessage**

The message object returned from the request.

formattingCulture **string**

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return **HTTP 4xx** status codes.

```
1 {  
2   "success": false,  
3   "errorMessage": "Your request failed due to...",  
4   "helpURL": "https://www.construct.net/en/game-services/manuals/game-s  
5   "shouldRetry": false  
6 }
```

Response Properties

success **bool**

If the request was successfull or not.

errorMessage **string**

An error message with more detailed information on why the request failed.

helpURL **url (string)**

A link to documentation which should provide help with the error.

shouldRetry **bool**

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.

Search this manual:



[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 5 Dec, 2025 at 11:57