

GET A MESSAGE

Overview

This end point allows you to retrieve a single **message**.

If a player is signed in, you should pass their session key in with the request as once the message is retrieved it will be **marked as read** for that player.

Request URL

All parameters in the request must be sent as a **POST** HTTP request. Make all requests to the following URL:

```
1 | https://broadcasts.construct.net/getmessage.json
```

Authenticating The Request

No authentication is required for calling this end point, however if the request is being made by a signed in player it is recommended to pass in a **sessionKey** parameter as the request response will return additional information useful to the player.

sessionKey string **Optional**

The **session key** of the player who is currently signed in and making this request.

Request Parameters

gameID **guid** **Required**

The ID of the game you are making this request against. You can find the ID of your game in your [Construct Game Services \(CGS\) account](#).

messageID guid **Required**

The ID of the message you want to retrieve.

requestedLanguage Language **Optional**

Optionally specify a [language](#) for returning translatable properties into this language. If not specified, your games default language will be used.

culture string **Optional**

Optionally specify a [supported culture code](#) for rendering various properties. If not specified, the `requestedLanguage` default culture code will be used.

Success Response

Successful responses always return a `HTTP 200` status code.

```
1 {  
2   "success": true,  
3   "message": { ... },  
4   "formattingCulture": "en-us"  
5 }
```

Response Properties

success bool

If the request was successful or not.

message BroadcastMessage

The message object returned from the request.

formattingCulture string

If some return values are [culture specific](#), this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
1 | {  
2 |   "success": false,  
3 |   "errorMessage": "Your request failed due to...",  
4 |   "helpURL": "https://www.construct.net/en/game-services/manuals/game  
5 |   "shouldRetry": false  
6 | }
```

Response Properties

success `bool`

If the request was successful or not.

errorMessage `string`

An error message with more detailed information on why the request failed.

helpURL `url (string)`

A link to documentation which should provide help with the error.

shouldRetry `bool`

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 9 Mar, 2026 at 15:59

