

CREATE RATING DIMENSION

Overview

This end point allows you to create a new rating dimension for a channel - all messages in that channel can then be rated using that dimension.

We strongly recommend you read about [rating concepts](#) to understand how dimensions in ratings work.

Request URL

All parameters in the request must be sent as a `post` HTTP request. Make all requests to the following URL:

```
1 | https://broadcasts.construct.net/channelcreateratingdimension.json
```

Authenticating The Request

This end point is for [secret key](#) authenticated requests only. Signed in players cannot call this end point.

secret string **Required**

Your games [secret API key](#).

Request Parameters

gameID guid **Required**

The ID of the game you are making this request against. You can find the ID of your game in your [Construct Game Services \(CGS\) account](#).

thingID guid Required

The ID of the **channel** you're creating a rating dimension for.

dimensionID string Required

The ID of the rating dimension you're creating. Must be unique for this **channel**. Cannot exceed **50** characters in length and must only contain alpha-numeric, dots (.) and dash (-) characters. Once set, this ID cannot be changed.

title string

The title of this rating dimension. Cannot exceed **128** characters in length.

description string

The description of this rating dimension. Cannot exceed **1024** characters in length.

maxRating uint8 Required

The maximum allowed rating value. **0** is always permitted, so the minimum permitted value is **1** and the maximum permitted value is **255**.

language string

Provide this parameter to set the language that the title and description of this dimension are written in. Permitted values are **AR**, **BG**, **CS**, **DA**, **DE**, **EL**, **EN**, **ES**, **ET**, **FI**, **FR**, **HE**, **HU**, **ID**, **IT**, **JA**, **KO**, **LT**, **LV**, **NB**, **NL**, **PL**, **PT**, **RO**, **RU**, **SK**, **SL**, **SV**, **TH**, **TR**, **UK**, **VI**, **ZH**.

requestedLanguage Language Optional

Optionally specify a **language** for returning translatable properties into this language. If not specified, your games default language will be used.

Success Response

Successful responses always return a **HTTP 200** status code.

```
1 {  
2   "success": true,  
3   "dimension": { ... },  
4   "formattingCulture": "en-us"  
5 }
```

Response Properties

success `bool`

If the request was successfull or not.

dimension `RatingDimension`

The returned dimension for the request.

formattingCulture `string`

If some return values are `culture specific`, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
1 {  
2   "success": false,  
3   "errorMessage": "Your request failed due to...",  
4   "helpURL": "https://www.construct.net/en/game-services/manuals/game-  
5   "shouldRetry": false  
6 }
```

Response Properties

success `bool`

If the request was successfull or not.

errorMessage `string`

An error message with more detailed information on why the request failed.

helpURL `url (string)`

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 5 Dec, 2025 at 11:57