

CREATE A BUCKET

Overview

This end point allows you to create a **bucket**. Game buckets are containers that can hold multiple **cloud save blobs**.

You can set up buckets with different access modes. For example, create a `PublicRead` bucket to upload game content to which players can only read from. Or, create a `PublicReadWrite` bucket to allow players to upload shared content such as level designs.

`Private` buckets cannot be written to or read from by players - you typically don't need these but they can be used for more advanced implementations.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
1 | https://cloudsave.construct.net/createbucket.json
```

Authenticating The Request

This end point is for **secret key** authenticated requests only. Signed in players cannot call this end point.

secret string **Required**

Your games **secret API key**.

Request Parameters

gameID guid Required

The ID of the game you are making this request against. You can find the ID of your game in your [Construct Game Services \(CGS\) account](#).

bucketName string Required

The name of the game bucket you're creating. Cannot exceed **50** characters in length.

accessMode string Required

The access mode of this bucket (case insensitive). Must be one of **Private**, **PublicRead** or **PublicReadWrite**.

allowRatings bool Required

If [cloud save blobs](#) in this bucket can be [rated](#) by players.

maxBlobs int32

Optionally specify the maximum number of [cloud save blobs](#) allowed in this bucket.

maxBlobSize int32

Optionally specify the maximum size in bytes of [cloud save blobs](#) in this bucket. If a picture is uploaded with a blob, the size of the picture is counted towards this limit as well as the actual cloud save blob size.

maxBlobsPerPlayer int16

Optionally specify the maximum number of blobs an individual player can save to this bucket.

Success Response

Successful responses always return a **HTTP 200** status code.

```
1 {  
2   "success": true,  
3   "bucket": { ... },  
4  
5 }
```

```
} "formattingCulture": "en-us"
```

Response Properties

success `bool`

If the request was successful or not.

bucket `Bucket`

The bucket returned from the request.

formattingCulture `string`

If some return values are `culture specific`, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
1 {  
2   "success": false,  
3   "errorMessage": "Your request failed due to...",  
4   "helpURL": "https://www.construct.net/en/game-services/manuals/game  
5   "shouldRetry": false  
6 }
```

Response Properties

success `bool`

If the request was successful or not.

errorMessage `string`

An error message with more detailed information on why the request failed.

helpURL `url (string)`

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 5 Dec, 2025 at 11:57