

GET BUCKETS

Overview

This end point allows you to retrieve all existing **buckets** for your game.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
1 | https://cloudsave.construct.net/getbuckets.json
```

Authenticating The Request

No authentication is required for this request type.

Request Parameters

gameID **guid** **Required**

The ID of the game you are making this request against. You can find the ID of your game in your **Construct Game Services (CGS) account**.

orderBy **string**

How you wish the players returned in this query to be ordered. Can be one of `AZ`, `ZA`, `MostBlobs`, `LeastBlobs`, `MostData` or `LeastData`. The default value if not specified is `AZ`.

perPage int32

How many buckets you wish to return on each page of results. Cannot be less than **1** or more than **100**. Default value is **20**.

page int32

The page of results you are requesting. The first page is always **1**. If this value is not specified the first page will be returned.

culture string **Optional**

Optionally specify a **supported culture code** for rendering various properties. If not specified, the culture code from your games default language will be used.

Success Response

Successful responses always return a **HTTP 200** status code.

```
1 {  
2   "success": true,  
3   "pagination": { ... },  
4   "buckets": [  
5     { ... },  
6     { ... }  
7   ],  
8   "formattingCulture": "en-us"  
9 }
```

Response Properties

success bool

If the request was successful or not.

pagination Pagination

If there are more buckets than can be displayed on one page of results, this pagination object can be used to help browse through other pages of results.

buckets Array<Bucket>

The buckets returned from the request.

formattingCulture string

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return **HTTP 4xx** status codes.

```
1 | {  
2 |   "success": false,  
3 |   "errorMessage": "Your request failed due to...",  
4 |   "helpURL": "https://www.construct.net/en/game-services/manuals/g  
5 |   "shouldRetry": false  
6 | }
```

Response Properties

success bool

If the request was successful or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.

You are here:

Search this manual:

Community Help

[Contact Us](#)

[Community Help](#)
[Contact Us](#)

This manual entry was last updated on 5 Dec, 2025 at 11:57