

# GET A CLOUD SAVE

## Overview

Use this end point to return a single cloud save object.

When retrieving a blob by using the `key` parameter, the following requirements must be met:

- If the blob exists in a bucket, the `bucketID` parameter must be specified.
- If the blob exists in a players account, the request must be authenticated with a session key, or if using a secret key the player ID must also be passed.

## Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
1 | https://cloudsave.construct.net/getcloudsave.json
```

## Authenticating The Request

The type of authentication that is required depends on who owns the blob, and where the blob is stored.

- For cloud save blobs in `PublicRead` Or `PublicReadWrite` buckets, no authentication is required.
- For cloud save blobs in `Private` buckets, authentication by secret API key is required.

- For cloud save blobs in a players account, authentication by secret API key or the players session key is required.

## Session Key Authentication

---

**sessionKey** string **Optional**

The **session key** of the player you're making the request against.

## Secret Key Authentication

---

**secret** string **Optional**

Your games **secret API key**.

## Request Parameters

---

**gameID** guid **Required**

The ID of the game you are making this request against. You can find the ID of your game in your **Construct Game Services (CGS) account**.

**blobID** guid **Sometimes required**

The ID of the cloud save blob you wish to retrieve. You must specify this or **key**.

**key** string **Sometimes required**

The key of the cloud save blob you wish to retrieve. You must specify this or **blobID**.

**bucketID** guid **Sometimes required**

If fetching a cloud save blob by **key** that exists in a bucket, you must specify the bucket ID.

**requestedLanguage** Language **Optional**

Optionally specify a **language** for returning translatable properties into this language. If not specified, your games default language will be used.

**culture** string **Optional**

Optionally specify a **supported culture code** for rendering various properties. If not specified, the `requestedLanguage` default culture code will be used.

## Success Response

Successful responses always return a `HTTP 200` status code.

```
1 {  
2   "success": true,  
3   "blob": { ... },  
4   "formattingCulture": "en-us"  
5 }
```

## Response Properties

**success** bool

If the request was successful or not.

**blob** Blob

The blob object returned from the query.

**formattingCulture** string

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

## Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
1 {  
2   "success": false,  
3   "errorMessage": "Your request failed due to...",  
4   "helpURL": "https://www.construct.net/en/game-services/manuals/",  
5   "shouldRetry": false  
6 }
```

## Response Properties

**success** bool

If the request was successful or not.

---

**errorMessage** string

An error message with more detailed information on why the request failed.

---

**helpURL** url (string)

A link to documentation which should provide help with the error.

---

**shouldRetry** bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 9 Mar, 2026 at 15:59