

SET PICTURE

Overview

Use this end point to set a picture for a cloud save.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
1 | https://cloudsave.construct.net/setpicture.json
```

Authenticating The Request

This end point can be called by `signed in` players, or with `secret key` authentication.

Session Key Authentication

`sessionKey` `string` **Required**

The `session key` of the player you're making the request against.

Secret Key Authentication

`secret` `string` **Required**

Your games `secret API key`.

Request Parameters

gameID guid Required

The ID of the game you are making this request against. You can find the ID of your game in your [Construct Game Services \(CGS\) account](#).

blobID guid Required

The ID of the cloud save blob you wish to set a picture for.

picture string Sometimes required

The base64 encoded picture being set. You must specify this, `pictureURL` or `pictureData`.

pictureURL url (string) Sometimes required

The absolute URL of the picture being set. You must specify this, `picture` or `pictureData`.

requestedLanguage Language Optional

Optionally specify a [language](#) for returning translatable properties into this language. If not specified, your games default language will be used.

culture string Optional

Optionally specify a [supported culture code](#) for rendering various properties. If not specified, the `requestedLanguage` default culture code will be used.

File Data

This request additionally supports the posting of files. These files should be sent as `multipart/form-data`, with the corresponding keys.

pictureData multipart/form-data Sometimes required

The data of the picture. You must specify this, `picture` or `pictureURL`.

Success Response

Successful responses always return a `HTTP 200` status code.

```
1 | {  
2 |   "success": true,  
3 |   "blob": { ... },  
4 |   "formattingCulture": "en-us"  
5 | }
```

Response Properties

success `bool`

If the request was successful or not.

blob `Blob`

The blob object returned from the query.

formattingCulture `string`

If some return values are `culture specific`, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
1 | {  
2 |   "success": false,  
3 |   "errorMessage": "Your request failed due to...",  
4 |   "helpURL": "https://www.construct.net/en/game-services/manuals/",  
5 |   "shouldRetry": false  
6 | }
```

Response Properties

success `bool`

If the request was successful or not.

errorMessage `string`

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 5 Dec, 2025 at 11:57