

DATATYPES IN CONSTRUCT GAME SERVICES

Datetime

Datetime values are UTC represented in ISO 8601 format. An example returned datetime value is:

```
1 | 2025-10-03T15:12:22.1333261Z
```

Guids (aka UUID)

Guids take the form of 32 hexadecimal characters, separated by hyphens, in the form 8-4-4-4-12 for a total of 36 characters. Example of a valid guid is:

```
1 | adf5b4d8-4c32-4ecd-8bcd-2b7788eddb43
2 | e7939cfd-ca5a-4f09-a286-b417fd7b9e47
3 | 0e0ebf19-805d-44c8-92c7-f63f23b585f1
4 | fc63773c-5461-44b3-aecd-5af982968748
5 | 5e33107a-f954-4d62-a526-54295b99fb83
```

uint8

Also known as a byte, this is an unsigned 8-bit integer with a range of 0 to 255.

Nullable Types

If a properties data type is nullable, it will be indicated by a question mark (?) after the data type. For example, a property with a data type of `int?` indicates that the property can either be an integer value or null. A

property with a data type of `int` indicates the property will always return a value.

Strings

Strings are never marked as nullable, but null or an empty string can be returned as a value for a string property. These should be treated the same.

Booleans

If a properties data type is `bool`, the values `1`, `yes`, `on` or `true` are treated as `true` values (case insensitive). Anything else will be treated as a `false` value.

Pagination

When [pagination objects](#) are returned in responses, it's important to note that pages are not 0-indexed, but rather 1-indexed. This means that the first page is page 1, the second page is page 2, and so on.

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 3 Nov, 2025 at 09:38