

ADJUST A SCORE

Overview

Adjusts the score value of an existing **score** in the leaderboard. You can pass a positive value to increase the value of the score, or a negative value to decrease it. A leaderboard must permit score adjustments in it's settings otherwise calls to adjust scores will fail.

Adjusting a score will not update the date of the score, but will increment it's updates counter.

Adjusting Score with Session Authentication

If you're calling this end point with a players session key to authenticate the request, if you do not pass in the `scoreID` parameter, the players best score will be adjusted.

Adjusting Score with Secret API Key Authentication

If you're calling this end point with a secret API key, then you need to pass in either a `scoreID` parameter or a `playerID` parameter which would adjust this players current best score.

Request URL

All parameters in the request must be sent as a `post` HTTP request. Make all requests to the following URL:

```
1 | https://leaderboards.construct.net/adjustscore.json
```

Authenticating The Request

This end point can be called by [signed in](#) players, or with [secret key](#) authentication.

Session Key Authentication

sessionKey string **Required**

The [session key](#) of the player you're making the request against.

Secret Key Authentication

secret string **Required**

Your games [secret API key](#).

Request Parameters

gameID guid **Required**

The ID of the game you are making this request against. You can find the ID of your game in your [Construct Game Services \(CGS\) account](#).

leaderboardID guid **Required**

The ID of the leaderboard you're adjusting a score on.

scoreID guid **Sometimes required**

The ID of the score you're adjusting.

playerID guid **Sometimes required**

The ID of the player to adjust the score for. This parameter is only supported for requests using a secret key. If there are multiple scores for the passed player ID then this players best score will be adjusted.

adjustment int64 **Required**

The amount you wish to adjust the existing score by. Pass a negative value to decrease the score, or a positive value to increase the score. The updated value must be no less than `-9223372036854775808` and no more than `9223372036854775807` otherwise an error will be returned.

hash string Sometimes required

If you are authenticating this request with a players session key, then a hash for the adjust score request must be provided. This makes it harder for players to submit fake scores or modify posted values in-flight.

A hash is generated as the SHA256 of a string of values in the request:

```
1 | var key = (leaderboardID + "." + adjustment + "." + unixTimestamp).Normaliz  
2 | return SHA256(key);
```

timestamp int64 Required

The unix timestamp of the date this request was sent. (seconds since January 1st 1970, UTC). Adding historic scores or scores for future dates is not supported.

opt1 int16

The amount to adjust optional value 1 by. Omit this parameter to not change the existing value. The maximum value of an optional value is **32767** and the minimum value is **-32768**. If the adjustment results in a value out of these bounds, the score won't be adjusted and an error will be returned.

opt2 int16

The amount to adjust optional value 2 by. Omit this parameter to not change the existing value. The maximum value of an optional value is **32767** and the minimum value is **-32768**. If the adjustment results in a value out of these bounds, the score won't be adjusted and an error will be returned.

opt3 int16

The amount to adjust optional value 3 by. Omit this parameter to not change the existing value. The maximum value of an optional value is **32767** and the minimum value is **-32768**. If the adjustment results in a value out of these bounds, the score won't be adjusted and an error will be returned.

culture string **Optional**

Optionally specify a **supported culture code** for rendering various properties. If not specified, the culture code from your games default language will be used.

Success Response

Successful responses always return a **HTTP 200** status code.

```
1  {
2    "success": true,
3    "personalBest": false,
4    "score": { ... },
5    "leaderboard": { ... },
6    "formattingCulture": "en-us"
7  }
```

Response Properties

success bool

If the request was successfull or not.

personalBest bool

Is this a personal best for the player who posted the score?

score Score

The score object for the new score.

leaderboard LeaderboardStatus

The status of the leaderboard after this score has been posted.

formattingCulture string

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return **HTTP 4xx** status codes.

```
1 | {  
2 |   "success": false,  
3 |   "errorMessage": "Your request failed due to...",  
4 |   "helpURL": "https://www.construct.net/en/game-services/manuals/game-  
5 |   "shouldRetry": false  
6 | }
```

Response Properties

success bool

If the request was successful or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 5 Dec, 2025 at 11:57