

GET PLAYER SCORES

Overview

Given a player ID, return all this players scores in the leaderboard, best first. Where a leaderboard only supports 1 score per player ID, only one result can ever be returned.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
1 | https://leaderboards.construct.net/getplayerscores.json
```

Authenticating The Request

No authentication is required for this request type.

Request Parameters

gameID guid Required

The ID of the game you are making this request against. You can find the ID of your game in your [Construct Game Services \(CGS\) account](#).

leaderboardID guid Required

The ID of the leaderboard you're fetching the scores for.

playerID guid Required

The ID of the player you're fetching scores for.

perPage int32

How many scores you wish to return on each page of results. Cannot be less than **1** or more than **500**. Default value is **20**.

page int32

The page of results you are requesting. The first page is always **1**. If this value is not specified the first page will be returned.

culture string **Optional**

Optionally specify a **supported culture code** for rendering various properties. If not specified, the culture code from your games default language will be used.

Success Response

Successful responses always return a **HTTP 200** status code.

```
1 {  
2   "success": true,  
3   "pagination": { ... },  
4   "scores": [  
5     { ... },  
6     { ... }  
7   ],  
8   "formattingCulture": "en-us"  
9 }
```

Response Properties

success bool

If the request was successful or not.

pagination Pagination

A pagination object helpful for navigating other pages of results.

scores Array<Score>

The list of score objects returned from the request.

formattingCulture string

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return **HTTP 4xx** status codes.

```
1 | {  
2 |   "success": false,  
3 |   "errorMessage": "Your request failed due to...",  
4 |   "helpURL": "https://www.construct.net/en/game-services/manuals/g  
5 |   "shouldRetry": false  
6 | }
```

Response Properties

success bool

If the request was successfull or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 9 Mar, 2026 at 15:59