

LIST IP SHADOW BANS

Overview

Retrieve a list of all IP hashes that have been shadow banned.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
1 | https://leaderboards.construct.net/listipshadowbans.json
```

Authenticating The Request

This end point is for `secret key` authenticated requests only. Signed in players cannot call this end point.

`secret` `string` **Required**

Your games `secret API key`.

Request Parameters

`gameID` `guid` **Required**

The ID of the game you are making this request against. You can find the ID of your game in your [Construct Game Services \(CGS\) account](#).

`leaderboardID` `guid` **Required**

The ID of the leaderboard you're fetching the shadow bans for.

perPage int32

How many bans you wish to return on each page of results.
Cannot be less than **1** or more than **500**. Default value is **20**.

page int32

The page of results you are requesting. The first page is always **1**.
If this value is not specified the first page will be returned.

culture string **Optional**

Optionally specify a **supported culture code** for rendering various properties. If not specified, the culture code from your games default language will be used.

Success Response

Successful responses always return a **HTTP 200** status code.

```
1 {  
2   "success": true,  
3   "bans": [  
4     { ... },  
5     { ... }  
6   ],  
7   "pagination": { ... },  
8   "formattingCulture": "en-us"  
9 }
```

Response Properties

success **bool**

If the request was successful or not.

bans Array<IPShadowBan>

The list of IP shadow bans returned in the request.

pagination **Pagination**

A pagination object helpful for navigating other pages of results.

formattingCulture string

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return **HTTP 4xx** status codes.

```
1  {  
2    "success": false,  
3    "errorMessage": "Your request failed due to...",  
4    "helpURL": "https://www.construct.net/en/game-services/manuals/  
5    "shouldRetry": false  
6  }
```

Response Properties

success **bool**

If the request was successful or not.

errorMessage **string**

An error message with more detailed information on why the request failed.

helpURL **url (string)**

A link to documentation which should provide help with the error.

shouldRetry **bool**

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

