

LIST PLAYERS ON A TEAM

Overview

Returns all players currently registered on a [team](#).

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
1 | https://leaderboards.construct.net/listteamplayers.json
```

Authenticating The Request

No authentication is required for calling this end point.

`secret` string **Optional**

Your games [secret API key](#).

Request Parameters

`gameID` guid **Required**

The ID of the game you are making this request against. You can find the ID of your game in your [Construct Game Services \(CGS\) account](#).

`leaderboardID` guid **Required**

The ID of the leaderboard you're fetching team players from.

teamID guid **Required**

The ID of the team you're fetching players from.

order string

Order method to return players in. Permitted values are

PlayerName or **Score**. Defaults to **PlayerName** if not specified.

perPage int32

How many players you wish to return on each page of results.

Cannot be less than **1** or more than **50**. Default value is **10**.

page int32

The page of results you are requesting. The first page is always **1**.

If this value is not specified the first page will be returned.

culture string **Optional**

Optionally specify a **supported culture code** for rendering various properties. If not specified, the culture code from your games default language will be used.

Success Response

Successful responses always return a **HTTP 200** status code.

```
1  {
2    "success": true,
3    "pagination": { ... },
4    "players": [
5      { ... },
6      { ... }
7    ],
8    "team": { ... },
9    "formattingCulture": "en-us"
10 }
```

Response Properties

success bool

If the request was successful or not.

pagination `Pagination`

A pagination object helpful for navigating other pages of results.

players `Array<TeamPlayer>`

The list of players returned in the request.

team `ExpandedTeam`

The team object these players belong to.

formattingCulture `string`

If some return values are `culture specific`, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
1 | {  
2 |   "success": false,  
3 |   "errorMessage": "Your request failed due to...",  
4 |   "helpURL": "https://www.construct.net/en/game-services/manuals/  
5 |   "shouldRetry": false  
6 | }
```

Response Properties

success `bool`

If the request was successful or not.

errorMessage `string`

An error message with more detailed information on why the request failed.

helpURL `url (string)`

A link to documentation which should provide help with the error.

shouldRetry `bool`

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 9 Mar, 2026 at 15:59